

**Safety Data Sheet**

Revision date: 09.05.2023

**Emirates lubricants**

Silicone Spray

Page 1 of 10

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Silicone Spray

UFI: 8178-MQCP-GN60-349S

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

Aerosol - Lubricant, lubricants and release products.

**1.3. Details of the supplier of the safety data sheet****Manufacturer**

Company name: Emirates lubricants

Street: Ras Al khaimah

Place: United Arab Emirates

Telephone: +971 55 105 2851 +971 52 660 6888

e-mail: info@emirateslubricant.

Contact person: Application Technology

Internet: www.emirateslubricant.com

Responsible Department: Emirates lubricants Application Technology

**1.4. Emergency telephone number:** +971 52 660 6888 - This number is serviced during office hours.**SECTION 2: Hazards identification**

## Safety Data Sheet

### 2.1. Classification of the substance or mixture

#### GB CLP Regulation

Aerosol 1; H222-H229

Full text of hazard statements: see SECTION 16.

This preparation is hazardous in the sense of regulation (EC) No 1272/2008 [GHS].

### 2.2. Label elements

#### GB CLP Regulation

Signal word: Danger



#### Pictograms:

#### Hazard statements

H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.

#### Precautionary statements

P102 Keep out of reach of children.

### 3.2. Mixtures

#### Hazardous components

| CAS No   | Chemical name                      |              |          | Quantity  |
|----------|------------------------------------|--------------|----------|-----------|
|          | EC No                              | Index No     | REACH No |           |
|          | Classification (GB CLP Regulation) |              |          |           |
| 106-97-8 | butane                             |              |          | 55 - 60 % |
|          | 203-448-7                          | 601-004-00-0 |          |           |
|          | Flam. Gas 1; H220                  |              |          |           |
| 74-98-6  | propane                            |              |          | 25 - 30 % |
|          | 200-827-9                          | 601-003-00-5 |          |           |
|          | Flam. Gas 1; H220                  |              |          |           |

Full text of H and EUH statements: see section 16.

**Safety Data Sheet****Emirates lubricants**

Revision date: 09.05.2023

Silicone Spray

Page 2 of 10

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211 Do not spray on an open flame or other ignition source.
- P251 Do not pierce or burn, even after use.
- P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. P501 Dispose of contents/container to an appropriate recycling or disposal facility.

**Special labelling of certain mixtures**

84 % by mass of the contents are flammable.

**Additional advice on labelling**

Product is classified and labelled in accordance with EC regulations or the corresponding national laws.

**2.3. Other hazards**

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

**SECTION 3: Composition/information on ingredients****Further Information**

Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

**SECTION 4: First aid measures****4.1. Description of first aid measures****General information**

Remove affected person from the danger area and lay down. Position and transport victim on their side. In case of respiratory distress, bring into semi-upright, seated position. Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

**After inhalation**

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist. In case of breathing difficulties administer oxygen.

**After contact with skin**

After contact with skin, wash immediately with plenty of water and soap. In case of skin irritation, seek medical treatment.

**After contact with eyes**

Rinse immediately carefully and thoroughly with eye-bath or water. In case of troubles or persistent symptoms, consult an ophthalmologist.

**After ingestion**

Do NOT induce vomiting.

**Emirates lubricants**

Revision date: 09.05.2023

Silicone Spray

Page 3 of 10

Rinse mouth thoroughly with water. Call a physician immediately.

Never give anything by mouth to an unconscious person or a person with cramps.

**4.2. Most important symptoms and effects, both acute and delayed**

following inhalation: drowsiness. Headache. Nausea.

**4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptomatically.

## Safety Data Sheet

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

##### **Suitable extinguishing media**

Carbon dioxide (CO<sub>2</sub>). Dry extinguishing powder. alcohol resistant foam.

##### **Unsuitable extinguishing media**

High power water jet.

#### 5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon dioxide (CO<sub>2</sub>). Carbon monoxide Nitrogen oxides (NO<sub>x</sub>). carbon black.

Vapours may form explosive mixtures with air.

#### 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

##### **Additional information**

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray/stream to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### **General advice**

Remove persons to safety. Wear a self-contained breathing apparatus and chemical resistant suit. Vapours are heavier than air and will spread at floor level. Avoid contact with skin and eyes. Keep away from sources of ignition - No smoking.

#### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Prevent spread over a wide area (e.g. by containment or oil barriers).

#### 6.3. Methods and material for containment and cleaning up

##### **Other information**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Collect in closed containers for disposal. Clean contaminated articles and floor according to the environmental legislation.

#### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Section 12: Ecological Information (non-mandatory)

Disposal: see section 13

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

## Emirates lubricants

Revision date: 09.05.2023

Silicone Spray

Page 4 of 10

## Safety Data Sheet

### Advice on safe handling

Work in well-ventilated zones or use proper respiratory protection. Do not breathe gas/fumes/vapour/spray. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. To avoid risks to man and the environment, comply with the instructions for use.

### Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Heating causes rise in pressure with risk of bursting.

### Advice on general occupational hygiene

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace. Avoid contact with skin, eyes and clothes.

### Further information on handling

People who suffer from asthma, allergies, chronic or recurring respiratory illnesses must not be deployed in processes, which use this substance.

## 7.2. Conditions for safe storage, including any incompatibilities

### Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorption of humidity. Keep container tightly closed in a cool place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Please note: TRG 300, aerosol directive (75/324/EEC).

### Hints on joint storage

Keep away from food, drink and animal feedingstuffs.

Keep away from: Oxidizing agent Material, rich in oxygen, oxidizing.

### Further information on storage conditions

Recommended storage temperature: 5 - 40°C.

Do not store at temperatures over: 50°C.

## 7.3. Specific end use(s)

Further information: see technical data sheet.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Exposure limits (EH40)

| CAS No   | Substance | ppm | mg/m <sup>3</sup> | fibres/ml | Category      | Origin |
|----------|-----------|-----|-------------------|-----------|---------------|--------|
| 106-97-8 | Butane    | 600 | 1450              |           | TWA (8 h)     | WEL    |
|          |           | 750 | 1810              |           | STEL (15 min) | WEL    |

### Additional advice on limit values

source: TRGS 900

### 8.2. Exposure controls



## Safety Data Sheet

### Emirates lubricants

Revision date: 09.05.2023

Silicone Spray

Page 5 of 10

#### Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

#### Individual protection measures, such as personal protective equipment

##### Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): EN 166

##### Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): EN ISO 374

Duration of wearing with permanent contact: 480

min Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.7 mm.

Wearing time with occasional contact (splashes): 30 min

Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

##### Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

##### Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Breathing protection with filter against organic gases and vapours type A - boiling point > 65°C: A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

|                  |                |
|------------------|----------------|
| Physical state:  | gaseous        |
| Colour:          | colourless     |
| Odour:           | characteristic |
| Odour threshold: | not determined |

|                                                           | Test method              |
|-----------------------------------------------------------|--------------------------|
| Melting point/freezing point:                             | not applicable           |
| Boiling point or initial boiling point and boiling range: | < -20 °C                 |
| Flammability:                                             | not applicable           |
| Lower explosion limits:                                   | 3 vol. %                 |
| Upper explosion limits:                                   | 15 vol. %                |
| Flash point:                                              | < -20 °C DIN EN ISO 2592 |
| Auto-ignition temperature:                                | 287 °C DIN 51794         |
| Decomposition temperature:                                | not determined           |

## Safety Data Sheet

|                                                   |                                   |
|---------------------------------------------------|-----------------------------------|
| pH-Value:                                         | not applicable                    |
| Viscosity / kinematic:                            | not applicable                    |
| Water solubility:<br>(at 20 °C)                   | insoluble                         |
| Solubility in other solvents<br>No data available |                                   |
| Partition coefficient n-octanol/water:            | not determined                    |
| Vapour pressure:<br>(at 20 °C)                    | not determined                    |
| Density (at 20 °C):                               | 0,598 g/cm <sup>3</sup> DIN 51757 |

### Emirates lubricants

Revision date: 09.05.2023

Silicone Spray

Page 6 of 10

|                          |                |
|--------------------------|----------------|
| Relative vapour density: | not determined |
|--------------------------|----------------|

#### **9.2. Other information**

##### **Information with regard to physical hazard classes**

###### Explosive properties

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

###### Sustaining combustion:

No data available

###### Self-ignition temperature

###### Solid:

not applicable

###### Gas:

not applicable

###### Oxidizing properties

Not oxidising.

##### **Other safety characteristics**

###### Evaporation rate:

No data available

### **SECTION 10: Stability and reactivity**

#### **10.1. Reactivity**

The product is stable under storage at normal ambient temperatures.

#### **10.2. Chemical stability**

The mixture is chemically stable under recommended conditions of storage, use and temperature. **10.3. Possibility of hazardous reactions** Ignition hazard.

Vapours may form explosive mixtures with air.

#### **10.4. Conditions to avoid**

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children. Take precautionary measures against static discharges. See protective measures under point 7 and 8.

#### **10.5. Incompatible materials**

No information available.

#### **10.6. Hazardous decomposition products**

In case of fire may be liberated: Carbon dioxide (CO<sub>2</sub>). Carbon monoxide Nitrogen oxides (NO<sub>x</sub>). carbon black.

Combustible. Vapours may form explosive mixtures with air.

## Safety Data Sheet

## Emirates lubricants

Revision date: 09.05.2023

Silicone Spray

Page 7 of  
10**SECTION 11: Toxicological information****11.1. Information on hazard classes as defined in GB CLP Regulation****Acute toxicity**

Based on available data, the classification criteria are not met.  
Mixture not tested.

**Irritation and corrosivity**

Based on available data, the classification criteria are not met.

**Sensitising effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction** Based  
on available data, the classification criteria are not met.

**STOT-single exposure**

Based on available data, the classification criteria are not met.

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**11.2. Information on other hazards****Endocrine disrupting properties**

not applicable **Further  
information**

If handled with proper care and at intended use, the product does not cause any harmful effects acc. to our experiences and available information.

**SECTION 12: Ecological information****12.1. Toxicity**

Based on available data, the classification criteria are not met.

| CAS No   | Chemical name            |               |       |           |                               |                                                |                                                |
|----------|--------------------------|---------------|-------|-----------|-------------------------------|------------------------------------------------|------------------------------------------------|
|          | Aquatic toxicity         | Dose          |       | [h]   [d] | Species                       | Source                                         | Method                                         |
| 106-97-8 | butane                   |               |       |           |                               |                                                |                                                |
|          | Acute fish toxicity      | LC50<br>mg/l  | 49,9  | 96 h      | Fish, no other<br>information | United States<br>Environmental<br>Protection A | The Ecosar class<br>program has been<br>develo |
|          | Acute algae toxicity     | ErC50<br>mg/l | 19,37 | 96 h      | Algae                         | USEPA OPPT<br>Risk Assessment<br>Division (200 | Calculation using<br>ECOSAR<br>Program v1.00.  |
|          | Acute crustacea toxicity | EC50<br>mg/l  | 69,43 | 48 h      | Daphnia sp.                   | USEPA OPPT<br>Risk Assessment<br>Division (200 | Calculation using<br>ECOSAR<br>Program v1.00.  |
| 74-98-6  | propane                  |               |       |           |                               |                                                |                                                |
|          | Acute fish toxicity      | LC50<br>mg/l  | 49,9  | 96 h      | Fish, no other<br>information | United States<br>Environmental<br>Protection A | The Ecosar class<br>program has been<br>develo |



## Safety Data Sheet

|  |                          |               |       |      |             |                                                |                                               |
|--|--------------------------|---------------|-------|------|-------------|------------------------------------------------|-----------------------------------------------|
|  | Acute algae toxicity     | ErC50<br>mg/l | 19,37 | 96 h | Algae       | USEPA OPPT<br>Risk Assessment<br>Division (200 | Calculation using<br>ECOSAR<br>Program v1.00. |
|  | Acute crustacea toxicity | EC50<br>mg/l  | 69,43 | 48 h | Daphnia sp. | USEPA OPPT<br>Risk Assessment<br>Division (200 | Calculation using<br>ECOSAR<br>Program v1.00. |

**12.2. Persistence and degradability**

Not easily bio-degradable (according to OECD-criteria). Do not allow to enter into surface water or drains.

**12.3. Bioaccumulative potential**

No data available

**Partition coefficient n-octanol/water**

| CAS No   | Chemical name | Log Pow |
|----------|---------------|---------|
| 106-97-8 | butane        | 1,09    |
| 74-98-6  | propane       | 1,09    |

**12.4. Mobility in soil**

Product is easily volatile. Product is difficult to dissolve in water.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria.

## Emirates lubricants

Revision date: 09.05.2023

Silicone Spray

Page 8 of 10

**12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**12.7. Other adverse effects**

No data available

**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Disposal recommendations**

Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

**List of Wastes Code - residues/unused products**

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

**Contaminated packaging**

Dispose of waste according to applicable legislation.

**SECTION 14: Transport information****Land transport (ADR/RID)**

- 14.1. UN number or ID number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2  
**14.4. Packing group:** -

## Safety Data Sheet

Hazard label: 2.1

Classification code: 5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L

Excepted quantity: E0

Transport category: 2

Tunnel restriction code: D

**Inland waterways transport (ADN)**

**14.1. UN number or ID number:** UN 1950

**14.2. UN proper shipping name:** AEROSOLS

**14.3. Transport hazard class(es):** 2

**14.4. Packing group:** -

Hazard label: 2.1



Classification code: 5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L

Excepted quantity: E0

**Marine transport (IMDG)**

**14.1. UN number or ID number:** UN 1950

**14.2. UN proper shipping name:** AEROSOLS

**14.3. Transport hazard class(es):** 2.1

**Emirates lubricants**

Revision date: 09.05.2023

Silicone Spray

Page 9 of 10

**14.4. Packing group:**

-

Hazard label: 2.1



Special Provisions: 63, 190, 277, 327, 344, 959

Limited quantity: 1000 mL

## Safety Data Sheet

Excepted quantity: E0

EmS: F-D, S-U

### Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number or ID number:** UN 1950

**14.2. UN proper shipping name:** AEROSOLS, flammable

**14.3. Transport hazard class(es):** 2.1

**14.4. Packing group:** -

Hazard label: 2.1



Special Provisions: A145 A167 A802

Limited quantity Passenger: 30 kg G

Passenger LQ: Y203

Excepted quantity: E0

IATA-packing instructions - Passenger: 203

IATA-max. quantity - Passenger: 75 kg

IATA-packing instructions - Cargo: 203

IATA-max. quantity - Cargo: 150 kg

### **14.5. Environmental hazards** No

ENVIRONMENTALLY HAZARDOUS:

### **14.6. Special precautions for user**

Warning: flammable gases.

### **14.7. Maritime transport in bulk according to instruments** not applicable

## SECTION 15: Regulatory information

### **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

#### EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 28, Entry 40

2010/75/EU (VOC): 84,5% (505,31 g/L)

2004/42/EC (VOC): 84,5% (505,31 g/L)

Information according to 2012/18/EU (III): P3a FLAMMABLE AEROSOLS (SEVESO)

#### Additional information

To follow: 850/2004/EC , 79/117/EEC , 689/2008/EC , 2008/47/EC

#### National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

## Safety Data Sheet

### Emirates lubricants

Revision date: 09.05.2023

Silicone Spray

Page 10 of 10

#### 15.2. Chemical safety assessment

Chemical safety assessments for substance s in this mixture were not carried out.

### SECTION 16: Other information

#### Changes

This data sheet contains changes from the previous version in section(s): 1,2,7,8,9,15.

#### Abbreviations and acronyms

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ASTM - American Society for the Testing of Materials; ATE - Acute Toxicity Estimates; bw - Body weight; CAO - Cargo Aircraft Only; CAS - Chemical Abstracts Service; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DNEL - Derived No-Effect Level; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); EG - European Union; EN - European standards; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISO - International Organisation for Standardization; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n;o;s; - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; OECD - Organization for Economic Co-operation and Development; PBT - Persistent, Bioaccumulative and Toxic substance; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulation concerning the International Carriage of Dangerous Goods by Rail; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

#### Relevant H and EUH statements (number and full text)

|      |                                             |
|------|---------------------------------------------|
| H220 | Extremely flammable gas.                    |
| H222 | Extremely flammable aerosol.                |
| H229 | Pressurised container: May burst if heated. |

#### Further Information

This preparation is hazardous in the sense of regulation (EC) No 1272/2008 [GHS].

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

## Safety Data Sheet

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*