

Safety Data Sheet**Emirates lubricants**

Revision date: 23.10.2023

Penta-Cool WS 300

Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Penta-Cool WS 300

UFI: E1QS-2642-520J-S61W

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Metal working fluids.

1.3. Details of the supplier of the safety data sheet**Manufacturer**

Company name: Emirates lubricants

Street: Ras Al khaimah

Place: United Arab Emirates

Telephone: +971 55 105 2851 +971 52 660 6888

e-mail: info@emirateslubricant.

Contact person: Application Technology

Internet: www.emirateslubricant.com

Responsible Department: Emirates lubricants Application Technology

1.4. Emergency telephone number: +971 52 660 6888 - This number is serviced during office hours.**SECTION 2: Hazards identification**

Safety Data Sheet

Emirates lubricants

Revision date: 23.10.2023

Penta-Cool WS 300

Page 2 of
12

2.1. Classification of the substance or mixture

GB CLP Regulation

Skin Irrit. 2; H315
 Eye Irrit. 2; H319
 Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

2.2. Label elements

GB CLP Regulation

Signal word:

Warning



Pictograms:

Hazard statements

H315	Causes skin irritation.
H319	Causes serious eye irritation.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P264	Wash hands thoroughly after handling.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P501	Dispose of contents/container to an appropriate recycling or disposal facility.

Additional advice on labelling

Product is classified and labelled in accordance with EC regulations or the corresponding national laws.

2.3. Other hazards

Prolonged/repetitive skin contact may cause skin defatting or dermatitis.
 Spilled product must not leak into the ground.
 Do not allow uncontrolled leakage of product into the environment.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
95-14-7	1,2,3-Triazaindene			< 5 - 10 %

Safety Data Sheet

	202-394-1			
	Acute Tox. 4, Eye Irrit. 2, Aquatic Chronic 2; H302 H319 H411			
770-35-4	1-phenoxypropan-2-ol			5 - < 10 %
	212-222-7		01-2119486566-23	
	Eye Irrit. 2; H319			
1310-58-3	potassium hydroxide; caustic potash			< 2 %
	215-181-3	019-002-00-8	01-2120767289-38	
	Acute Tox. 4, Skin Corr. 1A; H302 H314			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
95-14-7	202-394-1	1,2,3-Triazaindene	< 5 - 10 %
	dermal: LD50 = > 2000 mg/kg; oral: ATE = 500 mg/kg		
770-35-4	212-222-7	1-phenoxypropan-2-ol	5 - < 10 %
	dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 2000 mg/kg		
1310-58-3	215-181-3	potassium hydroxide; caustic potash	< 2 %
	oral: LD50 = 333 mg/kg Skin Corr. 1A; H314: >= 5 - 100 Skin Corr. 1B; H314: >= 2 - < 5 Skin Irrit. 2; H315: >= 0,5 - < 2 Eye Irrit. 2; H319: >= 0,5 - < 2		

Further Information

DMSO-Extrakt < 3 %, IP 346.

Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

Emirates lubricants

Revision date: 23.10.2023

Penta-Cool WS 300

Page 3 of 12

SECTION 4: First aid measures

Safety Data Sheet

4.1. Description of first aid measures

General information

Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

After inhalation

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. Protect skin by using skin protective cream. In case of skin irritation, seek medical treatment.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

After ingestion

Do NOT induce vomiting.
Rinse mouth thoroughly with water. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam. Extinguishing powder. Atomized water. Carbon dioxide (CO₂).

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon dioxide (CO₂). Carbon monoxide Nitrogen oxides (NO_x). carbon black.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray jet to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

High slip hazard because of leaking or spilled product. Remove all sources of ignition. Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Prevent spread over a wide area (e.g. by containment or oil barriers).

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the

Safety Data Sheet

Emirates lubricants

Revision date: 23.10.2023

Penta-Cool WS 300

Page 4 of 12

recovered material as prescribed in the section on waste disposal. Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Section 12: Ecological Information (non-mandatory)

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Work in well-ventilated zones or use proper respiratory protection. Avoid oil mist. If handled uncovered, arrangements with local exhaust ventilation have to be used. Avoid contact with skin, eyes and clothes.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Advice on general occupational hygiene

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorption of humidity. Keep container tightly closed in a cool place. Keep/Store only in original container.

Hints on joint storage

Keep away from food, drink and animal feedingstuffs.

Keep away from: Oxidizing agent

Further information on storage conditions

Protect against: UV-radiation/sunlight. frost. heat.

Recommended storage temperature: 5 - 40°C

7.3. Specific end use(s)

Further information: see technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
1310-58-3	Potassium hydroxide	-	2		STEL (15 min)	WEL

Safety Data Sheet

Emirates lubricants

Penta-Cool WS 300

Page 5 of
12

Revision date: 23.10.2023

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
95-14-7	1,2,3-Triazaindene			
Worker DNEL, long-term		inhalation	systemic	4,2 mg/m ³
Worker DNEL, long-term		dermal	systemic	0,24 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	2,1 mg/m ³
Consumer DNEL, long-term		dermal	systemic	0,12 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,12 mg/kg bw/day
Consumer DNEL, acute		oral	systemic	0,12 mg/kg bw/day
770-35-4	1-phenoxypropan-2-ol			
Worker DNEL, long-term		inhalation	systemic	25,7 mg/m ³
Worker DNEL, long-term		dermal	systemic	42 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	21 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	3,65 mg/kg bw/day

PNEC values

CAS No	Substance		
Environmental compartment		Value	
95-14-7	1,2,3-Triazaindene		
Freshwater		0,019 mg/l	
Freshwater (intermittent releases)		0,158 mg/l	
Marine water		0,019 mg/l	
Freshwater sediment		0,22 mg/kg	
Marine sediment		0,22 mg/kg	
Micro-organisms in sewage treatment plants (STP)		0,1 mg/l	
Soil		0,03 mg/kg	
770-35-4	1-phenoxypropan-2-ol		
Freshwater		0,1 mg/l	

Safety Data Sheet

Freshwater (intermittent releases)	1 mg/l
Marine water	0,01 mg/l
Freshwater sediment	0,38 mg/kg
Marine sediment	0,038 mg/kg
Micro-organisms in sewage treatment plants (STP)	10 mg/l
Soil	0,02 mg/kg

Additional advice on limit values

source:

Recommended limit value for cooling lubricants (steam and aerosol)

MAK: 10 mg/m³

8.2. Exposure controls

Emirates lubricants

Revision date: 23.10.2023

Penta-Cool WS 300

Page 6 of 12



Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

Individual protection measures, such as personal protective equipment

Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): EN 166

Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): EN ISO 374

Duration of wearing with permanent contact: 480 min

Suitable material: NBR (Nitrile rubber). CR (polychloroprenes, Chloroprene rubber).

Thickness of glove material: 0.7 mm.

Wearing time with occasional contact (splashes): 30 min

Suitable material: NBR (Nitrile rubber). CR (polychloroprenes, Chloroprene rubber).

Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. full mask (DIN EN 136). Breathing protection with filter against organic gases and vapours type A - boiling point > 65°C: A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

SECTION 9: Physical and chemical properties

Safety Data Sheet

9.1. Information on basic physical and chemical properties

Physical state:	liquid	
Colour:	yellow	
Odour:	like: lemon.	
Odour threshold:	not determined	
		Test method
Melting point/freezing point:	No data available	
Boiling point or initial boiling point and boiling range:	> 100 °C	
Flammability:	No data available	
Lower explosion limits:	No data available	
Upper explosion limits:	No data available	
Flash point:	>100 °C	
Auto-ignition temperature:	No data available	
Decomposition temperature:	No data available	
pH-Value (at 20 °C):	8,9 (5%)	DIN 51369
Viscosity / kinematic: (at 20 °C)	14 mm ² /s	DIN EN ISO 3104
Water solubility:	highly soluble.	
Solubility in other solvents	No data available	

Emirates lubricants

Revision date: 23.10.2023

Penta-Cool WS 300

Page 7 of 12

Partition coefficient n-octanol/water:	No data available
Vapour pressure:	No data available
Density (at 15 °C):	1,16 g/cm ³ DIN EN ISO 12185
Relative vapour density:	No data available

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

No data available

Self-ignition temperature

Solid:

No data available

Gas:

No data available

Oxidizing properties

No data available

Other safety characteristics

Evaporation rate:

No data available

Safety Data Sheet

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature. **10.3. Possibility of hazardous reactions** No known hazardous reactions.

10.4. Conditions to avoid

Refer to chapter 7 No further action is necessary.

Do not overheat to avoid decomposition by heat.

10.5. Incompatible materials

Oxidising agent, strong. Acid.

10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon dioxide (CO₂). Carbon monoxide Nitrogen oxides (NO_x). carbon black.
No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) 4628,9 mg/kg

Safety Data Sheet

Emirates lubricants

Revision date: 23.10.2023

Penta-Cool WS 300

Page 10 of 15

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
95-14-7	1,2,3-Triazaindene				
	oral	ATE 500 mg/kg			
	dermal	LD50 > 2000 mg/kg	Rabbit	Study report (1984)	OECD Guideline 402
770-35-4	1-phenoxypropan-2-ol				
	oral	LD50 > 2000 mg/kg	Rat	SIDS Initial Assessment Report For - SIA	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rat	Study report (1986)	OECD Guideline 402
1310-58-3	potassium hydroxide; caustic potash				
	oral	LD50 333 mg/kg	Rat	Fund. Appl. Toxicol., 8, 97-100 (1987)	OECD Guideline 425

Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards**Endocrine disrupting properties**

not applicable

SECTION 12: Ecological information**12.1. Toxicity**

Harmful to aquatic life with long lasting effects.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method

Safety Data Sheet

Emirates lubricants

Revision date: 23.10.2023

Penta-Cool WS 300

Page 11 of 15

95-14-7	1,2,3-Triazindene					
	Acute fish toxicity	LC50	55 mg/l	96 h	Cyprinodon variegatus	Study report (2003) other: The test procedure is based on te
	Acute algae toxicity	ErC50	75 mg/l	72 h	Pseudokirchneriella subcapitata	Study report (1994) OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	15,8	48 h	other aquatic crustacea: Daphnia galeata	Environ Sci Pollut Res 19:1781-1790 (201) OECD Guideline 202
	Crustacea toxicity	NOEC mg/l	25,9	21 d	Daphnia magna	Study report (1995) other: "Daphnia Reproduction Test" of OE
	Acute bacteria toxicity	(EC50 mg/l)	940	3 h	activated sludge of a predominantly domestic sewage	Study report (2015) OECD Guideline 209
770-35-4	1-phenoxypropan-2-ol					
	Acute fish toxicity	LC50	280 mg/l	96 h	Pimephales promelas	Study report (1978) OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	> 100	72 h	Desmodesmus subspicatus	Study report (1997) EU Method C.3
	Acute crustacea toxicity	EC50 mg/l	> 100	48 h	Daphnia magna	Study report (1997) EU Method C.2
	Acute bacteria toxicity	(EC50 mg/l)	> 1000	0,5 h	activated sludge, domestic	Study report (1999) OECD Guideline 209
1310-58-3	potassium hydroxide; caustic potash					
	Acute fish toxicity	LC50	80 mg/l	96 h	Gambusia affinis	IUCLID

12.2. Persistence and degradability

Part of the components is biodegradable.

12.3. Bioaccumulative potential

No indication of bioaccumulation potential.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
95-14-7	1,2,3-Triazindene	22,8
770-35-4	1-phenoxypropan-2-ol	1,41

12.4. Mobility in soil

Is eliminable from water only with difficulty.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

Safety Data Sheet

Emirates lubricants

Revision date: 23.10.2023

Penta-Cool WS 300

Page 12 of 15

12.7. Other adverse effects

No data available

Further information

Do not allow uncontrolled leakage of product into the environment.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

List of Wastes Code - residues/unused products

120110 WASTES FROM SHAPING AND PHYSICAL AND MECHANICAL SURFACE TREATMENT OF METALS AND PLASTICS; wastes from shaping and physical and mechanical surface treatment of metals and plastics; synthetic machining oils; hazardous waste

Contaminated packaging

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Dispose of waste according to applicable legislation. Packing which cannot be properly cleaned must be thrown away.

SECTION 14: Transport information**Land transport (ADR/RID)****14.1. UN number or ID number:** -**14.2. UN proper shipping name:** -**14.3. Transport hazard class(es):** -**14.4. Packing group:** -**Inland waterways transport (ADN)****14.1. UN number or ID number:** -**14.2. UN proper shipping name:** -**14.3. Transport hazard class(es):** -**14.4. Packing group:** -**Marine transport (IMDG)****14.1. UN number or ID number:** -**14.2. UN proper shipping name:** -**14.3. Transport hazard class(es):** -**14.4. Packing group:** -**Air transport (ICAO-TI/IATA-DGR)****14.1. UN number or ID number:** -**14.2. UN proper shipping name:** -**14.3. Transport hazard class(es):** -**14.4. Packing group:** -**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

Other applicable information

No dangerous good in sense of these transport regulations.

Safety Data Sheet**Emirates lubricants**

Revision date: 23.10.2023

Penta-Cool WS 300

Page 13 of 15

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 75

National regulatory**information** Water hazard class

(D):

2 - obviously hazardous to
water

Safety Data Sheet

Emirates lubricants

Revision date: 23.10.2023

Penta-Cool WS 300

Page 11 of 12

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,12,15.

Abbreviations and acronyms

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ASTM - American Society for the Testing of Materials; ATE - Acute Toxicity Estimates; bw - Body weight; CAO - Cargo Aircraft Only; CAS - Chemical Abstracts Service; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DNEL - Derived No-Effect Level; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); EG - European Union; EN - European standards; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISO - International Organisation for Standardization; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n;o;s; - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; OECD - Organization for Economic Co-operation and Development; PBT - Persistent, Bioaccumulative and Toxic substance; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulation concerning the International Carriage of Dangerous Goods by Rail; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Further Information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Safety Data Sheet**Emirates lubricants**

Penta-Cool WS 300

Page 12 of
12

Revision date: 23.10.2023

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. *(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*