

Safety Data Sheet

Revision date: 17.07.2023

Emirates lubricants
Welding Protection Spray

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Welding Protection Spray

UFI: U7G0-GS0C-A572-NGMF

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Aerosol - Welding, soldering, and flux products

1.3. Details of the supplier of the safety data sheet**Manufacturer**

Company name: Emirates lubricants

Street: Ras Al khaimah

Place: United Arab Emirates

Telephone: +971 55 105 2851 +971 52 660 6888

e-mail: info@emirateslubricant.

Contact person: Application Technology

Internet: www.emirateslubricant.com

Responsible Department: Emirates lubricants Application Technology

1.4. Emergency telephone number: +971 52 660 6888 - This number is serviced during office hours.**SECTION 2: Hazards identification**

Safety Data Sheet

Emirates lubricants

Revision date: 17.07.2023

Welding Protection Spray

Page 2 of 11

2.1. Classification of the substance or mixture**GB CLP Regulation**

Aerosol 1; H222-H229

Full text of hazard statements: see SECTION 16.

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

2.2. Label elements**GB CLP Regulation****Signal word:**

Danger

**Pictograms:****Hazard statements**

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container to an appropriate recycling or disposal facility.

Special labelling of certain mixtures

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

Additional advice on labelling

Product is classified and labelled in accordance with EC regulations or the corresponding national laws.

2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
106-97-8	butane			40 - < 60 %
	203-448-7	601-004-00-0		
	Flam. Gas 1, Liquefied gas; H220 H280			

Safety Data Sheet

74-98-6	propane			20 - < 40 %
	200-827-9	601-003-00-5		
	Flam. Gas 1, Liquefied gas; H220 H280			
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified			10 - < 20 %
	265-157-1		01-2119484627-25	
	Asp. Tox. 1; H304			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
64742-54-7	265-157-1	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified	10 - < 20 %
	dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg		

Further Information

DMSO-Extrakt < 3 %, IP 346.

Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove affected person from the danger area and lay down. Position and transport victim on their side. In case of respiratory distress, bring into semi-upright, seated position. Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

Emirates lubricants

Revision date: 17.07.2023

Welding Protection Spray

Page 3 of 11

Safety Data Sheet

After inhalation

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist. In case of breathing difficulties administer oxygen.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. In case of skin irritation, seek medical treatment.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of troubles or persistent symptoms, consult an ophthalmologist.

After ingestion

Do NOT induce vomiting.

Rinse mouth thoroughly with water. Call a physician immediately.

Never give anything by mouth to an unconscious person or a person with cramps.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂). Extinguishing powder. Foam.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon dioxide (CO₂). Carbon monoxide Nitrogen oxides (NO_x). carbon black.

Flammable. Vapours may form explosive mixtures with air.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray jet to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

SECTION 6: Accidental release measures

Safety Data Sheet

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Remove persons to safety. Wear a self-contained breathing apparatus and chemical resistant suit. Vapours are heavier than air and will spread at floor level. Avoid contact with skin and eyes. Keep away from sources of ignition - No smoking.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Prevent spread over a wide area (e.g. by containment or oil barriers).

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the

Emirates lubricants

Revision date: 17.07.2023

Welding Protection Spray

Page 4 of 11

recovered material as prescribed in the section on waste disposal. Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Section 12: Ecological Information (non-mandatory)

Disposal: see section 13

SECTION 7: Handling and storage

Safety Data Sheet

7.1. Precautions for safe handling

Advice on safe handling

Use only in well-ventilated areas. Take precautionary measures against static discharges. Do not spray on naked flames or any incandescent material. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Avoid contact with skin, eyes and clothes.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Heating causes rise in pressure with risk of bursting.

Advice on general occupational hygiene

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorption of humidity. Keep container tightly closed in a cool place. Keep away from sources of ignition - No smoking.

Please note: TRG 300, aerosol directive (75/324/EEC).

Hints on joint storage

Keep away from food, drink and animal feedingstuffs.

Keep away from: Oxidizing agent. Material, rich in oxygen, oxidizing.

Further information on storage conditions

Recommended storage temperature: 5 - 40°C. Do not store at temperatures over: 50°C.

7.3. Specific end use(s)

Further information: see technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL

DNEL/DMEL values

CAS No	Substance			
DNEL type	Exposure route		Effect	Value
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified			
Worker DNEL, long-term		inhalation	systemic	2,73 mg/m ³
Worker DNEL, long-term		inhalation	local	5,58 mg/m ³
Worker DNEL, long-term		dermal	systemic	0,97 mg/kg bw/day
Consumer DNEL, long-term		inhalation	local	1,19 mg/m ³

Safety Data Sheet

Emirates lubricants

Revision date: 17.07.2023

Welding Protection Spray

Page 5 of 11

Consumer DNEL, long-term	oral	systemic	0,74 mg/kg bw/day
--------------------------	------	----------	-------------------

PNEC values

CAS No	Substance
Environmental compartment	Value
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified
Secondary poisoning	9,33 mg/kg

Additional advice on limit values

source:

Does not contain substances above concentration limits fixing an occupational exposure limit.

8.2. Exposure controls**Appropriate engineering controls**

Provide adequate ventilation as well as local exhaust at critical locations.

Individual protection measures, such as personal protective equipment Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): EN 166

Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): EN ISO 374

Duration of wearing with permanent contact: 480

min Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.7 mm.

Wearing time with occasional contact (splashes): 30 min

Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Breathing protection with filter against organic gases and vapours type A - boiling point > 65°C: A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

Emirates lubricants

Revision date: 17.07.2023

Welding Protection Spray

Page 6 of 11

SECTION 9: Physical and chemical properties

Safety Data Sheet

9.1. Information on basic physical and chemical properties

Physical state:	gaseous	
Colour:	various colors	
Odour:	characteristic	
Odour threshold:	not determined	
		Test method
Melting point/freezing point:	not applicable	
Boiling point or initial boiling point and boiling range:	< -20 °C	
Flammability:	not applicable	
Lower explosion limits:	1,5 vol. %	
Upper explosion limits:	10,9 vol. %	
Flash point:	< -20 °C	DIN EN ISO 2592
Auto-ignition temperature:	365 °C	DIN 51794
Decomposition temperature:	not determined	
pH-Value:	not applicable	
Viscosity / kinematic:	not applicable	
Water solubility: (at 20 °C)	insoluble	
Solubility in other solvents		
No data available		
Partition coefficient n-octanol/water:	No data available	
Vapour pressure: (at 20 °C)	not determined	
Density (at 20 °C):	0,583 g/cm ³	DIN 51757
Relative vapour density:	No data available	

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

Sustaining combustion:

No data available

Self-ignition temperature

Solid:

not applicable

Gas:

not applicable

Oxidizing properties

No data available

Other safety characteristics

Evaporation rate:

No data available

SECTION 10: Stability and reactivity

Safety Data Sheet

10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature. **10.3. Possibility of hazardous reactions** Ignition hazard.

Vapours may form explosive mixtures with air.

Emirates lubricants

Revision date: 17.07.2023

Welding Protection Spray

Page 7 of 11

10.4. Conditions to avoid

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children. Take precautionary measures against static discharges. See protective measures under point 7 and 8.

10.5. Incompatible materials

Keep away from: Oxidizing agent. Material, rich in oxygen, oxidizing.

10.6. Hazardous decomposition products

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

In case of fire may be liberated: Carbon dioxide (CO₂). Carbon monoxide Nitrogen oxides (NO_x). carbon black.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

Mixture not tested.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified				
	oral	LD50 mg/kg > 5000	Rat	Study report (1982)	OECD Guideline 401
	dermal	LD50 mg/kg > 5000	Rabbit	Study report (1982)	OECD Guideline 402

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

Safety Data Sheet

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Endocrine disrupting properties

not applicable Further

information

If handled with proper care and at intended use, the product does not cause any harmful effects acc. to our experiences and available information.

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name						
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method	
106-97-8	butane						
	Acute fish toxicity	LC50 mg/l	49,9	96 h	Fish, no other information	United States Environmental Protection A	The Ecosar class program has been develo
	Acute algae toxicity	ErC50 mg/l	19,37	96 h	Algae	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.
	Acute crustacea toxicity	EC50 mg/l	69,43	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.
74-98-6	propane						
	Acute fish toxicity	LC50 mg/l	49,9	96 h	Fish, no other information	United States Environmental Protection A	The Ecosar class program has been develo
	Acute algae toxicity	ErC50 mg/l	19,37	96 h	Algae	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.
	Acute crustacea toxicity	EC50 mg/l	69,43	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.
64742-54-7	Distillates (petroleum), hy rotreated he ivy paraffi ic; Baseoil - unspecified						
	Acute fish toxicity	LL50 mg/l	> 100	96 h	Pimephales promelas	Study report (1995)	OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	>100	72 h			
	Fish toxicity	NOEC mg/l	>= 1000	14 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)	The aquatic toxicity was estimated by a

12.2. Persistence and degradability

Not easily bio-degradable (according to OECD-criteria). Do not allow to enter into surface water or drains.

12.3. Bioaccumulative potential

The product has not been tested.

Safety Data Sheet

Emirates lubricants

Revision date: 17.07.2023

Welding Protection Spray

Page 8 of 11

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
106-97-8	butane	1,09
74-98-6	propane	1,09

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria .

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No data available

SECTION 13: Disposal considerations**13.1. Waste treatment methods**

Emirates lubricants

Revision date: 17.07.2023

Welding Protection Spray

Page 9 of 11

Disposal recommendations

Do not open container by force. Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

Contaminated packaging

Dispose of waste according to applicable legislation.

SECTION 14: Transport information**Land transport (ADR/RID)**

- 14.1. UN number or ID number:** UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -

Hazard label: 2.1



Classification code: 5F

Safety Data Sheet

Special Provisions: 190 327 344 625

Limited quantity: 1 L

Excepted quantity: E0

Transport category: 2

Tunnel restriction code: D

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1950

14.2. UN proper shipping name: AEROSOLS

14.3. Transport hazard class(es): 2

14.4. Packing group: -

Hazard label: 2.1



Classification code: 5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L

Excepted quantity: E0

Marine transport (IMDG)

14.1. UN number or ID number: UN 1950

14.2. UN proper shipping name: AEROSOLS

14.3. Transport hazard class(es): 2.1

14.4. Packing group: -

Hazard label: 2.1



Special Provisions: 63, 190, 277, 327, 344, 959

Limited quantity: 1000 mL

Emirates lubricants

Welding Protection Spray

Revision date: 17.07.2023

Page 10 of 11

Excepted quantity: E0

EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1950

14.2. UN proper shipping name: AEROSOLS, flammable

Safety Data Sheet

14.3. Transport hazard class(es): 2.1

14.4. Packing group: -

Hazard label: 2.1



Special Provisions: A145 A167 A802

Limited quantity Passenger: 30 kg G

Passenger LQ: Y203

Excepted quantity: E0

IATA-packing instructions - Passenger: 203

IATA-max. quantity - Passenger: 75 kg

IATA-packing instructions - Cargo: 203

IATA-max. quantity - Cargo: 150 kg

14.5. Environmental hazards No

ENVIRONMENTALLY HAZARDOUS:

14.6. Special precautions for user

Warning: flammable gases.

14.7. Maritime transport in bulk as
instruments not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 28, Entry 40, Entry 75

2010/75/EU (VOC): 90 % (524,25 g/L)

2004/42/EC (VOC): 90 % (524,25 g/L)

Information according to 2012/18/EU (SEVESO III): P3a FLAMMABLE AEROSOLS

Additional information

To follow: 850/2004/EC, 79/117/EEC, 689/2008/EC, 2008/47/EC, Aerosol Directive (75/324/)

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,5,6,7,8,9,10,11,12,15,16.

Abbreviations and acronyms

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

Safety Data Sheet

Emirates lubricants

Revision date: 17.07.2023

Welding Protection Spray

Page 11 of 11

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ASTM - American Society for the Testing of Materials; ATE - Acute Toxicity Estimates; bw - Body weight; CAO - Cargo Aircraft Only; CAS - Chemical Abstracts Service; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DNEL - Derived No-Effect Level; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); EG - European Union; EN - European standards; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISO - International Organisation for Standardization; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n;o;s; - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; OECD - Organization for Economic Co-operation and Development; PBT - Persistent, Bioaccumulative and Toxic substance; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulation concerning the International Carriage of Dangerous Goods by Rail; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.

Further Information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)