

Safety Data Sheet

Revision date: 24.10.2023

Emirates lubricants

KO 7 C

Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

KO 7 C

UFI: U9U1-370D-120H-753F

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Corrosion inhibitor.

1.3. Details of the supplier of the safety data sheet**Manufacturer**

Company name: Emirates lubricants

Street: Ras Al khaimah

Place: United Arab Emirates

Telephone: +971 55 105 2851 +971 52 660 6888

e-mail: info@emirateslubricant.

Contact person: Application Technology

Internet: www.emirateslubricant.com

Responsible Department: Emirates lubricants Application Technology

1.4. Emergency telephone number: +971 52 660 6888 - This number is serviced during office hours.**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****GB CLP Regulation**

Asp. Tox. 1; H304

Full text of hazard statements: see SECTION 16.

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

2.2. Label elements**GB CLP Regulation Hazard components for labelling**

Distillates (petroleum), hydrotreated light naphthenic

Signal word: Danger**Pictograms:****Hazard statements**

H304 May be fatal if swallowed and enters airways.

Safety Data Sheet

Emirates lubricants

Revision date: 24.10.2023

KO 7 C

Page 2 of 12

Precautionary statements

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
 P331 Do NOT induce vomiting.
 P405 Store locked up.
 P501 Dispose of contents/container to a waste disposal system.

Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

Additional advice on labelling

Product is classified and labelled in accordance with EC regulations or the corresponding national laws.

2.3. Other hazards

Harmful by inhalation and if swallowed.
 Prolonged/repetitive skin contact may cause skin defatting or dermatitis.
 Do not allow uncontrolled leakage of product into the environment.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Chemical characterization**

Mixture of mineral oil raffinates and additives.

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
64742-53-6	Distillates (petroleum), hydrotreated light naphthenic			70 - 90 %
	265-156-6		01-2119480375-34	
	Asp. Tox. 1; H304			
68603-10-1	Barium salt of organic acids			< 5 %
	271-637-1			
	Acute Tox. 4, Acute Tox. 4; H332 H302			
111-76-2	Butylglycole			< 5 %
	203-905-0			
	Acute Tox. 3, Acute Tox. 3, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2; H331 H311 H302 H315 H319			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
64742-53-6	265-156-6	Distillates (petroleum), hydrotreated light naphthenic	70 - 90 %

Safety Data Sheet

	dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg		
68603-10-1	271-637-1	Barium salt of organic acids	< 5 %
	inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); oral: ATE = 500 mg/kg		
111-76-2	203-905-0	Butylglycole	< 5 %
	inhalation: LC50 = 523 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); dermal: LD50 = > 2000 mg/kg; oral: LD50 = 1414 mg/kg		

Further Information

DMSO-Extrakt < 3 %, IP 346.

Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

Emirates lubricants

Revision date: 24.10.2023

KO 7 C

Page 3 of 12

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

After inhalation

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. In case of skin irritation, seek medical treatment.

After contact with eyes

Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Seek medical attention if problems persist.

After ingestion

Do NOT induce vomiting.

Rinse mouth thoroughly with water. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

after ingestion: Coughing. shortage of breath. Vomiting. fever.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Where appropriate artificial ventilation. Regulation of the blood circulation, possible shock treatment. Subsequent observance for pneumonia and lung oedema.

SECTION 5: Firefighting measures

Safety Data Sheet

5.1. Extinguishing media

Suitable extinguishing media

Foam. Extinguishing powder. Carbon dioxide (CO₂). Atomized water.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO₂). Nitrogen oxides (NO_x). carbon black.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray jet to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

High slip hazard because of leaking or spilled product. Remove all sources of ignition. Wear breathing apparatus if exposed to vapours/dusts/aerosols. Avoid contact with skin, eyes and clothes.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Prevent spread over a wide area (e.g. by containment or oil barriers).

6.3. Methods and material for containment and cleaning up

Emirates lubricants

Revision date: 24.10.2023

KO 7 C

Page 4 of 12

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Section 12: Ecological Information (non-mandatory)

Disposal: see section 13

SECTION 7: Handling and storage

Safety Data Sheet

7.1. Precautions for safe handling

Advice on safe handling

Work in well-ventilated zones or use proper respiratory protection. Avoid oil mist. If handled uncovered, arrangements with local exhaust ventilation have to be used. Avoid contact with skin, eyes and clothes.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Use only antistatically equipped (spark-free) tools.

Advice on general occupational hygiene

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorption of humidity. Keep/Store only in original container.

Hints on joint storage

Keep away from food, drink and animal feedingsuffs.
Keep away from: Oxidising agent, strong.

Further information on storage conditions

Keep away from sources of ignition - No smoking.
Protect against: UV-radiation/sunlight. frost. heat. Humidity. Water. Recommended storage temperature: 5 - 40°C

7.3. Specific end use(s)

Further information: see technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
111-76-2	2-Butoxyethanol	25	123		TWA (8 h)	WEL
		50	246		STEL (15 min)	WEL

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
111-76-2	2-Butoxyethanol	butoxyacetic acid (creatinine)	240 mmol/mol	urine	Post shift

Safety Data Sheet

Emirates lubricants

Revision date: 24.10.2023

KO 7 C

Page 5 of
12

Emirates lubricants

Revision date: 24.10.2023

KO 7 C

Page 6 of
12

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
64742-53-6	Distillates (petroleum), hydrotreated light naphthenic			
Worker DNEL, long-term		inhalation	systemic	2,73 mg/m ³
Worker DNEL, long-term		inhalation	local	5,58 mg/m ³
Worker DNEL, long-term		dermal	systemic	0,97 mg/kg bw/day
Consumer DNEL, long-term		inhalation	local	1,19 mg/m ³
Consumer DNEL, long-term		oral	systemic	0,74 mg/kg bw/day
68603-10-1	Barium salt of organic acids			
Worker DNEL, long-term		inhalation	systemic	0,23 mg/m ³
Worker DNEL, long-term		dermal	systemic	1,7 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	0,06 mg/m ³
Consumer DNEL, long-term		dermal	systemic	0,8 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,8 mg/kg bw/day
111-76-2	Butylglycole			
Worker DNEL, acute		inhalation	systemic	1091 mg/m ³
Worker DNEL, acute		inhalation	local	246 mg/m ³
Consumer DNEL, long-term		inhalation	systemic	59 mg/m ³
Consumer DNEL, acute		inhalation	systemic	426 mg/m ³
Consumer DNEL, acute		inhalation	local	147 mg/m ³
Consumer DNEL, long-term		oral	systemic	6,3 mg/kg bw/day
Consumer DNEL, acute		oral	systemic	26,7 mg/kg bw/day
Worker DNEL, long-term		dermal	systemic	75 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	98 mg/m ³

Safety Data Sheet

PNEC values

CAS No	Substance	
Environmental compartment		Value
64742-53-6	Distillates (petroleum), hydrotreated light naphthenic	
Secondary poisoning		9,33 mg/kg
68603-10-1	Barium salt of organic acids	
Freshwater		0,1 mg/l
Freshwater (intermittent releases)		1 mg/l
Marine water		0,01 mg/l
Freshwater sediment		4270 mg/kg
Marine sediment		427 mg/kg
Secondary poisoning		66,7 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/l
Soil		854 mg/kg
111-76-2	Butylglycole	
Freshwater		8,8 mg/l
Freshwater (intermittent releases)		26,4 mg/l
Marine water		0,88 mg/l
Freshwater sediment		34,6 mg/kg
Marine sediment		3,46 mg/kg
Secondary poisoning		20 mg/kg
Micro-organisms in sewage treatment plants (STP)		463 mg/l
Soil		2,33 mg/kg

Additional advice on limit values

Recommended limit value for oil mist

TWA: 5 mg/m³

STEL: 10 mg/m³

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

Individual protection measures, such as personal protective equipment Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): EN 166

Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): EN ISO 374

Safety Data Sheet

Duration of wearing with permanent contact: 480 min
 Suitable material: NBR (Nitrile rubber).
 Thickness of glove material: 0.7 mm.

Wearing time with occasional contact (splashes): 30 min
 Suitable material: NBR (Nitrile rubber).

Emirates lubricants

KO 7 C

Revision date: 24.10.2023

Page 7 of 12

Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Breathing protection with filter against organic gases and vapours type A - boiling point > 65°C: A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	liquid
Colour:	brown
Odour:	like: mineral oil.
Odour threshold:	not determined

Test method

Melting point/freezing point:	No data available
Boiling point or initial boiling point and boiling range:	> 200 °C
Flammability:	No data available
Lower explosion limits:	0,6 vol. %
Upper explosion limits:	6,5 vol. %
Flash point:	>130 °C DIN EN ISO 2592
Auto-ignition temperature:	> 220 °C
Decomposition temperature:	No data available
pH-Value:	not applicable
Viscosity / kinematic: (at 40 °C)	7,3 mm²/s ASTM D 7042
Water solubility:	virtually insoluble
Solubility in other solvents	
No data available	
Partition coefficient n-octanol/water:	No data available

Safety Data Sheet

Vapour pressure:	No data available
Density (at 15 °C):	0,880 g/cm³ DIN 51757
Relative vapour density:	No data available

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

No data available

Self-ignition temperature

Solid:

No data available

Gas:

No data available

Oxidizing properties

No data available

Other safety characteristics

Evaporation rate:

No data available

Pour point:

-24 °C ASTM D 7346

SECTION 10: Stability and reactivity

Emirates lubricants

Revision date: 24.10.2023

KO 7 C

Page 8 of 12

10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature. **10.3. Possibility of hazardous reactions** No known hazardous reactions.

10.4. Conditions to avoid

Keep away from sources of ignition - No smoking.

Do not overheat to avoid decomposition by heat.

10.5. Incompatible materials

Reacts with: Oxidising agent, strong.

10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO₂). Nitrogen oxides (NO_x). carbon black.
No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) 7695,5 mg/kg; ATE (dermal) 6250,0 mg/kg; ATE (inhalation vapour) 49,11 mg/l; ATE (inhalation dust/mist) 7,813 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method

Safety Data Sheet

Emirates lubricants

Revision date: 24.10.2023

KO 7 C

Page 9 of
12

64742-53-6	Distillates (petroleum), hydrotreated light naphthe ic				
	oral	LD50 mg/kg	> 5000	Rat	Study report (1982) OECD Guideline 401
	dermal	LD50 mg/kg	> 5000	Rabbit	Study report (1982) OECD Guideline 402
68603-10-1	Barium salt of organic acids				
	oral	ATE mg/kg	500		
	inhalation vapour	ATE	11 mg/l		
	inhalation dust/mist	ATE	1,5 mg/l		
111-76-2	Butylglycole				
	oral	LD50 mg/kg	1414	Guinea pig	Study report (1994) OECD Guideline 401
	dermal	LD50 mg/kg	> 2000	Rat	Study report (1993) OECD Guideline 402
	inhalation (4 h) vapour	LC50	523 mg/l	Rat	Study report (1980) OECD Guideline 403
	inhalation dust/mist	ATE	0,5 mg/l		

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Repeated exposure may cause skin dryness or cracking.

Aspiration hazard

May be fatal if swallowed and enters airways.

11.2. Information on other hazards**Endocrine disrupting properties**

not applicable

SECTION 12: Ecological information**12.1. Toxicity**

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method

Safety Data Sheet

64742-53-6	Distillates (petroleum), hydrotreated light naphthe ic					
	Acute fish toxicity	LL50 mg/l	> 100	96 h	Pimephales promelas	Study report (1995) OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	> 100			
	Fish toxicity	NOEC mg/l	>= 1000	14 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010) The aquatic toxicity was estimated by a
68603-10-1	Barium salt of organic acids					
	Acute fish toxicity	LL50 mg/l	> 100	96 h	Oncorhynchus mykiss	Study report (2012) OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	> 100	72 h	Desmodesmus subspicatus	Study report (2012) OECD Guideline 201
	Acute crustacea toxicity	EL50 mg/l	> 100	48 h	Daphnia magna	Study report (2012) OECD Guideline 202
	Acute bacteria toxicity	(EC50 mg/l)	> 1000	3 h	activated sludge of a predominantly domestic sewage	Study report (2012) OECD Guideline 209
111-76-2	Butylglycole					
	Acute fish toxicity	LC50 mg/l	1474	96 h	Oncorhynchus mykiss	Toxicol Mech Meth 12, 255-63 (2002) OECD Guideline 203
	Acute algae toxicity	ErC50	911 mg/l	72 h	Pseudokirchneriella subcapitata	Toxicol Mech Meth 12, 255-63 (2002) OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	1550	48 h	Daphnia magna	Toxicol Mech Meth 12, 255-63 (2002) OECD Guideline 202
	Fish toxicity	NOEC mg/l	> 100	21 d	Danio rerio	Toxicol Mech Meth 12, 255-63 (2002) OECD Guideline 204
	Crustacea toxicity	NOEC	100 mg/l	21 d	Daphnia magna	Toxicol Mech Meth 12, 255-63 (2002) OECD Guideline 211

12.2. Persistence and degradability

Not easily bio-degradable (according to OECD-criteria). Do not allow to enter into surface water or drains.

12.3. Bioaccumulative potential

Mixture not tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
68603-10-1	Barium salt of organic acids	> 10000000000
111-76-2	Butylglycole	0,81

12.4. Mobility in soil

Due to its low solubility in water the product is almost completely mechanically separated in biological waste water treatment plants.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria .

Safety Data Sheet

Emirates lubricants

Revision date: 24.10.2023

KO 7 C

Page 10 of
12

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No data available

Further information

Do not allow uncontrolled leakage of product into the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

List of Wastes Code - residues/unused products

120107 WASTES FROM SHAPING AND PHYSICAL AND MECHANICAL SURFACE TREATMENT OF METALS AND PLASTICS; wastes from shaping and physical and mechanical surface treatment of metals and plastics; mineral-based machining oils free of halogens (except emulsions and solutions); hazardous waste

Contaminated packaging

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Dispose of waste according to applicable legislation. Packing which cannot be properly cleaned must be thrown away.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: -

14.2. UN proper shipping name: -

14.3. Transport hazard class(es): -

14.4. Packing group: -

Inland waterways transport (ADN)

14.1. UN number or ID number: -

14.2. UN proper shipping name: -

14.3. Transport hazard class(es): -

14.4. Packing group: -

Marine transport (IMDG)

14.1. UN number or ID number: -

14.2. UN proper shipping name: -

14.3. Transport hazard class(es): -

14.4. Packing group: -

Emirates lubricants

Revision date: 24.10.2023

KO 7 C

Page 11 of 12

Safety Data Sheet

Air transport (ICAO-TI/IATA-DGR)

- 14.1. UN number or ID number: -
 14.2. UN proper shipping name: -
 14.3. Transport hazard class(es): -
 14.4. Packing group: -

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

Other applicable information

No dangerous good in sense of these transport regulations.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28

National regulatory information

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 7,8,9,11,15.

Abbreviations and acronyms

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ASTM - American Society for the Testing of Materials; ATE - Acute Toxicity Estimates; bw - Body weight; CAO - Cargo Aircraft Only; CAS - Chemical Abstracts Service; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DNEL - Derived No-Effect Level; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); EG - European Union; EN - European standards; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISO - International Organisation for Standardization; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n;o;s - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; OECD - Organization for Economic Co-operation and Development; PBT - Persistent, Bioaccumulative and Toxic substance; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulation concerning the International Carriage of Dangerous Goods by Rail; RQ -

Safety Data Sheet**Emirates lubricants**

Revision date: 24.10.2023

KO 7 C

Page 12 of
12

Reportable Quantity; SADT - Self- Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Asp. Tox. 1; H304	Calculation method

Relevant H and EUH statements (number and full text)

H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)