

# Safety Data Sheet

**Emirates lubricants**

Revision date: 31.01.2023

Flushing Oil Super

Page 1 of 12

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Flushing Oil Super

UFI: 5W9A-E2K4-1207-6H71

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

Engine cleaning agent.

**1.3. Details of the supplier of the safety data sheet****Manufacturer**

Company name: Emirates lubricants

Street: Ras Al khaimah

Place: United Arab Emirates

Telephone: +971 55 105 2851 +971 52 660 6888

e-mail: info@emirateslubricant

Contact person: Application Technology

Internet: www.emirateslubricant.com

Responsible Department: Emirates lubricants Application Technology

**1.4. Emergency telephone number:** +971 52 660 6888 - This number is serviced during office hours.**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****GB CLP Regulation**

Asp. Tox. 1; H304

Eye Irrit. 2; H319

Skin Sens. 1; H317

Full text of hazard statements: see SECTION 16.

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

**2.2. Label elements****GB CLP Regulation Hazard components for labelling**

Distillates (petroleum), heavy hydrocracked; Base oil unspecified

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified

Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts

## Safety Data Sheet

## Emirates lubricants

Revision date: 31.01.2023

Flushing Oil Super

Page 2 of  
12

Signal word:

Danger



Pictograms:

## Hazard statements

- H304 May be fatal if swallowed and enters airways.  
 H317 May cause an allergic skin reaction.  
 H319 Causes serious eye irritation.

## Precautionary statements

- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
 P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.  
 P331 Do NOT induce vomiting.  
 P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.  
 P302+P352 IF ON SKIN: Wash with plenty of water.  
 P333+P313 If skin irritation or rash occurs: Get medical advice/attention.  
 P405 Store locked up.  
 P501 Dispose of contents/container to industrial incineration plant.

## Additional advice on labelling

The product is classified and labelled according to EC directives or corresponding national laws.

**2.3. Other hazards**

- Prolonged/repetitive skin contact may cause skin defatting or dermatitis.  
 Spilled product must not leak into the ground.  
 Do not allow uncontrolled leakage of product into the environment.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures**

## Hazardous components

| CAS No      | Chemical name                                                                    |          |                  | Quantity    |
|-------------|----------------------------------------------------------------------------------|----------|------------------|-------------|
|             | EC No                                                                            | Index No | REACH No         |             |
|             | Classification (GB CLP Regulation)                                               |          |                  |             |
| 64741-76-0  | Distillates (petroleum), heavy hydrocracked; Base oil unspecified                |          |                  | 60 - < 80 % |
|             | 265-077-7                                                                        |          | 01-2119486951-26 |             |
|             | Asp. Tox. 1; H304                                                                |          |                  |             |
| 64742-54-7  | Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified    |          |                  | 30 - < 40 % |
|             | 265-157-1                                                                        |          | 01-2119484627-25 |             |
|             | Asp. Tox. 1; H304                                                                |          |                  |             |
| 722503-68-6 | Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts |          |                  | 1 - < 2.5 % |

## Safety Data Sheet

## Emirates lubricants

Page 3 of  
12

Revision date: 31.01.2023

Flushing Oil Super

|            |                                                                                        |  |                  |         |
|------------|----------------------------------------------------------------------------------------|--|------------------|---------|
|            | 682-816-2                                                                              |  | 01-2119985162-35 |         |
|            | Skin Sens. 1, Aquatic Chronic 4; H317 H413                                             |  |                  |         |
| 84605-29-8 | Phosphorodithioic acid, mixed O,O-bis (1,3-dimethylbutyl and iso-Pr)esters, zinc salts |  |                  | < 1,5 % |
|            | 283-392-8                                                                              |  | 01-2119493626-26 |         |
|            | Skin Irrit. 2, Eye Dam. 1, Aquatic Chronic 2; H315 H318 H411                           |  |                  |         |

Full text of H and EUH statements: see section 16.

**Specific Conc. Limits, M-factors and ATE**

| CAS No     | EC No     | Chemical name                                                                                    | Quantity    |
|------------|-----------|--------------------------------------------------------------------------------------------------|-------------|
|            |           | Specific Conc. Limits, M-factors and ATE                                                         |             |
| 64741-76-0 | 265-077-7 | Distillates (petroleum), heavy hydrocracked; Base oil unspecified                                | 60 - < 80 % |
|            |           | inhalation: LC50 = > 5000 mg/l (vapours); dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg |             |
| 64742-54-7 | 265-157-1 | Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified                    | 30 - < 40 % |
|            |           | dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg                                           |             |
| 84605-29-8 | 283-392-8 | Phosphorodithioic acid, mixed O,O-bis (1,3-dimethylbutyl and iso-Pr)esters, zinc salts           | < 1,5 %     |
|            |           | inhalation: LC50 = > 2,3 mg/l (vapours); dermal: LD50 = > 2002 mg/kg; oral: LD50 = 4468 mg/kg    |             |

**Further Information**

DMSO-Extrakt &lt; 3 %, IP 346.

Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

**SECTION 4: First aid measures****4.1. Description of first aid measures****General information**

Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

**After inhalation**

Move victim to fresh air. Put victim at rest and keep warm. In case of breathing difficulties administer oxygen. If victim is at risk of losing consciousness, position and transport on their side.

**After contact with skin**

After contact with skin, wash immediately with plenty of water and soap. In case of skin irritation, seek medical treatment.

**After contact with eyes**

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

**After ingestion**

Do NOT induce vomiting.

Rinse mouth thoroughly with water. Call a physician immediately.

## Safety Data Sheet

### **4.2. Most important symptoms and effects, both acute and delayed**

No information available.

### **4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptomatically.

## **SECTION 5: Firefighting measures**

### **5.1. Extinguishing media**

#### **Suitable extinguishing media**

Foam. Extinguishing powder. Carbon dioxide (CO<sub>2</sub>). Atomized water.

#### **Unsuitable extinguishing media**

High power water jet.

### **5.2. Special hazards arising from the substance or mixture**

In case of fire may be liberated: Carbon monoxide. Carbon dioxide (CO<sub>2</sub>). Sulfur oxides. Phosphorus oxides. Nitrogen oxides (NO<sub>x</sub>). carbon black.

## **Emirates lubricants**

Revision date: 31.01.2023

Flushing Oil Super

Page 4 of 12

### **5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus.

#### **Additional information**

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray/stream to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

## **SECTION 6: Accidental release measures**

### **6.1. Personal precautions, protective equipment and emergency procedures**

#### **General advice**

High slip hazard because of leaking or spilled product. Remove all sources of ignition. Wear breathing apparatus if exposed to vapours/dusts/aerosols. Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work

### **6.2. Environmental precautions**

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Prevent spread over a wide area (e.g. by containment or oil barriers).

### **6.3. Methods and material for containment and cleaning up**

#### **Other information**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Collect in closed containers for disposal. Clean contaminated articles and floor according to the environmental legislation.

### **6.4. Reference to other sections**

Safe handling: see section 7  
Personal protection equipment: see section 8  
Section 12: Ecological Information (non-mandatory)  
Disposal: see section 13

## **SECTION 7: Handling and storage**

# Safety Data Sheet

## Emirates lubricants

Revision date: 31.01.2023

Flushing Oil Super

Page 5 of  
12

### 7.1. Precautions for safe handling

#### Advice on safe handling

Work in well-ventilated zones or use proper respiratory protection. Avoid oil mist. If handled uncovered, arrangements with local exhaust ventilation have to be used. Avoid contact with skin, eyes and clothes.

#### Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

#### Advice on general occupational hygiene

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorption of humidity. Keep container tightly closed in a cool place. Keep/Store only in original container.

#### Hints on joint storage

Keep away from food, drink and animal feedingstuffs.

Keep away from: Oxidizing agents.

#### Further information on storage conditions

Recommended storage temperature: 5 - 40°C

Protect against: heat. UV-radiation/sunlight. frost.

### 7.3. Specific end use(s)

Further information: see technical data sheet.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### DNEL/DMEL values

| DNEL-DNEL values         |                                                                               |                |          |                   |
|--------------------------|-------------------------------------------------------------------------------|----------------|----------|-------------------|
| CAS No                   | Substance                                                                     |                |          |                   |
| DNEL type                |                                                                               | Exposure route | Effect   | Value             |
| 64741-76-0               | Distillates (petroleum), heavy hydrocracked; Base oil unspecified             |                |          |                   |
| Worker DNEL, long-term   |                                                                               | inhalation     | systemic | 2,73 mg/m³        |
| Worker DNEL, long-term   |                                                                               | inhalation     | local    | 5,58 mg/m³        |
| Worker DNEL, long-term   |                                                                               | dermal         | systemic | 0,97 mg/kg bw/day |
| Consumer DNEL, long-term |                                                                               | inhalation     | local    | 1,19 mg/m³        |
| Consumer DNEL, long-term |                                                                               | oral           | systemic | 0,74 mg/kg bw/day |
| 64742-54-7               | Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified |                |          |                   |
| Worker DNEL, long-term   |                                                                               | inhalation     | systemic | 2,73 mg/m³        |
| Worker DNEL, long-term   |                                                                               | inhalation     | local    | 5,58 mg/m³        |

## Safety Data Sheet

|                          |                                                                                        |            |          |                        |
|--------------------------|----------------------------------------------------------------------------------------|------------|----------|------------------------|
| Worker DNEL, long-term   |                                                                                        | dermal     | systemic | 0,97 mg/kg bw/day      |
| Consumer DNEL, long-term |                                                                                        | inhalation | local    | 1,19 mg/m <sup>3</sup> |
| Consumer DNEL, long-term |                                                                                        | oral       | systemic | 0,74 mg/kg bw/day      |
| 84605-29-8               | Phosphorodithioic acid, mixed O,O-bis (1,3-dimethylbutyl and iso-Pr)esters, zinc salts |            |          |                        |
| Worker DNEL, long-term   |                                                                                        | dermal     | systemic | 12,1 mg/kg bw/day      |
| Worker DNEL, long-term   |                                                                                        | inhalation | systemic | 8,31 mg/m <sup>3</sup> |
| Consumer DNEL, long-term |                                                                                        | oral       | systemic | 0,24 mg/kg bw/day      |
| Consumer DNEL, long-term |                                                                                        | inhalation | systemic | 2,11 mg/m <sup>3</sup> |
| Consumer DNEL, long-term |                                                                                        | dermal     | systemic | 6,1 mg/kg bw/day       |

## Safety Data Sheet

### PNEC values

| CAS No                                           | Substance                                                                              |             |
|--------------------------------------------------|----------------------------------------------------------------------------------------|-------------|
| Environmental compartment                        |                                                                                        | Value       |
| 64741-76-0                                       | Distillates (petroleum), heavy hydrocracked; Base oil unspecified                      |             |
| Secondary poisoning                              |                                                                                        | 9,33 mg/kg  |
| 64742-54-7                                       | Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified          |             |
| Secondary poisoning                              |                                                                                        | 9,33 mg/kg  |
| 84605-29-8                                       | Phosphorodithioic acid, mixed O,O-bis (1,3-dimethylbutyl and iso-Pr)esters, zinc salts |             |
| Freshwater                                       |                                                                                        | 0,004 mg/l  |
| Freshwater (intermittent releases)               |                                                                                        | 0,045 mg/l  |
| Marine water                                     |                                                                                        | 0,0046 mg/l |
| Freshwater sediment                              |                                                                                        | 0,022 mg/kg |
| Marine sediment                                  |                                                                                        | 0,002 mg/kg |
| Secondary poisoning                              |                                                                                        | 10,67 mg/kg |
| Micro-organisms in sewage treatment plants (STP) |                                                                                        | 100 mg/l    |
| Soil                                             |                                                                                        | 0,002 mg/kg |

### Additional advice on limit values

TWA: 5 mg/m<sup>3</sup> oil mist

STEL: 10 mg/m<sup>3</sup> oil mist

The product does not contain any relevant quantities of substances with legally established exposure limitation.

### 8.2. Exposure controls



#### Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

#### Individual protection measures, such as personal protective equipment Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): EN 166

#### Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): EN ISO 374

Duration of wearing with permanent contact: 480

min Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.7 mm.

Wearing time with occasional contact (splashes): 30 min

Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

## Safety Data Sheet

### Emirates lubricants

Revision date: 31.01.2023

Flushing Oil Super

Page 8 of 14

#### Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

#### Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be

### Emirates lubricants

Revision date: 31.01.2023

Flushing Oil Super

Page 7 of 12

worn. Breathing protection with filter against organic gases and vapours type A - boiling point > 65°C: A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

|                  |                    |
|------------------|--------------------|
| Physical state:  | liquid             |
| Colour:          | brown              |
| Odour:           | like: mineral oil. |
| Odour threshold: | not determined     |

#### Test method

|                                                           |                          |
|-----------------------------------------------------------|--------------------------|
| Melting point/freezing point:                             | No data available        |
| Boiling point or initial boiling point and boiling range: | not determined           |
| Flammability:                                             | No data available        |
| Lower explosion limits:                                   | No data available        |
| Upper explosion limits:                                   | No data available        |
| Flash point:                                              | > 130 °C DIN EN ISO 2719 |
| Auto-ignition temperature:                                | not determined           |
| Decomposition temperature:                                | No data available        |
| pH-Value:                                                 | not determined           |
| Viscosity / kinematic:<br>(at 40 °C)                      | 8,9 mm²/s ASTM D 7042    |
| Water solubility:                                         | virtually insoluble      |
| Solubility in other solvents                              | not determined           |
| Partition coefficient n-octanol/water:                    | No data available        |
| Vapour pressure:                                          | No data available        |
| Density (at 15 °C):                                       | 0,860 g/cm³ DIN 51757    |
| Relative vapour density:                                  | No data available        |



## Safety Data Sheet

### 9.2. Other information

Explosive properties

No data available

Self-ignition temperature

Solid:

No data available

Gas:

No data available

### Other safety characteristics

Evaporation rate:

No data available

Solid content:

No data available

Pour point:

No data available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

### 10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

### 10.3. Possibility of hazardous reactions

No known hazardous reactions.

### 10.4. Conditions to avoid

Do not overheat to avoid decomposition by heat.

Refer to chapter 7 No further action is necessary.

### 10.5. Incompatible materials

Reacts with: Oxidizing agents, strong. Acid.

### 10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon monoxide. Carbon dioxide (CO<sub>2</sub>). Sulfur oxides. Phosphorus oxides.

Nitrogen oxides (NO<sub>x</sub>). carbon black.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in GB CLP Regulation

#### Acute toxicity

Based on available data, the classification criteria are not met.

No data available

Mixture not tested.

| CAS No     | Chemical name                                                                 |                   |         |                     |                    |
|------------|-------------------------------------------------------------------------------|-------------------|---------|---------------------|--------------------|
|            | Exposure route                                                                | Dose              | Species | Source              | Method             |
| 64741-76-0 | Distillates (petroleum), heavy hydrocracked; Base oil unspecified             |                   |         |                     |                    |
|            | oral                                                                          | LD50 > 5000 mg/kg | Rat     | Study report (1982) | OECD Guideline 401 |
|            | dermal                                                                        | LD50 > 5000 mg/kg | Rabbit  | Study report (1982) | OECD Guideline 402 |
|            | inhalation (4 h) vapour                                                       | LC50 > 5000 mg/l  | Rabbit  |                     |                    |
| 64742-54-7 | Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified |                   |         |                     |                    |

## Safety Data Sheet

## Emirates lubricants

Revision date: 31.01.2023

Flushing Oil Super

Page 10 of 14

|            |                                                                                        |               |        |        |                     |                    |
|------------|----------------------------------------------------------------------------------------|---------------|--------|--------|---------------------|--------------------|
|            | oral                                                                                   | LD50<br>mg/kg | > 5000 | Rat    | Study report (1982) | OECD Guideline 401 |
|            | dermal                                                                                 | LD50<br>mg/kg | > 5000 | Rabbit | Study report (1982) | OECD Guideline 402 |
| 84605-29-8 | Phosphorodithioic acid, mixed O,O-bis (1,3-dimethylbutyl and iso-Pr)esters, zinc salts |               |        |        |                     |                    |
|            | oral                                                                                   | LD50<br>mg/kg | 4468   | Rat    | Study report (1985) | OECD Guideline 401 |
|            | dermal                                                                                 | LD50<br>mg/kg | > 2002 | Rat    | Study report (1985) | OECD Guideline 402 |
|            | inhalation (4 h) vapour                                                                | LC50<br>mg/l  | > 2,3  | Rat    | Study report        | OECD Guideline 403 |

**Irritation and corrosivity**

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Irritant effect on the skin: Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

**Sensitising effects**

May cause an allergic skin reaction. (Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts)

**Carcinogenic/mutagenic/toxic effects for reproduction** Based

on available data, the classification criteria are not met.

**STOT-single exposure**

Based on available data, the classification criteria are not met.

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

## Safety Data Sheet

## Emirates lubricants

Revision date: 31.01.2023

Flushing Oil Super

Page 11 of 14

**Aspiration hazard**

May be fatal if swallowed and enters airways.

**Specific effects in experiment on an animal**

No data available

**11.2. Information on other hazards****Endocrine disrupting properties**

not applicable

**SECTION 12: Ecological information****12.1. Toxicity**

Based on available data, the classification criteria are not met.

No data available

Mixture not tested.

| CAS No     | Chemical name                                                                          |                     |           |                                                   |                                   |                                         |
|------------|----------------------------------------------------------------------------------------|---------------------|-----------|---------------------------------------------------|-----------------------------------|-----------------------------------------|
|            | Aquatic toxicity                                                                       | Dose                | [h]   [d] | Species                                           | Source                            | Method                                  |
| 64741-76-0 | Distillates (petroleum), heavily hydrocracked; Base oil unspecified                    |                     |           |                                                   |                                   |                                         |
|            | Acute fish toxicity                                                                    | LL50 > 100 mg/l     | 96 h      | Pimephales promelas                               | Study report (1995)               | OECD Guideline 203                      |
|            | Acute algae toxicity                                                                   | ErC50 > = 100 mg/l  | 72 h      | Algae                                             |                                   |                                         |
|            | Fish toxicity                                                                          | NOEC >= 1000 mg/l   | 14 d      | Oncorhynchus mykiss                               | CONCAWE, Brussels, Belgium (2010) | The aquatic toxicity was estimated by a |
| 64742-54-7 | Distillates (petroleum), hydroretreated heavily paraffinic; Baseoil - unspecified      |                     |           |                                                   |                                   |                                         |
|            | Acute fish toxicity                                                                    | LL50 > 100 mg/l     | 96 h      | Pimephales promelas                               | Study report (1995)               | OECD Guideline 203                      |
|            | Acute algae toxicity                                                                   | ErC50 >100 mg/l     | 72 h      |                                                   |                                   |                                         |
|            | Fish toxicity                                                                          | NOEC >= 1000 mg/l   | 14 d      | Oncorhynchus mykiss                               | CONCAWE, Brussels, Belgium (2010) | The aquatic toxicity was estimated by a |
| 84605-29-8 | Phosphorodithioic acid, mixed O,O-bis (1,3-dimethylbutyl and iso-Pr)esters, zinc salts |                     |           |                                                   |                                   |                                         |
|            | Acute fish toxicity                                                                    | LL50 4,5 mg/l       | 96 h      | Oncorhynchus mykiss                               | Study report (2005)               | OECD Guideline 203                      |
|            | Acute algae toxicity                                                                   | ErC50 21 mg/l       | 72 h      | Desmodesmus subspicatus                           | Study report                      | OECD Guideline 201                      |
|            | Acute crustacea toxicity                                                               | EL50 23 mg/l        | 48 h      | Daphnia magna                                     | Study report (2005)               | OECD Guideline 202                      |
|            | Crustacea toxicity                                                                     | NOEC 0,4 mg/l       | 21 d      | Daphnia magna                                     | Study report (2010)               | OECD Guideline 211                      |
|            | Acute bacteria toxicity                                                                | (EC50 > 10000 mg/l) | 3 h       | activated sludge of a domestic residential sewage | Study report (1994)               | OECD Guideline 209                      |

**12.2. Persistence and degradability**

## Safety Data Sheet

### Emirates lubricants

Revision date: 31.01.2023

Flushing Oil Super

Page 12 of 14

Not easily bio-degradable (according to OECD-criteria). Do not allow to enter into surface water or drains.

#### 12.3. Bioaccumulative potential

No data available

#### Partition coefficient n-octanol/water

| CAS No     | Chemical name                                                                          | Log Pow |
|------------|----------------------------------------------------------------------------------------|---------|
| 84605-29-8 | Phosphorodithioic acid, mixed O,O-bis (1,3-dimethylbutyl and iso-Pr)esters, zinc salts | 0,56    |

#### 12.4. Mobility in soil

Due to its low solubility in water the product is almost completely mechanically separated in biological waste water treatment plants.

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria.

#### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

#### 12.7. Other adverse effects

No data available

#### Further information

Do not allow uncontrolled leakage of product into the environment.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

##### Disposal recommendations

Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

##### List of Wastes Code - residues/unused products

130205 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; mineral-based non-chlorinated engine, gear and lubricating oils; hazardous waste

##### Contaminated packaging

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Dispose of waste according to applicable legislation. Packing which cannot be properly cleaned must be thrown away.

### SECTION 14: Transport information

#### Land transport (ADR/RID)

14.1. UN number or ID number: -

14.2. UN proper shipping name: -

14.3. Transport hazard class(es): -

14.4. Packing group: -

#### Inland waterways transport (ADN)

14.1. UN number or ID number: -

14.2. UN proper shipping name: -

14.3. Transport hazard class(es): -

14.4. Packing group: -

#### Marine transport (IMDG)

14.1. UN number or ID number: -

14.2. UN proper shipping name: -

14.3. Transport hazard class(es): -

14.4. Packing group: -

#### Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: -

## Safety Data Sheet

**14.2. UN proper shipping name:** -

**14.3. Transport hazard class(es):** -

**14.4. Packing group:** -

### Emirates lubricants

Revision date: 31.01.2023

Flushing Oil Super

Page 11 of 12

#### **14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

#### **14.6. Special precautions for user**

Unless specified otherwise, general measures for safe transport must be followed.

#### **14.7. Maritime transport in bulk according to IMO instruments**

not applicable

#### **Other applicable information**

No dangerous good in sense of these transport regulations.

### SECTION 15: Regulatory information

#### **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

##### **EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28

##### **National regulatory information**

Water hazard class (D): 1 - slightly hazardous to water

#### **15.2. Chemical safety assessment**

Chemical safety assessments for substances in this mixture were not carried out.

### SECTION 16: Other information

#### **Changes**

This data sheet contains changes from the previous version in section(s): 2,4,6,7,9,11,12,15,16.

#### **Abbreviations and acronyms**

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ASTM - American Society for the Testing of Materials; ATE - Acute Toxicity Estimates; bw - Body weight; CAO - Cargo Aircraft Only; CAS - Chemical Abstracts Service; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DNEL - Derived No-Effect Level; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); EG - European Union; EN - European standards; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISO - International Organisation for Standardization; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n;o;s; - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; OECD - Organization for Economic Co-operation and Development; PBT - Persistent, Bioaccumulative and Toxic substance; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of

**Safety Data Sheet****Emirates lubricants**

Revision date: 31.01.2023

Flushing Oil Super

Page 14 of 14

Chemicals; RID -Regulation concerning the International Carriage of Dangerous Goods by Rail; RQ - Reportable Quantity; SADT - Self- Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

**Classification for mixtures and used evaluation method according to GB CLP Regulation**

| Classification     | Classification procedure |
|--------------------|--------------------------|
| Asp. Tox. 1; H304  | Calculation method       |
| Eye Irrit. 2; H319 | Calculation method       |
| Skin Sens. 1; H317 | Calculation method       |

**Relevant H and EUH statements (number and full text)**

|      |                                                         |
|------|---------------------------------------------------------|
| H304 | May be fatal if swallowed and enters airways.           |
| H315 | Causes skin irritation.                                 |
| H317 | May cause an allergic skin reaction.                    |
| H318 | Causes serious eye damage.                              |
| H319 | Causes serious eye irritation.                          |
| H411 | Toxic to aquatic life with long lasting effects.        |
| H413 | May cause long lasting harmful effects to aquatic life. |

**Further Information**

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*