

# Safety Data Sheet

Revision date: 14.08.2024

**Emirates lubricants**

FoodProof XHF 15 S

Page 1 of 12

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

FoodProof XHF 15 S

UFI: 36GR-S3YH-0204-8540

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Lubricant and additive.

For industrial purposes only.

### 1.3. Details of the supplier of the safety data sheet

#### Manufacturer

|                         |                                            |                  |
|-------------------------|--------------------------------------------|------------------|
| Company name:           | Emirates lubricants                        |                  |
| Street:                 | Ras Al khaimah                             |                  |
| Place:                  | United Arab Emirates                       |                  |
| Telephone:              | +971 55 105 2851                           | +971 52 660 6888 |
| E-mail:                 | info@emirateslubricant.                    |                  |
| Contact person:         | Application Technology                     |                  |
| Internet:               | www.emirateslubricant.com                  |                  |
| Responsible Department: | Emirates lubricants Application Technology |                  |

### 1.4. Emergency telephone number:

+971 52 660 6888 - This number is serviced during office hours.

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### GB CLP Regulation

Asp. Tox. 1; H304  
Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

This preparation is hazardous in the sense of regulation (EC) No 1272/2008 [GHS].

### 2.2. Label elements

#### GB CLP Regulation

**Hazard components for labelling** Dec-1-  
ene, Trimers, hydrogenated  
1-Decene, Dimer, hydrogenated

## Safety Data Sheet

## Emirates lubricants

Revision date: 14.08.2024

FoodProof XHF 15 S

Page 2 of  
12

Signal word:

Danger



Pictograms:

## Hazard statements

H304 May be fatal if swallowed and enters airways.  
H412 Harmful to aquatic life with long lasting effects.

## Precautionary statements

P273 Avoid release to the environment.  
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.  
P331 Do NOT induce vomiting.  
P405 Store locked up.  
P501 Dispose of contents/container to an appropriate recycling or disposal facility.

## Additional advice on labelling

Product is classified and labelled in accordance with EC regulations or the corresponding national laws.

**2.3. Other hazards**

Prolonged/repetitive skin contact may cause skin defatting or dermatitis.  
Do not allow uncontrolled leakage of product into the environment.

If handled with proper care and at intended use, the product does not cause any harmful effects acc. to our experiences and available information.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures**

## Relevant ingredients

| CAS No      | Chemical name                        |          |                  | Quantity      |
|-------------|--------------------------------------|----------|------------------|---------------|
|             | EC No                                | Index No | REACH No         |               |
|             | Classification (GB CLP Regulation)   |          |                  |               |
| 157707-86-3 | Dec-1-ene, Trimers, hydrogenated     |          |                  | 60 - < 80 %   |
|             | 500-393-3                            |          |                  |               |
|             | Asp. Tox. 1; H304                    |          |                  |               |
| 68649-11-6  | 1-Decene, Dimer, hydrogenated        |          |                  | 10 - < 20 %   |
|             | 500-228-5                            |          | 01-2119493069-28 |               |
|             | Acute Tox. 4, Asp. Tox. 1; H332 H304 |          |                  |               |
| 128-37-0    | 2,6-Di-tert-butyl-4-methylphenol     |          |                  | 0.3 - < 0.5 % |
|             | 204-881-4                            |          | 01-2119480433-40 |               |

## Safety Data Sheet

## Emirates lubricants

Revision date: 14.08.2024

FoodProof XHF 15 S

Page 3 of  
12

|  |                                               |  |
|--|-----------------------------------------------|--|
|  | Aquatic Acute 1, Aquatic Chronic 1; H400 H410 |  |
|--|-----------------------------------------------|--|

Full text of H and EUH statements: see section 16.

**Specific Conc. Limits, M-factors and ATE**

| CAS No      | EC No     | Chemical name                                                                                      | Quantity      |
|-------------|-----------|----------------------------------------------------------------------------------------------------|---------------|
|             |           | Specific Conc. Limits, M-factors and ATE                                                           |               |
| 157707-86-3 | 500-393-3 | Dec-1-ene, Trimers, hydrogenated                                                                   | 60 - < 80 %   |
|             |           | dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg                                             |               |
| 68649-11-6  | 500-228-5 | 1-Decene, Dimer, hydrogenated                                                                      | 10 - < 20 %   |
|             |           | inhalation: LC50 = 900-5200 mg/l (vapours); dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg |               |
| 128-37-0    | 204-881-4 | 2,6-Di-tert-butyl-4-methylphenol                                                                   | 0.3 - < 0.5 % |
|             |           | dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 6000 mg/kg Aquatic Acute 1; H400: M=1                  |               |

**Further Information**

The product does not contain any dangerous substances with concentrations reaching or exceeding the limits acc. to 1272/2008 [GHS].

DMSO-Extract < 3 %; IP 346. Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

**SECTION 4: First aid measures****4.1. Description of first aid measures****General information**

Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

**After inhalation**

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist.

**After contact with skin**

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. In case of skin irritation, seek medical treatment.

**After contact with eyes**

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

**After ingestion**

Do NOT induce vomiting. Call a physician immediately.

Caution if victim vomits: Risk of aspiration!

**4.2. Most important symptoms and effects, both acute and delayed** The following symptoms may occur: Coughing, difficulties of breathing.**4.3. Indication of any immediate medical attention and special treatment needed**

First Aid, decontamination, treatment of symptoms.

**SECTION 5: Firefighting measures****5.1. Extinguishing media**

## Safety Data Sheet

**Suitable extinguishing media**

Carbon dioxide (CO<sub>2</sub>). Extinguishing powder. Water spray. alcohol resistant foam.

**Unsuitable extinguishing media**

High power water jet.

**5.2. Special hazards arising from the substance or mixture**

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO<sub>2</sub>). Nitrogen oxides (NO<sub>x</sub>). Sulfur oxides. carbon black.

**5.3. Advice for firefighters****Emirates lubricants**

Revision date: 14.08.2024

FoodProof XHF 15 S

Page 4 of 12

In case of fire: Wear self-contained breathing apparatus.

**Additional information**

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray jet to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures****General advice**

High slip hazard because of leaking or spilled product. Remove all sources of ignition. Wear breathing apparatus if exposed to vapours/dusts/aerosols. Avoid contact with skin, eyes and clothes.

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Prevent spread over a wide area (e.g. by containment or oil barriers).

**6.3. Methods and material for containment and cleaning up****Other information**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean contaminated articles and floor according to the environmental legislation.

**6.4. Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Section 12: Ecological Information (non-mandatory)

Disposal: see section 13

**SECTION 7: Handling and storage**

## Safety Data Sheet

### 7.1. Precautions for safe handling

#### Advice on safe handling

Work in well-ventilated zones or use proper respiratory protection. Avoid oil mist. If handled uncovered, arrangements with local exhaust ventilation have to be used. Avoid contact with skin, eyes and clothes.

#### Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

#### Advice on general occupational hygiene

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorption of humidity. Keep container tightly closed in a cool place. Keep/Store only in original container.

#### Hints on joint storage

Keep away from food, drink and animal feedingstuffs.

Keep away from: Oxidizing agent

#### Further information on storage conditions

Protect against: UV-radiation/sunlight. frost. heat.

Recommended storage temperature: 5 - 40°C

### 7.3. Specific end use(s)

Further information: see technical data sheet.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Exposure limits (EH40)

| CAS No   | Substance                  | ppm | mg/m <sup>3</sup> | fibres/ml | Category  | Origin |
|----------|----------------------------|-----|-------------------|-----------|-----------|--------|
| 128-37-0 | 2,6-Di-tert-butyl-p-cresol | -   | 10                |           | TWA (8 h) | WEL    |

#### DNEL/DMEL values

| CAS No                   | Substance                        | Exposure route | Effect   | Value                   |
|--------------------------|----------------------------------|----------------|----------|-------------------------|
| 68649-11-6               | 1-Decene, Dimer, hydrogenated    |                |          |                         |
| Worker DNEL, acute       |                                  | inhalation     | systemic | 60 mg/m <sup>3</sup>    |
| Consumer DNEL, acute     |                                  | inhalation     | systemic | 50 mg/m <sup>3</sup>    |
| 128-37-0                 | 2,6-Di-tert-butyl-4-methylphenol |                |          |                         |
| Consumer DNEL, long-term |                                  | inhalation     | systemic | 0,435 mg/m <sup>3</sup> |
| Consumer DNEL, long-term |                                  | dermal         | systemic | 0,25 mg/kg bw/day       |
| Consumer DNEL, long-term |                                  | oral           | systemic | 0,25 mg/kg bw/day       |
| Worker DNEL, long-term   |                                  | dermal         | systemic | 0,5 mg/kg bw/day        |

## Safety Data Sheet

## Emirates lubricants

Page 5 of  
12

Revision date: 14.08.2024

FoodProof XHF 15 S

|                        |            |          |                        |
|------------------------|------------|----------|------------------------|
| Worker DNEL, long-term | inhalation | systemic | 1,76 mg/m <sup>3</sup> |
|------------------------|------------|----------|------------------------|

**PNEC values**

| CAS No                                           | Substance                        |
|--------------------------------------------------|----------------------------------|
| Environmental compartment                        | Value                            |
| 128-37-0                                         | 2,6-Di-tert-butyl-4-methylphenol |
| Freshwater                                       | 0,000199 mg/l                    |
| Freshwater (intermittent releases)               | 0,00199 mg/l                     |
| Marine water                                     | 0,00002 mg/l                     |
| Freshwater sediment                              | 0,458 mg/kg                      |
| Marine sediment                                  | 0,046 mg/kg                      |
| Secondary poisoning                              | 16,67 mg/kg                      |
| Micro-organisms in sewage treatment plants (STP) | 0,017 mg/l                       |
| Soil                                             | 0,054 mg/kg                      |

**Additional advice on limit values**

Recommended limit value for oil mist

TWA: 5 mg/m<sup>3</sup>STEL: 10 mg/m<sup>3</sup>

The product does not contain any relevant quantities of substances with legally established exposure limitation.

**8.2. Exposure controls****Appropriate engineering controls**

Provide adequate ventilation as well as local exhaust at critical locations.

**Individual protection measures, such as personal protective equipment**

## Safety Data Sheet

### Emirates lubricants

Revision date: 14.08.2024

FoodProof XHF 15 S

Page 6 of 12

#### Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): EN 166

#### Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): EN ISO 374

Duration of wearing with permanent contact: 480

min Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.7 mm.

Wearing time with occasional contact (splashes): 30 min

Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

#### Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

#### Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Breathing protection with filter against organic gases and vapours type A - boiling point > 65°C: A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

|                                                           |                           |                    |
|-----------------------------------------------------------|---------------------------|--------------------|
| Physical state:                                           | liquid                    |                    |
| Colour:                                                   | colourless - light yellow |                    |
| Odour:                                                    | characteristic            |                    |
| Odour threshold:                                          | not determined            |                    |
| Melting point/freezing point:                             | No data available         | <b>Test method</b> |
| Boiling point or initial boiling point and boiling range: | not determined            |                    |
| Flammability:                                             | No data available         |                    |
| Lower explosion limits:                                   | No data available         |                    |
| Upper explosion limits:                                   | No data available         |                    |
| Flash point:                                              | 200 °C                    | DIN EN ISO 2592    |
| Auto-ignition temperature:                                | not determined            |                    |
| Decomposition temperature:                                | No data available         |                    |
| pH-Value:                                                 | not applicable            |                    |
| Viscosity / kinematic:<br>(at 40 °C)                      | 15,1 mm <sup>2</sup> /s   | ASTM D 7042        |

## Safety Data Sheet

|                                        |                                   |
|----------------------------------------|-----------------------------------|
| Water solubility:                      | practically insoluble             |
| Solubility in other solvents           |                                   |
| No data available                      |                                   |
| Partition coefficient n-octanol/water: | No data available                 |
| Vapour pressure:                       | No data available                 |
| Density (at 15 °C):                    | 0,827 g/cm <sup>3</sup> DIN 51757 |
| Relative vapour density:               | No data available                 |

### **9.2. Other information**

#### **Information with regard to physical hazard classes**

#### **Emirates lubricants**

Revision date: 14.08.2024

FoodProof XHF 15 S

Page 7 of 12

#### Explosive properties

No data available

#### Self-ignition temperature

Solid:

No data available

Gas:

No data available

#### Oxidizing properties

No data available

#### **Other safety characteristics**

Evaporation rate:

No data available

Pour point:

-70 °C ASTM D 7346

## **SECTION 10: Stability and reactivity**

### **10.1. Reactivity**

The product is stable under storage at normal ambient temperatures.

### **10.2. Chemical stability**

The mixture is chemically stable under recommended conditions of storage, use and temperature. **10.3. Possibility of hazardous reactions** No known hazardous reactions.

### **10.4. Conditions to avoid**

Do not overheat to avoid decomposition by heat.

Refer to chapter 7 No further action is necessary.

### **10.5. Incompatible materials**

Reacts with: Oxidising agent, strong; Acid.

### **10.6. Hazardous decomposition products**

In case of fire may be liberated: Carbon monoxide Nitrogen oxides (NOx). Sulfur oxides. Nitrogen oxides (NOx). carbon black. No known hazardous decomposition products.

## **SECTION 11: Toxicological information**

### **11.1. Information on hazard classes as defined in GB CLP Regulation**

#### **Acute toxicity**

Based on available data, the classification criteria are not met.

Mixture not tested.



## Safety Data Sheet

## Emirates lubricants

Revision date: 14.08.2024

FoodProof XHF 15 S

Page 8 of  
12**ATEmix calculated**

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) 91,67 mg/l; ATE (inhalation dust/mist) > 5 mg/l

| CAS No      | Chemical name                    |                       |         |                     |                    |
|-------------|----------------------------------|-----------------------|---------|---------------------|--------------------|
|             | Exposure route                   | Dose                  | Species | Source              | Method             |
| 157707-86-3 | Dec-1-ene, Trimers, hydrogenated |                       |         |                     |                    |
|             | oral                             | LD50 > 5000<br>mg/kg  | Rat     | Study report (1994) | OECD Guideline 401 |
|             | dermal                           | LD50 > 2000<br>mg/kg  | Rat     | Study report (1995) | OECD Guideline 402 |
| 68649-11-6  | 1-Decene, Dimer, hydrogenated    |                       |         |                     |                    |
|             | oral                             | LD50 > 5000<br>mg/kg  | Rat     | Study report (1988) | OECD Guideline 423 |
|             | dermal                           | LD50 > 2000<br>mg/kg  | Rat     | Study report (1989) | OECD Guideline 402 |
|             | inhalation (4 h) vapour          | LC50 900-5200<br>mg/l | Rat     | Study report (1989) | OECD Guideline 402 |
| 128-37-0    | 2,6-Di-tert-butyl-4-methylphenol |                       |         |                     |                    |
|             | oral                             | LD50 > 6000<br>mg/kg  | Rat     | Study report (1989) | OECD Guideline 401 |
|             | dermal                           | LD50 > 2000<br>mg/kg  | Rat     | Study report (1988) | OECD Guideline 402 |

**Irritation and corrosivity**

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

**Sensitising effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

**STOT-single exposure**

Based on available data, the classification criteria are not met.

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

**Aspiration hazard**

May be fatal if swallowed and enters airways.

**11.2. Information on other hazards****Endocrine disrupting properties**

not applicable

## Safety Data Sheet

## Emirates lubricants

Revision date: 14.08.2024

FoodProof XHF 15 S

Page 9 of  
12**SECTION 12: Ecological information****12.1. Toxicity**

Harmful to aquatic life with long lasting effects.  
Mixture not tested.

| CAS No      | Chemical name                    |                  |           |         |                                    |                                                           |
|-------------|----------------------------------|------------------|-----------|---------|------------------------------------|-----------------------------------------------------------|
|             | Aquatic toxicity                 | Dose             | [h]   [d] | Species | Source                             | Method                                                    |
| 157707-86-3 | Dec-1-ene, Trimers, hydrogenated |                  |           |         |                                    |                                                           |
|             | Acute fish toxicity              | LL50<br>mg/l     | > 1000    | 96 h    | Oncorhynchus mykiss                | Study report<br>(1995)<br>OECD Guideline<br>203           |
|             | Acute algae toxicity             | ErC50<br>mg/l    | > 1000    | 96 h    | Pseudokirchneriella<br>subcapitata | Study report<br>(1995)<br>OECD Guideline<br>201           |
|             | Acute crustacea toxicity         | EL50<br>mg/l     | > 1000    | 48 h    | Daphnia magna                      | Study report<br>(1995)<br>OECD Guideline<br>202           |
| 128-37-0    | 2,6-Di-tert-butyl-4-methylphenol |                  |           |         |                                    |                                                           |
|             | Acute fish toxicity              | LC50<br>mg/l     | 0,199     | 96 h    | Oryzias latipes                    | REACH<br>Registration<br>Dossier<br>OECD Guideline<br>203 |
|             | Acute algae toxicity             | ErC50<br>mg/l    | 0,758     | 96 h    | Pseudokirchneriella<br>subcapitata | REACH<br>Registration<br>Dossier<br>OECD Guideline<br>201 |
|             | Acute crustacea toxicity         | EC50<br>mg/l     | 0,48      | 48 h    | Daphnia magna                      | REACH<br>Registration<br>Dossier<br>OECD Guideline<br>202 |
|             | Fish toxicity                    | NOEC<br>mg/l     | 0,053     | 30 d    | Oryzias latipes                    | REACH<br>Registration<br>Dossier<br>OECD Guideline<br>210 |
|             | Crustacea toxicity               | NOEC<br>mg/l     | 0,069     | 21 d    | Daphnia magna                      | REACH<br>Registration<br>Dossier<br>OECD Guideline<br>211 |
|             | Acute bacteria toxicity          | EC50<br>mg/l ( ) | > 10000   | 3 h     | Activated sludge                   | Study report<br>(2000)<br>OECD Guideline<br>209           |

**12.2. Persistence and degradability**

Not easily bio-degradable (according to OECD-criteria). Do not allow to enter into surface water or drains.

**12.3. Bioaccumulative potential**

No data available

**Partition coefficient n-octanol/water**

| CAS No      | Chemical name                    | Log Pow |
|-------------|----------------------------------|---------|
| 157707-86-3 | Dec-1-ene, Trimers, hydrogenated | > 6,5   |
| 68649-11-6  | 1-Decene, Dimer, hydrogenated    | > 6,5   |
| 128-37-0    | 2,6-Di-tert-butyl-4-methylphenol | 5,03    |

## Safety Data Sheet

## Emirates lubricants

Revision date: 14.08.2024

FoodProof XHF 15 S

Page 10 of 12

## Further information

Do not allow uncontrolled leakage of product into the environment.

## SECTION 13: Disposal considerations

## BCF

| CAS No   | Chemical name                    | BCF | Species | Source               |
|----------|----------------------------------|-----|---------|----------------------|
| 128-37-0 | 2,6-Di-tert-butyl-4-methylphenol | 465 | Fish    | REACH Registration D |

**12.4. Mobility in soil**

Due to its low solubility in water the product is almost completely mechanically separated in biological waste water treatment plants.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria.

**12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**12.7. Other adverse effects**

No data available

**13.1. Waste treatment methods****Disposal recommendations**

Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

**List of Wastes Code - residues/unused products**

130206 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; synthetic engine, gear and lubricating oils; hazardous waste

**Contaminated packaging**

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Dispose of waste according to applicable legislation. Packing which cannot be properly cleaned must be thrown away.

## SECTION 14: Transport information

**Land transport (ADR/RID)**

**14.1. UN number or ID number:** -

**14.2. UN proper shipping name:** -

**14.3. Transport hazard class(es):** -

**14.4. Packing group:** -

**Inland waterways transport (ADN)**

**14.1. UN number or ID number:** -

**14.2. UN proper shipping name:** -

**14.3. Transport hazard class(es):** -

**14.4. Packing group:** -

**Marine transport (IMDG)**

**14.1. UN number or ID number:** -

**14.2. UN proper shipping name:** -

**14.3. Transport hazard class(es):** -

**14.4. Packing group:** -

## Safety Data Sheet

### Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number or ID number:** -

**14.2. UN proper shipping name:** -

**14.3. Transport hazard class(es):** -

**14.4. Packing group:** -

### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

### 14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

### 14.7. Maritime transport in bulk according to IMO instruments

not applicable

### Other applicable information

No dangerous good in sense of these transport regulations.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU regulatory information

#### Emirates lubricants

Revision date: 14.08.2024

FoodProof XHF 15 S

Page 11 of 12

Restrictions on use (REACH, annex XVII):

Entry 3

#### National regulatory information

Water hazard class (D):

1 - slightly hazardous to water

### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

## SECTION 16: Other information

### Changes

This data sheet contains changes from the previous version in section(s): 2,4,5,6,8,11.

### Abbreviations and acronyms

Acute Tox: Acute toxicity

Asp. Tox: Aspiration hazard

Aquatic Acute: Acute aquatic hazard

Aquatic Chronic: Chronic aquatic hazard

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; ADN -

European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ASTM

- American Society for the Testing of Materials; ATE - Acute Toxicity Estimates; bw - Body weight; CAO -

Cargo Aircraft Only; CAS - Chemical Abstracts Service; CMR - Carcinogen, Mutagen or Reproductive

Toxicant; DIN - Standard of the German Institute for Standardisation; DNEL - Derived No-Effect Level; DOT -

Department of Transportation; DSL - Domestic Substances List (Canada); EG - European Union; EN -

European standards; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous

Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air

Transport Association; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation

Organization; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISO

- International Organisation for Standardization; LC50 - Lethal Concentration to 50 % of a test population; LD50

- Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the

Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n;o;s; - Not Otherwise

## Safety Data Sheet

Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; OECD - Organization for Economic Co-operation and Development; PBT - Persistent, Bioaccumulative and Toxic substance; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulation concerning the International Carriage of Dangerous Goods by Rail; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Classification for mixtures and used evaluation method according to GB CLP Regulation

|                         |                          |
|-------------------------|--------------------------|
| Classification          | Classification procedure |
| Asp. Tox. 1; H304       | Calculation method       |
| Aquatic Chronic 3; H412 | Calculation method       |

### Relevant H and EUH statements (number and full text)

H304 May be fatal if swallowed and enters airways.  
H332 Harmful if inhaled.  
H400 Very toxic to aquatic life.  
H410 Very toxic to aquatic life with long lasting effects. H412  
Harmful to aquatic life with long lasting effects.

### Emirates lubricants

Revision date: 14.08.2024

FoodProof XHF 15 S

Page 12 of  
12

### Further Information

This preparation is hazardous in the sense of regulation (EC) No 1272/2008 [GHS].

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*