

# Safety Data Sheet

**Emirates lubricants**

Revision date: 27.08.2024

Chain Lube XHT 150

Page 1 of 13

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Chain Lube XHT 150

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

Lubricant and additive.

**1.3. Details of the supplier of the safety data sheet****Manufacturer**

|                         |                                            |                  |
|-------------------------|--------------------------------------------|------------------|
| Company name:           | Emirates lubricants                        |                  |
| Street:                 | Ras Al khaimah                             |                  |
| Place:                  | United Arab Emirates                       |                  |
| Telephone:              | +971 55 105 2851                           | +971 52 660 6888 |
| E-mail:                 | info@emirateslubricant.                    |                  |
| Contact person:         | Application Technology                     |                  |
| Internet:               | www.emirateslubricant.com                  |                  |
| Responsible Department: | Emirates lubricants Application Technology |                  |

**1.4. Emergency telephone number:** +971 52 660 6888 - This number is serviced during office hours.

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****GB CLP Regulation**

Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

This preparation is hazardous in the sense of regulation (EC) No 1272/2008 [GHS].

**2.2. Label elements****GB CLP Regulation Pictograms:****Hazard statements**

|      |                                                  |
|------|--------------------------------------------------|
| H411 | Toxic to aquatic life with long lasting effects. |
|------|--------------------------------------------------|

**Precautionary statements**

|      |                                   |
|------|-----------------------------------|
| P273 | Avoid release to the environment. |
| P391 | Collect spillage.                 |

## Safety Data Sheet

P501

Dispose of contents/container to a waste disposal system.

## Emirates lubricants

Revision date: 27.08.2024

Chain Lube XHT 150

Page 2 of 13

**Additional advice on labelling**

The product is classified and labelled according to EC directives or corresponding national laws.

**2.3. Other hazards**

Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

Spilled product must not leak into the ground.

Do not allow uncontrolled leakage of product into the environment.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures****Chemical characterization**

Mixture of synthetic base components and additives.

**Relevant ingredients**

| CAS No     | Chemical name                                           |          |                  | Quantity    |
|------------|---------------------------------------------------------|----------|------------------|-------------|
|            | EC No                                                   | Index No | REACH No         |             |
|            | Classification (GB CLP Regulation)                      |          |                  |             |
| 9003-29-6  | Polybutenes                                             |          |                  | 10 - < 20 % |
|            | 500-004-7                                               |          |                  |             |
|            | Asp. Tox. 1; H304                                       |          |                  |             |
| 68937-41-7 | Triaryl phosphate isopropylated                         |          |                  | 1 - < 2.5 % |
|            | 273-066-3                                               |          | 01-2119535109-41 |             |
|            | Repr. 2, STOT RE 2, Aquatic Chronic 1; H361fd H373 H410 |          |                  |             |
| 68442-68-2 | Styrenated N-phenyl-benzenamine                         |          |                  | 1 - < 2.5 % |
|            | 270-485-3                                               |          | 01-2120115789-46 |             |
|            | Aquatic Chronic 4; H413                                 |          |                  |             |

Full text of H and EUH statements: see section 16.

**Specific Conc. Limits, M-factors and ATE**

| CAS No     | EC No                                                                                           | Chemical name                   | Quantity    |
|------------|-------------------------------------------------------------------------------------------------|---------------------------------|-------------|
|            | Specific Conc. Limits, M-factors and ATE                                                        |                                 |             |
| 9003-29-6  | 500-004-7                                                                                       | Polybutenes                     | 10 - < 20 % |
|            | inhalation: LC50 = 4820 mg/l (vapours); dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 10000 mg/kg |                                 |             |
| 68937-41-7 | 273-066-3                                                                                       | Triaryl phosphate isopropylated | 1 - < 2.5 % |

## Safety Data Sheet

|            |                                                            |                                 |             |
|------------|------------------------------------------------------------|---------------------------------|-------------|
|            | dermal: LD50 = > 10000 mg/kg Aquatic Chronic 1; H410: M=10 |                                 |             |
| 68442-68-2 | 270-485-3                                                  | Styrenated N-phenyl-benzenamine | 1 - < 2.5 % |
|            | dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg     |                                 |             |

### Further Information

DMSO-Extract < 3 %; IP 346. Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

#### After inhalation

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist.

## Emirates lubricants

Revision date: 27.08.2024

Chain Lube XHT 150

Page 3 of 13

#### After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. In case of skin irritation, seek medical treatment.

#### After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

#### After ingestion

Do NOT induce vomiting.

Rinse mouth thoroughly with water. Call a physician immediately.

### 4.2. Most important symptoms and effects, both acute and delayed

No information available.

### 4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

## SECTION 5: Firefighting measures

## Safety Data Sheet

### **5.1. Extinguishing media**

#### **Suitable extinguishing media**

Foam. Extinguishing powder. Carbon dioxide (CO<sub>2</sub>). Atomized water.

#### **Unsuitable extinguishing media**

High power water jet.

### **5.2. Special hazards arising from the substance or mixture**

In case of fire may be liberated: Carbon monoxide. Carbon dioxide (CO<sub>2</sub>). Sulphur oxides. Nitrogen oxides (NO<sub>x</sub>). Phosphorus oxides. carbon black.

### **5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus.

#### **Additional information**

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray jet to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

## **SECTION 6: Accidental release measures**

### **6.1. Personal precautions, protective equipment and emergency procedures**

#### **General advice**

High slip hazard because of leaking or spilled product. Remove all sources of ignition. Wear breathing apparatus if exposed to vapours/dusts/aerosols. Avoid contact with skin, eye and clothing. Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work

### **6.2. Environmental precautions**

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Prevent spread over a wide area (e.g. by containment or oil barriers).

### **6.3. Methods and material for containment and cleaning up**

#### **Other information**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean contaminated articles and floor according to the environmental legislation.

### **6.4. Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

## **Emirates lubricants**

Revision date: 27.08.2024

Chain Lube XHT 150

Page 4 of 13

Section 12: Ecological Information (non-mandatory)

Disposal: see section 13

## **SECTION 7: Handling and storage**

## Safety Data Sheet

### Emirates lubricants

Chain Lube XHT 150

Revision date: 27.08.2024

Page 5 of  
13

#### 7.1. Precautions for safe handling

##### Advice on safe handling

Work in well-ventilated zones or use proper respiratory protection. Avoid oil mist. If handled uncovered, arrangements with local exhaust ventilation have to be used. Avoid contact with skin, eyes and clothes.

##### Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

##### Advice on general occupational hygiene

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

#### 7.2. Conditions for safe storage, including any incompatibilities

##### Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorption of humidity. Provide adequate ventilation as well as local exhaustion at critical locations. Keep/Store only in original container. Make sure spills can be contained, e.g. in sump pallets or kerbed areas.

##### Hints on joint storage

Keep away from food, drink and animal feedingstuffs.

Keep away from: Oxidizing agent

##### Further information on storage conditions

Protect against: UV-radiation/sunlight. Frost. heat.

Recommended storage temperature: 5 - 40°C

#### 7.3. Specific end use(s)

Further information: see technical data sheet.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### Exposure limits (EH40)

| CAS No   | Substance     | ppm | mg/m <sup>3</sup> | fibres/ml | Category      | Origin |
|----------|---------------|-----|-------------------|-----------|---------------|--------|
| 122-39-4 | Diphenylamine | -   | 10                |           | TWA (8 h)     | WEL    |
|          |               | -   | 20                |           | STEL (15 min) | WEL    |

##### DNEL/DMEL values

| CAS No                 | Substance                       |                |          |                   |
|------------------------|---------------------------------|----------------|----------|-------------------|
| DNEL type              |                                 | Exposure route | Effect   | Value             |
| 68937-41-7             | Triaryl phosphate isopropylated |                |          |                   |
| Consumer DNEL, acute   |                                 | oral           | systemic | 50 mg/kg bw/day   |
| Worker DNEL, long-term |                                 | inhalation     | systemic | 0,145 mg/m³       |
| Worker DNEL, acute     |                                 | inhalation     | systemic | 700 mg/m³         |
| Worker DNEL, long-term |                                 | dermal         | systemic | 0,25 mg/kg bw/day |
| Worker DNEL, acute     |                                 | dermal         | systemic | 2000 mg/kg bw/day |

## Safety Data Sheet

|                          |                                 |          |                        |
|--------------------------|---------------------------------|----------|------------------------|
| Worker DNEL, acute       | dermal                          | local    | 16 mg/cm <sup>2</sup>  |
| Consumer DNEL, acute     | inhalation                      | systemic | 350 mg/m <sup>3</sup>  |
| Consumer DNEL, long-term | dermal                          | systemic | 0,0298 mg/kg bw/day    |
| Consumer DNEL, acute     | dermal                          | systemic | 100 mg/kg bw/day       |
| Consumer DNEL, acute     | dermal                          | local    | 8 mg/cm <sup>2</sup>   |
| Consumer DNEL, long-term | oral                            | systemic | 0,00835 mg/kg bw/day   |
| 68442-68-2               | Styrenated N-phenyl-benzenamine |          |                        |
| Worker DNEL, long-term   | inhalation                      | systemic | 16,4 mg/m <sup>3</sup> |
| Worker DNEL, long-term   | dermal                          | systemic | 2,33 mg/kg bw/day      |
| Consumer DNEL, long-term | inhalation                      | systemic | 2,9 mg/m <sup>3</sup>  |
| Consumer DNEL, long-term | dermal                          | systemic | 0,833 mg/kg bw/day     |
| Consumer DNEL, long-term | oral                            | systemic | 0,167 mg/kg bw/day     |

### PNEC values

| CAS No                                           | Substance                       |
|--------------------------------------------------|---------------------------------|
| Environmental compartment                        | Value                           |
| 68937-41-7                                       | Triaryl phosphate isopropylated |
| Freshwater                                       | 0 mg/l                          |
| Freshwater (intermittent releases)               | 0,015 mg/l                      |
| Marine water                                     | 0 mg/l                          |
| Freshwater sediment                              | 0,185 mg/kg                     |
| Marine sediment                                  | 0,018 mg/kg                     |
| Secondary poisoning                              | 1,85 mg/kg                      |
| Micro-organisms in sewage treatment plants (STP) | 100 mg/l                        |
| Soil                                             | 2,5 mg/kg                       |

### Additional advice on limit values

Recommended limit value for oil mist

TWA: 5 mg/m<sup>3</sup>

STEL: 10 mg/m<sup>3</sup>

The product does not contain any relevant quantities of substances with legally established exposure limitation.

### 8.2. Exposure controls

## Safety Data Sheet

### Emirates lubricants

Revision date: 27.08.2024

Chain Lube XHT 150

Page 6 of 13



#### Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

#### Individual protection measures, such as personal protective equipment

##### Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): EN 166

##### Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): EN ISO 374

Duration of wearing with permanent contact: 480

min Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.7 mm.

Wearing time with occasional contact (splashes): 30 min

Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

##### Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

##### Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Breathing protection with filter against organic gases and vapours type A - boiling point > 65°C: A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

|                  |                |
|------------------|----------------|
| Physical state:  | liquid         |
| Colour:          | yellow - brown |
| Odour:           | characteristic |
| Odour threshold: | not determined |

#### Test method

|                                            |                        |
|--------------------------------------------|------------------------|
| Melting point/freezing point:              | No data available      |
| Boiling point or initial boiling point and | not determined         |
| boiling range:                             |                        |
| Flammability:                              | No data available      |
| Lower explosion limits:                    | No data available      |
| Upper explosion limits:                    | No data available      |
| Flash point:                               | 280 °C DIN EN ISO 2592 |

**Safety Data Sheet**

|                                      |                                  |
|--------------------------------------|----------------------------------|
| Auto-ignition temperature:           | not determined DIN 51794         |
| Decomposition temperature:           | No data available                |
| pH-Value:                            | not applicable                   |
| Viscosity / kinematic:<br>(at 40 °C) | 145 mm <sup>2</sup> /s DIN 51562 |
| Water solubility:                    | virtually insoluble              |
| Solubility in other solvents         |                                  |
| No data available                    |                                  |

**Emirates lubricants**

Revision date: 27.08.2024

Chain Lube XHT 150

Page 7 of 13

|                                        |                                   |
|----------------------------------------|-----------------------------------|
| Partition coefficient n-octanol/water: | No data available                 |
| Vapour pressure:                       | No data available                 |
| Density (at 15 °C):                    | 0,950 g/cm <sup>3</sup> DIN 51757 |
| Relative vapour density:               | No data available                 |
| Particle characteristics:              | No data available                 |

**9.2. Other information****Information with regard to physical hazard classes**

Explosive properties

No data available

Self-ignition temperature

Solid:

No data available

Gas:

No data available

Oxidizing properties

No data available

**Other safety characteristics**

Evaporation rate:

No data available

Pour point:

-48 °C ASTM D 7346

**SECTION 10: Stability and reactivity**



## Safety Data Sheet

### **10.1. Reactivity**

The product is stable under storage at normal ambient temperatures.

### **10.2. Chemical stability**

The mixture is chemically stable under recommended conditions of storage, use and temperature. **10.3. Possibility of hazardous reactions** No known hazardous reactions.

### **10.4. Conditions to avoid**

Refer to chapter 7 No further action is necessary.

Do not overheat to avoid decomposition by heat.

### **10.5. Incompatible materials**

Reacts with: Oxidising agent, strong. Acid.

### **10.6. Hazardous decomposition products**

In case of fire may be liberated: Carbon monoxide. Carbon dioxide (CO<sub>2</sub>). Sulphur oxides. Nitrogen oxides (NO<sub>x</sub>). Phosphorus oxides. carbon black.

## **SECTION 11: Toxicological information**

### **11.1. Information on hazard classes as defined in GB CLP Regulation**

#### **Acute toxicity**

Based on available data, the classification criteria are not met.

Mixture not tested.

#### **ATEmix calculated**

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

## Safety Data Sheet

## Emirates lubricants

Revision date: 27.08.2024

Chain Lube XHT 150

Page 10 of 15

| CAS No     | Chemical name                   |                    |         |                     |                       |
|------------|---------------------------------|--------------------|---------|---------------------|-----------------------|
|            | Exposure route                  | Dose               | Species | Source              | Method                |
| 9003-29-6  | Polybutenes                     |                    |         |                     |                       |
|            | oral                            | LD50 > 10000 mg/kg | Rat     | Study report (1986) | OECD Guideline 401    |
|            | dermal                          | LD50 > 2000 mg/kg  | Rat     | Study report (1996) | OECD Guideline 402    |
|            | inhalation (4 h) vapour         | LC50 4820 mg/l     | Rat     |                     |                       |
| 68937-41-7 | Triaryl phosphate isopropylated |                    |         |                     |                       |
|            | dermal                          | LD50 > 10000 mg/kg | Rabbit  | Study report (1976) | other: 16 CFR 1500.40 |
| 68442-68-2 | Styrenated N-phenyl-benzenamine |                    |         |                     |                       |
|            | oral                            | LD50 > 5000 mg/kg  | Rat     | Study report (1976) | OECD Guideline 401    |
|            | dermal                          | LD50 > 2000 mg/kg  | Rat     | Study report (2016) | OECD Guideline 402    |

**Irritation and corrosivity**

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

**Sensitising effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

**STOT-single exposure**

Based on available data, the classification criteria are not met.

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**11.2. Information on other hazards****Endocrine disrupting properties**

not applicable

**SECTION 12: Ecological information****12.1. Toxicity**

Toxic to aquatic life with long lasting effects.

Mixture not tested.

## Safety Data Sheet

## Emirates lubricants

Revision date: 27.08.2024

Chain Lube XHT 150

Page 11 of 15

| CAS No     | Chemical name                   |                      |           |                            |                                 |                                    |
|------------|---------------------------------|----------------------|-----------|----------------------------|---------------------------------|------------------------------------|
|            | Aquatic toxicity                | Dose                 | [h]   [d] | Species                    | Source                          | Method                             |
| 9003-29-6  | Polybutenes                     |                      |           |                            |                                 |                                    |
|            | Acute fish toxicity             | LL50 > 1000 mg/l     | 96 h      | Oncorhynchus mykiss        | REACH Registration Dossier      | other: REACH Guidance on QSARs R.6 |
|            | Acute algae toxicity            | ErC50 > 1000 mg/l    | 72 h      | Raphidocelis subcapitata   | REACH Registration Dossier      | other: REACH Guidance on QSARs R.6 |
|            | Acute crustacea toxicity        | EL50 > 1000 mg/l     | 48 h      | Daphnia magna              | REACH Registration Dossier      | other: REACH Guidance on QSARs R.6 |
| 68937-41-7 | Triaryl phosphate isopropylated |                      |           |                            |                                 |                                    |
|            | Acute fish toxicity             | LC50 10,8 mg/l       | 96 h      | Pimephales promelas        | REACH Registration Dossier      | OECD Guideline 203                 |
|            | Acute algae toxicity            | ErC50 > 2,5 mg/l     | 72 h      | Raphidocelis subcapitata   | REACH Registration Dossier      | EU Method C.3                      |
|            | Acute crustacea toxicity        | EC50 1,5 mg/l        | 48 h      | Daphnia magna              | REACH Registration Dossier      | OECD Guideline 202                 |
|            | Fish toxicity                   | NOEC 0,0031 mg/l     | 33 d      | Pimephales promelas        | REACH Registration Dossier      | OECD Guideline 210                 |
|            | Crustacea toxicity              | NOEC 0,0415 mg/l     | 21 d      | Daphnia magna              | REACH Registration Dossier      | OECD Guideline 211                 |
|            | Acute bacteria toxicity         | EC50 > 1000 mg/l ( ) | 3 h       | activated sludge, domestic | REACH Registration Dossier      | OECD Guideline 209                 |
| 68442-68-2 | Styrenated N-phenyl-benzenamine |                      |           |                            |                                 |                                    |
|            | Acute fish toxicity             | LC50 920 mg/l        | 96 h      | Danio rerio                | REACH Registration Dossier      | OECD Guideline 203                 |
|            | Acute algae toxicity            | ErC50 1,564 mg/l     | 72 h      | Desmodesmus subspicatus    | SSS QSAR Prediction Team (2016) | other: as mentioned below          |
|            | Acute crustacea toxicity        | EC50 0,051 mg/l      | 48 h      | Daphnia magna              | SSS QSAR Prediction Team (2016) | other: as mentioned below          |

**12.2. Persistence and degradability**

Not easily bio-degradable (according to OECD-criteria). Do not allow to enter into surface water or drains.

## Safety Data Sheet

## Emirates lubricants

Revision date: 27.08.2024

Chain Lube XHT 150

Page 12 of 15

**12.3. Bioaccumulative potential**

No data available

**Partition coefficient n-octanol/water**

| CAS No     | Chemical name                   | Log Pow        |
|------------|---------------------------------|----------------|
| 9003-29-6  | Polybutenes                     | 7,6 - 7,8      |
| 68937-41-7 | Triaryl phosphate isopropylated | 85000 - 150000 |
| 68442-68-2 | Styrenated N-phenyl-benzenamine | >= 32967       |

**BCF**

| CAS No     | Chemical name                   | BCF    | Species             | Source               |
|------------|---------------------------------|--------|---------------------|----------------------|
| 9003-29-6  | Polybutenes                     | 144,54 |                     | EPA (2021)           |
| 68937-41-7 | Triaryl phosphate isopropylated | 225    | Lepomis macrochirus | REACH Registration D |
| 68442-68-2 | Styrenated N-phenyl-benzenamine | 531,1  |                     | REACH Registration D |

**12.4. Mobility in soil**

Due to its low solubility in water the product is almost completely mechanically separated in biological waste water treatment plants.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria.

**12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**12.7. Other adverse effects**

No data available

**Further information**

Do not allow uncontrolled leakage of product into the environment.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Disposal recommendations**

Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

**List of Wastes Code - residues/unused products**

130206 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; synthetic engine, gear and lubricating oils; hazardous waste

**Contaminated packaging**

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Dispose of waste according to applicable legislation. Packing which cannot be properly cleaned must be disposed of.

**SECTION 14: Transport information****Land transport (ADR/RID)****14.1. UN number or ID number:** -**14.2. UN proper shipping name:** -**14.3. Transport hazard class(es):** -**14.4. Packing group:** -

**Safety Data Sheet****Emirates lubricants**

Revision date: 27.08.2024

Chain Lube XHT 150

Page 13 of 15

**Inland waterways transport (ADN)****14.1. UN number or ID number:** -**14.2. UN proper shipping name:** -**14.3. Transport hazard class(es):** -**14.4. Packing group:** -**Marine transport (IMDG)****14.1. UN number or ID number:** -**14.2. UN proper shipping name:** -**14.3. Transport hazard class(es):** -**14.4. Packing group:** -**Air transport (ICAO-TI/IATA-DGR)****14.1. UN number or ID number:** -

## Safety Data Sheet

### Emirates lubricants

Revision date: 27.08.2024

Chain Lube XHT 150

Page 11 of 13

**14.2. UN proper shipping name:** -

**14.3. Transport hazard class(es):** -

**14.4. Packing group:** -

#### **14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

#### **14.6. Special precautions for user**

Unless specified otherwise, general measures for safe transport must be followed.

#### **14.7. Maritime transport in bulk according to IMO instruments**

not applicable

#### **Other applicable information**

No dangerous good in sense of these transport regulations.

### SECTION 15: Regulatory information

#### **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

##### **EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 75

Information according to Directive (SEVESO III): Not subject to 2012/18/EU (SEVESO III) 2012/18/EU

##### **National regulatory information**

Water hazard class (D): 3 - highly hazardous to water

#### **15.2. Chemical safety assessment**

Chemical safety assessments for substances in this mixture were not carried out.

### SECTION 16: Other information

#### **Changes**

This data sheet contains changes from the previous version in section(s): 2,3,5,7,8,9,10,12,15.

#### **Abbreviations and acronyms**

Acute Tox: Acute toxicity

Asp. Tox: Aspiration hazard

Repr: Reproductive toxicity

STOT RE: Specific target organ toxicity - repeated exposure

Aquatic Acute: Acute aquatic hazard

Aquatic Chronic: Chronic aquatic hazard

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ASTM - American Society for the Testing of Materials; ATE - Acute Toxicity Estimates; bw - Body weight; CAO - Cargo Aircraft Only; CAS - Chemical Abstracts Service; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DNEL - Derived No-Effect Level; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); EG - European Union; EN - European standards; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous

**Safety Data Sheet****Emirates lubricants**

Revision date: 27.08.2024

Chain Lube XHT 150

Page 12 of  
13**Emirates lubricants**

Revision date: 27.08.2024

Chain Lube XHT 150

Page 13 of  
13

Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISO - International Organisation for Standardization; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; OECD - Organization for Economic Co-operation and Development; PBT - Persistent, Bioaccumulative and Toxic substance; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulation concerning the International Carriage of Dangerous Goods by Rail; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

**Classification for mixtures and used evaluation method according to GB CLP Regulation**

| Classification          | Classification procedure |
|-------------------------|--------------------------|
| Aquatic Chronic 2; H411 | Calculation method       |

**Relevant H and EUH statements (number and full text)**

|        |                                                                          |
|--------|--------------------------------------------------------------------------|
| H304   | May be fatal if swallowed and enters airways.                            |
| H361fd | Suspected of damaging fertility. Suspected of damaging the unborn child. |
| H373   | May cause damage to organs through prolonged or repeated exposure.       |
| H410   | Very toxic to aquatic life with long lasting effects.                    |
| H411   | Toxic to aquatic life with long lasting effects.                         |
| H413   | May cause long lasting harmful effects to aquatic life.                  |

**Further Information**

This preparation is hazardous in the sense of regulation (EC) No 1272/2008 [GHS].

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*