

Safety Data Sheet

Emirates lubricants

Revision date: 27.10.2023

Heat Transfer Oil XW 15 HT

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Heat Transfer Oil XW 15 HT

Substance name: Dibenzylbenzene, ar-methyl derivative
REACH Registration Number: 01-2119488667-17-0000
CAS No: 53585-53-8
EC No: 258-649-2
UFI: AJPG-S748-F20X-N1R1

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Material(s) for heat transfer

1.3. Details of the supplier of the safety data sheet**Manufacturer**

Company name: Emirates lubricants

Street: Ras Al khaimah

Place: United Arab Emirates

Telephone: +971 55 105 2851 +971 52 660 6888

e-mail: info@emirateslubricant.

Contact person: Application Technology

Internet: www.emirateslubricant.com

Responsible Department: Emirates lubricants Application Technology

1.4. Emergency telephone number:

+971 52 660 6888 - This number is serviced during office hours.

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****GB CLP Regulation**

Repr. 1B; H360FD
Asp. Tox. 1; H304
Aquatic Chronic 1; H410

Full text of hazard statements: see SECTION 16.

This preparation is hazardous in the sense of regulation (EC) No 1272/2008 [GHS].

2.2. Label elements**GB CLP Regulation Hazard components for labelling**

Dibenzylbenzene, ar-methyl derivative

Safety Data Sheet

Emirates lubricants

Revision date: 27.10.2023

Heat Transfer Oil XW 15 HT

Page 2 of 11

Signal word:

Danger



Pictograms:

Hazard statements

- H304 May be fatal if swallowed and enters airways.
 H360FD May damage fertility. May damage the unborn child.
 H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements

- P201 Obtain special instructions before use.
 P273 Avoid release to the environment.
 P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
 P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
 P308+P313 IF exposed or concerned: Get medical advice/attention.
 P331 Do NOT induce vomiting.
 P405 Store locked up.
 P501 Dispose of contents/container to an appropriate recycling or disposal facility.

Special labelling of certain mixtures

Restricted to professional users.

Additional advice on labelling

The product is classified and labelled according to EC directives or corresponding national laws.

2.3. Other hazards

- Prolonged/repetitive skin contact may cause skin defatting or dermatitis.
 Process vapors can irritate airways, skin and eyes.
 Do not allow uncontrolled leakage of product into the environment.

SECTION 3: Composition/information on ingredients**3.1. Substances**

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
53585-53-8	Dibenzylbenzene, ar-methyl derivative			100 %
	258-649-2		01-2119488667-17-0000	
	Repr. 1B, Asp. Tox. 1, Aquatic Chronic 1; H360FD H304 H410			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		

Safety Data Sheet

53585-53-8	258-649-2	Dibenzylbenzene, ar-methyl derivative	100 %
inhalation: LC50 = >0,24 mg/l (vapours); dermal: LD50 = > 2000 mg/kg; oral: LD50 = >= 10000 mg/kg Aquatic Chronic 1; H410: M=10			

Further Information

Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

SECTION 4: First aid measures

Emirates lubricants

Revision date: 27.10.2023

Heat Transfer Oil XW 15 HT

Page 3 of 11

4.1. Description of first aid measures

General information

Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets. Get medical advice/attention if you feel unwell.

After inhalation

Move victim to fresh air. Put victim at rest and keep warm. In case of persistent complaints seek medical advice.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. In case of skin irritation, seek medical treatment.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

After ingestion

Call a physician immediately. Do NOT induce vomiting. Caution if victim vomits: Risk of aspiration!

Rinse mouth immediately and drink plenty of water.

If unconscious but breathing normally, place in recovery position and seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

May be fatal if swallowed and enters airways.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂). Extinguishing powder. Water fog.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO₂).

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray jet to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately.

Safety Data Sheet

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

High slip hazard because of leaking or spilled product. Remove all sources of ignition. Wear breathing apparatus if exposed to vapours/dusts/aerosols. Avoid contact with skin, eye and clothing.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Prevent spread over a wide area (e.g. by containment or oil barriers).

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean contaminated articles and floor according to the environmental legislation.

Emirates lubricants

Revision date: 27.10.2023

Heat Transfer Oil XW 15 HT

Page 4 of 11

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Section 12: Ecological Information (non-mandatory)

Disposal: see section 13

SECTION 7: Handling and storage

Safety Data Sheet

7.1. Precautions for safe handling

Advice on safe handling

Work in well-ventilated zones or use proper respiratory protection. Avoid oil mist. If handled uncovered, arrangements with local exhaust ventilation have to be used. Avoid contact with skin, eyes and clothes. Wear personal protection equipment. Keep container tightly closed. Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Advice on protection against fire and explosion

Take precautionary measures against static discharges. Keep away from sources of ignition - No smoking. Ground and bond container and receiving equipment. Use explosion-proof [electrical/ventilating/lighting/] equipment. Vapours may form explosive mixtures with air.

Advice on general occupational hygiene

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorption of humidity. Keep container tightly closed in a cool place. Keep/Store only in original container.

Hints on joint storage

Keep away from food, drink and animal feedingstuffs.
Keep away from: Oxidizing agent

Further information on storage conditions

Protect against: UV-radiation/sunlight. frost. heat.
Recommended storage temperature: 5 - 40°C

7.3. Specific end use(s)

Further information: see technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
53585-53-8	Dibenzylbenzene, ar-methyl derivative			
Worker DNEL, long-term		inhalation	systemic	3,5 mg/m³
Worker DNEL, long-term		dermal	systemic	0,5 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,25 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	0,25 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	0,87 mg/m³

PNEC values

CAS No	Substance		
Environmental compartment	Value		
53585-53-8	Dibenzylbenzene, ar-methyl derivative		

Safety Data Sheet

Emirates lubricants

Revision date: 27.10.2023

Heat Transfer Oil XW 15 HT

Page 5 of 11

Freshwater	0,000028 mg/l
Marine water	0,000003 mg/l
Freshwater sediment	0,11 mg/kg
Marine sediment	0,11 mg/kg
Secondary poisoning	11,1 mg/kg
Soil	2 mg/kg

Additional advice on limit values

To date, no national critical limit values exist.

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations. Minimum room ventilation rate for handling/application (air changes per hour): 10

Individual protection measures, such as personal protective equipment Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): EN 166

Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): EN ISO 374

Duration of wearing with permanent contact: 480

min Suitable material: FKM (fluororubber).

Thickness of glove material: 0.4 mm.

Wearing time with occasional contact (splashes): 30 min

Suitable material: FKM (fluororubber).

Thickness of glove material: 0.2 mm

Protect skin by using skin protective cream.

Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Breathing protection with filter against organic gases and vapours type A - boiling point > 65°C: A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	liquid
Colour:	colourless, yellow
Odour:	characteristic

Safety Data Sheet

Emirates lubricants

Revision date: 27.10.2023

Heat Transfer Oil XW 15 HT

Page 6 of 11

Odour threshold: not determined

Test method

Melting point/freezing point: -39 - -32 °C

Boiling point or initial boiling point and 390 °C ASTM D 1078

boiling range:

Flammability: No data available

Lower explosion limits: No data available

Upper explosion limits: No data available

Flash point: 200 °C DIN EN ISO 22719

Auto-ignition temperature: No data available

Decomposition temperature: No data available

pH-Value: not applicable

Viscosity / kinematic: 16,4 mm²/s DIN 51562
(at 40 °C)

Water solubility: virtually insoluble

Solubility in other solvents

No data available

Partition coefficient n-octanol/water: > 6 OECD (TG) 117

Vapour pressure: <0,01 hPa

(at 20 °C)

Density (at 15 °C): 1,045 g/cm³ DIN 51757

Relative vapour density: No data available

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

No data available

Self-ignition temperature

Solid:

No data available

Gas:

No data available

Oxidizing properties

No data available

Other safety characteristics

Evaporation rate: No data available

Pour point: -34 °C DIN ISO 3016

SECTION 10: Stability and reactivity

Safety Data Sheet

10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

Vapours can form explosive mixtures with air.

10.4. Conditions to avoid

Protect from sunlight. Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Do not overheat to avoid decomposition by heat.

10.5. Incompatible materials

Oxidizing agent

10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO₂).
No known hazardous decomposition products.

Emirates lubricants

Revision date: 27.10.2023

Heat Transfer Oil XW 15 HT

Page 7 of 11

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
53585-53-8	Dibenzylbenzene, ar-methyl derivative				
	oral	LD50 mg/kg >= 10000	Rat	Study report (1984)	OECD Guideline 401
	dermal	LD50 mg/kg > 2000	Rat	Study report (1990)	OECD Guideline 402
	inhalation (4 h) vapour	LC50 mg/l >0,24	Rat		OECD 403

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

May damage fertility. May damage the unborn child. (Dibenzylbenzene, ar-methyl derivative)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

Safety Data Sheet

Emirates lubricants

Revision date: 27.10.2023

Heat Transfer Oil XW 15 HT

Page 8 of 11

11.2. Information on other hazards

Endocrine disrupting properties
not applicable

SECTION 12: Ecological information**12.1. Toxicity**

Very toxic to aquatic life with long lasting effects.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
53585-53-8	Dibenzylbenzene, ar-methyl derivative					
	Acute fish toxicity	LC50 mg/l	> 0,32	96 h	Danio rerio	REACH Registration Dossier
	Acute algae toxicity	ErC50 mg/l	>0,016	72 h	Skeletonema costatum	
	Acute crustacea toxicity	EC50 mg/l	>0,029	48 h	Daphnia magna	
	Fish toxicity	NOEC mg/l	>0,0046	14 d	Leuciscus idus (golden orfe)	OECD 204
	Crustacea toxicity	NOEC mg/l	>0,0014	21 d	Daphnia magna	OECD 211

12.2. Persistence and degradability

No data available

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
53585-53-8	Dibenzylbenzene, ar-methyl derivative			
		65%	62	

12.3. Bioaccumulative potential

Bioconcentration factor (BCF): 7525 (literature value)

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
53585-53-8	Dibenzylbenzene, ar-methyl derivative	>6

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

This substance does not meet the PBT/vPvB criteria of UK REACH.

12.6. Endocrine disrupting properties

This substance does not have endocrine disrupting properties with respect to non-target organisms.

Safety Data Sheet

12.7. Other adverse effects

No data available

Further information

Do not allow uncontrolled leakage of product into the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

List of Wastes Code - residues/unused products

130308 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste insulating and heat transmission oils; synthetic insulating and heat transmission oils; hazardous waste

Contaminated packaging

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Dispose of

Emirates lubricants

Revision date: 27.10.2023

Heat Transfer Oil XW 15 HT

Page 9 of 11

waste according to applicable legislation. Packing which cannot be properly cleaned must be thrown away.

SECTION 14: Transport information


Land transport (ADR/RID)

14.1. UN number or ID number: UN 3082 **14.2. UN proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

14.3. Transport hazard class(es): 9

14.4. Packing group: III

Hazard label: 9



Classification code: M6

Special Provisions: 274 335 375 601

Transport category: 3

Hazard No: 90

Tunnel restriction code: -


Inland waterways transport (ADN)

14.1. UN number or ID number: UN 3082 **14.2. UN proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Safety Data Sheet

14.3. Transport hazard class(es): 9**14.4. Packing group:** III

Hazard label: 9




Classification code: M6

Special Provisions: 274 335 375 601

Excepted quantity: E1

Marine transport (IMDG)**14.1. UN number or ID number:** UN 3082 **14.2. UN proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.**14.3. Transport hazard class(es):** 9**14.4. Packing group:** III

Hazard label: 9



Special Provisions: 274 335 969

Limited quantity: 5 L

Excepted quantity: E1

EmS: F-A, S-F

Air transport (ICAO-TI/IATA-DGR)**14.1. UN number or ID number:** UN 3082 **14.2. UN proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.**14.3. Transport hazard class(es):** 9**14.4. Packing group:** III


Hazard label: 9

Emirates lubricants

Heat Transfer Oil XW 15 HT

Revision date: 27.10.2023

Page 10 of 11



Special Provisions: A97 A158 A197 A215

Limited quantity Passenger: 30 kg G

Passenger LQ: Y964

Excepted quantity: E1

IATA-packing instructions - Passenger: 964

Safety Data Sheet

IATA-max. quantity - Passenger: 450 L
 IATA-packing instructions - Cargo: 964
 IATA-max. quantity - Cargo: 450 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS:

Yes



Danger releasing substance: Dibenzylbenzene, ar-methyl derivative

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3

Information according to 2012/18/EU E1 Hazardous to the Aquatic Environment

(SEVESO III):

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe employment restrictions for women of child-bearing age.

Water hazard class (D): 3 - highly hazardous to water

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,4,7,8,9,10,12,14,15.

Abbreviations and acronyms

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ASTM - American Society for the Testing of Materials; ATE - Acute Toxicity Estimates; bw - Body weight; CAO - Cargo Aircraft Only; CAS - Chemical Abstracts Service; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DNEL - Derived No-Effect Level; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); EG - European Union; EN - European standards; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous

Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air

Safety Data Sheet

Emirates lubricants

Revision date: 27.10.2023

Heat Transfer Oil XW 15 HT

Page 11 of 11

Transport Association; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISO
 - International Organisation for Standardization; LC50 - Lethal Concentration to 50 % of a test population; LD50
 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s.; - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; OECD - Organization for Economic Co-operation and Development; PBT - Persistent, Bioaccumulative and Toxic substance; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulation concerning the International Carriage of Dangerous Goods by Rail; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Relevant H and EUH statements (number and full text)

H304	May be fatal if swallowed and enters airways.
H360FD	May damage fertility. May damage the unborn child.
H410	Very toxic to aquatic life with long lasting effects.

Further Information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.