

# Safety Data Sheet

**Emirates lubricants**

Revision date: 06.03.2024

Ecosynth HVLPD 46 S

Page 1 of 10

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Ecosynth HVLPD 46 S

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

Hydraulic fluid.

**1.3. Details of the supplier of the safety data sheet****Manufacturer**

|                         |                                            |                  |
|-------------------------|--------------------------------------------|------------------|
| Company name:           | Emirates lubricants                        |                  |
| Street:                 | Ras Al khaimah                             |                  |
| Place:                  | United Arab Emirates                       |                  |
| Telephone:              | +971 55 105 2851                           | +971 52 660 6888 |
| e-mail:                 | info@emirateslubricant.                    |                  |
| Contact person:         | Application Technology                     |                  |
| Internet:               | www.emirateslubricant.com                  |                  |
| Responsible Department: | Emirates lubricants Application Technology |                  |

**1.4. Emergency telephone number:** +971 52 660 6888 - This number is serviced during office hours.**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****GB CLP Regulation**

This mixture is not classified as hazardous in accordance with GB CLP Regulation.

**2.2. Label elements****GB CLP Regulation****Special labelling of certain mixtures**

EUH210 Safety data sheet available on request.

**Additional advice on labelling**

According to EC directives or the corresponding national regulations the product does not have to be labelled.

**2.3. Other hazards**

Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

Process vapors can irritate airways, skin and eyes.

Do not allow uncontrolled leakage of product into the environment.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures****Chemical characterization**

## Safety Data Sheet

## Emirates lubricants

Revision date: 06.03.2024

Ecosynth HVLPD 46 S

Page 2 of  
10

Mixture based on synthetic oils and special additives.

**Hazardous components**

| CAS No | Chemical name                                                                                                                                 |          |                  | Quantity      |
|--------|-----------------------------------------------------------------------------------------------------------------------------------------------|----------|------------------|---------------|
|        | EC No                                                                                                                                         | Index No | REACH No         |               |
|        | Classification (GB CLP Regulation)                                                                                                            |          |                  |               |
|        | Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched) |          |                  | 0.1 - < 0.3 % |
|        | 931-384-6                                                                                                                                     |          | 01-2119493620-38 |               |
|        | Acute Tox. 4, Eye Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H302 H319 H317 H411                                                              |          |                  |               |

Full text of H and EUH statements: see section 16.

**Specific Conc. Limits, M-factors and ATE**

| CAS No | EC No                                                                                                                    | Chemical name                                                                                                                                 | Quantity      |
|--------|--------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|---------------|
|        | Specific Conc. Limits, M-factors and ATE                                                                                 |                                                                                                                                               |               |
|        | 931-384-6                                                                                                                | Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched) | 0.1 - < 0.3 % |
|        | dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 2000 mg/kg Eye Irrit. 2; H319: >= 50 - 100 Skin Sens. 1; H317: >= 9,39 - 100 |                                                                                                                                               |               |

**Further Information**

This mixture does not contain any substances which either present a health or environmental hazard according to Regulation (EC) No. 1272/2008 or have an occupational exposure limit assigned.

DMSO-Extrakt < 3 %, IP 346.

Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

**SECTION 4: First aid measures****4.1. Description of first aid measures****General information**

Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

**After inhalation**

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist.

**After contact with skin**

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. In case of skin irritation, seek medical treatment.

**After contact with eyes**

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

**After ingestion**

Do NOT induce vomiting.

Rinse mouth immediately and drink plenty of water. Call a physician immediately.

## Safety Data Sheet

### **4.2. Most important symptoms and effects, both acute and delayed**

No information available.

### **4.3. Indication of any immediate medical attention and special treatment needed**

First Aid, decontamination, treatment of symptoms.

## **SECTION 5: Firefighting measures**

### **5.1. Extinguishing media**

#### **Emirates lubricants**

Revision date: 06.03.2024

Ecosynth HVLPD 46 S

Page 3 of 10

#### **Suitable extinguishing media**

Foam. Extinguishing powder. Carbon dioxide (CO<sub>2</sub>). Atomized water.

#### **Unsuitable extinguishing media**

High power water jet.

### **5.2. Special hazards arising from the substance or mixture**

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO<sub>2</sub>). Nitrogen oxides (NO<sub>x</sub>). carbon black.

### **5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus.

#### **Additional information**

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray jet to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

## **SECTION 6: Accidental release measures**

### **6.1. Personal precautions, protective equipment and emergency procedures**

#### **General advice**

High slip hazard because of leaking or spilled product. Remove all sources of ignition. Wear breathing apparatus if exposed to vapours/dusts/aerosols.

### **6.2. Environmental precautions**

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Prevent spread over a wide area (e.g. by containment or oil barriers).

### **6.3. Methods and material for containment and cleaning up**

#### **Other information**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean contaminated articles and floor according to the environmental legislation.

### **6.4. Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Section 12: Ecological Information (non-mandatory)

Disposal: see section 13

## **SECTION 7: Handling and storage**

## Safety Data Sheet

## Emirates lubricants

Ecosynth HVLPD 46 S

Page 4 of  
10

Revision date: 06.03.2024

**7.1. Precautions for safe handling****Advice on safe handling**

Work in well-ventilated zones or use proper respiratory protection. Avoid oil mist. If handled uncovered, arrangements with local exhaust ventilation have to be used. Avoid contact with skin, eyes and clothes.

**Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking.

**Advice on general occupational hygiene**

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Keep the packing dry and well sealed to prevent contamination and absorption of humidity. Keep container tightly closed in a cool place. Keep/Store only in original container.

**Hints on joint storage**

Keep away from food, drink and animal feedingstuffs.

Keep away from: Oxidizing agent

**Further information on storage conditions**

Protect against: UV-radiation/sunlight, frost, heat.

Recommended storage temperature: 5 - 40°C

**7.3. Specific end use(s)**

Hydraulic fluid. Further information: see technical data sheet.

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****DNEL/DMEL values**

| CAS No                   | Substance                                                                                                                                     |                |          |                   |
|--------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|----------------|----------|-------------------|
| DNEL type                |                                                                                                                                               | Exposure route | Effect   | Value             |
|                          | Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched) |                |          |                   |
| Worker DNEL, long-term   |                                                                                                                                               | inhalation     | systemic | 4,28 mg/m³        |
| Worker DNEL, long-term   |                                                                                                                                               | dermal         | systemic | 12,5 mg/kg bw/day |
| Consumer DNEL, long-term |                                                                                                                                               | inhalation     | systemic | 1,09 mg/m³        |
| Consumer DNEL, long-term |                                                                                                                                               | dermal         | systemic | 6,25 mg/kg bw/day |
| Consumer DNEL, long-term |                                                                                                                                               | oral           | systemic | 0,25 mg/kg bw/day |

**PNEC values**

| CAS No                    | Substance |  |
|---------------------------|-----------|--|
| Environmental compartment | Value     |  |

## Safety Data Sheet

| Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched) |               |
|-----------------------------------------------------------------------------------------------------------------------------------------------|---------------|
| Freshwater                                                                                                                                    | 0,0024 mg/l   |
| Freshwater (intermittent releases)                                                                                                            | 0,15 mg/l     |
| Marine water                                                                                                                                  | 0,00024 mg/l  |
| Freshwater sediment                                                                                                                           | 0,0129 mg/kg  |
| Marine sediment                                                                                                                               | 0,00129 mg/kg |
| Secondary poisoning                                                                                                                           | 10 mg/kg      |
| Micro-organisms in sewage treatment plants (STP)                                                                                              | 24,33 mg/l    |
| Soil                                                                                                                                          | 0,00117 mg/kg |

### Additional advice on limit values

Recommended limit value for oil mist

TWA: 5 mg/m<sup>3</sup>

STEL: 10 mg/m<sup>3</sup>

The product does not contain any relevant quantities of substances with legally established exposure limitation.

### 8.2. Exposure controls



**Emirates lubricants**

Revision date: 06.03.2024

Ecosynth HVLPD 46 S

Page 5 of 10

## Safety Data Sheet

### Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

### Individual protection measures, such as personal protective equipment

#### Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): EN 166

#### Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): EN ISO 374

Duration of wearing with permanent contact: 480

min Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.7 mm.

Wearing time with occasional contact (splashes): 30 min

Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

#### Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

#### Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Breathing protection with filter against organic gases and vapours type A - boiling point > 65°C: A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

|                  |                |
|------------------|----------------|
| Physical state:  | liquid         |
| Colour:          | yellow         |
| Odour:           | characteristic |
| Odour threshold: | not determined |

#### Test method

|                                            |                                   |
|--------------------------------------------|-----------------------------------|
| Melting point/freezing point:              | No data available                 |
| Boiling point or initial boiling point and | not determined                    |
| boiling range:                             |                                   |
| Flammability:                              | No data available                 |
| Lower explosion limits:                    | No data available                 |
| Upper explosion limits:                    | No data available                 |
| Flash point:                               | 245 °C DIN EN ISO 2592            |
| Auto-ignition temperature:                 | No data available                 |
| Decomposition temperature:                 | No data available                 |
| pH-Value:                                  | not applicable                    |
| Viscosity / kinematic:<br>(at 40 °C)       | 45 mm <sup>2</sup> /s ASTM D 7042 |
| Water solubility:                          | virtually insoluble               |

## Safety Data Sheet

Solubility in other solvents

No data available

Partition coefficient n-octanol/water:

No data available

Vapour pressure:

No data available

Density (at 15 °C):

0,846 g/cm<sup>3</sup> DIN 51757

Relative vapour density:

No data available

### Emirates lubricants

Revision date: 06.03.2024

Ecosynth HVLPD 46 S

Page 6 of 10

#### 9.2. Other information

##### Information with regard to physical hazard classes

Explosive properties

No data available

Self-ignition temperature

Solid:

No data available

Gas:

No data available

Oxidizing properties

No data available

##### Other safety characteristics

Evaporation rate:

No data available

Pour point:

-38 °C ASTM D 7346

#### SECTION 10: Stability and reactivity

##### 10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

##### 10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature. **10.3. Possibility of hazardous reactions** No known hazardous reactions.

##### 10.4. Conditions to avoid

Refer to chapter 7 No further action is necessary.

Do not overheat to avoid decomposition by heat.

##### 10.5. Incompatible materials

Reacts with: Oxidising agent, strong. Acid.

##### 10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO<sub>2</sub>). Nitrogen oxides (NO<sub>x</sub>). carbon black.  
No known hazardous decomposition products.

#### SECTION 11: Toxicological information

##### 11.1. Information on hazard classes as defined in GB CLP Regulation

###### Acute toxicity

Based on available data, the classification criteria are not met.

Mixture not tested.

| CAS No | Chemical name |
|--------|---------------|
|--------|---------------|

## Safety Data Sheet

## Emirates lubricants

Revision date: 06.03.2024

Ecosynth HVLDPD 46 S

Page 7 of  
10

|  | Exposure route                                                                                                                                | Dose              | Species | Source              | Method             |
|--|-----------------------------------------------------------------------------------------------------------------------------------------------|-------------------|---------|---------------------|--------------------|
|  | Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched) |                   |         |                     |                    |
|  | oral                                                                                                                                          | LD50 > 2000 mg/kg | Rat     | Study report (1995) | OECD Guideline 401 |
|  | dermal                                                                                                                                        | LD50 > 2000 mg/kg | Rabbit  |                     |                    |

**Irritation and corrosivity**

Based on available data, the classification criteria are not met.

**Sensitising effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction** Based on available data, the classification criteria are not met.**STOT-single exposure**

Based on available data, the classification criteria are not met.

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**11.2. Information on other hazards****Endocrine disrupting properties**

not applicable

**SECTION 12: Ecological information****12.1. Toxicity**

Based on available data, the classification criteria are not met.

Mixture not tested.

| CAS No | Chemical name                                                                                                                                 |                      |           |                                 |                            |                    |
|--------|-----------------------------------------------------------------------------------------------------------------------------------------------|----------------------|-----------|---------------------------------|----------------------------|--------------------|
|        | Aquatic toxicity                                                                                                                              | Dose                 | [h]   [d] | Species                         | Source                     | Method             |
|        | Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched) |                      |           |                                 |                            |                    |
|        | Acute fish toxicity                                                                                                                           | LL50 ca. 24 mg/l     | 96 h      | Oncorhynchus mykiss             | REACH Registration Dossier | OECD Guideline 203 |
|        | Acute algae toxicity                                                                                                                          | ErC50 6,4 mg/l       | 96 h      | Pseudokirchneriella subcapitata | REACH Registration Dossier | OECD Guideline 201 |
|        | Acute crustacea toxicity                                                                                                                      | EL50 ca. 91,4 mg/l   | 48 h      | Daphnia magna                   | REACH Registration Dossier | OECD Guideline 202 |
|        | Acute bacteria toxicity                                                                                                                       | (EC50 ca. 2433 mg/l) | 3 h       | activated sludge, domestic      | REACH Registration Dossier | OECD Guideline 209 |



## Safety Data Sheet

### 12.2. Persistence and degradability

Product is biodegradable. CEC-L-103-12: > 60%

### 12.3. Bioaccumulative potential

No data available

#### Partition coefficient n-octanol/water

| CAS No | Chemical name                                                                                                                                 | Log Pow |
|--------|-----------------------------------------------------------------------------------------------------------------------------------------------|---------|
|        | Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched) | < 0,3   |

#### BCF

| CAS No | Chemical name                                                                                                                                 | BCF | Species              | Source               |
|--------|-----------------------------------------------------------------------------------------------------------------------------------------------|-----|----------------------|----------------------|
|        | Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched) | 436 | Onchorhynchus mykiss | REACH Registration D |

### 12.4. Mobility in soil

Due to its low solubility in water the product is almost completely mechanically separated in biological waste

## Safety Data Sheet

Revision date: 06.03.2024

**Emirates lubricants**

Ecosynth HVLPD 46 S

Page 8 of 10

water treatment plants.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria.

**12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**12.7. Other adverse effects**

No data available

**Further information**

Do not allow uncontrolled leakage of product into the environment.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Disposal recommendations**

Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

**List of Wastes Code - residues/unused products**

130112 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste hydraulic oils; readily biodegradable hydraulic oils; hazardous waste

**Contaminated packaging**

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Dispose of waste according to applicable legislation. Packing which cannot be properly cleaned must be thrown away.

**SECTION 14: Transport information****Land transport (ADR/RID)**

**14.1. UN number or ID number:** -

**14.2. UN proper shipping name:** -

**14.3. Transport hazard class(es):** -

**14.4. Packing group:** -

**Inland waterways transport (ADN)**

**14.1. UN number or ID number:** -

**14.2. UN proper shipping name:** -

**14.3. Transport hazard class(es):** -

**14.4. Packing group:** -

**Marine transport (IMDG)**

**14.1. UN number or ID number:** -

**14.2. UN proper shipping name:** -

**14.3. Transport hazard class(es):** -

## Safety Data Sheet

**14.4. Packing group:** -

**Air transport (ICAO-TI/IATA-DGR)**

**14.1. UN number or ID number:** -

**14.2. UN proper shipping name:** -

**14.3. Transport hazard class(es):** -

**14.4. Packing group:** -

### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

### 14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

### 14.7. Maritime transport in bulk according to IMO instruments

## Emirates lubricants

Revision date: 06.03.2024

Ecosynth HVLDP 46 S

Page 9 of 10

not applicable

### Other applicable information

No dangerous good in sense of these transport regulations.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations

#### Regulations/legislation specific for the substance or mixture

#### National regulatory information

Water hazard class (D): 1 - slightly hazardous to water

### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

## SECTION 16: Other information

### Changes

This data sheet contains changes from the previous version in section(s): 5,7,8,9,10,12,13,16.

### Abbreviations and acronyms

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ASTM - American Society for the Testing of Materials; ATE - Acute Toxicity Estimates; bw - Body weight; CAO - Cargo Aircraft Only; CAS - Chemical Abstracts Service; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DNEL - Derived No-Effect Level; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); EG - European Union; EN - European standards; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISO - International Organisation for Standardization; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate;

## Safety Data Sheet

**Emirates lubricants**

Revision date: 06.03.2024

Ecosynth HVLPD 46 S

Page 10 of  
10

present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

---

NTP - National Toxicology Program; OECD - Organization for Economic Co-operation and Development; PBT - Persistent, Bioaccumulative and Toxic substance; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulation concerning the International Carriage of Dangerous Goods by Rail; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

---

**Relevant H and EUH statements (number and full text)**

|        |                                                  |
|--------|--------------------------------------------------|
| H302   | Harmful if swallowed.                            |
| H317   | May cause an allergic skin reaction.             |
| H319   | Causes serious eye irritation.                   |
| H411   | Toxic to aquatic life with long lasting effects. |
| EUH210 | Safety data sheet available on request.          |

**Further Information**

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

The above information describes exclusively the safety requirements of the product and is based on our  
*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*