

Safety Data Sheet

Revision date: 30.11.2022

Emirates lubricants

Gear Oil CKT 460

Page 1 of 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Gear Oil CKT 460

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Gearbox oil.

1.3. Details of the supplier of the safety data sheet**Manufacturer**

Company name: Emirates lubricants

Street: Ras Al khaimah

Place: United Arab Emirates

Telephone: +971 55 105 2851 +971 52 660 6888

e-mail: info@emirateslubricant.

Contact person: Application Technology

Internet: www.emirateslubricant.com

Responsible Department: Emirates lubricants Application Technology

1.4. Emergency telephone number: +971 52 660 6888 - This number is serviced during office hours.**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****GB CLP Regulation**

This mixture is not classified as hazardous in accordance with GB CLP Regulation.

2.2. Label elements**GB CLP Regulation****Special labelling of certain mixtures**

EUH210 Safety data sheet available on request.

Additional advice on labelling

According to EC directives or the corresponding national regulations the product does not have to be labelled.

2.3. Other hazards

Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

Spilled product must not leak into the ground.

Do not allow uncontrolled leakage of product into the environment.

SECTION 3: Composition/information on ingredients

Safety Data Sheet

Emirates lubricants

Revision date: 30.11.2022

Gear Oil CKT 460

Page 2 of
9**3.2. Mixtures Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
68037-01-4	1-Decene, homopolymer, hydrogenated			60 - < 80 %
	500-183-1		01-2119486452-34	
	Asp. Tox. 1; H304			
9003-29-6	Polybutenes			10 - < 15 %
	500-004-7			
	Asp. Tox. 1; H304			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
68037-01-4	500-183-1	1-Decene, homopolymer, hydrogenated	60 - < 80 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg	
9003-29-6	500-004-7	Polybutenes	10 - < 15 %
		inhalation: LC50 = 4820 mg/l (vapours); dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 10000 mg/kg	

Further Information

DMSO-Extrakt < 3 %, IP 346.

Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

After inhalation

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. In case of skin irritation, seek medical treatment.

Safety Data Sheet

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

After ingestion

Do NOT induce vomiting.

Rinse mouth thoroughly with water. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

Emirates lubricants

Revision date: 30.11.2022

Gear Oil CKT 460

Page 3 of 9

5.1. Extinguishing media

Suitable extinguishing media

Foam. Extinguishing powder. Carbon dioxide (CO₂). Atomized water.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO₂). Sulfur oxides. Phosphorus oxides. Nitrogen oxides (NO_x). carbon black

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray/stream to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

High slip hazard because of leaking or spilled product. Remove all sources of ignition. Wear breathing apparatus if exposed to vapours/dusts/aerosols. Avoid contact with skin, eye and clothing.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Prevent spread over a wide area (e.g. by containment or oil barriers).

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Section 12: Ecological Information (non-mandatory)

Disposal: see section 13

Safety Data Sheet

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Work in well-ventilated zones or use proper respiratory protection. Avoid oil mist. If handled uncovered, arrangements with local exhaust ventilation have to be used. Avoid contact with skin, eyes and clothes.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Advice on general occupational hygiene

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorption of humidity. Keep container tightly closed in a cool place. Keep/Store only in original container.

Emirates lubricants

Revision date: 30.11.2022

Gear Oil CKT 460

Page 4 of 9

Hints on joint storage

Keep away from food, drink and animal feedingstuffs.
Keep away from: Oxidizing agents.

Further information on storage conditions

Protect against: UV-radiation/sunlight. frost. heat.
Recommended storage temperature: 5 - 40°C

7.3. Specific end use(s)

Further information: see technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Additional advice on limit values

Recommended limit value for oil mist
TWA: 5 mg/m³
STEL: 10 mg/m³

The product does not contain any relevant quantities of substances with legally established exposure limitation.

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

Individual protection measures, such as personal protective equipment Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): EN 166

Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): EN ISO 374

Safety Data Sheet

Duration of wearing with permanent contact: 480 min
 Suitable material: NBR (Nitrile rubber).
 Thickness of glove material: 0.7 mm.

Wearing time with occasional contact (splashes): 30 min
 Suitable material: NBR (Nitrile rubber).
 Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Breathing protection with filter against organic gases and vapours type A - boiling point > 65°C: A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

Emirates lubricants

Gear Oil CKT 460

Page 5 of 9

Revision date: 30.11.2022

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	liquid
Colour:	yellow
Odour:	characteristic
Odour threshold:	not determined

Test method

Changes in the physical state

Melting point/freezing point:	No data available
Boiling point or initial boiling point and boiling range:	not determined
Pour point:	-43 °C ASTM D 7346
Flash point:	250 °C DIN ISO 2592

Flammability

Solid/liquid:	No data available
Gas:	No data available

Explosive properties

No data available

Lower explosion limits:	No data available
Upper explosion limits:	No data available
Auto-ignition temperature:	not determined

Self-ignition temperature

Solid:	No data available
Gas:	No data available

Safety Data Sheet

Decomposition temperature:	No data available
pH-Value:	No data available
Viscosity / kinematic: (at 40 °C)	470 mm ² /s ASTM D 7042
Water solubility:	virtually insoluble
Solubility in other solvents	
No data available	
Partition coefficient n-octanol/water:	No data available
Vapour pressure:	No data available
Density (at 15 °C):	0,860 g/cm ³ DIN 51757
Relative vapour density:	No data available

9.2. Other information

Information with regard to physical hazard classes

Oxidizing properties
No data available

Other safety characteristics

Evaporation rate: No data available

Further Information

No data available

Emirates lubricants

Revision date: 30.11.2022

Gear Oil CKT 460

Page 6 of 9

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature. **10.3. Possibility of hazardous reactions** No known hazardous reactions.

10.4. Conditions to avoid

Refer to chapter 7 No further action is necessary.

Do not overheat to avoid decomposition by heat.

10.5. Incompatible materials

Reacts with: Oxidizing agents, strong.

10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO₂). Sulfur oxides. Phosphorus oxides. Nitrogen oxides (NO_x). carbon black.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Safety Data Sheet

Emirates lubricants

Revision date: 30.11.2022

Gear Oil CKT 460

Page 7 of
9**Acute toxicity**

Based on available data, the classification criteria are not met.
Mixture not tested.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
68037-01-4	1-Decene, homopolymer, hydrogenate d				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1994)	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rat	Study report (1995)	OECD Guideline 402
9003-29-6	Polybutenes				
	oral	LD50 > 10000 mg/kg	Rat	Study report (1986)	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rat	Study report (1996)	OECD Guideline 402
	inhalation (4 h) vapour	LC50 4820 mg/l	Rat		

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.
Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards**Endocrine disrupting properties**

not applicable

SECTION 12: Ecological information**12.1. Toxicity**

No data available

Mixture not tested.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method

Safety Data Sheet

68037-01-4	1-Decene, homopolymer, hydrogenated					
	Acute fish toxicity	LL50 mg/l	> 1000	96 h	Oncorhynchus mykiss	Study report (1995) OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	> 1000	96 h	Pseudokirchneriella subcapitata	Study report (1995) OECD Guideline 201
	Acute crustacea toxicity	EL50 mg/l	> 1000	48 h	Daphnia magna	Study report (1995) OECD Guideline 202
9003-29-6	Polybutenes					
	Acute fish toxicity	LC50 mg/l	> 1,55	96 h	Cyprinus carpio	Other company data (2002) OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	> 19,2	72 h	Desmodesmus subspicatus	Other company data (2009) OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	> 3,1	48 h	Daphnia magna	Study report (2000) OECD Guideline 202

12.2. Persistence and degradability

Not easily bio-degradable (according to OECD-criteria). Do not allow to enter into surface water or drains.

12.3. Bioaccumulative potential

No data available

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
68037-01-4	1-Decene, homopolymer, hydrogenated	> 6,5
9003-29-6	Polybutenes	7,6 - 7,8

BCF

CAS No	Chemical name	BCF	Species	Source
9003-29-6	Polybutenes	314 - 1882		USEPA (2008)

12.4. Mobility in soil

Due to its low solubility in water the product is almost completely mechanically separated in biological waste water treatment plants.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No data available

Emirates lubricants

Revision date: 30.11.2022

Gear Oil CKT 460

Page 8 of 9

Further information

Do not allow uncontrolled leakage of product into the environment.

SECTION 13: Disposal considerations

Safety Data Sheet

13.1. Waste treatment methods

Disposal recommendations

Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

List of Wastes Code - residues/unused products

130206 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; synthetic engine, gear and lubricating oils; hazardous waste

Contaminated packaging

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Packing which cannot be properly cleaned must be thrown away. Dispose of waste according to applicable legislation.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: -

14.2. UN proper shipping name: -

14.3. Transport hazard class(es): -

14.4. Packing group: -

Inland waterways transport (ADN)

14.1. UN number or ID number: -

14.2. UN proper shipping name: -

14.3. Transport hazard class(es): -

14.4. Packing group: -

Marine transport (IMDG)

14.1. UN number or ID number: -

14.2. UN proper shipping name: -

14.3. Transport hazard class(es): -

14.4. Packing group: -

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: -

14.2. UN proper shipping name: -

14.3. Transport hazard class(es): -

14.4. Packing group: -

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

Other applicable information

No dangerous good in sense of these transport regulations.

Safety Data Sheet

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulatory information

Emirates lubricants

Revision date: 30.11.2022

Gear Oil CKT 460

Page 9 of 9

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,4,6,7,9,11,12,16.

Abbreviations and acronyms

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ASTM - American Society for the Testing of Materials; ATE - Acute Toxicity Estimates; bw - Body weight; CAO - Cargo Aircraft Only; CAS - Chemical Abstracts Service; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DNEL - Derived No-Effect Level; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); EG - European Union; EN - European standards; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISO - International Organisation for Standardization; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; OECD - Organization for Economic Co-operation and Development; PBT - Persistent, Bioaccumulative and Toxic substance; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulation concerning the International Carriage of Dangerous Goods by Rail; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Relevant H and EUH statements (number and full text)

H304 May be fatal if swallowed and enters airways.
EUH210 Safety data sheet available on request.

Further Information

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

Safety Data Sheet

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)