

Safety Data Sheet

Revision date: 15.01.2025

Emirates lubricants

Liquid Grease LIC 000

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Liquid Grease LIC 000

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Lubricant and additive.

1.3. Details of the supplier of the safety data sheet**Manufacturer**

Company name: Emirates lubricants

Street: Ras Al khaimah

Place: United Arab Emirates

Telephone: +971 55 105 2851 +971 52 660 6888

E-mail: info@emirateslubricant.

Contact person: Application Technology

Internet: www.emirateslubricant.com

Responsible Department: Emirates lubricants Application Technology

1.4. Emergency telephone number: +971 52 660 6888 - This number is serviced during office hours.**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****GB CLP Regulation**

This mixture is not classified as hazardous in accordance with GB CLP Regulation.

2.2. Label elements**GB CLP Regulation****Special labelling of certain mixtures**

EUH208 Contains Di-Tert-Dodecyl Polysulphide, Zinc naphthenate. May produce an allergic reaction.

EUH210 Safety data sheet available on request.

Additional advice on labelling

Product is classified and labelled in accordance with EC regulations or the corresponding national laws.

2.3. Other hazards

No risks worthy of mention.

If handled with proper care and at intended use, the product does not cause any harmful effects acc. to our experiences and available information.

Safety Data Sheet

Emirates lubricants

Revision date: 15.01.2025

Liquid Grease LIC 000

Page 2 of 11

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
68425-15-0	Di-Tert-Dodecyl Polysulphide			0.5 - < 1 %
	270-335-7		01-2119540516-41	
	Skin Sens. 1B; H317			
12001-85-3	Zinc naphthenate			0.5 - < 1 %
	234-409-2			
	Eye Irrit. 2, Skin Sens. 1B, Aquatic Chronic 2; H319 H317 H411			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
68425-15-0	270-335-7	Di-Tert-Dodecyl Polysulphide	0.5 - < 1 %
	inhalation: LC50 = > 15,5 mg/l (vapours); dermal: LD50 = 2000 mg/kg; oral: LD50 = 2000 mg/kg		
12001-85-3	234-409-2	Zinc naphthenate	0.5 - < 1 %
	oral: LD50 = > 2000 mg/kg		

Further Information

DMSO-Extract < 3 %; IP 346. Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

After inhalation

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. In case of skin irritation, seek medical treatment.

Safety Data Sheet

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

After ingestion

Do NOT induce vomiting.

Rinse mouth thoroughly with water. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Emirates lubricants

Revision date: 15.01.2025

Liquid Grease LIC 000

Page 3 of 11

Suitable extinguishing media

Carbon dioxide (CO₂). Extinguishing powder. Foam Sand.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO₂). Nitrogen oxides (NO_x).

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray jet to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

High slip hazard because of leaking or spilled product. Avoid contact with skin, eye and clothing.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Section 12: Ecological Information (non-mandatory)

Disposal: see section 13

SECTION 7: Handling and storage

Safety Data Sheet

Emirates lubricants

Liquid Grease LIC 000

Revision date: 15.01.2025

Page 4 of 11

7.1. Precautions for safe handling**Advice on safe handling**

Avoid contact with skin, eyes and clothes.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Advice on general occupational hygiene

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep the packing dry and well sealed to prevent contamination and absorption of humidity. Keep container tightly closed in a cool place. Keep/Store only in original container.

Hints on joint storage

Keep away from food, drink and animal feedingstuffs.

Keep away from: Oxidizing agent

Further information on storage conditions

Protect against: UV-radiation/sunlight. frost. heat.

Recommended storage temperature: 0 - 40°C

7.3. Specific end use(s)

Further information: see technical data sheet.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****DNEL/DMEL values**

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
68425-15-0	Di-Tert-Dodecyl Polysulphide			
Worker DNEL, long-term		inhalation	systemic	23,5 mg/m³
Worker DNEL, long-term		dermal	systemic	33,3 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	1,66 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	16,6 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	5,8 mg/m³
12001-85-3	Zinc naphthenate			
Worker DNEL, long-term		inhalation	systemic	1,18 mg/m³
Worker DNEL, long-term		dermal	systemic	3,3 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	0,29 mg/m³

Safety Data Sheet

Consumer DNEL, long-term	dermal	systemic	1,7 mg/kg bw/day
--------------------------	--------	----------	------------------

PNEC values

CAS No	Substance		
Environmental compartment			Value
68425-15-0	Di-Tert-Dodecyl Polysulphide		
Freshwater sediment			3,85 mg/kg
Marine sediment			0,385 mg/kg
Secondary poisoning			66,7 mg/kg
Micro-organisms in sewage treatment plants (STP)			1000 mg/l
12001-85-3	Zinc naphthenate		
Freshwater			0,004 mg/l
Freshwater (intermittent releases)			0,04 mg/l
Marine water			0 mg/l
Freshwater sediment			0,015 mg/kg
Marine sediment			0,002 mg/kg
Micro-organisms in sewage treatment plants (STP)			0,6897 mg/l
Soil			0,001 mg/kg

Additional advice on limit values

The product does not contain any relevant quantities of substances with legally established exposure limitation.

8.2. Exposure controls

Emirates lubricants

Revision date: 15.01.2025

Liquid Grease LIC 000

Page 5 of 11

Safety Data Sheet



Individual protection measures, such as personal protective equipment

Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): DIN EN ISO 16321

Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): EN ISO 374

Duration of wearing with permanent contact: 480 min

Suitable material: NBR (Nitrile rubber). Thickness of glove material: 0.7 mm.

Wearing time with occasional contact (splashes): 30 min

Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets. **Respiratory protection**

With correct and proper use, and under normal conditions, breathing protection is not required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	green
Odour:	characteristic
Odour threshold:	not determined

Test method

Melting point/freezing point:	> 120 °C
Boiling point or initial boiling point and boiling range:	> 250 °C
Flammability:	No data available
Lower explosion limits:	No data available
Upper explosion limits:	No data available
Flash point:	> 170 °C DIN EN ISO 2592
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
pH-Value:	not applicable
Viscosity / kinematic: (at 40 °C)	45 mm ² /s DIN 51562 - Base oil

Safety Data Sheet

Water solubility:	virtually insoluble
Solubility in other solvents	
No data available	
Partition coefficient n-octanol/water:	No data available
Vapour pressure:	No data available
Density (at 25 °C):	0,900 g/cm ³ DIN 51757
Relative vapour density:	No data available

Emirates lubricants

Revision date: 15.01.2025

Liquid Grease LIC 000

Page 6 of 11

Particle characteristics: No data available

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

No data available

Self-ignition temperature

Solid:

incapable of spontaneous heating.

Gas:

No data available

Oxidizing properties

No data available

Other safety characteristics

Evaporation rate:

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature. **10.3. Possibility of hazardous reactions** No known hazardous reactions.

10.4. Conditions to avoid

Refer to chapter 7 No further action is necessary.

Do not overheat to avoid decomposition by heat.

10.5. Incompatible materials

Reacts with: Oxidising agent, strong. Acids

10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO₂). Nitrogen oxides (NO_x).

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

Mixture not tested.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

Safety Data Sheet

Emirates lubricants

Revision date: 15.01.2025

Liquid Grease LIC 000

Page 7 of 11

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
68425-15-0	Di-Tert-Dodecyl Polysulphide				
	oral	LD50 20008 mg/kg	Rat	https://www.epa.gov/chemical-research/to	other: REACH guidance. Chapter R.6: QSAR
	dermal	LD50 2000 mg/kg	Rat	OECD 402	
	inhalation (4 h) vapour	LC50 > 15,5 mg/l	Rat	OECD 403	
12001-85-3	Zinc naphthenate				
	oral	LD50 > 2000 mg/kg	Rat	Study report (2018)	OECD Guideline 423

Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Contains Di-Tert-Dodecyl Polysulphide, Zinc naphthenate. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards**Endocrine disrupting properties**not applicable **Further****information**

If handled with proper care and at intended use, the product does not cause any harmful effects acc. to our experiences and available information.

SECTION 12: Ecological information**12.1. Toxicity**

Based on available data, the classification criteria are not met.

No data available

Mixture not tested.

Safety Data Sheet

Emirates lubricants

Revision date: 15.01.2025

Liquid Grease LIC 000

Page 8 of 11

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
68425-15-0	Di-Tert-Dodecyl Polysulphide					
	Acute fish toxicity	LC50 > 100 mg/l	96 h	Danio rerio (zebrafish)	OECD 203	
	Acute algae toxicity	ErC50 > 100 mg/l	72 h	Raphidocelis subcapitata	Study report (2010)	OECD Guideline 201
	Acute crustacea toxicity	EC50 < 0,1 mg/l	48 h	Daphnia magna		
12001-85-3	Zinc naphthenate					
	Acute fish toxicity	LL50 > 100 mg/l	96 h	Cyprinus carpio	REACH Registration Dossier	OECD Guideline 203
	Acute algae toxicity	ErC50 4 mg/l	72 h	Pseudokirchneriella subcapitata	REACH Registration Dossier	OECD Guideline 201
	Acute crustacea toxicity	EL50 35 mg/l	48 h	Daphnia magna	REACH Registration Dossier	OECD Guideline 202
	Acute bacteria toxicity	EC50 () 5,2 mg/l	3 h	activated sludge of a predominantly domestic sewage	Water research volume 17, nr10, 1363-136	OECD Guideline 209

12.2. Persistence and degradability

Not easily bio-degradable (according to OECD-criteria). Do not allow to enter into surface water or drains.

12.3. Bioaccumulative potential

No data available

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
68425-15-0	Di-Tert-Dodecyl Polysulphide	> 6,2
12001-85-3	Zinc naphthenate	0,8

BCF

CAS No	Chemical name	BCF	Species	Source
68425-15-0	Di-Tert-Dodecyl Polysulphide	< 0,01	Cyprinus carpio	REACH Registration D
12001-85-3	Zinc naphthenate	69,48	Capoeta fusca	Water Qual Expo Heal

12.4. Mobility in soil

Due to its low solubility in water the product is almost completely mechanically separated in biological waste water treatment plants.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria.

12.6. Endocrine disrupting properties

Safety Data Sheet

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No data available

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

Emirates lubricants

Revision date: 15.01.2025

Liquid Grease LIC 000

Page 9 of 11

13.1. Waste treatment methods

Disposal recommendations

Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

List of Wastes Code - residues/unused products

120112 WASTES FROM SHAPING AND PHYSICAL AND MECHANICAL SURFACE TREATMENT OF METALS AND PLASTICS; wastes from shaping and physical and mechanical surface treatment of metals and plastics; spent waxes and fats; hazardous waste

Contaminated packaging

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Dispose of waste according to applicable legislation. Packing which cannot be properly cleaned must be thrown away.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: -

14.2. UN proper shipping name: -

14.3. Transport hazard class(es): -

14.4. Packing group: -

Inland waterways transport (ADN)

14.1. UN number or ID number: -

14.2. UN proper shipping name: -

14.3. Transport hazard class(es): -

14.4. Packing group: -

Marine transport (IMDG)

14.1. UN number or ID number: -

14.2. UN proper shipping name: -

14.3. Transport hazard class(es): -

14.4. Packing group: -

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: -

14.2. UN proper shipping name: -

Safety Data Sheet

14.3. Transport hazard class(es): -

14.4. Packing group: -

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

Other applicable information

No dangerous good in sense of these transport regulations.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations

Regulations/legislation specific for the substance or mixture

EU regulatory information

Directive 2004/42/EC on VOC in
paints and varnishes: < 3 %

National regulatory information

Water hazard class (D):
1 - slightly hazardous to water

Emirates lubricants

Revision date: 15.01.2025

Liquid Grease LIC 000

Page 10 of 11

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,3,5,7,8,9,10,12,15.

Abbreviations and acronyms

Eye Irrit: Eye irritation

Skin Sens: Skin sensitisation

Aquatic Chronic: Chronic aquatic hazard

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ASTM - American Society for the Testing of Materials; ATE - Acute Toxicity Estimates; bw - Body weight; CAO - Cargo Aircraft Only; CAS - Chemical Abstracts Service; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DNEL - Derived No-Effect Level; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); EG - European Union; EN - European standards; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISO - International Organisation for Standardization; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate;

Safety Data Sheet

Emirates lubricants

Revision date: 15.01.2025

Liquid Grease LIC 000

Page 11 of 11

NTP - National Toxicology Program; OECD - Organization for Economic Co-operation and Development; PBT - Persistent, Bioaccumulative and Toxic substance; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulation concerning the International Carriage of Dangerous Goods by Rail; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Relevant H and EUH statements (number and full text)

H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.
EUH208	Contains Di-Tert-Dodecyl Polysulphide, Zinc naphthenate. May produce an allergic reaction.
EUH210	Safety data sheet available on request.

Further Information

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)