

Safety Data Sheet

Emirates lubricants

Revision date: 13.02.2024

Penta-Cool WM 442

Page 1 of 14

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Penta-Cool WM 442

UFI: 0ERS-565E-7203-CJTA

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Metal working fluids.

1.3. Details of the supplier of the safety data sheet**Manufacturer**

Company name: Emirates lubricants

Street: Ras Al khaimah

Place: United Arab Emirates

Telephone: +971 55 105 2851 +971 52 660 6888

e-mail: info@emirateslubricant.

Contact person: Application Technology

Internet: www.emirateslubricant.com

Responsible Department: Emirates lubricants Application Technology

1.4. Emergency telephone number: +971 52 660 6888 - This number is serviced during office hours.**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****GB CLP Regulation**

Skin Irrit. 2; H315

Eye Irrit. 2; H319

Skin Sens. 1; H317

Full text of hazard statements: see SECTION 16.

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

2.2. Label elements**GB CLP Regulation Hazard components for labelling**

1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one

Safety Data Sheet

Emirates lubricants

Revision date: 13.02.2024

Penta-Cool WM 442

Page 2 of
14

Signal word: Warning

Pictograms:



Hazard statements

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 Wash hands thoroughly after handling.
P272 Contaminated work clothing should not be allowed out of the workplace.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P501 Dispose of contents/container to an appropriate recycling or disposal facility.

Additional advice on labelling

The product is classified and labelled according to EC directives or corresponding national laws.

2.3. Other hazards

Prolonged/repetitive skin contact may cause skin defatting or dermatitis.
Spilled product must not leak into the ground.
Do not allow uncontrolled leakage of product into the environment.

SECTION 3: Composition/information on ingredients**3.2. Mixtures**

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
770-35-4	1-phenoxypropan-2-ol			2.5 - < 5 %
	212-222-7		01-2119486566-23	
	Eye Irrit. 2; H319			
1702655-09-1	Alkylamine Polyol Alkylphosphate			2.5 - < 5 %
	Eye Irrit. 2; STOT RE 2; H319 H373			
141-43-5	2-aminoethanol; ethanolamine			1 - < 2.5 %
	205-483-3	603-030-00-8		
	Acute Tox. 4, Acute Tox. 4, Acute Tox. 4, Skin Corr. 1B; H332 H312 H302 H314			

Safety Data Sheet

68920-66-1	Alcohols, C16-18 and C18-unsatd., ethoxylated			1 - < 2.5 %
	500-236-9		01-2119489407-26	
	Skin Irrit. 2, Aquatic Chronic 2; H315 H411			
3855-32-1	N-[3-(dimethylamino)propyl]-N,N',N'-trimethylpropane-1,3-diamine			0.5 - < 1 %
	223-362-3		01-2119983518-22	
	Acute Tox. 3, Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1, Aquatic Chronic 3; H311 H302 H314 H318 H412			
101-83-7	dicyclohexylamine			< 1 %
	202-980-7	612-066-00-3		
	Acute Tox. 4, Skin Corr. 1B, Aquatic Acute 1, Aquatic Chronic 1; H302 H314 H400 H410			
2634-33-5	1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one			0.1 - < 0.3 %
	220-120-9	613-088-00-6		
	Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, Skin Sens. 1, Aquatic Acute 1; H302 H315 H318 H317 H400			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
770-35-4	212-222-7	1-phenoxypropan-2-ol	2.5 - < 5 %
	dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 2000 mg/kg		
141-43-5	205-483-3	2-aminoethanol; ethanolamine	1 - < 2.5 %
	inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = 1025 mg/kg; oral: LD50 = 1515 mg/kg STOT SE 3; H335: >= 5 - 100		
68920-66-1	500-236-9	Alcohols, C16-18 and C18-unsatd., ethoxylated	1 - < 2.5 %
	dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 2000 mg/kg		
3855-32-1	223-362-3	N-[3-(dimethylamino)propyl]-N,N',N'-trimethylpropane-1,3-diamine	0.5 - < 1 %
	dermal: ATE = 300 mg/kg; oral: ATE = 500 mg/kg		
101-83-7	202-980-7	dicyclohexylamine	< 1 %
	dermal: LD50 = 200 - 316 mg/kg; oral: LD50 = 200 mg/kg		
2634-33-5	220-120-9	1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one	0.1 - < 0.3 %
	dermal: LD50 = > 2000 mg/kg; oral: LD50 = 670 mg/kg Skin Sens. 1; H317: >= 0,05 - 100		

Further Information

DMSO-Extrakt < 3 %, IP 346.

Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

Safety Data Sheet

Revision date: 13.02.2024

Emirates lubricants
Penta-Cool WM 442Page 3 of
14

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

After inhalation

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. Protect skin by using skin protective cream. In case of skin irritation, seek medical treatment.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

After ingestion

Do NOT induce vomiting.
Rinse mouth thoroughly with water. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam. Extinguishing powder. Carbon dioxide (CO₂). Atomized water.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon dioxide (CO₂). Carbon monoxide. Nitrogen oxides (NO_x). carbon black.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray jet to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

SECTION 6: Accidental release measures

Safety Data Sheet

Emirates lubricants

Revision date: 13.02.2024

Penta-Cool WM 442

Page 5 of
14**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

High slip hazard because of leaking or spilled product. Remove all sources of ignition. Wear breathing apparatus if exposed to vapours/dusts/aerosols. Avoid contact with skin, eye and clothing.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Prevent spread over a wide area (e.g. by containment or oil barriers).

6.3. Methods and material for containment and cleaning up**Other information**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Section 12: Ecological Information (non-mandatory)

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Work in well-ventilated zones or use proper respiratory protection. Avoid oil mist. If handled uncovered, arrangements with local exhaust ventilation have to be used. Avoid contact with skin, eyes and clothes.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Advice on general occupational hygiene

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep the packing dry and well sealed to prevent contamination and absorption of humidity. Keep container tightly closed in a cool place. Keep/Store only in original container.

Hints on joint storage

Keep away from food, drink and animal feedingstuffs.

Keep away from: Oxidizing agent

Further information on storage conditions

Protect against: UV-radiation/sunlight. frost. heat.

Recommended storage temperature: 5 - 40°C

7.3. Specific end use(s)

Further information: see technical data sheet.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters**

Safety Data Sheet

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
141-43-5	2-Aminoethanol	1	2.5		TWA (8 h)	WEL
		3	7.6		STEL (15 min)	WEL

DNEL/DMEL values

CAS No	Substance			
DNEL type	Exposure route		Effect	Value
770-35-4	1-phenoxypropan-2-ol			
Worker DNEL, long-term		inhalation	systemic	25,7 mg/m ³
Worker DNEL, long-term		dermal	systemic	42 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	21 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	3,65 mg/kg bw/day
68920-66-1	Alcohols, C16-18 and C18-unsatd., ethoxylated			
Consumer DNEL, long-term		inhalation	systemic	87 mg/m ³
Consumer DNEL, long-term		dermal	systemic	1250 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	25 mg/kg bw/day
Worker DNEL, long-term		dermal	systemic	2080 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	294 mg/m ³

Safety Data Sheet

Emirates lubricants

Penta-Cool WM 442

Page 6 of
14

Revision date: 13.02.2024

PNEC values

CAS No	Substance	
Environmental compartment		Value
770-35-4	1-phenoxypropan-2-ol	
Freshwater		0,1 mg/l
Freshwater (intermittent releases)		1 mg/l
Marine water		0,01 mg/l
Freshwater sediment		0,38 mg/kg
Marine sediment		0,038 mg/kg
Micro-organisms in sewage treatment plants (STP)		10 mg/l
Soil		0,02 mg/kg
68920-66-1	Alcohols, C16-18 and C18-unsatd., ethoxylated	
Freshwater		0,007 mg/l
Freshwater (intermittent releases)		0,1 mg/l
Marine water		0,001 mg/l
Freshwater sediment		22,79 mg/kg
Marine sediment		2,28 mg/kg
Micro-organisms in sewage treatment plants (STP)		10000 mg/l
Soil		1 mg/kg

Additional advice on limit values

source:

Recommended limit value for cooling lubricants (steam and aerosol)

MAK: 10 mg/m³**8.2. Exposure controls****Appropriate engineering controls**

Provide adequate ventilation as well as local exhaust at critical locations.

Individual protection measures, such as personal protective equipment Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): EN 166

Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): EN ISO 374

Safety Data Sheet

Duration of wearing with permanent contact: 480
min Suitable material: NBR (Nitrile rubber).
Thickness of glove material: 0.7 mm.

Wearing time with occasional contact (splashes): 30 min
Suitable material: NBR (Nitrile rubber).
Thickness of glove material: 0.4 mm

Protect skin by using skin protective
cream.

Emirates lubricants

Revision date: 13.02.2024

Penta-Cool WM 442

Page 7 of 14

Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. full mask (DIN EN 136). Breathing protection with filter against organic gases and vapours type A - boiling point > 65°C: A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid
Colour: yellow
Odour: like: mineral oil.
Odour threshold: not determined

Test method

Melting point/freezing point:	No data available
Boiling point or initial boiling point and boiling range:	> 100 °C
Flammability:	No data available
Lower explosion limits:	No data available
Upper explosion limits:	No data available
Flash point:	> 100 °C DIN EN ISO 2592
Auto-ignition temperature:	> 240 °C
Decomposition temperature:	No data available
pH-Value (at 20 °C):	9,7 5% - DIN 51369
Viscosity / kinematic: (at 20 °C)	200 mm ² /s DIN EN ISO 3104
Water solubility:	highly soluble.

Safety Data Sheet

Solubility in other solvents

No data available

Partition coefficient n-octanol/water:

No data available

Vapour pressure:

No data available

Density (at 15 °C):

0,988 g/cm³ DIN 12185

Relative vapour density:

No data available

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

No data available

Sustaining combustion:

No data available

Self-ignition temperature

Solid:

No data available

Gas:

No data available

Oxidizing properties

No data available

Other safety characteristics

Evaporation rate:

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

Emirates lubricants

Revision date: 13.02.2024

Penta-Cool WM 442

Page 8 of 14

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature. **10.3. Possibility of hazardous reactions** No known hazardous reactions.

10.4. Conditions to avoid

Refer to chapter 7 No further action is necessary.

10.5. Incompatible materials

Reacts with: Oxidising agent, strong

10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon dioxide (CO₂). Carbon monoxide. Nitrogen oxides (NO_x). carbon black.

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

Mixture not tested.

Safety Data Sheet

ATEmix calculated

ATE (oral) 63125,0 mg/kg; ATE (dermal) 18721,5 mg/kg; ATE (inhalation vapour) 458,33 mg/l; ATE (inhalation dust/mist) 62,500 mg/l

Safety Data Sheet

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
770-35-4	1-phenoxypropan-2-ol				
	oral	LD50 > 2000 mg/kg	Rat	SIDS Initial Assessment Report For - SIA	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rat	Study report (1986)	OECD Guideline 402
141-43-5	2-aminoethanol; ethanolamine				
	oral	LD50 1515 mg/kg	Rat		
	dermal	LD50 1025 mg/kg	Rabbit	IUCLID	
	inhalation vapour	ATE 11 mg/l			
	inhalation dust/mist	ATE 1,5 mg/l			
68920-66-1	Alcohols, C16-18 and C13-unsatd., ethoxylated				
	oral	LD50 > 2000 mg/kg	Rat	Study report (1982)	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rabbit	Study report (1982)	OECD Guideline 402
3855-32-1	N-[3-(dimethylamino)propyl]-N,N',N'-trimethylpropylamine-1,3-diamine				
	oral	ATE 500 mg/kg			
	dermal	ATE 300 mg/kg			
101-83-7	dicyclohexylamine				
	oral	LD50 200 mg/kg	Rat	Other company data (1978)	Single oral application by gavage, undil
	dermal	LD50 200 - 316 mg/kg	Rabbit	Other company data (1977)	other:
2634-33-5	1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one				
	oral	LD50 670 mg/kg	Rat	Study report (1988)	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rat	Study report (1994)	OECD Guideline 402

Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

Sensitising effects

May cause an allergic skin reaction. (1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one)

Safety Data Sheet**Emirates lubricants**

Revision date: 13.02.2024

Penta-Cool WM 442

Page 9 of
14

Carcinogenic/mutagenic/toxic effects for reproduction Based
on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

Aspiration hazard

Based on available data, the classification criteria are not met.

Emirates lubricants

Revision date: 13.02.2024

Penta-Cool WM 442

Page 10 of 14

11.2. Information on other hazards**Endocrine disrupting properties**

not applicable

SECTION 12: Ecological information**12.1. Toxicity**

Based on available data, the classification criteria are not met.

Mixture not tested.

Safety Data Sheet

Emirates lubricants

Revision date: 13.02.2024

Penta-Cool WM 442

Page 11 of 14

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
770-35-4	1-phenoxypropan-2-ol					
	Acute fish toxicity	LC50 280 mg/l	96 h	Pimephales promelas	Study report (1978)	OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l > 100	72 h	Desmodesmus subspicatus	Study report (1997)	EU Method C.3
	Acute crustacea toxicity	EC50 mg/l > 100	48 h	Daphnia magna	Study report (1997)	EU Method C.2
	Acute bacteria toxicity	(EC50 mg/l) > 1000	0,5 h	activated sludge, domestic	Study report (1999)	OECD Guideline 209
141-43-5	2-aminoethanol; ethanolamine					
	Acute fish toxicity	LC50 150 mg/l	96 h	Onchorhynchus mykiss	IUCLID	
	Acute algae toxicity	ErC50 22 mg/l	72 h	Desmodesmus subspicatus		
	Acute crustacea toxicity	EC50 65 mg/l	48 h	Daphnia magna		
68920-66-1	Alcohols, C16-18 and C18-unsatd., ethoxylated					
	Acute fish toxicity	LC50 108 mg/l	96 h	Danio rerio	Study report (2008)	OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l > 100	72 h	Desmodesmus subspicatus	Study report (1997)	other: EU-Guideline 92/69/EEG
	Acute crustacea toxicity	EL50 51 mg/l	48 h	Daphnia magna	Study report (2000)	OECD Guideline 202
	Fish toxicity	NOEC mg/l 0,16	10 d	Pimephales promelas	Study report (1995)	The effect of the test substance on survival
	Crustacea toxicity	NOEC mg/l 0,77	21 d	Daphnia magna	Publication (1999)	other: USEPA-TSCA
101-83-7	dicyclohexylamine					
	Acute fish toxicity	LC50 62 mg/l	96 h	Danio rerio	Study report (1992)	EU Method C.1
	Acute algae toxicity	ErC50 > 1 mg/l	72 h	Desmodesmus subspicatus	Other company data (1992)	EU Method C.3
	Acute crustacea toxicity	EC50 8 mg/l	48 h	Daphnia magna	Study report (1999)	OECD Guideline 202

Safety Data Sheet

Emirates lubricants

Revision date: 13.02.2024

Penta-Cool WM 442

Page 12 of
14

	Crustacea toxicity	NOEC mg/l	0,016	21 d	Daphnia magna	Study report (1999)	other: OECD Guideline 202, part 2 "Daphn
	Acute bacteria toxicity	(EC50 mg/l)	712	3 h	Activated sludge	Study report (1990)	ISO 8192
2634-33-5	1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one						
	Acute fish toxicity	LC50 mg/l	ca. 16,7	96 h	Cyprinodon variegatus	REACH Registration Dossier	other:
	Acute algae toxicity	ErC50 mg/l	0,15	72 h	Pseudokirchneriella subcapitata	Study report (1994)	OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	2,94	48 h	Daphnia magna	Study report (1995)	OECD Guideline 202
	Acute bacteria toxicity	(EC50 mg/l)	13	3 h	activated sludge of a predominantly domestic sewage	REACH Registration Dossier	OECD Guideline 209

12.2. Persistence and degradability

Not easily bio-degradable (according to OECD-criteria). Do not allow to enter into surface water or drains.

12.3. Bioaccumulative potential

Mixture not tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
770-35-4	1-phenoxypropan-2-ol	1,41
141-43-5	2-aminoethanol; ethanolamine	-1,91 (25°C)
68920-66-1	Alcohols, C16-18 and C18-unsatd., ethoxylated	ca. 7,19
101-83-7	dicyclohexylamine	2,724
2634-33-5	1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one	0,63

BCF

CAS No	Chemical name	BCF	Species	Source
68920-66-1	Alcohols, C16-18 and C18-unsatd., ethoxylated	387,5	Pimephales promelas	Publication (2000)
101-83-7	dicyclohexylamine	459		BCFWIN v. 2.1 (2005)
2634-33-5	1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one	ca. 6,62	Lepomis macrochirus	REACH Registration D

12.4. Mobility in soil

Is eliminable from water only with difficulty.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

Safety Data Sheet

12.7. Other adverse effects

No data available

Further information

Do not allow uncontrolled leakage of product into the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

List of Wastes Code - residues/unused products

120107 WASTES FROM SHAPING AND PHYSICAL AND MECHANICAL SURFACE TREATMENT OF METALS AND PLASTICS; wastes from shaping and physical and mechanical surface treatment of metals and plastics; mineral-based machining oils free of halogens (except emulsions and solutions); hazardous waste

List of Wastes Code - used product

120109 WASTES FROM SHAPING AND PHYSICAL AND MECHANICAL SURFACE TREATMENT OF METALS AND PLASTICS; wastes from shaping and physical and mechanical surface treatment of metals and plastics; machining emulsions and solutions free of halogens; hazardous waste

Contaminated packaging

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Dispose of waste according to applicable legislation. Packing which cannot be properly cleaned must be thrown away.

SECTION 14: Transport information

Safety Data Sheet

Revision date: 13.02.2024

Emirates lubricants

Penta-Cool WM 442

Page 13 of 14

Land transport (ADR/RID)

14.1. UN number or ID number: -**14.2. UN proper shipping name:** -**14.3. Transport hazard class(es):** -**14.4. Packing group:** -

Inland waterways transport (ADN)

14.1. UN number or ID number: -**14.2. UN proper shipping name:** -**14.3. Transport hazard class(es):** -**14.4. Packing group:** -

Marine transport (IMDG)

14.1. UN number or ID number: -**14.2. UN proper shipping name:** -**14.3. Transport hazard class(es):** -**14.4. Packing group:** -

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: -**14.2. UN proper shipping name:** -**14.3. Transport hazard class(es):** -**14.4. Packing group:** -**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

Other applicable information

No dangerous good in sense of these transport regulations.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 75

National regulatory information

Water hazard class (D): 1 - slightly hazardous to water

Safety Data Sheet

Emirates lubricants

Revision date: 13.02.2024

Penta-Cool WM 442

Page 14 of
14

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 9,15.

Abbreviations and acronyms

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ASTM - American Society for the Testing of Materials; ATE - Acute Toxicity Estimates; bw - Body weight; CAO -

Cargo Aircraft Only; CAS - Chemical Abstracts Service; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DNEL - Derived No-Effect Level; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); EG - European Union; EN - European standards; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISO - International Organisation for Standardization; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; OECD - Organization for Economic Co-operation and Development; PBT - Persistent, Bioaccumulative and Toxic substance; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulation concerning the International Carriage of Dangerous Goods by Rail; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1; H317	Calculation method

Relevant H and EUH statements (number and full text)

H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.

Safety Data Sheet

H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Further Information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)