

Safety Data Sheet

Revision date: 09.09.2024

Emirates lubricants
Chain Lube XHT 3000 Spray

Page 1 of 14

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Chain Lube XHT 3000 Spray

UFI: WNEK-JR24-K37Q-454Y

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Aerosol - Lubricating agent

1.3. Details of the supplier of the safety data sheet**Manufacturer**

Company name:	Emirates lubricants	
Street:	Ras Al khaimah	
Place:	United Arab Emirates	
Telephone:	+971 55 105 2851	+971 52 660 6888
E-mail:	info@emirateslubricant.	
Contact person:	Application Technology	
Internet:	www.emirateslubricant.com	
Responsible Department:	Emirates lubricants Application Technology	

1.4. Emergency telephone number:

+971 52 660 6888 - This number is serviced during office hours.

SECTION 2: Hazards identification

Safety Data Sheet

Emirates lubricants

Revision date: 09.09.2024

Chain Lube XHT 3000 Spray

Page 2 of
14**2.1. Classification of the substance or mixture****GB CLP Regulation**

Aerosol 1; H222-H229
 Asp. Tox. 1; H304
 Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

2.2. Label elements**GB CLP Regulation****Signal word:**

Danger

**Pictograms:****Hazard statements**

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P273	Avoid release to the environment.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container to an appropriate recycling or disposal facility.

Special labelling of certain mixtures

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

Additional advice on labelling

Product is classified and labelled in accordance with EC regulations or the corresponding national laws.

2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Relevant ingredients**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
106-97-8	butane			20 - < 40 %

Safety Data Sheet

	203-448-7		01-2119474691-32	
	Flam. Gas 1, Liquefied gas; H220 H280			
74-98-6	propane			10 - < 20 %
	200-827-9		01-2119486944-21	
	Flam. Gas 1, Liquefied gas; H220 H280			
	Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics			10 - < 20 %
	920-107-4		01-2119453414-43	
	Asp. Tox. 1; H304			
68937-41-7	Triaryl phosphate isopropylated			0.5 - < 1 %
	273-066-3		01-2119535109-41	
	Repr. 2, STOT RE 2, Aquatic Chronic 1; H361fd H373 H410			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
106-97-8	203-448-7	butane	20 - < 40 %
	inhalation: LC50 = 658 mg/l (vapours)		
	920-107-4	Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	10 - < 20 %
	dermal: LD50 = >= 3160 mg/kg; oral: LD50 = > 15000 mg/kg		
68937-41-7	273-066-3	Triaryl phosphate isopropylated	0.5 - < 1 %
	dermal: LD50 = > 10000 mg/kg Aquatic Chronic 1; H410: M=10		

Emirates lubricants

Revision date: 09.09.2024

Chain Lube XHT 3000 Spray

Page 3 of 14

Further Information

DMSO-Extract < 3 %; IP 346. Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

SECTION 4: First aid measures

Safety Data Sheet

4.1. Description of first aid measures

General information

Remove affected person from the danger area and lay down. Position and transport victim on their side. In case of respiratory distress, bring into semi-upright, seated position. Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

After inhalation

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist. In case of breathing difficulties administer oxygen. In case of respiratory tract irritation, consult a physician.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. In case of skin irritation, seek medical treatment.

After contact with eyes

If product gets into the eye, keep eyelid open and rinse immediately with large quantities of water, for at least 5 minutes. Subsequently consult an ophthalmologist.

After ingestion

Do NOT induce vomiting.

Rinse mouth thoroughly with water. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

following inhalation: drowsiness. Headache. Nausea.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water spray jet. Carbon dioxide (CO₂). Extinguishing powder. Foam.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon dioxide (CO₂). Carbon monoxide Nitrogen oxides (NO_x). carbon black.

Flammable. Vapours may form explosive mixtures with air.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Wear chemical resistant suit.

Additional information

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray jet to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Remove persons to safety. Wear a self-contained breathing apparatus and chemical resistant suit. Vapours

Emirates lubricants

Chain Lube XHT 3000 Spray

Revision date: 09.09.2024

Page 4 of 14

Safety Data Sheet

are heavier than air and will spread at floor level. Avoid contact with skin and eyes. Keep away from sources of ignition - No smoking.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Prevent spread over a wide area (e.g. by containment or oil barriers).

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7
Personal protection equipment: see section 8
Section 12: Ecological Information (non-mandatory)
Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use only in well-ventilated areas. Take precautionary measures against static discharges. Do not spray on naked flames or any incandescent material. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Avoid contact with skin, eyes and clothes.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Heating causes rise in pressure with risk of bursting.

Advice on general occupational hygiene

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorption of humidity. Keep container tightly closed in a cool place. Keep away from sources of ignition - No smoking.

Please note: TRG 300, aerosol directive (75/324/EEC).

Hints on joint storage

Keep away from food, drink and animal feedingstuffs.

Keep away from: Oxidizing agent. Material, rich in oxygen, oxidizing.

Further information on storage conditions

Recommended storage temperature: 5 - 40°C.
Do not store at temperatures over: 50°C.

7.3. Specific end use(s)

Further information: see technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Safety Data Sheet

Emirates lubricants

Chain Lube XHT 3000 Spray

Page 5 of
14

Revision date: 09.09.2024

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL

DNEL/DMEL values

CAS No	Substance			
DNEL type	Exposure route		Effect	Value
68937-41-7	Triaryl phosphate isopropylated			
Consumer DNEL, acute	oral		systemic	50 mg/kg bw/day
Worker DNEL, long-term	inhalation		systemic	0,145 mg/m ³
Worker DNEL, acute	inhalation		systemic	700 mg/m ³
Worker DNEL, long-term	dermal		systemic	0,25 mg/kg bw/day
Worker DNEL, acute	dermal		systemic	2000 mg/kg bw/day
Worker DNEL, acute	dermal		local	16 mg/cm ²
Consumer DNEL, acute	inhalation		systemic	350 mg/m ³
Consumer DNEL, long-term	dermal		systemic	0,0298 mg/kg bw/day
Consumer DNEL, acute	dermal		systemic	100 mg/kg bw/day
Consumer DNEL, acute	dermal		local	8 mg/cm ²
Consumer DNEL, long-term	oral		systemic	0,00835 mg/kg bw/day

PNEC values

CAS No	Substance	
Environmental compartment	Value	
68937-41-7	Triaryl phosphate isopropylated	
Freshwater	0 mg/l	
Freshwater (intermittent releases)	0,015 mg/l	
Marine water	0 mg/l	
Freshwater sediment	0,185 mg/kg	
Marine sediment	0,018 mg/kg	
Secondary poisoning	1,85 mg/kg	

Safety Data Sheet

Micro-organisms in sewage treatment plants (STP)	100 mg/l
Soil	2,5 mg/kg

Additional advice on limit values

source:

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

Emirates lubricants

Revision date: 09.09.2024

Chain Lube XHT 3000 Spray

Page 6 of 14

Individual protection measures, such as personal protective equipment

Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): EN 166

Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): EN ISO 374

Duration of wearing with permanent contact: 480

min Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.7 mm.

Wearing time with occasional contact (splashes): 30 min

Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Breathing protection with filter against organic gases and vapours type A - boiling point > 65°C: A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	gaseous
Colour:	light yellow
Odour:	characteristic
Odour threshold:	not determined

Melting point/freezing point:	not determined	Test method
Boiling point or initial boiling point and	< -20 °C	

Safety Data Sheet

boiling range:	
Flammability:	not applicable
Lower explosion limits:	0,5 vol. %
Upper explosion limits:	10,9 vol. %
Flash point:	< -20 °C DIN EN ISO 2592
Auto-ignition temperature:	232 °C DIN 51794
Decomposition temperature:	No data available
pH-Value:	not applicable
Viscosity / kinematic: (at 40 °C)	not applicable ASTM D 7042
Water solubility: (at 20 °C)	virtually insoluble
Solubility in other solvents	
No data available	
Partition coefficient n-octanol/water:	not applicable
Vapour pressure: (at 20 °C)	No data available
Density (at 20 °C):	0,722 g/cm³ DIN 51757
Relative vapour density:	not determined
Particle characteristics:	No data available

Emirates lubricants

Revision date: 09.09.2024

Chain Lube XHT 3000 Spray

Page 7 of 14

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

Self-ignition temperature

Solid:

not applicable

Gas:

not applicable

Oxidizing properties

No data available

Other safety characteristics

Evaporation rate:

not determined

SECTION 10: Stability and reactivity

Safety Data Sheet

10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature. **10.3. Possibility of hazardous reactions** Ignition hazard.

Vapours may form explosive mixtures with air.

10.4. Conditions to avoid

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children. Take precautionary measures against static discharges. See protective measures under point 7 and 8.

10.5. Incompatible materials

Keep away from: Oxidizing agent. Material, rich in oxygen, oxidizing.

10.6. Hazardous decomposition products

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

In case of fire may be liberated: Carbon dioxide (CO₂). Carbon monoxide Nitrogen oxides (NO_x). carbon black.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.
Mixture not tested.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

Safety Data Sheet

Emirates lubricants

Revision date: 09.09.2024

Chain Lube XHT 3000 Spray

Page 10 of 17

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
106-97-8	butane				
	inhalation (4 h) vapour	LC50 658 mg/l	Rat		
	Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics				
	oral	LD50 > 15000 mg/kg	Rat	Study report (1977)	OECD Guideline 401
	dermal	LD50 >= 3160 mg/kg	Rabbit	Study report (1984)	OECD Guideline 402
68937-41-7	Triaryl phosphate isopropylated				
	dermal	LD50 > 10000 mg/kg	Rabbit	Study report (1976)	other: 16 CFR 1500.40

Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

Aspiration hazard

May be fatal if swallowed and enters airways.

11.2. Information on other hazards**Endocrine disrupting properties**

not applicable Further information

If handled with proper care and at intended use, the product does not cause any harmful effects acc. to our experiences and available information.

SECTION 12: Ecological information**12.1. Toxicity**

Toxic to aquatic life with long lasting effects.

Mixture not tested.

CAS No	Chemical name				
	Aquatic toxicity	Dose	[h] [d]	Species	Source
					Method

Safety Data Sheet

Emirates lubricants

Revision date: 09.09.2024

Chain Lube XHT 3000 Spray

Page 11 of 17

106-97-8	butane					
	Acute fish toxicity	LC50 mg/l	49,9	96 h	Fish, no other information	United States Environmental Protection A The Ecosar class program has been develo
	Acute algae toxicity	ErC50 mg/l	19,37	96 h	Algae	USEPA OPPT Risk Assessment Division (200 Calculation using ECOSAR Program v1.00.
	Acute crustacea toxicity	EC50 mg/l	69,43	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200 Calculation using ECOSAR Program v1.00.
74-98-6	propane					
	Acute fish toxicity	LC50 mg/l	49,9	96 h	Fish, no other information	United States Environmental Protection A The Ecosar class program has been develo
	Acute algae toxicity	ErC50 mg/l	19,37	96 h	Algae	USEPA OPPT Risk Assessment Division (200 Calculation using ECOSAR Program v1.00.
	Acute crustacea toxicity	EC50 mg/l	69,43	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200 Calculation using ECOSAR Program v1.00.
	Hydrocarbons, C12-C15, -alkanes, iso alkanes, c /clics, < 2% aromatics					
	Acute fish toxicity	LC50 mg/l	> 1000	96 h	Oncorhynchus mykiss (Rainbow trout)	
	Acute algae toxicity	ErC50 mg/l	> 1000	72 h	Pseudokirchneriella subcapitata	REACH Registration Dossier OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	> 1000	48 h	Daphnia magna	
	Crustacea toxicity	NOEC mg/l	> 1000	21 d	Daphnia magna	REACH Registration Dossier The aquatic toxicity was estimated by a
68937-41-7	Triaryl phosphate isopropylated					
	Acute fish toxicity	LC50 mg/l	10,8	96 h	Pimephales promelas	REACH Registration Dossier OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	> 2,5	72 h	Raphidocelis subcapitata	REACH Registration Dossier EU Method C.3
	Acute crustacea toxicity	EC50	1,5 mg/l	48 h	Daphnia magna	REACH Registration Dossier OECD Guideline 202
	Fish toxicity	NOEC mg/l	0,0031	33 d	Pimephales promelas	REACH Registration Dossier OECD Guideline 210

Safety Data Sheet

Emirates lubricants

Revision date: 09.09.2024

Chain Lube XHT 3000 Spray

Page 12 of 17

	Crustacea toxicity	NOEC mg/l	0,0415	21 d	Daphnia magna	REACH Registration Dossier	OECD Guideline 211
	Acute bacteria toxicity	EC50 mg/l ()	> 1000	3 h	activated sludge, domestic	REACH Registration Dossier	OECD Guideline 209

12.2. Persistence and degradability

Not easily bio-degradable (according to OECD-criteria). Do not allow to enter into surface water or drains.

12.3. Bioaccumulative potential

No data available

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
106-97-8	butane	1,09
74-98-6	propane	1,09
	Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	>= 5,03
68937-41-7	Triaryl phosphate isopropylated	85000 - 150000

BCF

CAS No	Chemical name	BCF	Species	Source
	Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	>= 207,7		REACH Registration D
68937-41-7	Triaryl phosphate isopropylated	225	Lepomis macrochirus	REACH Registration D

12.4. Mobility in soil

Product is easily volatile. Product is difficult to dissolve in water.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No data available

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Do not open container by force. Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

Contaminated packaging

Dispose of waste according to applicable legislation.

SECTION 14: Transport information

Safety Data Sheet

Emirates lubricants

Revision date: 09.09.2024

Chain Lube XHT 3000 Spray

Page 13 of 17

Land transport (ADR/RID)

14.1. UN number or ID number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
Hazard label: 2.1



Classification code: 5F
Special Provisions: 190 327 344 625

Safety Data Sheet

Emirates lubricants

Revision date: 09.09.2024

Chain Lube XHT 3000 Spray

Page 11 of 14

Limited quantity: 1 L

Excepted quantity: E0

Transport category: 2

Tunnel restriction code: D

Inland waterways transport (ADN)**14.1. UN number or ID number:** UN 1950**14.2. UN proper shipping name:** AEROSOLS**14.3. Transport hazard class(es):** 2**14.4. Packing group:** -

Hazard label: 2.1



Classification code: 5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L

Excepted quantity: E0

Marine transport (IMDG)**14.1. UN number or ID number:** UN 1950**14.2. UN proper shipping name:** AEROSOLS**14.3. Transport hazard class(es):** 2.1**14.4. Packing group:** -

Hazard label: 2.1



Marine pollutant: no

Special Provisions: 63, 190, 277, 327, 344, 381, 959

Limited quantity: 1000mL

Excepted quantity: E0

EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)**14.1. UN number or ID number:** UN 1950

Safety Data Sheet

14.2. UN proper shipping name: AEROSOLS, flammable

14.3. Transport hazard class(es): 2.1

14.4. Packing group: -

Hazard label: 2.1



Special Provisions: A145 A167 A802

Limited quantity Passenger: 30 kg G

Passenger LQ: Y203

Excepted quantity: E0

IATA-packing instructions - Passenger: 203

IATA-max. quantity - Passenger: 75 kg

IATA-packing instructions - Cargo: 203

IATA-max. quantity - Cargo: 150 kg

Other applicable information (air transport)

Passenger LQ: Y203

Quantities released: E0

Emirates lubricants

Revision date: 09.09.2024

Chain Lube XHT 3000 Spray

Page 12 of 14

Danger: Y203

Special provisions: A145 - A153

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: flammable gases.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 29, Entry 40

Directive 2010/75/EU on industrial emissions: 42 % (303,24 g/l)

Directive 2004/42/EC on VOC in paints and varnishes: 53,6 % (386,992 g/l)

Information according to Directive 2012/18/EU (SEVESO III): P3a FLAMMABLE AEROSOLS

Additional information

To follow: 850/2004/EC , 79/117/EEC , 689/2008/EC , 2008/47/EC

Safety Data Sheet

Emirates lubricants

Revision date: 09.09.2024

Chain Lube XHT 3000 Spray

Page 13 of
14

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D):

2 - obviously hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,5,9,15.

Abbreviations and acronyms

Flam. Gas: Flammable gases

Aerosol: Aerosols

Liquefied gas

Asp. Tox: Aspiration hazard

Repr: Reproductive toxicity

STOT RE: Specific target organ toxicity - repeated exposure

Aquatic Chronic: Chronic aquatic hazard

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ASTM

- American Society for the Testing of Materials; ATE - Acute Toxicity Estimates; bw - Body weight; CAO -

Cargo Aircraft Only; CAS - Chemical Abstracts Service; CMR - Carcinogen, Mutagen or Reproductive

Toxicant; DIN - Standard of the German Institute for Standardisation; DNEL - Derived No-Effect Level; DOT -

Department of Transportation; DSL - Domestic Substances List (Canada); EG - European Union; EN -

European standards; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous

Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air

Transport Association; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation

Organization; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISO

- International Organisation for Standardization; LC50 - Lethal Concentration to 50 % of a test population; LD50

- Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the

Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise

Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect

Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate;

NTP - National Toxicology Program; OECD - Organization for Economic Co-operation and Development; PBT -

Persistent, Bioaccumulative and Toxic substance; (Q)SAR - (Quantitative) Structure Activity Relationship;

RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European

Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of

Chemicals; RID - Regulation concerning the International Carriage of Dangerous Goods by Rail; RQ -

Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments

and Reauthorization Act; SDS - Safety Data Sheet; TSCA - Toxic Substances Control Act (United States); UN -

United Nations; vPvB - Very Persistent and Very Bioaccumulative

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Aerosol 1; H222-H229	
Asp. Tox. 1; H304	
Aquatic Chronic 2; H411	Calculation method

Safety Data Sheet

Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Further Information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product

Emirates lubricants

Chain Lube XHT 3000 Spray

Page 14 of
14

Revision date: 09.09.2024

named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)