

Safety Data Sheet

Revision date: 20.10.2023

Emirates lubricants

Creep Oil

Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Creep Oil

UFI: VVU1-M7U5-520Y-UJ5W

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Corrosion inhibitor.

1.3. Details of the supplier of the safety data sheet**Manufacturer**

Company name: Emirates lubricants

Street: Ras Al khaimah

Place: United Arab Emirates

Telephone: +971 55 105 2851 +971 52 660 6888

e-mail: info@emirateslubricant.

Contact person: Application Technology

Internet: www.emirateslubricant.com

Responsible Department: Emirates lubricants Application Technology

1.4. Emergency telephone number: +971 52 660 6888 - This number is serviced during office hours.**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****GB CLP Regulation**

Asp. Tox. 1; H304

Full text of hazard statements: see SECTION 16.

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

2.2. Label elements**GB CLP Regulation Hazard components for labelling**

Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclics, < 2% aromatics

Signal word: Danger**Pictograms:**

Safety Data Sheet

Hazard statements

H304 May be fatal if swallowed and enters airways.

Emirates lubricants

Revision date: 20.10.2023

Creep Oil

Page 2 of 13

Precautionary statements

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
 P331 Do NOT induce vomiting.
 P405 Store locked up.
 P501 Dispose of contents/container to a waste disposal system.

Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

Additional advice on labelling

Product is classified and labelled in accordance with EC regulations or the corresponding national laws.

2.3. Other hazards

Prolonged/repetitive skin contact may cause skin defatting or dermatitis.
 Spilled product must not leak into the ground.
 Do not allow uncontrolled leakage of product into the environment.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture of mineral oil raffinates and additives.

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
	Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclics, < 2% aromatics			60 - < 80 %
	918-481-9		01-2119457273-39	
	Asp. Tox. 1; H304 EUH066			
112-34-5	2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether			2.5 - < 5 %
	203-961-6	603-096-00-8		
	Eye Irrit. 2; H319			
1474044-79-5	Calcium bis(di C8-C10, branched, C9 rich, alkyl naphthalenesulphonate)			1 - < 2.5 %
	939-717-7		01-2119980985-16	
	Skin Irrit. 2, Eye Irrit. 2; H315 H319			
110-25-8	N-methyl-N-[C18-(unsaturated)alkanoyl]glycine			0.5 - < 1 %
	203-749-3		01-2119488991-20	

Safety Data Sheet

Emirates lubricants

Revision date: 20.10.2023

Creep Oil

Page 3 of
13

	Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, Aquatic Acute 1, Aquatic Chronic 3; H332 H315 H318 H400 H412			
1471316-72-9	Benzenesulfonic acid, di-C10-14-alkyl derivs., calcium salts			0.5 - < 1 %
	939-603-7		01-2119978241-36	
	Skin Sens. 1; H317			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
	918-481-9	Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclics, < 2% aromatics	60 - < 80 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg	
112-34-5	203-961-6	2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether	2.5 - < 5 %
		dermal: LD50 = 2764 mg/kg; oral: LD50 = 2410 mg/kg	
1474044-79-5	939-717-7	Calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate)	1 - < 2.5 %
		inhalation: LC50 = > 18 mg/l (vapours)	
110-25-8	203-749-3	N-methyl-N-[C18-(unsaturated)alkanoyl]glycine	0.5 - < 1 %
		inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); oral: LD50 = > 5000 mg/kg	
1471316-72-9	939-603-7	Benzenesulfonic acid, di-C10-14-alkyl derivs., calcium salts	0.5 - < 1 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 10000 - < 20000 mg/kg Skin Sens. 1; H317: >= 10 - 100	

Further Information

DMSO-Extrakt < 3 %, IP 346.

Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets. In all cases of doubt, or when symptoms persist, seek medical advice.

After inhalation

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. In case of skin irritation, seek medical treatment.

Safety Data Sheet

After contact with eyes

Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Seek medical attention if problems persist.

After ingestion

Do NOT induce vomiting. Aspiration hazard

Rinse mouth thoroughly with water. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

The following symptoms may occur: Coughing, difficulties of breathing. In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam. Extinguishing powder. Carbon dioxide (CO₂).

Unsuitable extinguishing media

High power water jet.

Emirates lubricants

Revision date: 20.10.2023

Creep Oil

Page 4 of 13

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO₂). Sulfur oxides. Phosphorus oxides. Nitrogen oxides (NO_x). carbon black.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray jet to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

SECTION 6: Accidental release measures

Safety Data Sheet

Emirates lubricants

Revision date: 20.10.2023

Creep Oil

Page 5 of
13

6.1. Personal precautions, protective equipment and emergency procedures

General advice

High slip hazard because of leaking or spilled product. Remove all sources of ignition. Wear breathing apparatus if exposed to vapours/dusts/aerosols. Avoid contact with skin, eye and clothing.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Prevent spread over a wide area (e.g. by containment or oil barriers).

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Section 12: Ecological Information (non-mandatory)

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Work in well-ventilated zones or use proper respiratory protection. Avoid oil mist. If handled uncovered, arrangements with local exhaust ventilation have to be used. Avoid contact with skin, eyes and clothes.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Provide adequate ventilation. When hot, product develops flammable vapours.

Advice on general occupational hygiene

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorption of humidity. Keep container tightly closed in a cool place. Keep/Store only in original container.

Hints on joint storage

Keep away from food, drink and animal feedingstuffs.

Keep away from: Oxidizing agent

Further information on storage conditions

Recommended storage temperature: 5 - 40°C

Protect against: heat. UV-radiation/sunlight. frost.

7.3. Specific end use(s)

Further information: see technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Safety Data Sheet

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
112-34-5	2-(2-Butoxyethoxy)ethanol	10	67.5		TWA (8 h)	WEL
		15	101.2		STEL (15 min)	WEL

DNEL/DMEL values

CAS No	Substance			
DNEL type	Exposure route		Effect	Value
1474044-79-5	Calcium bis(di C8-C10, branched, C9 rich, alkyl)naphthalenesulphonate)			
Worker DNEL, long-term	inhalation		systemic	70 mg/m ³
Worker DNEL, long-term	dermal		systemic	10 mg/kg bw/day
Consumer DNEL, long-term	dermal		systemic	0,00032 mg/kg bw/day
Consumer DNEL, long-term	inhalation		systemic	2,23 mg/m ³
110-25-8	N-methyl-N-[C18-(unsaturated)alkanoyl]glycine			
Worker DNEL, long-term	inhalation		systemic	0,8 mg/m ³
Worker DNEL, long-term	dermal		systemic	4,2 mg/kg bw/day
Consumer DNEL, long-term	inhalation		systemic	0,4 mg/m ³
Consumer DNEL, long-term	dermal		systemic	1,5 mg/kg bw/day
Consumer DNEL, long-term	oral		systemic	1,5 mg/kg bw/day
1471316-72-9	Benzenesulfonic acid, di-C10-14-alkyl derivs., calcium salts			
Worker DNEL, long-term	inhalation		systemic	35,26 mg/m ³
Worker DNEL, long-term	dermal		systemic	25 mg/kg bw/day
Worker DNEL, acute	dermal		local	1,04 mg/cm ²
Consumer DNEL, long-term	inhalation		systemic	8,7 mg/m ³
Consumer DNEL, long-term	dermal		systemic	12,5 mg/kg bw/day
Consumer DNEL, acute	dermal		local	0,518 mg/cm ²
Consumer DNEL, long-term	oral		systemic	2,5 mg/kg bw/day

Safety Data Sheet

Emirates lubricants

Revision date: 20.10.2023

Creep Oil

Page 6 of
13

PNEC values

CAS No	Substance
Environmental compartment	
Value	
1474044-79-5	Calcium bis(di C8-C10, branched, C9 rich, alkyl naphthalenesulphonate)
Freshwater	
0,004 mg/l	
Freshwater (intermittent releases)	
0,0027 mg/l	
Marine water	
0,0004 mg/l	
Freshwater sediment	
69 mg/kg	
Marine sediment	
6,9 mg/kg	
Secondary poisoning	
22,2 mg/kg	
Micro-organisms in sewage treatment plants (STP)	
10 mg/l	
Soil	
13,9 mg/kg	
110-25-8	N-methyl-N-[C18-(unsaturated)alkanoyl]glycine
Freshwater	
0,004 mg/l	
Freshwater (intermittent releases)	
0,004 mg/l	
Marine water	
0 mg/l	
Freshwater sediment	
0,057 mg/kg	
Marine sediment	
0,006 mg/kg	
Micro-organisms in sewage treatment plants (STP)	
1 mg/l	
Soil	
1,71 mg/kg	
1471316-72-9	Benzenesulfonic acid, di-C10-14-alkyl derivs., calcium salts
Freshwater	
0,1 mg/l	
Freshwater (intermittent releases)	
1 mg/l	
Marine water	
0,1 mg/l	
Freshwater sediment	
45211 mg/kg	
Marine sediment	
45211 mg/kg	
Micro-organisms in sewage treatment plants (STP)	
1000 mg/l	

Safety Data Sheet

Soil	36739,74 mg/kg
------	----------------

Additional advice on limit values

Recommended limit value for oil mist

TWA: 5 mg/m³

STEL: 10 mg/m³

The product does not contain any relevant quantities of substances with legally established exposure limitation.

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

Individual protection measures, such as personal protective equipment

Emirates lubricants

Revision date: 20.10.2023

Creep Oil

Page 7 of 13

Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): EN 166

Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): EN ISO 374

Duration of wearing with permanent contact: 480 min

Suitable material: NBR (Nitrile rubber). PVC (polyvinyl chloride).

Thickness of glove material: 0.7 mm.

Wearing time with occasional contact (splashes): 30 min

Suitable material: NBR (Nitrile rubber). PVC (polyvinyl chloride).

Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Breathing protection with filter against organic gases and vapours type A - boiling point > 65°C: A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	liquid
Colour:	brown
Odour:	like: mineral oil.
Odour threshold:	not determined

Melting point/freezing point:

Test method
No data available

Safety Data Sheet

Boiling point or initial boiling point and boiling range:	100 °C
Flammability:	No data available
Lower explosion limits:	0,6 vol. %
Upper explosion limits:	6,5 vol. %
Flash point:	> 61 °C DIN EN ISO 2719
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
pH-Value:	not applicable
Viscosity / kinematic: (at 20 °C)	2,6 mm²/s DIN 51562
Water solubility:	insoluble
Solubility in other solvents	No data available
Partition coefficient n-octanol/water:	No data available
Vapour pressure:	No data available
Density (at 15 °C):	0,820 g/cm³ DIN 51757
Relative vapour density:	No data available

9.2. Other information

Information with regard to physical hazard classes

Emirates lubricants

Revision date: 20.10.2023

Creep Oil

Page 8 of 13

Explosive properties

No data available

Self-ignition temperature

Solid:

No data available

Gas:

No data available

Oxidizing properties

No data available

Other safety characteristics

Evaporation rate:

No data available

Pour point:

-30 °C ISO 3016

SECTION 10: Stability and reactivity

Safety Data Sheet

10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature. **10.3. Possibility of hazardous reactions** No known hazardous reactions.

10.4. Conditions to avoid

Refer to chapter 7 No further action is necessary.

Do not overheat to avoid decomposition by heat.

10.5. Incompatible materials

Reacts with: Oxidising agent, strong

10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO₂). Sulfur oxides. Phosphorus oxides.
Nitrogen oxides (NO_x). carbon black.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.
Mixture not tested.

Safety Data Sheet

Emirates lubricants

Revision date: 20.10.2023

Creep Oil

Page 11 of 16

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
	Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclics, < 2% aromatics				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1988)	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rat	Study report (1989)	OECD Guideline 402
112-34-5	2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether				
	oral	LD50 2410 mg/kg	Mouse	Study report (1981)	OECD Guideline 401
	dermal	LD50 2764 mg/kg	Rabbit	Study report (1981)	OECD Guideline 402
1474044-79-5	Calcium bis(di C8-C10, branched, C9 rich, alkyl naphthalenesulphonate)				
	inhalation (1 h) vapour	LC50 > 18 mg/l	Rat	Study report (1978)	other: FHSLA, CFR, Title 21 J para. 191.
110-25-8	N-methyl-N-[C18-(unsaturated)alkanol]glycine				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1981)	OECD Guideline 401
	inhalation vapour	ATE 11 mg/l			
	inhalation dust/mist	ATE 1,5 mg/l			
1471316-72-9	Benzenesulfonic acid, di-C10-14-alkyl derivs., calcium salts				
	oral	LD50 > 10000 - < 20000 mg/kg	Rat	Study report (1972)	Adult albino male Sprague-Dawley rats we
	dermal	LD50 > 2000 mg/kg	Rat	Study report (1989)	OECD Guideline 402

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction Based on available data, the classification criteria are not met.**STOT-single exposure**

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Repeated exposure may cause skin dryness or cracking.

Safety Data Sheet

Emirates lubricants

Revision date: 20.10.2023

Creep Oil

Page 12 of 16

Aspiration hazard

May be fatal if swallowed and enters airways.

11.2. Information on other hazards**Endocrine disrupting properties**

not applicable

SECTION 12: Ecological information**12.1. Toxicity**

Based on available data, the classification criteria are not met.

Mixture not tested.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
	Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclics, < 2% aromatics					
	Acute fish toxicity	LC50 1000 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)		
	Acute algae toxicity	ErC50 > 1000 mg/l	72 h	Pseudokirchneriella subcapitata	REACH Registration Dossier	OECD Guideline 201
	Acute crustacea toxicity	EC50 1000 mg/l	48 h	Daphnia magna		
	Fish toxicity	NOEC 0,101 mg/l	28 d	Oncorhynchus mykiss	REACH Registration Dossier	The aquatic toxicity was estimated by a
	Crustacea toxicity	NOEC 0,176 mg/l	21 d	Daphnia magna	REACH Registration Dossier	The aquatic toxicity was estimated by a
112-34-5	2-(2-butoxyethoxy)ethanol diethylene glycol monobutyl ether					
	Acute fish toxicity	LC50 1300 mg/l	96 h	Lepomis macrochirus	J Haz Mat, 1, p303-18 (1977)	OECD Guideline 203
	Acute algae toxicity	ErC50 > 100 mg/l	96 h	Desmodesmus subspicatus	Study report (1992)	OECD Guideline 201
	Acute crustacea toxicity	EC50 > 100 mg/l	48 h	Daphnia magna	Study report (1992)	EU Method C.2
1474044-79-5	Calcium bis(di C8-C10, branched, C9 ring, alkylmethylphthalenesulphonate)					
	Acute algae toxicity	ErC50 > 1,2 mg/l	72 h	Pseudokirchneriella subcapitata	REACH Registration Dossier	OECD Guideline 201
	Acute crustacea toxicity	EC50 >= 0,18 mg/l	48 h	Daphnia magna	REACH Registration Dossier	OECD Guideline 202

Safety Data Sheet

Emirates lubricants

Revision date: 20.10.2023

Creep Oil

Page 13 of 16

	Crustacea toxicity	NOEC	4,6 mg/l	21 d	Daphnia magna	REACH Registration Dossier	OECD Guideline 211
110-25-8	N-methyl-N-[C18-(unsaturated)alkanoyl]glycine						
	Acute fish toxicity	LC50 mg/l	> 0,43	96 h	Leuciscus idus	REACH Registration Dossier	EU Method C.1
	Acute algae toxicity	ErC50	5,1 mg/l	72 h	Desmodesmus subspicatus	REACH Registration Dossier	OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	0,53	48 h	Daphnia magna	REACH Registration Dossier	EU Method C.2
	Crustacea toxicity	NOEC mg/l	>= 0,183	21 d	Daphnia magna	REACH Registration Dossier	OECD Guideline 211
	Acute bacteria toxicity	(EC50 mg/l)	1300	3 h	Activated sludge	REACH Registration Dossier	OECD Guideline 209
1471316-72-9	Benzenesulfonic acid, di-10-14-alkyl derivs., calcium salts						
	Acute fish toxicity	LL50 mg/l	> 100	96 h	Oncorhynchus mykiss	Study report (2005)	OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	> 1000	72 h	Raphidocelis subcapitata	Study report (1994)	EPA OTS 797.1050
	Acute crustacea toxicity	EL50 mg/l	> 1000	48 h	Daphnia magna	Study report (1993)	EPA OTS 797.1300
	Acute bacteria toxicity	(EC50 mg/l)	> 10000	3 h	activated sludge of a predominantly domestic sewage	Study report (1994)	OECD Guideline 209

12.2. Persistence and degradability

Not easily bio-degradable (according to OECD-criteria). Do not allow to enter into surface water or drains.

12.3. Bioaccumulative potential

No data available

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
112-34-5	2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether	1
1474044-79-5	Calcium bis(di C8-C10, branched, C9 rich, alkyl)naphthalenesulphonate)	> 6,6
110-25-8	N-methyl-N-[C18-(unsaturated)alkanoyl]glycine	>= 3,5
1471316-72-9	Benzenesulfonic acid, di-C10-14-alkyl derivs., calcium salts	> 6,91

BCF

CAS No	Chemical name	BCF	Species	Source
	Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclics, < 2% aromatics	144,3	calculated	Other company data (

Safety Data Sheet

Emirates lubricants

Revision date: 20.10.2023

Creep Oil

Page 14 of 16

1474044-79-5	Calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate)	3,16	Fish	Study report (2013)
110-25-8	N-methyl-N-[C18-(unsaturated)alkanoyl]glycine	1,98	Fish	BCFBAF version 3.01
1471316-72-9	Benzenesulfonic acid, di-C10-14-alkyl derivs., calcium salts	70,8	Fish, not further specified.	Study report (2013)

12.4. Mobility in soil

Due to its low solubility in water the product is almost completely mechanically separated in biological waste water treatment plants.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No data available

Further information

Do not allow uncontrolled leakage of product into the environment.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

List of Wastes Code - residues/unused products

120199 WASTES FROM SHAPING AND PHYSICAL AND MECHANICAL SURFACE TREATMENT OF METALS AND PLASTICS; wastes from shaping and physical and mechanical surface treatment of metals and plastics; wastes not otherwise specified

Contaminated packaging

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Dispose of waste according to applicable legislation. Packing which cannot be properly cleaned must be thrown away.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number or ID number: -

14.2. UN proper shipping name: -

14.3. Transport hazard class(es): -

14.4. Packing group: -

Inland waterways transport (ADN)

14.1. UN number or ID number: -

14.2. UN proper shipping name: -

14.3. Transport hazard class(es): -

14.4. Packing group: -

Marine transport (IMDG)

14.1. UN number or ID number: -

14.2. UN proper shipping name: -

14.3. Transport hazard class(es): -

14.4. Packing group: -

Safety Data Sheet

Emirates lubricants

Revision date: 20.10.2023

Creep Oil

Page 15 of 16

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: -

14.2. UN proper shipping name: -

14.3. Transport hazard class(es): -

14.4. Packing group: -

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

Other applicable information

No dangerous good in sense of these transport regulations.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28, Entry 55

National regulatory information

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,5,7,9,10,12,13,15.

Abbreviations and acronyms

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ASTM - American Society for the Testing of Materials; ATE - Acute Toxicity Estimates; bw - Body weight; CAO - Cargo Aircraft Only; CAS - Chemical Abstracts Service; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DNEL - Derived No-Effect Level; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); EG - European Union; EN - European standards; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISO - International Organisation for Standardization; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; OECD - Organization for Economic Co-operation and Development; PBT - Persistent, Bioaccumulative and Toxic substance; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European

Safety Data Sheet

Emirates lubricants

Revision date: 20.10.2023

Creep Oil

Page 16 of 16

Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID -Regulation concerning the International Carriage of Dangerous Goods by Rail; RQ - Reportable Quantity; SADT - Self- Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Asp. Tox. 1; H304	Calculation method

Relevant H and EUH statements (number and full text)

H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H400	Very toxic to aquatic life.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)