

Safety Data Sheet

Revision date: 07.02.2024

Emirates lubricants
Multi Transmission Fluid 75W-80

Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Multi Transmission Fluid 75W-80

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Gearbox oil.

1.3. Details of the supplier of the safety data sheet**Manufacturer**

Company name:	Emirates lubricants		
Street:	Ras Al khaimah		
Place:	United Arab Emirates		
Telephone:	+971 55 105 2851	+971 52 660 6888	
e-mail:	info@emirateslubricant.		
Contact person:	Application Technology		
Internet:	www.emirateslubricant.com		
Responsible Department:	Emirates lubricants Application Technology		

1.4. Emergency telephone number: +971 52 660 6888 - This number is serviced during office hours.**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****GB CLP Regulation**

Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

2.2. Label elements**GB CLP Regulation Hazard statements**

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P273	Avoid release to the environment.
P501	Dispose of contents/container to industrial incineration plant.

Special labelling of certain mixtures

EUH208	Contains Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched). May produce an allergic reaction.
--------	---

Additional advice on labelling

Product is classified and labelled in accordance with EC regulations or the corresponding national laws.

Safety Data Sheet

Emirates lubricants

Revision date: 07.02.2024

Multi Transmission Fluid 75W-80

Page 2 of
13**2.3. Other hazards**

Prolonged/repetitive skin contact may cause skin defatting or dermatitis.
Spilled product must not leak into the ground.
Do not allow uncontrolled leakage of product into the environment.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified			60 - < 80 %
	265-157-1		01-2119484627-25	
	Asp. Tox. 1; H304			
64741-88-4	Distillates (petroleum), solvent-refined heavy paraffinic			20 - < 40 %
	265-090-8		01-2119488706-23	
	Asp. Tox. 1; H304			
	Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)			0.5 - < 1 %
	931-384-6		01-2119493620-38	
	Acute Tox. 4, Eye Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H302 H319 H317 H411			
1213789-63-9	(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines			0.1 - < 0.3 %
	627-034-4		01-2119473797-19	
	Acute Tox. 4, Skin Corr. 1B, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Acute 1, Aquatic Chronic 1; H302 H314 H335 H373 H304 H400 H410			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
64742-54-7	265-157-1	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified	60 - < 80 %
	dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg		
64741-88-4	265-090-8	Distillates (petroleum), solvent-refined heavy paraffinic	20 - < 40 %
	dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg		

Safety Data Sheet

	931-384-6	Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)	0.5 - < 1 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 2000 mg/kg Eye Irrit. 2; H319: >= 50 - 100 Skin Sens. 1; H317: >= 9,39 - 100	
1213789-63-9	627-034-4	(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines	0.1 - < 0.3 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = 1689 mg/kg Aquatic Acute 1; H400: M=10 Aquatic Chronic 1; H410: M=10	

Further Information

DMSO-Extrakt < 3 %, IP 346.

Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

SECTION 4: First aid measures

4.1. Description of first aid measures

Emirates lubricants

Revision date: 07.02.2024

Multi Transmission Fluid 75W-80

Page 3 of 13

General information

Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

After inhalation

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. In case of skin irritation, seek medical treatment.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

After ingestion

Do NOT induce vomiting.

Rinse mouth thoroughly with water. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

Safety Data Sheet

5.1. Extinguishing media

Suitable extinguishing media

Foam. Extinguishing powder. Carbon dioxide (CO₂). Atomized water.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO₂). Sulfur oxides. Phosphorus oxides. Nitrogen oxides (NO_x). carbon black.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray jet to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

High slip hazard because of leaking or spilled product. Remove all sources of ignition. Wear breathing apparatus if exposed to vapours/dusts/aerosols. Avoid contact with skin, eye and clothing.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Prevent spread over a wide area (e.g. by containment or oil barriers).

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean contaminated articles and floor according to the environmental legislation.

Emirates lubricants

Revision date: 07.02.2024

Multi Transmission Fluid 75W-80

Page 4 of 13

6.4. Reference to other sections

Safe handling: see section 7
Personal protection equipment: see section 8
Section 12: Ecological Information (non-mandatory)
Disposal: see section 13

SECTION 7: Handling and storage

Safety Data Sheet

Emirates lubricants

Revision date: 07.02.2024

Multi Transmission Fluid 75W-80

Page 5 of
13

7.1. Precautions for safe handling

Advice on safe handling

Work in well-ventilated zones or use proper respiratory protection. Avoid oil mist. If handled uncovered, arrangements with local exhaust ventilation have to be used. Avoid contact with skin, eyes and clothes.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Advice on general occupational hygiene

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorption of humidity. Keep container tightly closed in a cool place. Keep/Store only in original container.

Hints on joint storage

Keep away from food, drink and animal feedingstuffs.
Keep away from: Oxidizing agent

Further information on storage conditions

Recommended storage temperature: 5 - 40°C
Protect against: heat. UV-radiation/sunlight. frost.

7.3. Specific end use(s)

Further information: see technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified			
Worker DNEL, long-term		inhalation	systemic	2,73 mg/m³
Worker DNEL, long-term		inhalation	local	5,58 mg/m³
Worker DNEL, long-term		dermal	systemic	0,97 mg/kg bw/day
Consumer DNEL, long-term		inhalation	local	1,19 mg/m³
Consumer DNEL, long-term		oral	systemic	0,74 mg/kg bw/day
64741-88-4	Distillates (petroleum), solvent-refined heavy paraffinic			
Worker DNEL, long-term		inhalation	systemic	2,73 mg/m³
Worker DNEL, long-term		inhalation	local	5,58 mg/m³
Worker DNEL, long-term		dermal	systemic	0,97 mg/kg bw/day

Safety Data Sheet

Emirates lubricants

Revision date: 07.02.2024

Multi Transmission Fluid 75W-80

Page 6 of
13

Consumer DNEL, long-term	inhalation	local	1,19 mg/m ³
Consumer DNEL, long-term	oral	systemic	0,74 mg/kg bw/day
Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)			
Worker DNEL, long-term	inhalation	systemic	4,28 mg/m ³
Worker DNEL, long-term	dermal	systemic	12,5 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	1,09 mg/m ³
Consumer DNEL, long-term	dermal	systemic	6,25 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	0,25 mg/kg bw/day
1213789-63-9	(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines		
Worker DNEL, long-term	inhalation	systemic	0,38 mg/m ³
Worker DNEL, long-term	inhalation	local	1 mg/m ³
Worker DNEL, acute	inhalation	local	1 mg/m ³
Consumer DNEL, long-term	inhalation	systemic	0,035 mg/m ³
Consumer DNEL, long-term	oral	systemic	0,04 mg/kg bw/day

PNEC values

CAS No	Substance	
Environmental compartment		Value
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified	
Secondary poisoning		9,33 mg/kg
64741-88-4	Distillates (petroleum), solvent-refined heavy paraffinic	
Secondary poisoning		9,33 mg/kg
	Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)	
Freshwater		0,0024 mg/l
Freshwater (intermittent releases)		0,15 mg/l
Marine water		0,00024 mg/l
Freshwater sediment		0,0129 mg/kg
Marine sediment		0,00129 mg/kg

Safety Data Sheet

Secondary poisoning		10 mg/kg
Micro-organisms in sewage treatment plants (STP)		24,33 mg/l
Soil		0,00117 mg/kg
1213789-63-9	(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines	
Freshwater		0,00026 mg/l
Freshwater (intermittent releases)		0,0016 mg/l
Marine water		0,000026 mg/l
Freshwater sediment		3,76 mg/kg
Marine sediment		0,376 mg/kg
Micro-organisms in sewage treatment plants (STP)		0,55 mg/l
Soil		10 mg/kg

Additional advice on limit values

Recommended limit value for oil mist

TWA: 5 mg/m³

STEL: 10 mg/m³

The product does not contain any relevant quantities of substances with legally established exposure limitation.

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

Individual protection measures, such as personal protective equipment Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): EN 166

Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): EN ISO 374

Duration of wearing with permanent contact: 480 min

Emirates lubricants

Revision date: 07.02.2024

Multi Transmission Fluid 75W-80

Page 7 of 13

Safety Data Sheet

Suitable material: NBR (Nitrile rubber).
Thickness of glove material: 0.4 mm.

Wearing time with occasional contact (splashes): 30 min
Suitable material: NBR (Nitrile rubber).
Thickness of glove material: 0.2 mm

Protect skin by using skin protective cream.

Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Breathing protection with filter against organic gases and vapours type A - boiling point > 65°C: A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	liquid
Colour:	yellow - brown
Odour:	characteristic
Odour threshold:	not determined

Test method

Melting point/freezing point:	No data available
Boiling point or initial boiling point and boiling range:	No data available
Flammability:	No data available
Lower explosion limits:	No data available
Upper explosion limits:	No data available
Flash point:	220 °C DIN EN ISO 2592
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
pH-Value:	not applicable
Viscosity / kinematic: (at 100 °C)	9,3 mm ² /s ASTM D 7042
Water solubility:	No data available
Solubility in other solvents	No data available
Partition coefficient n-octanol/water:	No data available
Vapour pressure:	No data available
Density (at 15 °C):	0,867 g/cm ³ DIN 51757
Relative vapour density:	No data available

Safety Data Sheet

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

No data available

Self-ignition temperature

Solid:

No data available

Gas:

No data available

Oxidizing properties

No data available

Other safety characteristics

Emirates lubricants

Revision date: 07.02.2024

Multi Transmission Fluid 75W-80

Page 8 of 13

Evaporation rate:

No data available

Pour point:

-50 °C ASTM D 7346

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature. **10.3. Possibility of hazardous reactions** No known hazardous reactions.

10.4. Conditions to avoid

Refer to chapter 7 No further action is necessary.

Do not overheat to avoid decomposition by heat.

10.5. Incompatible materials

Reacts with: Oxidising agent, strong. Acid.

10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO₂). Sulfur oxides. Phosphorus oxides. Nitrogen oxides (NO_x). carbon black.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

Mixture not tested.

Safety Data Sheet

Emirates lubricants

Revision date: 07.02.2024

Multi Transmission Fluid 75W-80

Page 10 of 15

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1982)	OECD Guideline 401
	dermal	LD50 > 5000 mg/kg	Rabbit	Study report (1982)	OECD Guideline 402
64741-88-4	Distillates (petroleum), solvent-refined heavy paraffinic				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1982)	OECD Guideline 401
	dermal	LD50 > 5000 mg/kg	Rabbit	Study report (1982)	OECD Guideline 402
	Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)				
	oral	LD50 > 2000 mg/kg	Rat	Study report (1995)	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rabbit		
1213789-63-9	(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines				
	oral	LD50 1689 mg/kg	Rat	Study report (1993)	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rat	Study report (1985)	OECD Guideline 402

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Contains Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched). May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction Based

on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards**Endocrine disrupting properties**

not applicable

SECTION 12: Ecological information**12.1. Toxicity**

Safety Data Sheet

Emirates lubricants

Revision date: 07.02.2024

Multi Transmission Fluid 75W-80

Page 11 of 15

Harmful to aquatic life with long lasting effects.
Mixture not tested.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
64742-54-7	Distillates (petroleum), hydro-treated heavy paraffinic; Baseoil - unspecified					
	Acute fish toxicity	LL50 > 100 mg/l	96 h	Pimephales promelas	Study report (1995)	OECD Guideline 203
	Acute algae toxicity	ErC50 >100 mg/l	72 h			
	Fish toxicity	NOEC >= 1000 mg/l	14 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)	The aquatic toxicity was estimated by a
64741-88-4	Distillates (petroleum), solvent-refined heavy paraffinic					
	Acute fish toxicity	LL50 > 100 mg/l	96 h	Pimephales promelas	Study report (1995)	OECD Guideline 203
	Fish toxicity	NOEC >= 1000 mg/l	14 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)	The aquatic toxicity was estimated by a
	Reaction products of bis(4-methylpenta-1,2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)					
	Acute fish toxicity	LL50 ca. 24 mg/l	96 h	Oncorhynchus mykiss	REACH Registration Dossier	OECD Guideline 203
	Acute algae toxicity	ErC50 6,4 mg/l	96 h	Pseudokirchneriella subcapitata	REACH Registration Dossier	OECD Guideline 201
	Acute crustacea toxicity	EL50 ca. 91,4 mg/l	48 h	Daphnia magna	REACH Registration Dossier	OECD Guideline 202
	Acute bacteria toxicity	(EC50 ca. 2433 mg/l)	3 h	activated sludge, domestic	REACH Registration Dossier	OECD Guideline 209
1213789-63-9	(Z)-octadec-9-enylamine, 16-18-(even numbered, saturated and unsaturated)-alkylamines					
	Acute fish toxicity	LC50 0,84 mg/l	96 h	Danio rerio	Study report (2006)	OECD Guideline 203
	Acute algae toxicity	ErC50 0,39 mg/l	72 h	Desmodesmus subspicatus	Study report (2002)	OECD Guideline 201
	Acute crustacea toxicity	EC50 0,32 mg/l	48 h	Daphnia magna	Study report (2006)	OECD Guideline 202
	Crustacea toxicity	NOEC 0,013 mg/l	21 d	Daphnia magna	Study report (2002)	OECD Guideline 211
	Acute bacteria toxicity	(EC50 32 mg/l)	3 h	activated sludge of a predominantly domestic sewage	Study report (1989)	OECD Guideline 209

12.2. Persistence and degradability

Not easily bio-degradable (according to OECD-criteria). Do not allow to enter into surface water or drains.

Safety Data Sheet

Emirates lubricants

Revision date: 07.02.2024

Multi Transmission Fluid 75W-80

Page 12 of 15

12.3. Bioaccumulative potential

No data available

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
	Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)	< 0,3
1213789-63-9	(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines	5,16

BCF

CAS No	Chemical name	BCF	Species	Source
	Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)	436	Onchorhynchus mykiss	REACH Registration D
1213789-63-9	(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated) - alkylamines	173		Environmental Toxicology

12.4. Mobility in soil

Due to its low solubility in water the product is almost completely mechanically separated in biological waste water treatment plants.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meet the criteria.

12.7. Other adverse effects

No data available

Further information

Do not allow uncontrolled leakage of product into the environment.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

List of Wastes Code - residues/unused products

130205 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; mineral-based non-chlorinated engine, gear and lubricating oils; hazardous waste

Contaminated packaging

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Dispose of waste according to applicable legislation. Packing which cannot be properly cleaned must be thrown away.

SECTION 14: Transport information**Land transport (ADR/RID)****14.1. UN number or ID number:** -**14.2. UN proper shipping name:** -**14.3. Transport hazard class(es):** -

Safety Data Sheet**Emirates lubricants**

Revision date: 07.02.2024

Multi Transmission Fluid 75W-80

Page 13 of 15

14.4. Packing group: -

Inland waterways transport (ADN)

14.1. UN number or ID number: -**14.2. UN proper shipping name:** -**14.3. Transport hazard class(es):** -**14.4. Packing group:** -

Marine transport (IMDG)

14.1. UN number or ID number: -**14.2. UN proper shipping name:** -**14.3. Transport hazard class(es):** -

Safety Data Sheet

Emirates lubricants

Revision date: 07.02.2024

Multi Transmission Fluid 75W-80

Page 12 of 13

14.4. Packing group: -**Air transport (ICAO-TI/IATA-DGR)****14.1. UN number or ID number:** -**14.2. UN proper shipping name:** -**14.3. Transport hazard class(es):** -**14.4. Packing group:** -**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

Other applicable information

No dangerous good in sense of these transport regulations.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 75

National regulatory information

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 5,7,8,9,10,12,16.

Abbreviations and acronyms

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ASTM - American Society for the Testing of Materials; ATE - Acute Toxicity Estimates; bw - Body weight; CAO - Cargo Aircraft Only; CAS - Chemical Abstracts Service; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DNEL - Derived No-Effect Level; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); EG - European Union; EN - European standards; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISO - International Organisation for Standardization; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; OECD - Organization for Economic Co-operation and Development; PBT -

Safety Data Sheet

Emirates lubricants

Revision date: 07.02.2024

Multi Transmission Fluid 75W-80

Page 13 of
13

Persistent, Bioaccumulative and Toxic substance; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulation concerning the International Carriage of Dangerous Goods by Rail; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH208	Contains Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched). May produce an allergic reaction.

Further Information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)