

**Safety Data Sheet**

Revision date: 17.06.2024

**Emirates lubricants**  
Transmission Oil GH 75W-140

Page 1 of 12

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Transmission Oil GH 75W-140

UFI: QHSC-2451-G20Y-674M

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

Gearbox oil.

**1.3. Details of the supplier of the safety data sheet****Manufacturer**

Company name: Emirates lubricants

Street: Ras Al khaimah

Place: United Arab Emirates

Telephone: +971 55 105 2851 +971 52 660 6888

E-mail: info@emirateslubricant.

Contact person: Application Technology

Internet: www.emirateslubricant.com

Responsible Department: Emirates lubricants Application Technology

**1.4. Emergency telephone number:** +971 52 660 6888 - This number is serviced during office hours.**SECTION 2: Hazards identification**

## Safety Data Sheet

## Emirates lubricants

Revision date: 17.06.2024

Transmission Oil GH 75W-140

Page 2 of  
12**2.1. Classification of the substance or mixture****GB CLP Regulation**Skin Sens. 1; H317  
Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

**2.2. Label elements****GB CLP Regulation****Hazard components for labelling**

Amines, C10-C14-tert-alkyl

Signal word: Warning

**Pictograms:****Hazard statements**

|      |                                                    |
|------|----------------------------------------------------|
| H317 | May cause an allergic skin reaction.               |
| H412 | Harmful to aquatic life with long lasting effects. |

**Precautionary statements**

|           |                                                                                               |
|-----------|-----------------------------------------------------------------------------------------------|
| P261      | Avoid breathing dust/fume/gas/mist/vapours/spray.                                             |
| P280      | Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. |
| P302+P352 | IF ON SKIN: Wash with plenty of water.                                                        |
| P333+P313 | If skin irritation or rash occurs: Get medical advice/attention.                              |
| P362+P364 | Take off contaminated clothing and wash it before reuse.                                      |
| P501      | Dispose of contents/container to industrial incineration plant.                               |

**Additional advice on labelling**

The product is classified and labelled according to EC directives or corresponding national laws.

**2.3. Other hazards**

Prolonged/repetitive skin contact may cause skin defatting or dermatitis.  
Spilled product must not leak into the ground.  
Do not allow uncontrolled leakage of product into the environment.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures****Relevant ingredients**

| CAS No     | Chemical name                                                           |          |                  | Quantity    |
|------------|-------------------------------------------------------------------------|----------|------------------|-------------|
|            | EC No                                                                   | Index No | REACH No         |             |
|            | Classification (GB CLP Regulation)                                      |          |                  |             |
| 68037-01-4 | Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated |          |                  | 40 - < 60 % |
|            | 500-183-1                                                               |          | 01-2119486452-34 |             |

## Safety Data Sheet

|            |                                                                                                                                                                 |  |                  |               |
|------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|--|------------------|---------------|
|            | Asp. Tox. 1; H304                                                                                                                                               |  |                  |               |
| 68511-50-2 | 1-Propene, 2-methyl-, sulfurized                                                                                                                                |  |                  | 1 - < 2.5 %   |
|            | 270-943-2                                                                                                                                                       |  |                  |               |
|            | Aquatic Chronic 4; H413                                                                                                                                         |  |                  |               |
| 68955-53-3 | Amines, C10-C14-tert-alkyl                                                                                                                                      |  |                  | 0.3 - < 0.5 % |
|            | 701-175-2                                                                                                                                                       |  | 01-2119456798-18 |               |
|            | Acute Tox. 2, Acute Tox. 3, Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1, Skin Sens. 1A, Aquatic Acute 1, Aquatic Chronic 1; H330 H311 H302 H314 H318 H317 H400 H410 |  |                  |               |
| 112-90-3   | Oleinamine                                                                                                                                                      |  |                  | 0.1 - < 0.3 % |
|            | 204-015-5                                                                                                                                                       |  |                  |               |
|            | Acute Tox. 4, Skin Corr. 1C, Eye Dam. 1, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Acute 1, Aquatic Chronic 1; H302 H314 H318 H335 H373 H304 H400 H410         |  |                  |               |

Full text of H and EUH statements: see section 16.

#### Specific Conc. Limits, M-factors and ATE

| CAS No     | EC No                                                                                                                                      | Chemical name                                                           | Quantity      |
|------------|--------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------|---------------|
|            | Specific Conc. Limits, M-factors and ATE                                                                                                   |                                                                         |               |
| 68037-01-4 | 500-183-1                                                                                                                                  | Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated | 40 - < 60 %   |
|            | dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg                                                                                     |                                                                         |               |
| 68955-53-3 | 701-175-2                                                                                                                                  | Amines, C10-C14-tert-alkyl                                              | 0.3 - < 0.5 % |
|            | inhalation: LC50 = >= 157 mg/l (vapours); inhalation: ATE = 0,05 mg/l (dusts or mists); dermal: LD50 = 251 mg/kg; oral: LD50 = > 500 mg/kg |                                                                         |               |
| 112-90-3   | 204-015-5                                                                                                                                  | Oleinamine                                                              | 0.1 - < 0.3 % |
|            | oral: ATE = 500 mg/kg Aquatic Acute 1; H400: M=10<br>Aquatic Chronic 1; H410: M=10                                                         |                                                                         |               |

#### Emirates lubricants

Revision date: 17.06.2024

Transmission Oil GH 75W-140

Page 3 of 12

#### Further Information

DMSO-Extract < 3 %; IP 346. Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

#### SECTION 4: First aid measures

## Safety Data Sheet

### **4.1. Description of first aid measures**

#### **General information**

Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

#### **After inhalation**

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist.

#### **After contact with skin**

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. In case of skin irritation, seek medical treatment.

#### **After contact with eyes**

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

#### **After ingestion**

Do NOT induce vomiting.

Rinse mouth thoroughly with water. Call a physician immediately.

### **4.2. Most important symptoms and effects, both acute and delayed**

No information available.

### **4.3. Indication of any immediate medical attention and special treatment needed**

First Aid, decontamination, treatment of symptoms.

## **SECTION 5: Firefighting measures**

### **5.1. Extinguishing media**

#### **Suitable extinguishing media**

Foam. Extinguishing powder. Carbon dioxide (CO<sub>2</sub>). Atomized water.

#### **Unsuitable extinguishing media**

High power water jet.

### **5.2. Special hazards arising from the substance or mixture**

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO<sub>2</sub>). Sulfur oxides. Phosphorus oxides. Nitrogen oxides (NO<sub>x</sub>). carbon black.

### **5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus.

#### **Additional information**

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray jet to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. In case of fire: Wear self-contained breathing apparatus. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

## **SECTION 6: Accidental release measures**

### **6.1. Personal precautions, protective equipment and emergency procedures**

#### **General advice**

High slip hazard because of leaking or spilled product. Remove all sources of ignition. Wear breathing apparatus if exposed to vapours/dusts/aerosols. Avoid contact with skin, eyes and clothes.

**Emirates lubricants**

Revision date: 17.06.2024

Transmission Oil GH 75W-140

Page 4 of 12

## Safety Data Sheet

### **6.2. Environmental precautions**

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Prevent spread over a wide area (e.g. by containment or oil barriers).

### **6.3. Methods and material for containment and cleaning up**

#### **Other information**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean contaminated articles and floor according to the environmental legislation.

### **6.4. Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Section 12: Ecological Information (non-mandatory)

Disposal: see section 13

## **SECTION 7: Handling and storage**

### **7.1. Precautions for safe handling**

#### **Advice on safe handling**

Work in well-ventilated zones or use proper respiratory protection. Avoid oil mist. If handled uncovered, arrangements with local exhaust ventilation have to be used. Avoid contact with skin, eyes and clothes.

#### **Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking.

#### **Advice on general occupational hygiene**

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

### **7.2. Conditions for safe storage, including any incompatibilities**

#### **Requirements for storage rooms and vessels**

Keep the packing dry and well sealed to prevent contamination and absorption of humidity. Keep container tightly closed in a cool place.

#### **Hints on joint storage**

Keep away from food, drink and animal feedingstuffs.

Keep away from: Oxidizing agent

#### **Further information on storage conditions**

Recommended storage temperature: 5 - 40°C

Protect against: heat. UV-radiation/sunlight. frost.

### **7.3. Specific end use(s)**

Further information: see technical data sheet.

## **SECTION 8: Exposure controls/personal protection**

### **8.1. Control parameters**

## Safety Data Sheet

## Emirates lubricants

Transmission Oil GH 75W-140

Page 5 of  
12

Revision date: 17.06.2024

## DNEL/DMEL values

| CAS No                   | Substance                  |                |          |                   |
|--------------------------|----------------------------|----------------|----------|-------------------|
| DNEL type                |                            | Exposure route | Effect   | Value             |
| 68955-53-3               | Amines, C10-C14-tert-alkyl |                |          |                   |
| Worker DNEL, long-term   |                            | inhalation     | systemic | 12,5 mg/m³        |
| Worker DNEL, long-term   |                            | inhalation     | local    | 12,1 mg/m³        |
| Consumer DNEL, long-term |                            | inhalation     | systemic | 2,5 mg/m³         |
| Consumer DNEL, long-term |                            | inhalation     | local    | 1,2 mg/m³         |
| Consumer DNEL, long-term |                            | oral           | systemic | 0,35 mg/kg bw/day |

## PNEC values

| CAS No                                           | Substance                  |  |  |
|--------------------------------------------------|----------------------------|--|--|
| Environmental compartment                        | Value                      |  |  |
| 68955-53-3                                       | Amines, C10-C14-tert-alkyl |  |  |
| Freshwater                                       | 0,001 mg/l                 |  |  |
| Freshwater (intermittent releases)               | 0,004 mg/l                 |  |  |
| Marine water                                     | 0 mg/l                     |  |  |
| Freshwater sediment                              | 2,14 mg/kg                 |  |  |
| Marine sediment                                  | 0,214 mg/kg                |  |  |
| Secondary poisoning                              | 4,71 mg/kg                 |  |  |
| Micro-organisms in sewage treatment plants (STP) | 0,635 mg/l                 |  |  |
| Soil                                             | 0,428 mg/kg                |  |  |

## Additional advice on limit values

Recommended limit value for oil mist

TWA: 5 mg/m<sup>3</sup>STEL: 10 mg/m<sup>3</sup>

The product does not contain any relevant quantities of substances with legally established exposure limitation.

## 8.2. Exposure controls



## Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

## Individual protection measures, such as personal protective equipment Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): EN 166

## Safety Data Sheet

### Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): EN ISO 374

Duration of wearing with permanent contact: 480

min Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.7 mm.

Wearing time with occasional contact (splashes): 30 min

Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.4 mm

### Emirates lubricants

Revision date: 17.06.2024

Transmission Oil GH 75W-140

Page 6 of 12

Protect skin by using skin protective cream.

### Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

### Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Breathing protection with filter against organic gases and vapours type A - boiling point > 65°C: A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

|                  |                |
|------------------|----------------|
| Physical state:  | liquid         |
| Colour:          | brown          |
| Odour:           | characteristic |
| Odour threshold: | not determined |

#### Test method

|                                                           |                                   |
|-----------------------------------------------------------|-----------------------------------|
| Melting point/freezing point:                             | No data available                 |
| Boiling point or initial boiling point and boiling range: | not determined                    |
| Flammability:                                             | No data available                 |
| Lower explosion limits:                                   | No data available                 |
| Upper explosion limits:                                   | No data available                 |
| Flash point:                                              | >210 °C DIN EN ISO 2592           |
| Auto-ignition temperature:                                | not determined                    |
| Decomposition temperature:                                | No data available                 |
| pH-Value:                                                 | No data available                 |
| Viscosity / kinematic:<br>(at 100 °C)                     | 28 mm <sup>2</sup> /s ASTM D 7042 |
| Water solubility:                                         | virtually insoluble               |

## Safety Data Sheet

Solubility in other solvents

No data available

Partition coefficient n-octanol/water:

No data available

Vapour pressure:

No data available

Density (at 15 °C):

0,877 g/cm<sup>3</sup> DIN 51757

Relative vapour density:

No data available

Particle characteristics:

No data available

### 9.2. Other information

#### Information with regard to physical hazard classes

Explosive properties

No data available

Self-ignition temperature

Solid:

No data available

Gas:

No data available

Oxidizing properties

No data available

#### Other safety characteristics

Evaporation rate:

No data available

Pour point:

< - 48 °C ASTM D 7346

## SECTION 10: Stability and reactivity

### Emirates lubricants

Revision date: 17.06.2024

Transmission Oil GH 75W-140

Page 7 of 12

#### 10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

#### 10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature. **10.3. Possibility of hazardous reactions** No known hazardous reactions.

#### 10.4. Conditions to avoid

Refer to chapter 7 No further action is necessary.

Do not overheat to avoid decomposition by heat.

#### 10.5. Incompatible materials

Reacts with: Oxidising agent, strong. Acid.

#### 10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO<sub>2</sub>). Sulfur oxides. Phosphorus oxides. Nitrogen oxides (NO<sub>x</sub>). carbon black.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in GB CLP Regulation

#### Acute toxicity

Based on available data, the classification criteria are not met.

Mixture not tested.



## Safety Data Sheet

### ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) 83667 mg/kg; ATE (inhalation vapour) 166,7 mg/l; ATE (inhalation dust/mist) 16,67 mg/l

| CAS No     | Chemical name                                                               |                   |         |                     |                    |
|------------|-----------------------------------------------------------------------------|-------------------|---------|---------------------|--------------------|
|            | Exposure route                                                              | Dose              | Species | Source              | Method             |
| 68037-01-4 | Dec-1-ene, homopolymer, hydrogenated and Dec-1-ene, oligomers, hydrogenated |                   |         |                     |                    |
|            | oral                                                                        | LD50 > 5000 mg/kg | Rat     | Study report (1994) | OECD Guideline 401 |
|            | dermal                                                                      | LD50 > 2000 mg/kg | Rat     | Study report (1995) | OECD Guideline 402 |
| 68955-53-3 | Amines, C10-C14-tert-alkyl                                                  |                   |         |                     |                    |
|            | oral                                                                        | LD50 > 500 mg/kg  | Rat     | Study report (1993) | OECD Guideline 401 |
|            | dermal                                                                      | LD50 251 mg/kg    | Rat     | Study report (1993) | OECD Guideline 402 |
|            | inhalation (4 h) vapour                                                     | LC50 >= 157 mg/l  | Rat     | Study report (2001) | OECD Guideline 403 |
|            | inhalation dust/mist                                                        | ATE 0,05 mg/l     |         |                     |                    |
| 112-90-3   | Oleamine                                                                    |                   |         |                     |                    |
|            | oral                                                                        | ATE 500 mg/kg     |         |                     |                    |

### Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Irritant effect on the eye: mild irritant.

Irritant effect on the skin: Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

### Sensitising effects

May cause an allergic skin reaction. (Amines, C10-C14-tert-alkyl)

### Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

### STOT-single exposure

Based on available data, the classification criteria are not met.

### STOT-repeated exposure

Based on available data, the classification criteria are not met.

Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

### Aspiration hazard

Based on available data, the classification criteria are not met.

### 11.2. Information on other hazards

#### Endocrine disrupting properties

not applicable

## SECTION 12: Ecological information

### 12.1. Toxicity

Harmful to aquatic life with long lasting effects.

## Safety Data Sheet

## Emirates lubricants

Revision date: 17.06.2024

Transmission Oil GH 75W-140

Page 8 of  
12

Mixture not tested.

| CAS No     | Chemical name                                                           |                  |           |         |                                                     |                     |                    |
|------------|-------------------------------------------------------------------------|------------------|-----------|---------|-----------------------------------------------------|---------------------|--------------------|
|            | Aquatic toxicity                                                        | Dose             | [h]   [d] | Species | Source                                              | Method              |                    |
| 68037-01-4 | Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated |                  |           |         |                                                     |                     |                    |
|            | Acute fish toxicity                                                     | LL50<br>mg/l     | > 1000    | 96 h    | Oncorhynchus mykiss                                 | Study report (1995) | OECD Guideline 203 |
|            | Acute algae toxicity                                                    | ErC50<br>mg/l    | > 1000    | 96 h    | Raphidocelis subcapitata                            | Study report (1995) | OECD Guideline 201 |
|            | Acute crustacea toxicity                                                | EL50<br>mg/l     | > 1000    | 48 h    | Daphnia magna                                       | Study report (1995) | OECD Guideline 202 |
| 68955-53-3 | Amines, C10-C14-tert-alkyl                                              |                  |           |         |                                                     |                     |                    |
|            | Acute fish toxicity                                                     | LC50             | 1,3 mg/l  | 96 h    | Oncorhynchus mykiss                                 | Study report (1994) | OECD Guideline 203 |
|            | Acute algae toxicity                                                    | ErC50<br>mg/l    | 0,44      | 72 h    | Raphidocelis subcapitata                            | Study report (1994) | OECD Guideline 201 |
|            | Acute crustacea toxicity                                                | EC50             | 4,1 mg/l  | 48 h    | Daphnia magna                                       | Study report (1984) | OECD Guideline 202 |
|            | Fish toxicity                                                           | NOEC<br>mg/l     | 0,078     | 96 d    | Oncorhynchus mykiss                                 | Study report (2002) | OECD Guideline 210 |
|            | Acute bacteria toxicity                                                 | EC50<br>mg/l ( ) | 63,5      | 0,5 h   | activated sludge of a predominantly domestic sewage | Study report (2008) | OECD Guideline 209 |

**12.2. Persistence and degradability**

Not easily bio-degradable (according to OECD-criteria). Do not allow to enter into surface water or drains.

**12.3. Bioaccumulative potential**

No data available

**Partition coefficient n-octanol/water**

| CAS No     | Chemical name                                                           | Log Pow |
|------------|-------------------------------------------------------------------------|---------|
| 68037-01-4 | Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated | > 6,5   |
| 68955-53-3 | Amines, C10-C14-tert-alkyl                                              | 2,9     |

**12.4. Mobility in soil**

Due to its low solubility in water the product is almost completely mechanically separated in biological waste water treatment plants.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria.

**12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**12.7. Other adverse effects**

No data available

**Further information**

## Safety Data Sheet

## Emirates lubricants

Revision date: 17.06.2024

Transmission Oil GH 75W-140

Page 9 of  
12

Do not allow uncontrolled leakage of product into the environment.

## SECTION 13: Disposal considerations

## 13.1. Waste treatment methods

## Disposal recommendations

Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

## List of Wastes Code - residues/unused products

130206 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; synthetic engine, gear and lubricating oils; hazardous waste

## Contaminated packaging

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Dispose of waste according to applicable legislation. Packing which cannot be properly cleaned must be thrown away.

## SECTION 14: Transport information

## Land transport (ADR/RID)

- 14.1. UN number or ID number: -  
14.2. UN proper shipping name: -  
14.3. Transport hazard class(es): -  
14.4. Packing group: -

## Inland waterways transport (ADN)

- 14.1. UN number or ID number: -  
14.2. UN proper shipping name: -  
14.3. Transport hazard class(es): -  
14.4. Packing group: -

## Marine transport (IMDG)

- 14.1. UN number or ID number: -  
14.2. UN proper shipping name: -  
14.3. Transport hazard class(es): -  
14.4. Packing group: -

## Air transport (ICAO-TI/IATA-DGR)

- 14.1. UN number or ID number: -  
14.2. UN proper shipping name: -  
14.3. Transport hazard class(es): -

## Emirates lubricants

Revision date: 17.06.2024

Transmission Oil GH 75W-140

Page 10 of 12

- 14.4. Packing group: -

## Safety Data Sheet

### **14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

### **14.6. Special precautions for user**

Unless specified otherwise, general measures for safe transport must be followed.

### **14.7. Maritime transport in bulk according to IMO instruments**

not applicable

### **Other applicable information**

No dangerous good in sense of these transport regulations.

## **SECTION 15: Regulatory information**

### **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

#### **EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3

#### **National regulatory information**

Water hazard class (D): 1 - slightly hazardous to water

### **15.2. Chemical safety assessment**

Chemical safety assessments for substances in this mixture were not carried out.

## **SECTION 16: Other information**

### **Changes**

This data sheet contains changes from the previous version in section(s): 2,3,5,6,7,8,9,10,11,12,16.

### **Abbreviations and acronyms**

Acute Tox: Acute toxicity

Asp. Tox: Aspiration hazard

Skin Corr: Skin corrosion

Eye Dam: Eye damage

Skin Sens: Skin sensitisation

STOT SE: Specific target organ toxicity - single exposure

STOT RE: Specific target organ toxicity - repeated exposure

Aquatic Acute: Acute aquatic hazard

Aquatic Chronic: Chronic aquatic hazard

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ASTM - American Society for the Testing of Materials; ATE - Acute Toxicity Estimates; bw - Body weight; CAO - Cargo Aircraft Only; CAS - Chemical Abstracts Service; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DNEL - Derived No-Effect Level; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); EG - European Union; EN - European standards; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISO - International Organisation for Standardization; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate;

**Safety Data Sheet****Emirates lubricants**

Revision date: 17.06.2024

Transmission Oil GH 75W-140

Page 11 of 12

NTP - National Toxicology Program; OECD - Organization for Economic Co-operation and Development; PBT - Persistent, Bioaccumulative and Toxic substance; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulation concerning the International Carriage of Dangerous Goods by Rail; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

**Classification for mixtures and used evaluation method according to GB CLP Regulation**

| Classification          | Classification procedure |
|-------------------------|--------------------------|
| Skin Sens. 1; H317      | Calculation method       |
| Aquatic Chronic 3; H412 | Calculation method       |

**Relevant H and EUH statements (number and full text)**

|      |                                                                    |
|------|--------------------------------------------------------------------|
| H302 | Harmful if swallowed.                                              |
| H304 | May be fatal if swallowed and enters airways.                      |
| H311 | Toxic in contact with skin.                                        |
| H314 | Causes severe skin burns and eye damage.                           |
| H317 | May cause an allergic skin reaction.                               |
| H318 | Causes serious eye damage.                                         |
| H330 | Fatal if inhaled.                                                  |
| H335 | May cause respiratory irritation.                                  |
| H373 | May cause damage to organs through prolonged or repeated exposure. |
| H400 | Very toxic to aquatic life.                                        |
| H410 | Very toxic to aquatic life with long lasting effects.              |
| H412 | Harmful to aquatic life with long lasting effects.                 |
| H413 | May cause long lasting harmful effects to aquatic life.            |

**Emirates lubricants**

Revision date: 17.06.2024

Transmission Oil GH 75W-140

Page 12 of 12

**Further Information**

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*