

Safety Data Sheet

Revision date: 03.01.2024

Emirates lubricants
Compressor Oil VDL 68 S

Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Compressor Oil VDL 68 S

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Lubricant and additive.

1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name:	Emirates lubricants	
Street:	Ras Al khaimah	
Place:	United Arab Emirates	
Telephone:	+971 55 105 2851	+971 52 660 6888
e-mail:	info@emirateslubricant.	
Contact person:	Application Technology	
Internet:	www.emirateslubricant.com	
Responsible Department:	Emirates lubricants Application Technology	

1.4. Emergency telephone number: +971 52 660 6888 - This number is serviced during office hours.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

This mixture is not classified as hazardous in accordance with GB CLP Regulation.

2.2. Label elements

GB CLP Regulation

Special labelling of certain mixtures

EUH210 Safety data sheet available on request.

Additional advice on labelling

According to EC directives or the corresponding national regulations the product does not have to be labelled.

2.3. Other hazards

The mixture contains the following substances fulfilling the PBT criteria : alkylated diphenylamine.
Prolonged/repetitive skin contact may cause skin defatting or dermatitis.
Process vapors can irritate airways, skin and eyes.
Do not allow uncontrolled leakage of product into the environment.

SECTION 3: Composition/information on ingredients

Safety Data Sheet

Emirates lubricants

Revision date: 03.01.2024

Compressor Oil VDL 68 S

Page 2 of
10**3.2. Mixtures Chemical characterization**

Mixture based on synthetic oils and special additives.

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
68037-01-4	1-Decene, homopolymer, hydrogenated			80 - < 100 %
	500-183-1		01-2119486452-34	
	Asp. Tox. 1; H304			
68411-46-1	alkylated diphenylamine			0.1 - < 0.3 %
	270-128-1		01-2119491299-23	
	Repr. 2; H361f			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
68037-01-4	500-183-1	1-Decene, homopolymer, hydrogenated	80 - < 100 %
	dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg		
68411-46-1	270-128-1	alkylated diphenylamine	0.1 - < 0.3 %
	dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg		

Further Information

DMSO-Extrakt < 3 %, IP 346.

Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

After inhalation

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. In case of skin irritation, seek medical treatment.

Safety Data Sheet

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

After ingestion

Do NOT induce vomiting.

Rinse mouth thoroughly with water. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

Emirates lubricants

Revision date: 03.01.2024

Compressor Oil VDL 68 S

Page 3 of 10

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam. Extinguishing powder. Carbon dioxide (CO₂). Atomized water.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO₂). Sulfur oxides. Phosphorus oxides. Nitrogen oxides (NO_x). carbon black.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray jet to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately.

SECTION 6: Accidental release measures

Safety Data Sheet

Emirates lubricants

Revision date: 03.01.2024

Compressor Oil VDL 68 S

Page 4 of
10

6.1. Personal precautions, protective equipment and emergency procedures

General advice

High slip hazard because of leaking or spilled product. Remove all sources of ignition. Wear breathing apparatus if exposed to vapours/dusts/aerosols. Avoid contact with skin, eye and clothing.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Prevent spread over a wide area (e.g. by containment or oil barriers).

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Section 12: Ecological Information (non-mandatory)

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Work in well-ventilated zones or use proper respiratory protection. Avoid oil mist. If handled uncovered, arrangements with local exhaust ventilation have to be used. Avoid contact with skin, eyes and clothes.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Advice on general occupational hygiene

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorption of humidity. Keep container

tightly closed in a cool place. Keep/Store only in original container.

Hints on joint storage

Keep away from food, drink and animal feedingstuffs.

Keep away from: Oxidizing agent

Further information on storage conditions

Recommended storage temperature: 5 - 40°C

Protect against: heat. UV-radiation/sunlight. frost.

7.3. Specific end use(s)

Further information: see technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Safety Data Sheet

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
68411-46-1	alkylated diphenylamine			
Worker DNEL, long-term		inhalation	systemic	0,6 mg/m³
Worker DNEL, long-term		dermal	systemic	0,08 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	0,14 mg/m³
Consumer DNEL, long-term		dermal	systemic	0,04 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,04 mg/kg bw/day

PNEC values

CAS No	Substance			
Environmental compartment				Value
68411-46-1	alkylated diphenylamine			
Freshwater				0,034 mg/l
Freshwater (intermittent releases)				0,51 mg/l
Marine water				0,003 mg/l
Freshwater sediment				0,446 mg/kg
Marine sediment				0,045 mg/kg
Micro-organisms in sewage treatment plants (STP)				10 mg/l
Soil				1,76 mg/kg

Additional advice on limit values

Recommended limit value for oil mist

TWA: 5 mg/m³

STEL: 10 mg/m³

The product does not contain any relevant quantities of substances with legally established exposure limitation.

8.2. Exposure controls



Emirates lubricants

Revision date: 03.01.2024

Compressor Oil VDL 68 S

Page 5 of 10

Safety Data Sheet

Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

Individual protection measures, such as personal protective equipment

Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): EN 166

Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): EN ISO 374

Duration of wearing with permanent contact: 480

min Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.7 mm.

Wearing time with occasional contact (splashes): 30 min

Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Breathing protection with filter against organic gases and vapours type A - boiling point > 65°C: A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	liquid
Colour:	yellow - brown
Odour:	like: mineral oil.
Odour threshold:	not determined

Test method

Melting point/freezing point:	No data available
Boiling point or initial boiling point and	not determined
boiling range:	
Flammability:	No data available
Lower explosion limits:	No data available
Upper explosion limits:	No data available
Flash point:	277 °C DIN EN ISO 2592
Auto-ignition temperature:	not determined
Decomposition temperature:	No data available
pH-Value:	not applicable
Viscosity / kinematic: (at 40 °C)	66,2 mm ² /s ASTM D 7042
Water solubility:	virtually insoluble

Safety Data Sheet

Solubility in other solvents

No data available

Partition coefficient n-octanol/water:

No data available

Vapour pressure:

No data available

Density (at 15 °C):

0,842 g/cm³ DIN 51757

Relative vapour density:

No data available

Emirates lubricants

Revision date: 03.01.2024

Compressor Oil VDL 68 S

Page 6 of 10

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

No data available

Self-ignition temperature

Solid:

No data available

Gas:

No data available

Oxidizing properties

No data available

Other safety characteristics

Evaporation rate:

No data available

Pour point:

-60 °C ASTM D 7346

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature. **10.3. Possibility of hazardous reactions** No known hazardous reactions.

10.4. Conditions to avoid

Refer to chapter 7 No further action is necessary.

Do not overheat to avoid decomposition by heat.

10.5. Incompatible materials

Reacts with: Oxidising agent, strong. Acid.

10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO₂). Sulfur oxides. Phosphorus oxides. Nitrogen oxides (NO_x). carbon black.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

Mixture not tested.

CAS No	Chemical name
--------	---------------

Safety Data Sheet

Emirates lubricants

Revision date: 03.01.2024

Compressor Oil VDL 68 S

Page 7 of
10

	Exposure route	Dose	Species	Source	Method
68037-01-4	1-Decene, homopolymer, hydrogenated				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1994)	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rat	Study report (1995)	OECD Guideline 402
68411-46-1	alkylated diphenylamine				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1982)	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rat	Study report (1988)	OECD Guideline 402

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards**Endocrine disrupting properties**

not applicable

SECTION 12: Ecological information**12.1. Toxicity**

Based on available data, the classification criteria are not met.

Mixture not tested.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
68037-01-4	1-Decene, homopolymer, hydrogenated					
	Acute fish toxicity	LL50 > 1000 mg/l	96 h	Oncorhynchus mykiss	Study report (1995)	OECD Guideline 203
	Acute algae toxicity	ErC50 > 1000 mg/l	96 h	Pseudokirchneriella subcapitata	Study report (1995)	OECD Guideline 201

Safety Data Sheet

	Acute crustacea toxicity	EL50 mg/l	> 1000	48 h	Daphnia magna	Study report (1995)	OECD Guideline 202
68411-46-1	alkylated diphenylamine						
	Acute fish toxicity	LC50 mg/l	> 100	96 h	Danio rerio	Study report (1988)	OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	> 100	72 h	Desmodesmus subspicatus	Study report (2006)	OECD Guideline 201
	Acute crustacea toxicity	EC50	51 mg/l	48 h	Daphnia magna	Study report (2004)	OECD Guideline 202

12.2. Persistence and degradability

Not easily bio-degradable (according to OECD-criteria). Do not allow to enter into surface water or drains.

12.3. Bioaccumulative potential

No data available

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
68037-01-4	1-Decene, homopolymer, hydrogenated	> 6,5
68411-46-1	alkylated diphenylamine	6,66

BCF

CAS No	Chemical name	BCF	Species	Source
68411-46-1	alkylated diphenylamine	411	Cyprinus carpio	Study report (2000)

Safety Data Sheet

Revision date: 03.01.2024

Emirates lubricants

Compressor Oil VDL 68 S

Page 8 of 10

12.4. Mobility in soil

Due to its low solubility in water the product is almost completely mechanically separated in biological waste water treatment plants.

12.5. Results of PBT and vPvB assessment

The mixture contains the following substances fulfilling the PBT criteria: alkylated diphenylamine.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No data available

Further information

Do not allow uncontrolled leakage of product into the environment.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

List of Wastes Code - residues/unused products

130206 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; synthetic engine, gear and lubricating oils; hazardous waste

Contaminated packaging

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Dispose of waste according to applicable legislation. Packing which cannot be properly cleaned must be thrown away.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number or ID number: -

14.2. UN proper shipping name: -

14.3. Transport hazard class(es): -

14.4. Packing group: -

Inland waterways transport (ADN)

14.1. UN number or ID number: -

14.2. UN proper shipping name: -

14.3. Transport hazard class(es): -

14.4. Packing group: -

Marine transport (IMDG)

14.1. UN number or ID number: -

14.2. UN proper shipping name: -

Safety Data Sheet

14.3. Transport hazard class(es): -

14.4. Packing group: -

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: -

14.2. UN proper shipping name: -

14.3. Transport hazard class(es): -

14.4. Packing group: -

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

Emirates lubricants

Revision date: 03.01.2024

Compressor Oil VDL 68 S

Page 9 of 10

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

Other applicable information

No dangerous good in sense of these transport regulations.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations

National regulatory information

Water hazard class (D): 1 - slightly hazardous to water

Regulations/legislation specific for the substance or mixture

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,7,8,9,10,11,12,13,16.

Abbreviations and acronyms

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ASTM - American Society for the Testing of Materials; ATE - Acute Toxicity Estimates; bw - Body weight; CAO - Cargo Aircraft Only; CAS - Chemical Abstracts Service; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DNEL - Derived No-Effect Level; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); EG - European Union; EN - European standards; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISO - International Organisation for Standardization; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n;o;s; - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect

Safety Data Sheet

Emirates lubricants

Compressor Oil VDL 68 S

Page 10 of
10

Revision date: 03.01.2024

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; OECD - Organization for Economic Co-operation and Development; PBT - Persistent, Bioaccumulative and Toxic substance; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulation concerning the International Carriage of Dangerous Goods by Rail; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Relevant H and EUH statements (number and full text)

H304	May be fatal if swallowed and enters airways.
H361f	Suspected of damaging fertility.
EUH210	Safety data sheet available on request.

Further Information

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)