

# Safety Data Sheet

Revision date: 10.01.2025

**Emirates lubricants**

Adhesive Lubricant OG 0

Page 1 of 11

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Adhesive Lubricant OG 0

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

Lubricant and additive.

**1.3. Details of the supplier of the safety data sheet****Manufacturer**

|                         |                                            |                  |
|-------------------------|--------------------------------------------|------------------|
| Company name:           | Emirates lubricants                        |                  |
| Street:                 | Ras Al khaimah                             |                  |
| Place:                  | United Arab Emirates                       |                  |
| Telephone:              | +971 55 105 2851                           | +971 52 660 6888 |
| E-mail:                 | info@emirateslubricant.                    |                  |
| Contact person:         | Application Technology                     |                  |
| Internet:               | www.emirateslubricant.com                  |                  |
| Responsible Department: | Emirates lubricants Application Technology |                  |

**1.4. Emergency telephone number:** +971 52 660 6888 - This number is serviced during office hours.

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****GB CLP Regulation**

This mixture is not classified as hazardous in accordance with GB CLP Regulation.

**2.2. Label elements****GB CLP Regulation Special labelling of certain mixtures**

|        |                                                                                                                                                                                                              |
|--------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EUH208 | Contains Benzenesulfonic acid, di-C10-14-alkyl derivs., calcium salts, Molybdenum trioxide, reaction products with bis[O,O-bis(2-ethylhexyl)] hydrogen dithiophosphate.<br>May produce an allergic reaction. |
| EUH210 | Safety data sheet available on request.                                                                                                                                                                      |

**Additional advice on labelling**

According to EC directives or the corresponding national regulations the product does not have to be labelled.

**2.3. Other hazards**

Spilled product must not leak into the ground.  
Do not allow uncontrolled leakage of product into the environment.

If handled with proper care and at intended use, the product does not cause any harmful effects acc. to our experiences and available information.

## Safety Data Sheet

## Emirates lubricants

Revision date: 10.01.2025

Adhesive Lubricant OG 0

Page 2 of 11

## SECTION 3: Composition/information on ingredients

## 3.2. Mixtures

## Relevant ingredients

| CAS No       | Chemical name                                                                                   |          |                  | Quantity    |
|--------------|-------------------------------------------------------------------------------------------------|----------|------------------|-------------|
|              | EC No                                                                                           | Index No | REACH No         |             |
|              | Classification (GB CLP Regulation)                                                              |          |                  |             |
| 1471316-72-9 | Benzenesulfonic acid, di-C10-14-alkyl derivs., calcium salts                                    |          |                  | 1 - < 5 %   |
|              | 939-603-7                                                                                       |          | 01-2119978241-36 |             |
|              | Skin Sens. 1; H317                                                                              |          |                  |             |
| 4259-15-8    | Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)                                            |          |                  | < 2,50 %    |
|              | 224-235-5                                                                                       |          | 01-2119493635-27 |             |
|              | Eye Dam. 1, Aquatic Chronic 2; H318 H411                                                        |          |                  |             |
|              | Molybdenum trioxide, reaction products with bis[O,O-bis(2-ethylhexyl)] hydrogen dithiophosphate |          |                  | 0.5 - < 1 % |
|              | 947-946-9                                                                                       |          | 01-2120772600-59 |             |
|              | Skin Irrit. 2, Skin Sens. 1B, Aquatic Chronic 4; H315 H317 H413                                 |          |                  |             |

Full text of H and EUH statements: see section 16.

## Specific Conc. Limits, M-factors and ATE

| CAS No       | EC No     | Chemical name                                                                                                        | Quantity  |
|--------------|-----------|----------------------------------------------------------------------------------------------------------------------|-----------|
|              |           | Specific Conc. Limits, M-factors and ATE                                                                             |           |
| 1471316-72-9 | 939-603-7 | Benzenesulfonic acid, di-C10-14-alkyl derivs., calcium salts                                                         | 1 - < 5 % |
|              |           | dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 10000 - < 20000 mg/kg Skin Sens. 1; H317: >= 10 - 100                    |           |
| 4259-15-8    | 224-235-5 | Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)                                                                 | < 2,50 %  |
|              |           | dermal: LD50 = > 5000 mg/kg; oral: LD50 = 3100 mg/kg Eye Dam. 1; H318: >= 50 - 100 Eye Irrit. 2; H319: >= 2,5 - < 50 |           |

## Further Information

DMSO-Extract < 3 %; IP 346. Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

## SECTION 4: First aid measures

## 4.1. Description of first aid measures

## General information

Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

## After inhalation

## Safety Data Sheet

Provide fresh air. In case of persistent complaints seek medical advice.

### After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Protect skin by using skin protective cream.

### After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

### After ingestion

Do NOT induce vomiting.

Rinse mouth thoroughly with water. Call a physician immediately.

### **4.2. Most important symptoms and effects, both acute and delayed**

No information available.

## Emirates lubricants

Revision date: 10.01.2025

Adhesive Lubricant OG 0

Page 3 of 11

### **4.3. Indication of any immediate medical attention and special treatment needed**

First Aid, decontamination, treatment of symptoms.

## SECTION 5: Firefighting measures

### **5.1. Extinguishing media**

#### **Suitable extinguishing media**

Carbon dioxide (CO<sub>2</sub>). Extinguishing powder. Sand. alcohol resistant foam.

#### **Unsuitable extinguishing media**

Water.

### **5.2. Special hazards arising from the substance or mixture**

In case of fire may be liberated: Carbon monoxide. Carbon dioxide (CO<sub>2</sub>). Nitrogen oxides (NO<sub>x</sub>). Sulfur oxides. carbon black.

### **5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus.

### **Additional information**

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray jet to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

## SECTION 6: Accidental release measures

# Safety Data Sheet

## Emirates lubricants

Revision date: 10.01.2025

Adhesive Lubricant OG 0

Page 4 of 11

### **6.1. Personal precautions, protective equipment and emergency procedures**

#### **General advice**

High slip hazard because of leaking or spilled product. Avoid contact with skin, eye and clothing.

### **6.2. Environmental precautions**

Do not allow to enter into surface water or drains.

### **6.3. Methods and material for containment and cleaning up**

#### **Other information**

Take up mechanically. Dispose of waste according to applicable legislation. Clean contaminated articles and floor according to the environmental legislation.

### **6.4. Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Section 12: Ecological Information (non-mandatory)

Disposal: see section 13

## **SECTION 7: Handling and storage**

### **7.1. Precautions for safe handling**

#### **Advice on safe handling**

Take precautionary measures against static discharges. Avoid contact with skin, eyes and clothes.

#### **Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking.

#### **Advice on general occupational hygiene**

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

### **7.2. Conditions for safe storage, including any incompatibilities**

#### **Requirements for storage rooms and vessels**

Keep the packing dry and well sealed to prevent contamination and absorption of humidity. Keep container tightly closed in a cool place. Keep/Store only in original container.

#### **Hints on joint storage**

Keep away from food, drink and animal feedingstuffs.

Keep away from: Oxidizing agent

#### **Further information on storage conditions**

Protect against: UV-radiation/sunlight. frost.

heat.

Recommended storage temperature: 5 - 40°C

### **7.3. Specific end use(s)**

Further information: see technical data sheet.

## **SECTION 8: Exposure controls/personal protection**

### **8.1. Control parameters**

#### **DNEL/DMEL values**

| CAS No | Substance |
|--------|-----------|
|        |           |

## Safety Data Sheet

| DNEL type                |                                                                                                 | Exposure route | Effect   | Value                    |
|--------------------------|-------------------------------------------------------------------------------------------------|----------------|----------|--------------------------|
| 1471316-72-9             | Benzenesulfonic acid, di-C10-14-alkyl derivs., calcium salts                                    |                |          |                          |
| Worker DNEL, long-term   |                                                                                                 | inhalation     | systemic | 35,26 mg/m <sup>3</sup>  |
| Worker DNEL, long-term   |                                                                                                 | dermal         | systemic | 25 mg/kg bw/day          |
| Worker DNEL, acute       |                                                                                                 | dermal         | local    | 1,04 mg/cm <sup>2</sup>  |
| Consumer DNEL, long-term |                                                                                                 | inhalation     | systemic | 8,7 mg/m <sup>3</sup>    |
| Consumer DNEL, long-term |                                                                                                 | dermal         | systemic | 12,5 mg/kg bw/day        |
| Consumer DNEL, acute     |                                                                                                 | dermal         | local    | 0,518 mg/cm <sup>2</sup> |
| Consumer DNEL, long-term |                                                                                                 | oral           | systemic | 2,5 mg/kg bw/day         |
| 4259-15-8                | Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)                                            |                |          |                          |
| Worker DNEL, long-term   |                                                                                                 | dermal         | systemic | 9,6 mg/kg bw/day         |
| Consumer DNEL, long-term |                                                                                                 | inhalation     | systemic | 1,67 mg/m <sup>3</sup>   |
| Consumer DNEL, long-term |                                                                                                 | dermal         | systemic | 4,8 mg/kg bw/day         |
| Consumer DNEL, long-term |                                                                                                 | oral           | systemic | 0,19 mg/kg bw/day        |
| Worker DNEL, long-term   |                                                                                                 | inhalation     | systemic | 6,6 mg/m <sup>3</sup>    |
|                          | Molybdenum trioxide, reaction products with bis[O,O-bis(2-ethylhexyl)] hydrogen dithiophosphate |                |          |                          |
| Worker DNEL, long-term   |                                                                                                 | inhalation     | systemic | 4,93 mg/m <sup>3</sup>   |
| Worker DNEL, long-term   |                                                                                                 | dermal         | systemic | 1,4 mg/kg bw/day         |
| Consumer DNEL, long-term |                                                                                                 | inhalation     | systemic | 0,87 mg/m <sup>3</sup>   |
| Consumer DNEL, long-term |                                                                                                 | dermal         | systemic | 0,5 mg/kg bw/day         |
| Consumer DNEL, long-term |                                                                                                 | oral           | systemic | 0,5 mg/kg bw/day         |

## Safety Data Sheet

## Emirates lubricants

Revision date: 10.01.2025

Adhesive Lubricant OG 0

Page 5 of 11

## PNEC values

| CAS No                                           | Substance                                                    |                |
|--------------------------------------------------|--------------------------------------------------------------|----------------|
| Environmental compartment                        |                                                              | Value          |
| 1471316-72-9                                     | Benzenesulfonic acid, di-C10-14-alkyl derivs., calcium salts |                |
| Freshwater                                       |                                                              | 0,1 mg/l       |
| Freshwater (intermittent releases)               |                                                              | 1 mg/l         |
| Marine water                                     |                                                              | 0,1 mg/l       |
| Freshwater sediment                              |                                                              | 45211 mg/kg    |
| Marine sediment                                  |                                                              | 45211 mg/kg    |
| Micro-organisms in sewage treatment plants (STP) |                                                              | 1000 mg/l      |
| Soil                                             |                                                              | 36739,74 mg/kg |
| 4259-15-8                                        | Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)         |                |
| Freshwater                                       |                                                              | 0,004 mg/l     |
| Freshwater (intermittent releases)               |                                                              | 0,044 mg/l     |
| Marine water                                     |                                                              | 0,0046 mg/l    |
| Freshwater sediment                              |                                                              | 0,322 mg/kg    |
| Marine sediment                                  |                                                              | 0,032 mg/kg    |
| Secondary poisoning                              |                                                              | 8,33 mg/kg     |
| Micro-organisms in sewage treatment plants (STP) |                                                              | 3,8 mg/l       |
| Soil                                             |                                                              | 0,062 mg/kg    |

## Additional advice on limit values

The product does not contain any relevant quantities of substances with legally established exposure limitation.

## 8.2. Exposure controls



## Individual protection measures, such as personal protective equipment Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): DIN EN ISO 16321

## Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): EN ISO 374

Duration of wearing with permanent contact: 480

min Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.4 mm.

## Safety Data Sheet

Wearing time with occasional contact (splashes): 30 min  
 Suitable material: NBR (Nitrile rubber).  
 Thickness of glove material: 0.2 mm

Protect skin by using skin protective cream.

### Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

### Emirates lubricants

Revision date: 10.01.2025

Adhesive Lubricant OG 0

Page 6 of 11

### Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

|                                                           |                             |                      |
|-----------------------------------------------------------|-----------------------------|----------------------|
| Physical state:                                           | Paste                       |                      |
| Colour:                                                   | black                       |                      |
| Odour:                                                    | like: mineral oil.          |                      |
| Odour threshold:                                          | not determined              |                      |
|                                                           |                             | <b>Test method</b>   |
| Melting point/freezing point:                             | > 180 °C                    |                      |
| Boiling point or initial boiling point and boiling range: | > 240 °C                    |                      |
| Flammability:                                             | No data available           |                      |
| Lower explosion limits:                                   | No data available           |                      |
| Upper explosion limits:                                   | No data available           |                      |
| Flash point:                                              | > 200 °C                    | DIN EN ISO 2592      |
| Auto-ignition temperature:                                | No data available           |                      |
| Decomposition temperature:                                | No data available           |                      |
| pH-Value:                                                 | not applicable              |                      |
| Viscosity / kinematic:<br>(at 40 °C)                      | ca. 1000 mm <sup>2</sup> /s | DIN 51562 - Base oil |
| Water solubility:                                         | insoluble                   |                      |
| Solubility in other solvents                              | No data available           |                      |
| Partition coefficient n-octanol/water:                    | No data available           |                      |
| Vapour pressure:                                          | No data available           |                      |
| Density (at 20 °C):                                       | 0,95 g/cm <sup>3</sup>      | DIN 51757            |
| Relative vapour density:                                  | No data available           |                      |
| Particle characteristics:                                 | No data available           |                      |

## Safety Data Sheet

### 9.2. Other information

#### Information with regard to physical hazard classes

Explosive properties

evaluation: not Explosive.

Sustaining combustion:

No data available

Self-ignition temperature

Solid:

incapable of spontaneous heating.

Gas:

No data available

Oxidizing properties

No data available

#### Other safety characteristics

Evaporation rate:

No data available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

### 10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

### 10.3. Possibility of hazardous reactions

No known hazardous reactions.

## Emirates lubricants

Revision date: 10.01.2025

Adhesive Lubricant OG 0

Page 7 of 11

### 10.4. Conditions to avoid

Refer to chapter 7 No further action is necessary.

Do not overheat to avoid decomposition by heat.

### 10.5. Incompatible materials

Oxidising agent, strong

### 10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO<sub>2</sub>). Nitrogen oxides (NO<sub>x</sub>). Sulfur oxides. carbon black.

No known hazardous decomposition products.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in GB CLP Regulation

#### Acute toxicity

Based on available data, the classification criteria are not met.

#### ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

| CAS No       | Chemical name                                                |      |         |        |        |
|--------------|--------------------------------------------------------------|------|---------|--------|--------|
|              | Exposure route                                               | Dose | Species | Source | Method |
| 1471316-72-9 | Benzenesulfonic acid, di-C10-14-alkyl derivs., calcium salts |      |         |        |        |



## Safety Data Sheet

## Emirates lubricants

Revision date: 10.01.2025

Adhesive Lubricant OG 0

Page 8 of 11

|           |                                                      |                                 |        |                     |                                             |
|-----------|------------------------------------------------------|---------------------------------|--------|---------------------|---------------------------------------------|
|           | oral                                                 | LD50 > 10000 -<br>< 20000 mg/kg | Rat    | Study report (1972) | Adult albino male<br>Sprague-Dawley rats we |
|           | dermal                                               | LD50 > 2000<br>mg/kg            | Rat    | Study report (1989) | OECD Guideline 402                          |
| 4259-15-8 | Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) |                                 |        |                     |                                             |
|           | oral                                                 | LD50 3100<br>mg/kg              | Rat    | Study report (1975) | OECD Guideline 401                          |
|           | dermal                                               | LD50 > 5000<br>mg/kg            | Rabbit | Study report (1975) | OECD Guideline 402                          |

**Irritation and corrosivity**

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

**Sensitising effects**

Based on available data, the classification criteria are not met.

Contains Benzenesulfonic acid, di-C10-14-alkyl derivs., calcium salts, Molybdenum trioxide, reaction products with bis[O,O-bis(2-ethylhexyl)] hydrogen dithiophosphate. May produce an allergic reaction.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

**STOT-single exposure**

Based on available data, the classification criteria are not met.

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**11.2. Information on other hazards****Endocrine disrupting properties**not applicable **Further****information**

If handled with proper care and at intended use, the product does not cause any harmful effects acc. to our experiences and available information.

**SECTION 12: Ecological information****12.1. Toxicity**

Based on available data, the classification criteria are not met.

Mixture not tested.

| CAS No       | Chemical name                                                |                    |           |                     |                     |                    |
|--------------|--------------------------------------------------------------|--------------------|-----------|---------------------|---------------------|--------------------|
|              | Aquatic toxicity                                             | Dose               | [h]   [d] | Species             | Source              | Method             |
| 1471316-72-9 | Benzenesulfonic acid, di- 10-14-alkyl derivs., calcium salts |                    |           |                     |                     |                    |
|              | Acute fish toxicity                                          | LL50 > 100<br>mg/l | 96 h      | Oncorhynchus mykiss | Study report (2005) | OECD Guideline 203 |

## Safety Data Sheet

|           |                                                                                                 |                  |          |      |                                                           |                                  |                       |
|-----------|-------------------------------------------------------------------------------------------------|------------------|----------|------|-----------------------------------------------------------|----------------------------------|-----------------------|
|           | Acute algae toxicity                                                                            | ErC50<br>mg/l    | > 1000   | 72 h | Raphidocelis<br>subcapitata                               | Study report<br>(1994)           | EPA OTS<br>797.1050   |
|           | Acute crustacea toxicity                                                                        | EL50<br>mg/l     | > 1000   | 48 h | Daphnia magna                                             | Study report<br>(1993)           | EPA OTS<br>797.1300   |
|           | Acute bacteria toxicity                                                                         | EC50<br>mg/l ( ) | > 10000  | 3 h  | activated sludge of a<br>predominantly<br>domestic sewage | Study report<br>(1994)           | OECD Guideline<br>209 |
| 4259-15-8 | Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)                                            |                  |          |      |                                                           |                                  |                       |
|           | Acute fish toxicity                                                                             | LL50             | 4,4 mg/l | 96 h | Oncorhynchus mykiss                                       | Study report<br>(2002)           | OECD Guideline<br>203 |
|           | Acute algae toxicity                                                                            | ErC50            | 410 mg/l | 72 h | Desmodesmus<br>subspicatus                                | Study report<br>(2004)           | OECD Guideline<br>201 |
|           | Acute crustacea toxicity                                                                        | EL50             | 75 mg/l  | 48 h | Daphnia magna                                             | Study report<br>(2005)           | OECD Guideline<br>202 |
|           | Crustacea toxicity                                                                              | NOEC             | 0,4 mg/l | 21 d | Daphnia magna                                             | Study report<br>(2010)           | OECD Guideline<br>211 |
|           | Molybdenum trioxide, reaction products with bis[O O-bis(2-ethylhexyl)] hydrogen dithiophosphate |                  |          |      |                                                           |                                  |                       |
|           | Acute algae toxicity                                                                            | ErC50<br>mg/l    | > 100    | 72 h | Raphidocelis<br>subcapitata                               | REACH<br>Registration<br>Dossier | OECD Guideline<br>201 |
|           | Acute bacteria toxicity                                                                         | EC50<br>mg/l ( ) | > 1000   | 3 h  | activated sludge of a<br>predominantly<br>domestic sewage | REACH<br>Registration<br>Dossier | OECD Guideline<br>209 |

### 12.2. Persistence and degradability

Not easily bio-degradable (according to OECD-criteria). Do not allow to enter into surface water or drains.

### 12.3. Bioaccumulative potential

No data available

### Partition coefficient n-octanol/water

| CAS No       | Chemical name                                                | Log Pow |
|--------------|--------------------------------------------------------------|---------|
| 1471316-72-9 | Benzenesulfonic acid, di-C10-14-alkyl derivs., calcium salts | > 6,91  |
| 4259-15-8    | Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)         | 3,59    |

### BCF

| CAS No       | Chemical name                                                | BCF  | Species                      | Source              |
|--------------|--------------------------------------------------------------|------|------------------------------|---------------------|
| 1471316-72-9 | Benzenesulfonic acid, di-C10-14-alkyl derivs., calcium salts | 70,8 | Fish, not further specified. | Study report (2013) |

### 12.4. Mobility in soil

Due to its low solubility in water the product is almost completely mechanically separated in biological waste water treatment plants.

### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria.

### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

### 12.7. Other adverse effects

No data available

### Further information

Do not allow uncontrolled leakage of product into the environment.

## Safety Data Sheet

### Emirates lubricants

Revision date: 10.01.2025

Adhesive Lubricant OG 0

Page 9 of 11

#### SECTION 13: Disposal considerations

##### 13.1. Waste treatment methods

###### Disposal recommendations

Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

###### List of Wastes Code - residues/unused products

120112 WASTES FROM SHAPING AND PHYSICAL AND MECHANICAL SURFACE TREATMENT OF METALS AND PLASTICS; wastes from shaping and physical and mechanical surface treatment of metals and plastics; spent waxes and fats; hazardous waste

###### Contaminated packaging

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Dispose of waste according to applicable legislation. Packing which cannot be properly cleaned must be thrown away.

#### SECTION 14: Transport information

##### Land transport (ADR/RID)

14.1. UN number or ID number: -

14.2. UN proper shipping name: -

14.3. Transport hazard class(es): -

14.4. Packing group: -

##### Inland waterways transport (ADN)

14.1. UN number or ID number: -

14.2. UN proper shipping name: -

14.3. Transport hazard class(es): -

14.4. Packing group: -

##### Marine transport (IMDG)

14.1. UN number or ID number: -

14.2. UN proper shipping name: -

14.3. Transport hazard class(es): -

14.4. Packing group: -

##### Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: -

14.2. UN proper shipping name: -

14.3. Transport hazard class(es): -

14.4. Packing group: -

##### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

##### 14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

##### 14.7. Maritime transport in bulk according to IMO instruments

not applicable

##### Other applicable information

No dangerous good in sense of these transport regulations.

### Emirates lubricants

Revision date: 10.01.2025

Adhesive Lubricant OG 0

Page 10 of 11

## Safety Data Sheet

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations

##### National regulatory information

Water hazard class (D): 1 - slightly hazardous to water

#### Regulations/legislation specific for the substance or mixture

#### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

### SECTION 16: Other information

#### Changes

This data sheet contains changes from the previous version in section(s): 2,3,4,5,8,9.

#### Abbreviations and acronyms

Skin Irrit: Skin irritation

Eye Dam: Eye damage

Skin Sens: Skin sensitisation

Aquatic Chronic: Chronic aquatic hazard

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ASTM - American Society for the Testing of Materials; ATE - Acute Toxicity Estimates; bw - Body weight; CAO - Cargo Aircraft Only; CAS - Chemical Abstracts Service; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DNEL - Derived No-Effect Level; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); EG - European Union; EN - European standards; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISO - International Organisation for Standardization; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n; o; s; - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; OECD - Organization for Economic Co-operation and Development; PBT - Persistent, Bioaccumulative and Toxic substance; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulation concerning the International Carriage of Dangerous Goods by Rail; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

#### Relevant H and EUH statements (number and full text)

|        |                                                                                                                                                                                                           |
|--------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| H315   | Causes skin irritation.                                                                                                                                                                                   |
| H317   | May cause an allergic skin reaction.                                                                                                                                                                      |
| H318   | Causes serious eye damage.                                                                                                                                                                                |
| H411   | Toxic to aquatic life with long lasting effects.                                                                                                                                                          |
| H413   | May cause long lasting harmful effects to aquatic life.                                                                                                                                                   |
| EUH208 | Contains Benzenesulfonic acid, di-C10-14-alkyl derivs., calcium salts, Molybdenum trioxide, reaction products with bis[O,O-bis(2-ethylhexyl)] hydrogen dithiophosphate. May produce an allergic reaction. |
| EUH210 | Safety data sheet available on request.                                                                                                                                                                   |

**Safety Data Sheet****Emirates lubricants**

Revision date: 10.01.2025

Adhesive Lubricant OG 0

Page 11 of 11

**Further Information**

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

---

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*