

Safety Data Sheet**Emirates lubricants**

Revision date: 08.11.2022

Penta-Cool WM 102

Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Penta-Cool WM 102

UFI: THRS-N6UT-C20X-0YY0

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Metal working fluids.

1.3. Details of the supplier of the safety data sheet**Manufacturer**

Company name: Emirates lubricants

Street: Ras Al khaimah

Place: United Arab Emirates

Telephone: +971 55 105 2851 +971 52 660 6888

e-mail: info@emirateslubricant.

Contact person: Application Technology

Internet: www.emirateslubricant.com

Responsible Department: Emirates lubricants Application Technology

1.4. Emergency telephone number: +971 52 660 6888 - This number is serviced during office hours.**SECTION 2: Hazards identification**

Safety Data Sheet

Emirates lubricants

Revision date: 08.11.2022

Penta-Cool WM 102

Page 2 of
12**2.1. Classification of the substance or mixture****GB CLP Regulation**

Skin Irrit. 2; H315
 Eye Irrit. 2; H319
 Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

2.2. Label elements**GB CLP Regulation****Signal word:**

Warning

**Pictograms:****Hazard statements**

H315	Causes skin irritation.
H319	Causes serious eye irritation.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P264	Wash hands thoroughly after handling.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P501	Dispose of contents/container to an appropriate recycling or disposal facility.

Special labelling of certain mixtures

EUH208	Contains 2-n-butyl-benzo[d]isothiazol-3-one. May produce an allergic reaction.
--------	--

Additional advice on labelling

The product is classified and labelled according to EC directives or corresponding national laws.

2.3. Other hazards

Prolonged/repetitive skin contact may cause skin defatting or dermatitis.
 Spilled product must not leak into the ground.
 Do not allow uncontrolled leakage of product into the environment.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
78-96-6	1-aminopropan-2-ol; isopropanolamine			1 - < 2.5 %

Safety Data Sheet

	201-162-7	603-082-00-1		
	Skin Corr. 1B; H314			
141-43-5	2-aminoethanol; ethanolamine			1 - < 2.5 %
	205-483-3	603-030-00-8		
	Acute Tox. 4, Acute Tox. 4, Acute Tox. 4, Skin Corr. 1B; H332 H312 H302 H314			
101-83-7	dicyclohexylamine			0.5 - < 1 %
	202-980-7	612-066-00-3		
	Acute Tox. 4, Skin Corr. 1B, Aquatic Acute 1, Aquatic Chronic 1; H302 H314 H400 H410			
4299-07-4	2-n-butyl-benzo[d]isothiazol-3-one			0.1 - < 0.3 %
	420-590-7	606-079-00-3		
	Skin Corr. 1B, Skin Sens. 1, Aquatic Acute 1, Aquatic Chronic 1; H314 H317 H400 H410			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
78-96-6	201-162-7	1-aminopropan-2-ol; isopropanolamine	1 - < 2.5 %
		oral: LD50 = 2813 mg/kg	
141-43-5	205-483-3	2-aminoethanol; ethanolamine	1 - < 2.5 %
		inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = 1025 mg/kg; oral: LD50 = 1515 mg/kg STOT SE 3; H335: >= 5 - 100	
101-83-7	202-980-7	dicyclohexylamine	0.5 - < 1 %
		dermal: LD50 = 200 - 316 mg/kg; oral: LD50 = 200 mg/kg	

Emirates lubricants

Revision date: 08.11.2022

Penta-Cool WM 102

Page 3 of 12

Further Information

DMSO-Extrakt < 3 %, IP 346.

Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

SECTION 4: First aid measures

Safety Data Sheet

4.1. Description of first aid measures

General information

Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

After inhalation

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. Use skin protection ointment after cleaning. In case of skin irritation, seek medical treatment.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

After ingestion

Do NOT induce vomiting.
Rinse mouth thoroughly with water. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam. Extinguishing powder. Carbon dioxide (CO₂). Atomized water.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon dioxide (CO₂). Carbon monoxide. Nitrogen oxides (NO_x). carbon black. Phosphorus oxides

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray/stream to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

High slip hazard because of leaking or spilled product. Remove all sources of ignition. Wear breathing apparatus if exposed to vapours/dusts/aerosols. Avoid contact with skin, eye and clothing.

Emirates lubricants

Revision date: 08.11.2022

Penta-Cool WM 102

Page 4 of 12

Safety Data Sheet

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Prevent spread over a wide area (e.g. by containment or oil barriers).

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Section 12: Ecological Information (non-mandatory)

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Work in well-ventilated zones or use proper respiratory protection. Avoid oil mist. If handled uncovered, arrangements with local exhaust ventilation have to be used. Avoid contact with skin, eyes and clothes.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Advice on general occupational hygiene

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorption of humidity. Keep container tightly closed in a cool place. Keep/Store only in original container.

Hints on joint storage

Keep away from food, drink and animal feedingstuffs.

Keep away from: Oxidizing agents.

Further information on storage conditions

Protect against: UV-radiation/sunlight. frost. heat.

Recommended storage temperature: 5 - 40°C

7.3. Specific end use(s)

Further information: see technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
141-43-5	2-Aminoethanol	1	2.5		TWA (8 h)	WEL
		3	7.6		STEL (15 min)	WEL

Safety Data Sheet

Emirates lubricants

Penta-Cool WM 102

Page 5 of
12

Revision date: 08.11.2022

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
78-96-6	1-aminopropan-2-ol; isopropanolamine			
Worker DNEL, long-term		inhalation	systemic	3,6 mg/m³
Consumer DNEL, long-term		oral	systemic	0,76 mg/kg bw/day
101-83-7	dicyclohexylamine			
Worker DNEL, long-term		inhalation	systemic	0,353 mg/m³
Worker DNEL, long-term		dermal	systemic	0,1 mg/kg bw/day

PNEC values

CAS No	Substance			
Environmental compartment				Value
78-96-6	1-aminopropan-2-ol; isopropanolamine			
Freshwater				0,033 mg/l
Freshwater (intermittent releases)				0,327 mg/l
Marine water				0,003 mg/l
Freshwater sediment				0,229 mg/kg
Marine sediment				0,023 mg/kg
Micro-organisms in sewage treatment plants (STP)				3,3 mg/l
Soil				0,026 mg/kg
101-83-7	dicyclohexylamine			
Freshwater				0,002 mg/l
Freshwater (intermittent releases)				0,01 mg/l
Marine water				0 mg/l
Freshwater sediment				0,075 mg/kg
Marine sediment				0,007 mg/kg
Micro-organisms in sewage treatment plants (STP)				21 mg/l
Soil				0,014 mg/kg

Additional advice on limit values

source:

Safety Data Sheet

Recommended limit value for cooling lubricants (steam and aerosol)

MAK: 10 mg/m³

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

Individual protection measures, such as personal protective equipment Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): EN 166

Emirates lubricants

Revision date: 08.11.2022

Penta-Cool WM 102

Page 6 of 12

Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): EN ISO 374

Duration of wearing with permanent contact: 480

min Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.7 mm.

Wearing time with occasional contact (splashes): 30 min

Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. full mask (DIN EN 136). Breathing protection with filter against organic gases and vapours type A - boiling point > 65°C: A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	liquid
Colour:	brown
Odour:	like: mineral oil.
Odour threshold:	not determined

Test method

Changes in the physical state

Melting point/freezing point:	No data available
Boiling point or initial boiling point and	> 100 °C
boiling range:	
Pour point:	No data available
Flash point:	> 100 °C DIN EN ISO 2592

Safety Data Sheet

Flammability

Solid/liquid:

No data available

Gas:

No data available

Explosive properties

No data available

Lower explosion limits:

0,6 vol. %

Upper explosion limits:

6,5 vol. %

Auto-ignition temperature:

> 240 °C

Self-ignition temperature

Solid:

No data available

Gas:

No data available

Decomposition temperature:

No data available

pH-Value (at 20 °C):

10,4 5% - DIN 51369

Viscosity / kinematic:
(at 20 °C)460 mm²/s DIN EN ISO 3104

Emirates lubricants

Revision date: 08.11.2022

Penta-Cool WM 102

Page 7 of 12

Water solubility:

highly soluble.

Solubility in other solvents

No data available

Partition coefficient n-octanol/water:

No data available

Vapour pressure:

No data available

Density (at 15 °C):

0,989 g/cm³ DIN EN ISO 12185

Relative vapour density:

No data available

9.2. Other information

Information with regard to physical hazard classes

Oxidizing properties

No data available

Other safety characteristics

Evaporation rate:

Further Information

No data available

No data available

SECTION 10: Stability and reactivity

Safety Data Sheet

10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature. **10.3. Possibility of hazardous reactions** No known hazardous reactions.

10.4. Conditions to avoid

Refer to chapter 7 No further action is necessary.

10.5. Incompatible materials

Reacts with: Oxidizing agents, strong.

10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon dioxide (CO₂). Carbon monoxide. Nitrogen oxides (NO_x). carbon black. Phosphorus oxides

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

Mixture not tested.

Safety Data Sheet

Emirates lubricants

Revision date: 08.11.2022

Penta-Cool WM 102

Page 8 of
12

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
78-96-6	1-aminopropan-2-ol; isop opanolamine				
	oral	LD50 2813 mg/kg	Rat	Study report (1965)	OECD Guideline 401
141-43-5	2-aminoethanol; ethanolamine				
	oral	LD50 1515 mg/kg	Rat		
	dermal	LD50 1025 mg/kg	Rabbit	IUCLID	
	inhalation vapour	ATE 11 mg/l			
	inhalation dust/mist	ATE 1,5 mg/l			
101-83-7	dicyclohexylamine				
	oral	LD50 200 mg/kg	Rat	Other company data (1978)	Single oral application by gavage, undil
	dermal	LD50 200 - 316 mg/kg	Rabbit	Other company data (1977)	other:

Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

Sensitising effects

Contains 2-n-butyl-benzo[d]isothiazol-3-one. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction Based

on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards**Endocrine disrupting properties**

not applicable

SECTION 12: Ecological information**12.1. Toxicity** Mixture

not tested.

CAS No	Chemical name
--------	---------------

Safety Data Sheet

Emirates lubricants

Revision date: 08.11.2022

Penta-Cool WM 102

Page 9 of
12

	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
78-96-6	1-aminopropan-2-ol; isopropanolamine					
	Acute fish toxicity	LC50 > 1000 mg/l	96 h	Leuciscus idus	Study report (1987)	other: German industrial standard test g
	Acute algae toxicity	ErC50 32,7 mg/l	72 h	Desmodesmus subspicatus	Study report (1989)	other: German industrial standard test g
	Acute crustacea toxicity	EC50 108,82 mg/l	48 h	Daphnia magna	Study report (1987)	Method: other: Directive 79/831/EEC, Ann
	Acute bacteria toxicity	(EC50 > 261 mg/l)	0,5 h	Activated sludge	Study report (1978)	Method: other
141-43-5	2-aminoethanol; ethanolamine					
	Acute fish toxicity	LC50 150 mg/l	96 h	Onchorhynchus mykiss	IUCLID	
	Acute algae toxicity	ErC50 22 mg/l	72 h	Desmodesmus subspicatus		
	Acute crustacea toxicity	EC50 65 mg/l	48 h	Daphnia magna		
101-83-7	dicyclohexylamine					
	Acute fish toxicity	LC50 62 mg/l	96 h	Danio rerio	Study report (1992)	EU Method C.1
	Acute algae toxicity	ErC50 > 1 mg/l	72 h	Desmodesmus subspicatus	Other company data (1992)	EU Method C.3
	Acute crustacea toxicity	EC50 8 mg/l	48 h	Daphnia magna	Study report (1999)	OECD Guideline 202
	Crustacea toxicity	NOEC 0,016 mg/l	21 d	Daphnia magna	Study report (1999)	other: OECD Guideline 202, part 2 "Daphn
	Acute bacteria toxicity	(EC50 712 mg/l)	3 h	Activated sludge	Study report (1990)	ISO 8192

12.2. Persistence and degradability

Not easily bio-degradable (according to OECD-criteria). Do not allow to enter into surface water or drains.

12.3. Bioaccumulative potential

Mixture not tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
78-96-6	1-aminopropan-2-ol; isopropanolamine	-0,93
141-43-5	2-aminoethanol; ethanolamine	-1,91 (25°C)
101-83-7	dicyclohexylamine	2,724

Safety Data Sheet

BCF

CAS No	Chemical name	BCF	Species	Source
78-96-6	1-aminopropan-2-ol; isopropanolamine	3,16	Fish	United States Enviro
101-83-7	dicyclohexylamine	459		BCFWIN v. 2.1 (2005)

12.4. Mobility in soil

Is eliminable from water only with difficulty.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria.

Emirates lubricants

Revision date: 08.11.2022

Penta-Cool WM 102

Page 10 of 12

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No data available

Further information

Do not allow uncontrolled leakage of product into the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

List of Wastes Code - residues/unused products

120107 WASTES FROM SHAPING AND PHYSICAL AND MECHANICAL SURFACE TREATMENT OF METALS AND PLASTICS; wastes from shaping and physical and mechanical surface treatment of metals and plastics; mineral-based machining oils free of halogens (except emulsions and solutions); hazardous waste

Contaminated packaging

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Dispose of waste according to applicable legislation. Packing which cannot be properly cleaned must be thrown away.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: -

14.2. UN proper shipping name: -

14.3. Transport hazard class(es): -

14.4. Packing group: -

Inland waterways transport (ADN)

14.1. UN number or ID number: -

14.2. UN proper shipping name: -

14.3. Transport hazard class(es): -

14.4. Packing group: -

Marine transport (IMDG)

14.1. UN number or ID number: -

14.2. UN proper shipping name: -

14.3. Transport hazard class(es): -

Safety Data Sheet

Emirates lubricants

Revision date: 08.11.2022

Penta-Cool WM 102

Page 11 of 12

No dangerous good in sense of these transport regulations.

SECTION 15: Regulatory information

14.4. Packing group: -

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: -

14.2. UN proper shipping name: -

14.3. Transport hazard class(es): -

14.4. Packing group: -

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

Other applicable information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 75

National regulatory information

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ASTM - American Society for the Testing of Materials; ATE - Acute Toxicity Estimates; bw - Body weight; CAO - Cargo Aircraft Only; CAS - Chemical Abstracts Service; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DNEL - Derived No-Effect Level; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); EG - European Union; EN - European standards; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISO - International Organisation for Standardization; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n;o;s; - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; OECD - Organization for Economic Co-operation and Development; PBT - Persistent, Bioaccumulative and Toxic substance; (Q)SAR - (Quantitative) Structure Activity Relationship;

Safety Data Sheet

RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulation concerning the International Carriage of Dangerous Goods by Rail; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.

Emirates lubricants

Revision date: 08.11.2022

Penta-Cool WM 102

Page 12 of 12

H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH208	Contains 2-n-butyl-benzo[d]isothiazol-3-one. May produce an allergic reaction.

Further Information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)