

Safety Data Sheet**Emirates lubricants**

Revision date: 04.10.2023

Care Protect

Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Care Protect

UFI: DST1-17V0-620J-83M2

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Corrosion inhibitor.

1.3. Details of the supplier of the safety data sheet**Manufacturer**

Company name: Emirates lubricants

Street: Ras Al khaimah

Place: United Arab Emirates

Telephone: +971 55 105 2851 +971 52 660 6888

e-mail: info@emirateslubricant.

Contact person: Application Technology

Internet: www.emirateslubricant.com

Responsible Department: Emirates lubricants Application Technology

1.4. Emergency telephone number:

+971 52 660 6888 - This number is serviced during office hours.

SECTION 2: Hazards identification

Safety Data Sheet

Emirates lubricants

Revision date: 04.10.2023

Care Protect

Page 2 of
12**2.1. Classification of the substance or mixture****GB CLP Regulation**

Asp. Tox. 1; H304

Full text of hazard statements: see SECTION 16.

This preparation is hazardous in the sense of regulation (EC) No 1272/2008 [GHS].

2.2. Label elements**GB CLP Regulation****Hazard components for labelling**

1-Decene, homopolymer, hydrogenated

1-Decene, Dimer, hydrogenated

Signal word: Danger**Pictograms:****Hazard statements**

H304 May be fatal if swallowed and enters airways.

Precautionary statements

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331 Do NOT induce vomiting.

P405 Store locked up.

P501 Dispose of contents/container to industrial incineration plant.

Additional advice on labelling

Product is classified and labelled in accordance with EC regulations or the corresponding national laws.

2.3. Other hazards

Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

Spilled product must not leak into the ground.

Do not allow uncontrolled leakage of product into the environment.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
68037-01-4	1-Decene, homopolymer, hydrogenated			20 - < 40 %
	500-183-1		01-2119486452-34	
	Asp. Tox. 1; H304			
68649-11-6	1-Decene, Dimer, hydrogenated			20 - < 40 %

Safety Data Sheet

	500-228-5		01-2119493069-28	
	Acute Tox. 4, Asp. Tox. 1; H332 H304			
1474044-79-5	Calcium bis(di C8-C10, branched, C9 rich, alkyl naphthalenesulphonate)			2.5 - < 5 %
	939-717-7		01-2119980985-16	
	Skin Irrit. 2, Eye Irrit. 2; H315 H319			
128-37-0	2,6-Di-tert-butyl-4-methylphenol			0.1 - < 0.3 %
	204-881-4		01-2119480433-40	
	Aquatic Acute 1, Aquatic Chronic 1; H400 H410			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
68037-01-4	500-183-1	1-Decene, homopolymer, hydrogenated	20 - < 40 %
	dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg		
68649-11-6	500-228-5	1-Decene, Dimer, hydrogenated	20 - < 40 %
	inhalation: LC50 = 900-5200 mg/l (vapours); dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg		
1474044-79-5	939-717-7	Calcium bis(di C8-C10, branched, C9 rich, alkyl naphthalenesulphonate)	2.5 - < 5 %
	inhalation: LC50 = > 18 mg/l (vapours); oral: LD50 = 5 mg/kg		
128-37-0	204-881-4	2,6-Di-tert-butyl-4-methylphenol	0.1 - < 0.3 %
	dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 6000 mg/kg		

Further Information

DMSO-Extrakt < 3 %, IP 346.

Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

Emirates lubricants

Revision date: 04.10.2023

Care Protect

Page 3 of 12

SECTION 4: First aid measures

Safety Data Sheet

4.1. Description of first aid measures

General information

Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

After inhalation

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. Protect skin by using skin protective cream. In case of skin irritation, seek medical treatment.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

After ingestion

Do NOT induce vomiting.

Rinse mouth thoroughly with water. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

The following symptoms may occur: Coughing, difficulties of breathing.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam. Extinguishing powder. Carbon dioxide (CO₂). Atomized water.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO₂). Sulfur oxides. Phosphorus oxides. Nitrogen oxides (NO_x). carbon black.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray jet to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

High slip hazard because of leaking or spilled product. Remove all sources of ignition. Wear breathing apparatus if exposed to vapours/dusts/aerosols. Avoid contact with skin, eye and clothing.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Prevent spread over a wide area (e.g. by containment or oil barriers).

6.3. Methods and material for containment and cleaning up

Emirates lubricants

Safety Data Sheet

Emirates lubricants

Revision date: 04.10.2023

Care Protect

Page 5 of 12

Revision date: 04.10.2023

Care Protect

Page 4 of 12

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Section 12: Ecological Information (non-mandatory)

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Work in well-ventilated zones or use proper respiratory protection. Avoid oil mist. If handled uncovered, arrangements with local exhaust ventilation have to be used. Avoid contact with skin, eyes and clothes.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Advice on general occupational hygiene

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorption of humidity. Keep container tightly closed in a cool place. Keep/Store only in original container.

Hints on joint storage

Keep away from food, drink and animal feedingstuffs.

Keep away from: Oxidising agent, strong

Further information on storage conditions

Recommended storage temperature: 5 - 40°C

Protect against: heat. UV-radiation/sunlight. frost.

7.3. Specific end use(s)

Further information: see technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
128-37-0	2,6-Di-tert-butyl-p-cresol	-	10		TWA (8 h)	WEL

DNEL/DMEL values

CAS No	Substance
--------	-----------

Safety Data Sheet

DNEL type		Exposure route	Effect	Value
68649-11-6	1-Decene, Dimer, hydrogenated			
Worker DNEL, acute		inhalation	systemic	60 mg/m ³
Consumer DNEL, acute		inhalation	systemic	50 mg/m ³
1474044-79-5	Calcium bis(di C8-C10, branched, C9 rich, alkyl naphthalenesulphonate)			
Worker DNEL, long-term		inhalation	systemic	70 mg/m ³
Worker DNEL, long-term		dermal	systemic	10 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	0,00032 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	2,23 mg/m ³
128-37-0	2,6-Di-tert-butyl-4-methylphenol			
Consumer DNEL, long-term		inhalation	systemic	0,435 mg/m ³
Consumer DNEL, long-term		dermal	systemic	0,25 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,25 mg/kg bw/day
Worker DNEL, long-term		dermal	systemic	0,5 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	1,76 mg/m ³

PNEC values

CAS No	Substance		
Environmental compartment			Value
1474044-79-5	Calcium bis(di C8-C10, branched, C9 rich, alkyl naphthalenesulphonate)		
Freshwater			0,004 mg/l
Freshwater (intermittent releases)			0,0027 mg/l
Marine water			0,0004 mg/l
Freshwater sediment			69 mg/kg
Marine sediment			6,9 mg/kg
Secondary poisoning			22,2 mg/kg
Micro-organisms in sewage treatment plants (STP)			10 mg/l
Soil			13,9 mg/kg
128-37-0	2,6-Di-tert-butyl-4-methylphenol		
Freshwater			0,000199 mg/l

Safety Data Sheet

Freshwater (intermittent releases)	0,00199 mg/l
Marine water	0,00002 mg/l
Freshwater sediment	0,458 mg/kg
Marine sediment	0,046 mg/kg
Secondary poisoning	16,67 mg/kg
Micro-organisms in sewage treatment plants (STP)	0,017 mg/l
Soil	0,054 mg/kg

Emirates lubricants

Revision date: 04.10.2023

Care Protect

Page 6 of 12

Additional advice on limit values

Recommended limit value for oil mist

TWA: 5 mg/m³STEL: 10 mg/m³

The product does not contain any relevant quantities of substances with legally established exposure limitation.

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

Individual protection measures, such as personal protective equipment

Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): EN 166

Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): EN ISO 374

Duration of wearing with permanent contact: 480 min

Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.4 mm

Change gloves frequently under permanent contact.

Wearing time with occasional contact (splashes): 30 min

Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.2 mm

Protect skin by using skin protective cream.

Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Breathing protection with filter against organic gases and vapours type A - boiling point > 65°C: A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

Safety Data Sheet

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	liquid	
Colour:	yellow - brown	Odour: like: mineral oil.
Odour threshold:	not determined	
Melting point/freezing point:	No data available	Boiling point or initial boiling point and determined boiling range:
Flammability:	No data available	Test method not
Lower explosion limits:	No data available	

Emirates lubricants

Revision date: 04.10.2023

Care Protect

Page 7 of 12

Upper explosion limits:	No data available
Flash point:	186 °C DIN EN ISO 2592
Auto-ignition temperature:	not determined
Decomposition temperature:	No data available
pH-Value:	not applicable
Viscosity / kinematic: (at 40 °C)	17,6 mm ² /s ASTM D 7042
Water solubility:	virtually insoluble
Solubility in other solvents	
No data available	
Partition coefficient n-octanol/water:	No data available
Vapour pressure:	No data available
Density (at 15 °C):	0,865 g/cm ³ DIN 51757
Relative vapour density:	No data available

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

No data available

Self-ignition temperature

Solid:

No data available

Gas:

No data available

Oxidizing properties

No data available

Other safety characteristics

Evaporation rate:

No data available

Safety Data Sheet

Pour point:

-65 °C ASTM D 7346

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature. **10.3. Possibility of hazardous reactions** No known hazardous reactions.

10.4. Conditions to avoid

Refer to chapter 7 No further action is necessary.

Do not overheat to avoid decomposition by heat.

10.5. Incompatible materials

Reacts with: Oxidising agent, strong. Acid.

10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO₂). Sulfur oxides. Phosphorus oxides.
Nitrogen oxides (NO_x). carbon black.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.
Mixture not tested.

Safety Data Sheet

Emirates lubricants

Revision date: 04.10.2023

Care Protect

Page 10 of 15

ATEmix calculated

ATE (inhalation vapour) 52,38 mg/l; ATE (inhalation dust/mist) 7,143 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
68037-01-4	1-Decene, homopolymer, hydrogenated				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1994)	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rat	Study report (1995)	OECD Guideline 402
68649-11-6	1-Decene, Dimer, hydrogenated				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1988)	OECD Guideline 423
	dermal	LD50 > 2000 mg/kg	Rat	Study report (1989)	OECD Guideline 402
	inhalation (4 h) vapour	LC50 900-5200 mg/l	Rat	Study report (1989)	OECD Guideline 402
1474044-79-5	Calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate)				
	oral	LD50 5 mg/kg	Rat	Study report (1978)	other: FHSLA, CFR, Title 21 J para. 191.
	inhalation (1 h) vapour	LC50 > 18 mg/l	Rat	Study report (1978)	other: FHSLA, CFR, Title 21 J para. 191.
128-37-0	2,6-Di-tert-butyl-4-methyl phenol				
	oral	LD50 > 6000 mg/kg	Rat	Study report (1989)	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rat	Study report (1988)	OECD Guideline 402

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

Aspiration hazard

May be fatal if swallowed and enters airways.

11.2. Information on other hazards

Safety Data Sheet

Emirates lubricants

Revision date: 04.10.2023

Care Protect

Page 11 of 15

Endocrine disrupting properties

not applicable

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

Mixture not tested.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
68037-01-4	1-Decene, homopolymer, hydrogenated					
	Acute fish toxicity	LL50 mg/l	> 1000	96 h	Oncorhynchus mykiss	Study report (1995) OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	> 1000	96 h	Pseudokirchneriella subcapitata	Study report (1995) OECD Guideline 201
	Acute crustacea toxicity	EL50 mg/l	> 1000	48 h	Daphnia magna	Study report (1995) OECD Guideline 202
1474044-79-5	Calcium bis(di C8-C10, branched, C9 ring, alkylphenylthioethanesulphonate)					
	Acute fish toxicity	LC50 mg/l	0,28	96 h		
	Acute algae toxicity	ErC50 mg/l	> 1,2	72 h	Pseudokirchneriella subcapitata	REACH Registration Dossier OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	>= 0,18	48 h	Daphnia magna	REACH Registration Dossier OECD Guideline 202
	Crustacea toxicity	NOEC	4,6 mg/l	21 d	Daphnia magna	REACH Registration Dossier OECD Guideline 211
128-37-0	2,6-Di-tert-butyl-4-methylphenol					
	Acute fish toxicity	LC50 mg/l	0,199	96 h	Oryzias latipes	REACH Registration Dossier OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	0,758	96 h	Pseudokirchneriella subcapitata	REACH Registration Dossier OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	0,48	48 h	Daphnia magna	REACH Registration Dossier OECD Guideline 202
	Fish toxicity	NOEC mg/l	0,053	30 d	Oryzias latipes	REACH Registration Dossier OECD Guideline 210

Safety Data Sheet

Emirates lubricants

Revision date: 04.10.2023

Care Protect

Page 12 of 15

	Crustacea toxicity	NOEC mg/l	0,069	21 d	Daphnia magna	REACH Registration Dossier	OECD Guideline 211
	Acute bacteria toxicity	(EC50 mg/l)	> 10000	3 h	Activated sludge	Study report (2000)	OECD Guideline 209

12.2. Persistence and degradability

Not easily bio-degradable (according to OECD-criteria). Do not allow to enter into surface water or drains.

12.3. Bioaccumulative potential

No data available

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
68037-01-4	1-Decene, homopolymer, hydrogenated	> 6,5
68649-11-6	1-Decene, Dimer, hydrogenated	> 6,5
1474044-79-5	Calcium bis(di C8-C10, branched, C9 rich, alkyl naphthalenesulphonate)	> 6,6
128-37-0	2,6-Di-tert-butyl-4-methylphenol	5,03

BCF

CAS No	Chemical name	BCF	Species	Source
1474044-79-5	Calcium bis(di C8-C10, branched, C9 rich, alkyl naphthalenesulphonate)	3,16	Fish	Study report (2013)
128-37-0	2,6-Di-tert-butyl-4-methylphenol	465	Fish	REACH Registration D

12.4. Mobility in soil

Due to its low solubility in water the product is almost completely mechanically separated in biological waste water treatment plants.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No data available

Further information

Do not allow uncontrolled leakage of product into the environment.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

List of Wastes Code - residues/unused products

130206 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; synthetic engine, gear and lubricating oils; hazardous waste

Contaminated packaging

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Dispose of waste according to applicable legislation. Packing which cannot be properly cleaned must be thrown away.

Safety Data Sheet**Emirates lubricants**

Revision date: 04.10.2023

Care Protect

Page 13 of 15

SECTION 14: Transport information**Land transport (ADR/RID)****14.1. UN number or ID number:** -**14.2. UN proper shipping name:** -**14.3. Transport hazard class(es):** -**14.4. Packing group:** -**Inland waterways transport (ADN)****14.1. UN number or ID number:** -**14.2. UN proper shipping name:** -**14.3. Transport hazard class(es):** -**14.4. Packing group:** -**Marine transport (IMDG)****14.1. UN number or ID number:** -**14.2. UN proper shipping name:** -**14.3. Transport hazard class(es):** -**14.4. Packing group:** -**Air transport (ICAO-TI/IATA-DGR)****14.1. UN number or ID number:** -**14.2. UN proper shipping name:** -

Safety Data Sheet

Emirates lubricants

Revision date: 04.10.2023

Care Protect

Page 11 of 12

14.3. Transport hazard class(es): _____ -**14.4. Packing group:** _____ -**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

Other applicable information

No dangerous good in sense of these transport regulations.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3

National regulatory information

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 4,5,7,8,9,10,11,12.

Abbreviations and acronyms

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ASTM - American Society for the Testing of Materials; ATE - Acute Toxicity Estimates; bw - Body weight; CAO - Cargo Aircraft Only; CAS - Chemical Abstracts Service; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DNEL - Derived No-Effect Level; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); EG - European Union; EN - European standards; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISO - International Organisation for Standardization; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n;o;s; - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; OECD - Organization for Economic Co-operation and Development; PBT - Persistent, Bioaccumulative and Toxic substance; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of

Safety Data Sheet

Emirates lubricants

Revision date: 04.10.2023

Care Protect

Page 12 of
12

Chemicals; RID -Regulation concerning the International Carriage of Dangerous Goods by Rail; RQ - Reportable Quantity; SADT - Self- Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Asp. Tox. 1; H304	Calculation method

Relevant H and EUH statements (number and full text)

H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Further Information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)