

**Safety Data Sheet**

Revision date: 10.07.2024

**Emirates lubricants**  
Weapon Oil W 18 Spray

Page 1 of 13

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Weapon Oil W 18 Spray

UFI: XRVP-WW52-J67W-JRFD

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

Aerosol - Corrosion inhibitor

**1.3. Details of the supplier of the safety data sheet****Manufacturer**

Company name: Emirates lubricants

Street: Ras Al khaimah

Place: United Arab Emirates

Telephone: +971 55 105 2851 +971 52 660 6888

E-mail: info@emirateslubricant.

Internet: www.emirateslubricant.com

Responsible Department: Emirates lubricants Application Technology

**1.4. Emergency telephone number:**

+971 52 660 6888 - This number is serviced during office hours.

**SECTION 2: Hazards identification**

# Safety Data Sheet

## Emirates lubricants

Revision date: 10.07.2024

Weapon Oil W 18 Spray

Page 2 of 13

H229 Pressurised container: May burst if heated.

### Precautionary statements

P102 Keep out of reach of children.  
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P211 Do not spray on an open flame or other ignition source.  
 P251 Do not pierce or burn, even after use.  
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
 P501 Dispose of contents/container to an appropriate recycling or disposal facility.

### Additional advice on labelling

Product is classified and labelled in accordance with EC regulations or the corresponding national laws.

### 2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

## SECTION 3: Composition/information on ingredients

### 2.1. Classification of the substance or mixture

#### GB CLP Regulation

Aerosol 1; H222-H229  
 Asp. Tox. 1; H304

Full text of hazard statements: see SECTION 16.

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

### 2.2. Label elements

#### GB CLP Regulation

#### Hazard components for labelling

1-Decene, Dimer, hydrogenated

Signal word: Danger



Pictograms:

#### Hazard statements

H222 Extremely flammable aerosol.

### 3.2. Mixtures

#### Relevant ingredients

| CAS No   | Chemical name                      |              |          | Quantity  |
|----------|------------------------------------|--------------|----------|-----------|
|          | EC No                              | Index No     | REACH No |           |
|          | Classification (GB CLP Regulation) |              |          |           |
| 106-97-8 | butane                             |              |          | 35 - 40 % |
|          | 203-448-7                          | 601-004-00-0 |          |           |

## Safety Data Sheet

|              |                                                                       |              |                  |             |
|--------------|-----------------------------------------------------------------------|--------------|------------------|-------------|
|              | Flam. Gas 1, Liquefied gas; H220 H280                                 |              |                  |             |
| 74-98-6      | propane                                                               |              |                  | 15 - 20 %   |
|              | 200-827-9                                                             | 601-003-00-5 |                  |             |
|              | Flam. Gas 1, Liquefied gas; H220 H280                                 |              |                  |             |
| 68649-11-6   | 1-Decene, Dimer, hydrogenated                                         |              |                  | 10 - < 20 % |
|              | 500-228-5                                                             |              | 01-2119493069-28 |             |
|              | Acute Tox. 4, Asp. Tox. 1; H332 H304                                  |              |                  |             |
| 1474044-79-5 | Calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate) |              |                  | < 2,5 %     |
|              | 939-717-7                                                             |              | 01-2119980985-16 |             |
|              | Skin Irrit. 2, Eye Irrit. 2; H315 H319                                |              |                  |             |

Full text of H and EUH statements: see section 16.

### Specific Conc. Limits, M-factors and ATE

| CAS No       | EC No                                                                                                                                  | Chemical name                                                         | Quantity    |
|--------------|----------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------|-------------|
|              | Specific Conc. Limits, M-factors and ATE                                                                                               |                                                                       |             |
| 68649-11-6   | 500-228-5                                                                                                                              | 1-Decene, Dimer, hydrogenated                                         | 10 - < 20 % |
|              | inhalation: LC50 = 900-5200 mg/l (vapours); inhalation: ATE = 4500 ppm (gases); dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg |                                                                       |             |
| 1474044-79-5 | 939-717-7                                                                                                                              | Calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate) | < 2,5 %     |
|              | inhalation: LC50 = > 18 mg/l (vapours); oral: LD50 = 5 mg/kg                                                                           |                                                                       |             |

### Further Information

DMSO-Extract < 3 %; IP 346. Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

## Emirates lubricants

Revision date: 10.07.2024

Weapon Oil W 18 Spray

Page 3 of 13

## Safety Data Sheet

### General information

Remove affected person from the danger area and lay down. Position and transport victim on their side. In case of respiratory distress, bring into semi-upright, seated position. Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

### After inhalation

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist. In case of breathing difficulties administer oxygen.

### After contact with skin

After contact with skin, wash immediately with plenty of water and soap. In case of skin irritation, seek medical treatment.

### After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

### After ingestion

Do NOT induce vomiting.

Rinse mouth thoroughly with water. Call a physician immediately.

### **4.2. Most important symptoms and effects, both acute and delayed**

following inhalation: drowsiness. Headache. Nausea.

### **4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptomatically.

## SECTION 5: Firefighting measures

### **5.1. Extinguishing media**

#### Suitable extinguishing media

Atomized water. Carbon dioxide (CO<sub>2</sub>). Extinguishing powder. Foam.

#### Unsuitable extinguishing media

Water.

### **5.2. Special hazards arising from the substance or mixture**

In case of fire may be liberated: Carbon dioxide (CO<sub>2</sub>). Carbon monoxide Nitrogen oxides (NO<sub>x</sub>). carbon black.

Combustible. Vapours may form explosive mixtures with air.

### **5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus. Wear chemical resistant suit.

### **Additional information**

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray jet to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

## SECTION 6: Accidental release measures

### **6.1. Personal precautions, protective equipment and emergency procedures**

#### General advice

Remove persons to safety. Wear a self-contained breathing apparatus and chemical resistant suit. Vapours are heavier than air and will spread at floor level. Avoid contact with skin and eyes. Keep away from sources of ignition - No smoking.

### **6.2. Environmental precautions**

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Prevent spread over a wide area (e.g. by containment or oil barriers).

### **6.3. Methods and material for containment and cleaning up**

## Safety Data Sheet

### Emirates lubricants

Revision date: 10.07.2024

Weapon Oil W 18 Spray

Page 4 of 13

#### Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Collect in closed containers for disposal. Clean contaminated articles and floor according to the environmental legislation.

#### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Section 12: Ecological Information (non-mandatory)

Disposal: see section 13

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

##### Advice on safe handling

Use only in well-ventilated areas. Take precautionary measures against static discharges. Do not spray on naked flames or any incandescent material. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Avoid contact with skin, eyes and clothes.

##### Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Heating causes rise in pressure with risk of bursting.

##### Advice on general occupational hygiene

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

#### 7.2. Conditions for safe storage, including any incompatibilities

##### Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorption of humidity. Keep container tightly closed in a cool place. Keep away from sources of ignition - No smoking.

Please note: TRG 300, aerosol directive (75/324/EEC).

##### Hints on joint storage

Keep away from food, drink and animal feedingstuffs.

Keep away from: Oxidizing agent Material, rich in oxygen, oxidizing.

##### Further information on storage conditions

Recommended storage temperature: 5 - 40°C. Do not store at temperatures over: 50°C.

#### 7.3. Specific end use(s)

Further information: see technical data sheet.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### Exposure limits (EH40)

| CAS No   | Substance | ppm | mg/m <sup>3</sup> | fibres/ml | Category  | Origin |
|----------|-----------|-----|-------------------|-----------|-----------|--------|
| 106-97-8 | Butane    | 600 | 1450              |           | TWA (8 h) | WEL    |

Safety Data Sheet

|  |  |     |      |  |               |     |
|--|--|-----|------|--|---------------|-----|
|  |  | 750 | 1810 |  | STEL (15 min) | WEL |
|--|--|-----|------|--|---------------|-----|

## Safety Data Sheet

Revision date: 10.07.2024

Emirates lubricants

Weapon Oil W 18 Spray

Page 5 of  
13**DNEL/DMEL values**

| CAS No                   | Substance                                                              |                |          |                      |
|--------------------------|------------------------------------------------------------------------|----------------|----------|----------------------|
| DNEL type                |                                                                        | Exposure route | Effect   | Value                |
| 68649-11-6               | 1-Decene, Dimer, hydrogenated                                          |                |          |                      |
| Worker DNEL, acute       |                                                                        | inhalation     | systemic | 60 mg/m³             |
| Consumer DNEL, acute     |                                                                        | inhalation     | systemic | 50 mg/m³             |
| 1474044-79-5             | Calcium bis(di C8-C10, branched, C9 rich, alkyl)naphthalenesulphonate) |                |          |                      |
| Worker DNEL, long-term   |                                                                        | inhalation     | systemic | 70 mg/m³             |
| Worker DNEL, long-term   |                                                                        | dermal         | systemic | 10 mg/kg bw/day      |
| Consumer DNEL, long-term |                                                                        | dermal         | systemic | 0,00032 mg/kg bw/day |
| Consumer DNEL, long-term |                                                                        | inhalation     | systemic | 2,23 mg/m³           |

**PNEC values**

| CAS No                                           | Substance                                                              |  |
|--------------------------------------------------|------------------------------------------------------------------------|--|
| Environmental compartment                        | Value                                                                  |  |
| 1474044-79-5                                     | Calcium bis(di C8-C10, branched, C9 rich, alkyl)naphthalenesulphonate) |  |
| Freshwater                                       | 0,004 mg/l                                                             |  |
| Freshwater (intermittent releases)               | 0,0027 mg/l                                                            |  |
| Marine water                                     | 0,0004 mg/l                                                            |  |
| Freshwater sediment                              | 69 mg/kg                                                               |  |
| Marine sediment                                  | 6,9 mg/kg                                                              |  |
| Secondary poisoning                              | 22,2 mg/kg                                                             |  |
| Micro-organisms in sewage treatment plants (STP) | 10 mg/l                                                                |  |
| Soil                                             | 13,9 mg/kg                                                             |  |

**Additional advice on limit values**

source:

**8.2. Exposure controls****Appropriate engineering controls**

## Safety Data Sheet

Provide adequate ventilation as well as local exhaust at critical locations.

### Individual protection measures, such as personal protective equipment Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): EN 166

### Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): EN ISO 374

Duration of wearing with permanent contact: 480 min

Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.4 mm

### Emirates lubricants

Revision date: 10.07.2024

Weapon Oil W 18 Spray

Page 6 of 13

Change gloves frequently under permanent contact.

Wearing time with occasional contact (splashes): 30 min

Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.2 mm

Protect skin by using skin protective cream.

### Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

### Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Breathing protection with filter against organic gases and vapours type A - boiling point > 65°C: A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

|                  |                |
|------------------|----------------|
| Physical state:  | gaseous        |
| Colour:          | light yellow   |
| Odour:           | characteristic |
| Odour threshold: | not determined |

|                                                           | Test method              |
|-----------------------------------------------------------|--------------------------|
| Melting point/freezing point:                             | not determined           |
| Boiling point or initial boiling point and boiling range: | < -20 °C                 |
| Flammability:                                             | not determined           |
| Lower explosion limits:                                   | 1,5 vol. %               |
| Upper explosion limits:                                   | 10,9 vol. %              |
| Flash point:                                              | < -20 °C DIN EN ISO 2592 |
| Auto-ignition temperature:                                | 365 °C                   |
| Decomposition temperature:                                | not determined           |
| pH-Value:                                                 | not applicable           |



## Safety Data Sheet

|                                        |                                     |
|----------------------------------------|-------------------------------------|
| Viscosity / kinematic:<br>(at 40 °C)   | 17,6 mm <sup>2</sup> /s DIN 51562-1 |
| Water solubility:                      | insoluble                           |
| Solubility in other solvents           |                                     |
| No data available                      |                                     |
| Partition coefficient n-octanol/water: | No data available                   |
| Vapour pressure:                       | No data available                   |
| Density (at 20 °C):                    | 0,653 g/cm <sup>3</sup> calculated. |
| Relative vapour density:               | No data available                   |
| Particle characteristics:              | No data available                   |

### 9.2. Other information

#### Information with regard to physical hazard classes

Explosive properties

In case of insufficient ventilation and/or through use, explosive/highly flamm Self-ignition temperature Solid:

able mixtures m:  
develop.

Gas:

not applicable

Oxidizing properties

No data available

not applicable

#### Other safety characteristics

### Emirates lubricants

Weapon Oil W 18 Spray

Page 7 of 13

Revision date: 10.07.2024

|                   |                |
|-------------------|----------------|
| Evaporation rate: | not determined |
| Softening point:  | not applicable |
| Pour point:       | -62 °C Di      |

### SECTION 10: Stability and reactivity

## Safety Data Sheet

### 10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

### 10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

### 10.3. Possibility of hazardous reactions

Vapours may form explosive mixtures with air.

### 10.4. Conditions to avoid

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children. Take precautionary measures against static discharges. See protective measures under point 7 and 8.

### 10.5. Incompatible materials

Keep away from: Oxidising agent, strong

### 10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon dioxide (CO<sub>2</sub>). Carbon monoxide Nitrogen oxides (NO<sub>x</sub>). carbon black.

Vapours may form explosive mixtures with air.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in GB CLP Regulation

#### Acute toxicity

Based on available data, the classification criteria are not met.

Mixture not tested.

#### ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation gas) 14954 ppm

| CAS No       | Chemical name                                                          |                    |         |                     |                                          |
|--------------|------------------------------------------------------------------------|--------------------|---------|---------------------|------------------------------------------|
|              | Exposure route                                                         | Dose               | Species | Source              | Method                                   |
| 68649-11-6   | 1-Decene, Dimer, hydrogenated                                          |                    |         |                     |                                          |
|              | oral                                                                   | LD50 > 5000 mg/kg  | Rat     | Study report (1988) | OECD Guideline 423                       |
|              | dermal                                                                 | LD50 > 2000 mg/kg  | Rat     | Study report (1989) | OECD Guideline 402                       |
|              | inhalation (4 h) vapour                                                | LC50 900-5200 mg/l | Rat     | Study report (1989) | OECD Guideline 402                       |
|              | inhalation gas                                                         | ATE 4500 ppm       |         |                     |                                          |
| 1474044-79-5 | Calcium bis(di C8-C10, branched, C9 rich, alkyl)naphthalenesulphonate) |                    |         |                     |                                          |
|              | oral                                                                   | LD50 5 mg/kg       | Rat     | Study report (1978) | other: FHSLA, CFR, Title 21 J para. 191. |
|              | inhalation (1 h) vapour                                                | LC50 > 18 mg/l     | Rat     | Study report (1978) | other: FHSLA, CFR, Title 21 J para. 191. |

## Safety Data Sheet

### Emirates lubricants

Revision date: 10.07.2024

Weapon Oil W 18 Spray

Page 8 of 13

#### Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

#### Sensitising effects

Based on available data, the classification criteria are not met.

#### Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

#### STOT-single exposure

Based on available data, the classification criteria are not met.

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

#### Aspiration hazard

May be fatal if swallowed and enters airways.

#### 11.2. Information on other hazards

##### Endocrine disrupting properties

not applicable

#### Further information

If handled with proper care and at intended use, the product does not cause any harmful effects acc. to our experiences and available information.

### SECTION 12: Ecological information

#### 12.1. Toxicity

Based on available data, the classification criteria are not met.

Mixture not tested.

| CAS No   | Chemical name            |               |           |         |                            |                                          |                                          |
|----------|--------------------------|---------------|-----------|---------|----------------------------|------------------------------------------|------------------------------------------|
|          | Aquatic toxicity         | Dose          | [h]   [d] | Species | Source                     | Method                                   |                                          |
| 106-97-8 | butane                   |               |           |         |                            |                                          |                                          |
|          | Acute fish toxicity      | LC50<br>mg/l  | 49,9      | 96 h    | Fish, no other information | United States Environmental Protection A | The Ecosar class program has been develo |
|          | Acute algae toxicity     | ErC50<br>mg/l | 19,37     | 96 h    | Algae                      | USEPA OPPT Risk Assessment Division (200 | Calculation using ECOSAR Program v1.00.  |
|          | Acute crustacea toxicity | EC50<br>mg/l  | 69,43     | 48 h    | Daphnia sp.                | USEPA OPPT Risk Assessment Division (200 | Calculation using ECOSAR Program v1.00.  |
| 74-98-6  | propane                  |               |           |         |                            |                                          |                                          |
|          | Acute fish toxicity      | LC50<br>mg/l  | 49,9      | 96 h    | Fish, no other information | United States Environmental Protection A | The Ecosar class program has been develo |

## Safety Data Sheet

## Emirates lubricants

Revision date: 10.07.2024

Weapon Oil W 18 Spray

Page 9 of 13

|              |                                                                       |               |          |      |                                    |                                                |                                               |
|--------------|-----------------------------------------------------------------------|---------------|----------|------|------------------------------------|------------------------------------------------|-----------------------------------------------|
|              | Acute algae toxicity                                                  | ErC50<br>mg/l | 19,37    | 96 h | Algae                              | USEPA OPPT<br>Risk Assessment<br>Division (200 | Calculation using<br>ECOSAR<br>Program v1.00. |
|              | Acute crustacea toxicity                                              | EC50<br>mg/l  | 69,43    | 48 h | Daphnia sp.                        | USEPA OPPT<br>Risk Assessment<br>Division (200 | Calculation using<br>ECOSAR<br>Program v1.00. |
| 1474044-79-5 | Calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate) |               |          |      |                                    |                                                |                                               |
|              | Acute fish toxicity                                                   | LC50<br>mg/l  | 0,28     | 96 h |                                    |                                                |                                               |
|              | Acute algae toxicity                                                  | ErC50<br>mg/l | > 1,2    | 72 h | Pseudokirchneriella<br>subcapitata | REACH<br>Registration<br>Dossier               | OECD Guideline<br>201                         |
|              | Acute crustacea toxicity                                              | EC50<br>mg/l  | >= 0,18  | 48 h | Daphnia magna                      | REACH<br>Registration<br>Dossier               | OECD Guideline<br>202                         |
|              | Crustacea toxicity                                                    | NOEC          | 4,6 mg/l | 21 d | Daphnia magna                      | REACH<br>Registration<br>Dossier               | OECD Guideline<br>211                         |

**12.2. Persistence and degradability**

Not easily bio-degradable (according to OECD-criteria). Do not allow to enter into surface water or drains.

**12.3. Bioaccumulative potential**

The product has not been tested.

**Partition coefficient n-octanol/water**

| CAS No       | Chemical name                                                         | Log Pow |
|--------------|-----------------------------------------------------------------------|---------|
| 106-97-8     | butane                                                                | 1,09    |
| 74-98-6      | propane                                                               | 1,09    |
| 68649-11-6   | 1-Decene, Dimer, hydrogenated                                         | > 6,5   |
| 1474044-79-5 | Calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate) | > 6,6   |

**BCF**

| CAS No       | Chemical name                                                         | BCF  | Species | Source              |
|--------------|-----------------------------------------------------------------------|------|---------|---------------------|
| 1474044-79-5 | Calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate) | 3,16 | Fish    | Study report (2013) |

**12.4. Mobility in soil**

Due to its low solubility in water the product is almost completely mechanically separated in biological waste

## Emirates lubricants

Revision date: 10.07.2024

Weapon Oil W 18 Spray

Page 10 of 13

## Safety Data Sheet

water treatment plants.

### **12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria.

### **12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

### **12.7. Other adverse effects**

No data available

## **SECTION 13: Disposal considerations**

### **13.1. Waste treatment methods**

#### **Disposal recommendations**

Do not open container by force. Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

#### **List of Wastes Code - residues/unused products**

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

#### **Contaminated packaging**

Dispose of waste according to applicable legislation.

## **SECTION 14: Transport information**

### **Land transport (ADR/RID)**

**14.1. UN number or ID number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2  
**14.4. Packing group:** -  
 Hazard label: 2.1



Classification code: 5F  
 Special Provisions: 190 327 344 625  
 Limited quantity: 1 L  
 Excepted quantity: E0  
 Transport category: 2  
 Tunnel restriction code: D

### **Inland waterways transport (ADN)**

**14.1. UN number or ID number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2  
**14.4. Packing group:** -

## Safety Data Sheet

Hazard label:

2.1



Classification code:

5F

Special Provisions:

190 327 344 625

Limited quantity:

1 L

Excepted quantity:

E0

---

## Safety Data Sheet

Revision date: 10.07.2024

### Emirates lubricants

### Weapon Oil W 18 Spray

Page 11 of 13

#### Marine transport (IMDG)

**14.1. UN number or ID number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS

**14.3. Transport hazard class(es):** 2.1

**14.4. Packing group:** -

Hazard label: 2.1



Special Provisions: 63, 190, 277, 327, 344, 959

Limited quantity: 1000 mL

Excepted quantity: E0

EmS: F-D, S-U

#### Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number or ID number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS, flammable

**14.3. Transport hazard class(es):** 2.1

**14.4. Packing group:** -

Hazard label: 2.1



Special Provisions: A145 A167 A802

Limited quantity Passenger: 30 kg G

Passenger LQ: Y203

Excepted quantity: E0

IATA-packing instructions - Passenger: 203

IATA-max. quantity - Passenger: 75 kg

IATA-packing instructions - Cargo: 203

IATA-max. quantity - Cargo: 150 kg

## Safety Data Sheet

### Emirates lubricants

Revision date: 10.07.2024

Weapon Oil W 18 Spray

Page 12 of  
13

#### 14.5. Environmental hazards

No

ENVIRONMENTALLY HAZARDOUS:

#### 14.6. Special precautions for user

Warning: flammable gases.

#### 14.7. Maritime transport in bulk acc instruments not applicable

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 28, Entry 40

|                                               |                      |
|-----------------------------------------------|----------------------|
| Directive 2010/75/EU on industrial emissions: | 59,5 % (388,535 g/l) |
|-----------------------------------------------|----------------------|

|                                                      |                      |
|------------------------------------------------------|----------------------|
| Directive 2004/42/EC on VOC in paints and varnishes: | 59,5 % (388,535 g/l) |
|------------------------------------------------------|----------------------|

|                                                             |                        |
|-------------------------------------------------------------|------------------------|
| Information according to Directive 2012/18/EU (SEVESO III): | P3a FLAMMABLE AEROSOLS |
|-------------------------------------------------------------|------------------------|

##### Additional information

Please note: 850/2004/EC , 79/117/EEC , 689/2008/EC , 2008/47/EC

##### National regulatory information

|                          |                                                                                                                    |
|--------------------------|--------------------------------------------------------------------------------------------------------------------|
| Employment restrictions: | Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). |
|--------------------------|--------------------------------------------------------------------------------------------------------------------|

|                         |                                  |
|-------------------------|----------------------------------|
| Water hazard class (D): | 2 - obviously hazardous to water |
|-------------------------|----------------------------------|

#### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

### SECTION 16: Other information

#### Changes

This data sheet contains changes from the previous version in section(s): 1,2,3,5,7,9,10,11.

#### Abbreviations and acronyms

Flam. Gas: Flammable gases

Aerosol: Aerosols

Liquefied gas

Acute Tox: Acute toxicity

Asp. Tox: Aspiration hazard

Skin Irrit: Skin irritation

Eye Irrit: Eye irritation

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ASTM

- American Society for the Testing of Materials; ATE - Acute Toxicity Estimates; bw - Body weight; CAO -

Cargo Aircraft Only; CAS - Chemical Abstracts Service; CMR - Carcinogen, Mutagen or Reproductive

Toxicant; DIN - Standard of the German Institute for Standardisation; DNEL - Derived No-Effect Level; DOT -

Department of Transportation; DSL - Domestic Substances List (Canada); EG - European Union; EN -

European standards; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous



## Safety Data Sheet

Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISO - International Organisation for Standardization; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; OECD - Organization for Economic Co-operation and Development; PBT - Persistent, Bioaccumulative and Toxic substance; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulation concerning the International Carriage of Dangerous Goods by Rail; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Classification for mixtures and used evaluation method according to GB CLP Regulation

| Classification       | Classification procedure |
|----------------------|--------------------------|
| Aerosol 1; H222-H229 | On basis of test data    |
| Asp. Tox. 1; H304    |                          |

### Relevant H and EUH statements (number and full text)

|      |                                             |
|------|---------------------------------------------|
| H220 | Extremely flammable gas.                    |
| H222 | Extremely flammable aerosol.                |
| H229 | Pressurised container: May burst if heated. |

### Emirates lubricants

Revision date: 10.07.2024

Weapon Oil W 18 Spray

Page 13 of 13

|      |                                                     |
|------|-----------------------------------------------------|
| H280 | Contains gas under pressure; may explode if heated. |
| H304 | May be fatal if swallowed and enters airways.       |
| H315 | Causes skin irritation.                             |
| H319 | Causes serious eye irritation.                      |
| H332 | Harmful if inhaled.                                 |

### Further Information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*