



Object-Oriented Design

Lecturer: Raman Ramsin

Lecture 8: Relationships



Analysis Workflow: *Analyze a Use Case*

- The *analysis workflow* consists of the following activities:
 - Architectural analysis
 - **Analyze a use case**
 - **Outputs:**
 - **analysis classes**
 - **use case realizations**
 - Analyze a class
 - Analyze a package



Relationships: Links and Associations

- Relationships are semantic connections between things.
 - *Links* are connections between objects.
 - *Associations* are connections between classes.
 - *Links* are instances of *associations* or *dependencies*.





Links

- A link occurs when one object holds an object reference to another object.
- Objects realize system behavior by collaborating:
 - collaboration occurs when objects send each other messages across links;
 - when a message is received by an object, it executes the appropriate operation.



Links and Object Diagrams


- Object diagrams show objects and their links at a particular point in time.
 - They are snapshots of an executing OO system at a particular time.
 - Objects may adopt roles with respect to each other - the role played by an object in a link defines the semantics of its part in the collaboration.
 - N-ary links may connect more than two objects - they are drawn as a diamond with a path to each object but are not widely used.





Associations



- Associations are semantic connections between classes.
 - If there is a link between two objects, there *must* be an association or dependency between the classes of those objects.
 - Links are instances of associations just as objects are instances of classes.





Associations: Details



- Associations may optionally have the following:
 - Association name
 - Role names
 - Multiplicity
 - Navigability





Associations: Names and Roles


- Association name:
 - may be prefixed or postfixed with a small black arrowhead to indicate the direction in which the name should be read;
 - should be a verb or verb phrase;
 - in lowerCamelCase.
- Role names:
 - on one or both association ends;
 - should be a noun or noun phrase describing the semantics of the role;
 - in lowerCamelCase.
- Use either an association name or role names but *not* both.





Associations: Multiplicity


- Indicates the number of objects that can be involved in the relationship at any point in time.
- Objects may come and go, but multiplicity constrains the number of objects in the relationship at any point in time.
- Multiplicity is specified by a comma-separated list of intervals, for example, 0..1, 3..5.
- There is no default multiplicity - if multiplicity is not explicitly shown, then it is undecided.







Associations: Multiplicity Syntax

Adornment	Semantics
0..1	Zero or 1
1	Exactly 1
0..*	Zero or more
*	Zero or more
1..*	1 or more
1..6	1 to 6
1..3, 7..10, 15, 19..*	1 to 3 <i>or</i> 7 to 10 <i>or</i> 15 exactly <i>or</i> 19 to many






Reflexive Associations






Reflexive Associations: Hierarchies and Networks


Class diagram




Example object diagram



Class diagram




Example object diagram






Associations: Navigability

- Shown by an arrowhead on one end of the relationship - if a relationship has no arrowheads, then it is bidirectional.
- Navigability indicates that you can traverse the relationship in the direction of the arrow.
- You may also be able to traverse back the other way, but it will be computationally expensive to do so.




Visibility Idiom 3 is used almost exclusively in practice






Associations and Attributes

- An association between two classes is equivalent to one class having a pseudo-attribute that can hold a reference to an object of the other class:
 - you can often use associations and attributes interchangeably;
 - use association when you have an important class on the end of the association that you wish to emphasize;
 - use attributes when the class on the end of the relationship is unimportant (e.g., a library class such as String or Date).




If a navigable relationship has a role name, then it is as though the source class has a pseudo-attribute with the same name as the role name and the same type as the target class





Association Classes



- An association class is an association that is also a class:
 - it may have attributes, operations, and relationships;
 - you can use an association class when there is exactly one unique link between any pair of objects at any point in time;
 - if a pair of objects may have many links to each other at a given point in time, then you reify the relationship by replacing it with a normal class.





Qualified Associations

- Qualified associations use a qualifier to select a unique object from the target set:
 - the qualifier must be a unique key into the target set;
 - qualified associations reduce the multiplicity of n-to-many relationships, to n-to-one;
 - they are a useful way of drawing attention to unique identifiers.






Dependencies

- Dependencies are relationships in which a change to the supplier affects or supplies information to the client.
- The client depends on the supplier in some way.
- Dependencies are drawn as a dashed arrow from client to supplier.

Type	Semantics
Usage	The client uses some of the services made available by the supplier to implement its own behavior – this is the most commonly used type of dependency
Abstraction	<p>This indicates a relationship between client and supplier, where the supplier is more abstract than the client.</p> <p>What do we mean by “more abstract”? This could mean that the supplier is at a different point in development than the client (e.g., in the analysis model rather than the design model)</p>
Permission	The supplier grants some sort of permission for the client to access its contents – this is a way for the supplier to control and limit access to its contents




Dependencies: Example





Usage Dependencies

- «use»- the client makes use of the supplier in some way - this is the catch-all and the default.
- «call»- the client operation invokes the supplier operation.
- «parameter»- the supplier is a parameter in one of the client's operations.
- «send»- the client sends the supplier (which must be a signal) to the specified target.
- «instantiate»- the client instantiates the supplier.





Abstraction Dependencies

- «trace»- the client is a historical development of the supplier.
- «substitute»- the client can be substituted for the supplier at runtime.
- «refine»- the client is a version of the supplier.
- «instantiate»- the client is an instance of the supplier.
- «derive»- the client can be derived in some way from the supplier:
 - you may show derived relationships explicitly by using a «derive» dependency;
 - you may show derived relationships by prefixing the role or relationship name with a slash;
 - you may show derived attributes by prefixing the attribute name with a slash.



Abstraction Dependencies: «derive»

Model	Description
<pre> classDiagram class BankAccount class Transaction class Quantity BankAccount "1" -- "0..*" Transaction Transaction "1" -- "1" Quantity Transaction ..> Quantity : «derive» </pre>	<p>The BankAccount class has a derived association to Quantity where Quantity plays the role of the balance of the BankAccount</p> <p>This model emphasizes that the balance is derived from the BankAccount's collection of Transactions</p>
<pre> classDiagram class BankAccount class Transaction class Quantity BankAccount "1" -- "0..*" Transaction Transaction "1" -- "1" Quantity BankAccount -- Quantity : /balance 1 </pre>	<p>In this case a slash is used on the role name to indicate that the relationship between BankAccount and Quantity is derived</p> <p>This is less explicit as it does not show what the balance is derived from</p>
<pre> classDiagram class BankAccount class Transaction class Quantity BankAccount "1" -- "0..*" Transaction Transaction "1" -- "1" Quantity class BankAccount { /balance:Quantity } </pre>	<p>Here the balance is shown as a derived attribute – this is indicated by the slash that prefixes the attribute name</p> <p>This is the most concise expression of the dependency</p>



Permission Dependencies

- «access»- a dependency between packages where the client package can access all of the public contents of the supplier package – the name spaces of the packages remain separate.
- «import»- a dependency between packages where the client package can access all of the public contents of the supplier package – the namespaces of the packages are merged.
- «permit»- a controlled violation of encapsulation where the client may access the private members of the supplier - this is not widely supported and should be avoided if possible.



Reference

- Arlow, J., Neustadt, I., *UML 2 and the Unified Process: Practical Object-Oriented Analysis and Design*, 2nd Ed. Addison-Wesley, 2005.