

# Taint Analysis via CFL-Reachability

Mostafa Hassanein

03, January 2026

# Agenda

- What is taint analysis?

# Agenda

- What is taint analysis?
- Why is it important?

# Agenda

- What is taint analysis?
- Why is it important?
- Why context sensitivity is needed?

# Agenda

- What is taint analysis?
- Why is it important?
- Why context sensitivity is needed?
- CFL-reachability formulation

# Agenda

- What is taint analysis?
- Why is it important?
- Why context sensitivity is needed?
- CFL-reachability formulation
- Examples

- Static analysis reasons about *all executions* without running the program

- Static analysis reasons about *all executions* without running the program
- It computes a sound over-approximation of behaviors



- Static analysis reasons about *all executions* without running the program
- It computes a sound over-approximation of behaviors
- Taint analysis is a data-flow-based static analysis

# What Is Taint Analysis?

- Tracks flow of untrusted (tainted) data

# What Is Taint Analysis?

- Tracks flow of untrusted (tainted) data
- Detects whether tainted data reaches sensitive operations

# What Is Taint Analysis?

- Tracks flow of untrusted (tainted) data
- Detects whether tainted data reaches sensitive operations
- Abstracts away concrete values, tracking dependencies

# What Is Taint Analysis?

- Tracks flow of untrusted (tainted) data
- Detects whether tainted data reaches sensitive operations
- Abstracts away concrete values, tracking dependencies

## Core Question:

*Does tainted data flow from a source to a sink along a valid execution?*

## Example: SQL Query Template

### Intended Query

```
SELECT balance  
FROM AcctData  
WHERE name = ':n' AND password = ':p'
```

# Malicious User Input

$n = \text{'Charles Dickens' --}$      $p = \text{'who cares'}$

# Malicious User Input

$n = \text{'Charles Dickens' --}$      $p = \text{'who cares'}$

## Resulting Query

```
SELECT balance FROM AcctData
WHERE name = 'Charles Dickens' --'
AND password = 'who cares'
```



# Malicious User Input

$n = \text{'Charles Dickens' --}$      $p = \text{'who cares'}$

## Resulting Query

```
SELECT balance FROM AcctData
WHERE name = 'Charles Dickens' --
AND password = 'who cares'
```

- Password check is commented out

# Malicious User Input

$n = \text{'Charles Dickens' --}$      $p = \text{'who cares'}$

## Resulting Query

```
SELECT balance FROM AcctData
WHERE name = 'Charles Dickens' --
AND password = 'who cares'
```

- Password check is commented out
- Sensitive data is leaked

# Taint Propagation Graph



# Taint Propagation Graph



- Nodes represent program entities (variables or functions)

# Taint Propagation Graph



- Nodes represent program entities (variables or functions)
- Edges represent labeled data-flow relations

# Why Context Sensitivity Is Needed

- The same function may be called from different sites

# Why Context Sensitivity Is Needed


- The same function may be called from different sites
- Taint behavior depends on the calling context

# Why Context Sensitivity Is Needed


- The same function may be called from different sites
- Taint behavior depends on the calling context
- Context-insensitive analysis merges incompatible flows



# Context-Insensitive Call Graph



# Context-Insensitive Call Graph



**Spurious taint flow appears due to context merging.**

# Invalid Reachability Path

- Clean call enters function

# Invalid Reachability Path

- Clean call enters function
- Tainted return exits function

# Invalid Reachability Path

- Clean call enters function
- Tainted return exits function
- Path exists in graph but not in execution

# Invalid Reachability Path

- Clean call enters function
- Tainted return exits function
- Path exists in graph but not in execution

$\text{call}_{\text{clean}} \quad \text{return}_{\text{tainted}} \quad (\text{invalid})$

# Program Graph Model

A program is modeled as a labeled graph

$$G = (V, E, \Sigma)$$

# Program Graph Model

A program is modeled as a labeled graph

$$G = (V, E, \Sigma)$$

- $V$ : program entities



# Program Graph Model

A program is modeled as a labeled graph

$$G = (V, E, \Sigma)$$

- $V$ : program entities
- $E \subseteq V \times \Sigma \times V$ : labeled edges

# Program Graph Model

A program is modeled as a labeled graph

$$G = (V, E, \Sigma)$$

- $V$ : program entities
- $E \subseteq V \times \Sigma \times V$ : labeled edges
- $\Sigma$ : flow actions (call, return, assign)

A path

$$\pi = v_0 \xrightarrow{a_1} v_1 \xrightarrow{a_2} \dots \xrightarrow{a_k} v_k$$

A path

$$\pi = v_0 \xrightarrow{a_1} v_1 \xrightarrow{a_2} \cdots \xrightarrow{a_k} v_k$$

induces a word

$$\ell(\pi) = a_1 a_2 \cdots a_k$$

A path

$$\pi = v_0 \xrightarrow{a_1} v_1 \xrightarrow{a_2} \cdots \xrightarrow{a_k} v_k$$

induces a word

$$\ell(\pi) = a_1 a_2 \cdots a_k$$

Only some words correspond to valid executions.

# Grammar for Valid Taint Flows

$$F \rightarrow FF \mid \text{call}_i F \text{ return}_i \mid \text{assign} \mid \varepsilon$$

$$F \rightarrow FF \mid call_i F return_i \mid assign \mid \varepsilon$$

- $call_i/return_i$ : Procedure invocation and return matching call site  $i$

$$F \rightarrow FF \mid call_i F return_i \mid assign \mid \varepsilon$$

- $call_i/return_i$ : Procedure invocation and return matching call site  $i$
- $assign$ : Local data flow within a procedure



$$F \rightarrow FF \mid call_i F return_i \mid assign \mid \varepsilon$$

- $call_i/return_i$ : Procedure invocation and return matching call site  $i$
- $assign$ : Local data flow within a procedure
- **Result:** Only matching pairs  $(call_i, return_i)$  are derivable. This filters out paths that do not correspond to feasible call stacks.

## Problem

Given  $s, t \in V$ , does there exist a path  $\pi$  from  $s$  to  $t$  such that

$$\ell(\pi) \in L(\mathcal{G})?$$

# Taint Analysis as CFL-Reachability


## Problem

Given  $s, t \in V$ , does there exist a path  $\pi$  from  $s$  to  $t$  such that


$$\ell(\pi) \in L(\mathcal{G})?$$

This exactly captures context-sensitive taint analysis.

## Example 1: The Identity Crisis (Context Matching)




## Example 1: The Identity Crisis (Context Matching)




- **Graph Path:** A path exists from *Tainted Input* to *Log File* via  $call_1 \rightarrow ret_2$ .

## Example 1: The Identity Crisis (Context Matching)




- **Graph Path:** A path exists from *Tainted Input* to *Log File* via  $call_1 \rightarrow ret_2$ .
- **CFL Check:**  $call_1 ret_2$  is **not** in  $L(\mathcal{G})$  because indices 1 and 2 don't match.

## Example 1: The Identity Crisis (Context Matching)




- **Graph Path:** A path exists from *Tainted Input* to *Log File* via  $call_1 \rightarrow ret_2$ .
- **CFL Check:**  $call_1 ret_2$  is **not** in  $L(\mathcal{G})$  because indices 1 and 2 don't match.
- **Insight:** Grammar prevents tainted data from "leaking" into different call sites.

## Example 2: Deep Recursion (Self-Referential Flow)






## Example 2: Deep Recursion (Self-Referential Flow)




- **Scenario:** A function calls itself. Taint flows through an arbitrary number of recursive steps.

## Example 2: Deep Recursion (Self-Referential Flow)




- **Scenario:** A function calls itself. Taint flows through an arbitrary number of recursive steps.
- **Word:**  $\ell(\pi) = call_1(call_2)^n(ret_2)^n ret_1$ .

## Example 2: Deep Recursion (Self-Referential Flow)




- **Scenario:** A function calls itself. Taint flows through an arbitrary number of recursive steps.
- **Word:**  $\ell(\pi) = call_1(call_2)^n(ret_2)^n ret_1$ .
- **CFL Validation:** This is a classic  $a^n b^n$  structure. The grammar  $F \rightarrow call_i F ret_i$  naturally accepts balanced recursive calls, ensuring the data eventually returns to the correct caller.

## Example 3: Sanitization Logic (Path Selection)




- **Formal Condition:** A path  $\pi$  is a violation if  $\ell(\pi) \in L(\mathcal{G})$  and  $V(\pi) \cap V_{san} = \emptyset$ .

## Example 3: Sanitization Logic (Path Selection)



- **Formal Condition:** A path  $\pi$  is a violation if  $\ell(\pi) \in L(\mathcal{G})$  and  $V(\pi) \cap V_{san} = \emptyset$ .
- **Sanitized Path:**  $\pi_{top} = (\text{Untrusted} \rightarrow \text{Sanitizer} \rightarrow \text{Sink})$ . Since  $\text{Sanitizer} \in V_{san}$ , this path is **discarded** despite being in  $L(\mathcal{G})$ .

## Example 3: Sanitization Logic (Path Selection)



- **Formal Condition:** A path  $\pi$  is a violation if  $\ell(\pi) \in L(\mathcal{G})$  and  $V(\pi) \cap V_{san} = \emptyset$ .
- **Sanitized Path:**  $\pi_{top} = (\text{Untrusted} \rightarrow \text{Sanitizer} \rightarrow \text{Sink})$ . Since  $\text{Sanitizer} \in V_{san}$ , this path is **discarded** despite being in  $L(\mathcal{G})$ .
- **Vulnerable Path:**  $\pi_{bot} = (\text{Untrusted} \rightarrow \text{Bypass} \rightarrow \text{Sink})$ .  
 $\ell(\pi_{bot}) = \text{assign} \cdot \text{assign} \in L(\mathcal{G})$  and avoids  $V_{san}$ . **Violation detected.**

- Taint analysis tracks information flow

# Summary

- Taint analysis tracks information flow
- Context insensitivity yields false positives



- Taint analysis tracks information flow
- Context insensitivity yields false positives
- Valid executions form a context-free language

- Taint analysis tracks information flow
- Context insensitivity yields false positives
- Valid executions form a context-free language
- CFL-reachability provides principled context sensitivity

- Aho, Alfred V., et al. Compilers: Principles, Techniques, and Tools. 2nd ed., Pearson Education, 2006.

Thank you

*Questions?*