

MITRE ATTACK Technique Identification Report

1) General Information

- **Assessment Date:** 27/2/2026
 - **Analyst Name:** Mustafa Jbili
 - **Scope of Work:** Cybersecurity Analyst
 - **Objective:** identify and detect TTP for various scenarios
-

2) Methodology & Tools

- **Methodology:** figure out the tactics and techniques and procedures for given scenarios
- **Tools Used:** mitre attack data base

3) scenarios

1) Scenario 1: Phishing Attack

- **Tactic:** Initial Access
- **Identified Technique:**
T1566 – Phishing
- **Explanation:**
In this scenario, the attacker sends a deceptive email that appears to come from a trusted source. The email contains a malicious link, which leads to malware being downloaded when the employee clicks it. This aligns with the Phishing technique, as the attacker relies on social engineering through email to gain initial access to the victim's system.

2) Scenario 2: Exploitation of Vulnerability

- **Tactics:** Initial Access, Execution
- **Identified Technique:**
T1190 – Exploit Public-Facing Application
T1059 – Command and Scripting Interpreter

- **Explanation:**
The attacker exploits a vulnerability in outdated software installed on a web server. This corresponds to Exploit Public-Facing Application, as the attack targets an externally accessible system. After gaining access, the attacker executes malicious commands, which aligns with Command and Scripting Interpreter, since commands are used to control the compromised server.

3) Scenario 3: Password Cracking / Credential Abuse

- **Tactic:** Credential Access
- **Identified Technique:**
T1110.003 – Password Spraying
- **Explanation:**
The attacker uses a list of stolen usernames and passwords and attempts authentication across multiple services until valid credentials are found. This behavior matches Password Spraying, where attackers test commonly used passwords across multiple accounts to gain unauthorized access.

4) Scenario 4: Denial-of-Service (DoS) Attack

- **Tactic:** Impact
- **Identified Technique:**
T1498 – Network Denial of Service
- **Explanation:**
The attacker uses a network of compromised devices to generate a large volume of traffic directed at a target server. The overwhelming traffic disrupts normal operations and prevents legitimate users from accessing services. This corresponds to Network Denial of Service, which focuses on degrading or interrupting system availability.

5) Scenario 5: Lateral Movement Within a Network

- **Tactics:** Lateral Movement, Collection
- **Identified Techniques:**
T1021 – Remote Services
T1005 – Data from Local System
- **Explanation:**
After compromising an initial device, the attacker moves laterally across the network using remote access tools. This behavior aligns with Remote Services, which enables attackers to pivot between systems. Additionally, the attacker collects sensitive data from compromised machines, which corresponds to Data from Local System under the Collection tactic.

