

Planha Licensed Architect Rule Review Book

Architecture residential rulebook | 32 rules | Decision record template

Purpose: enable a licensed architect to confirm source interpretation, applicability, exceptions, machine logic and cross-code behavior. All decision fields are intentionally blank. This document grants no runtime, Golden, merge or deployment authority.

Package status	AWAITING_LICENSED_ARCHITECT_REVIEW
Branch	feature/architecture-rulebook-qualification
Prepared from SHA	4451f9953ccbd8201991e92db671ad6520fed059
Allowed decisions	APPROVED APPROVED_WITH_CHANGE REJECTED NEEDS_MORE_EVIDENCE
Blank decision	NOT_REVIEWED

Reviewer instructions

1. Inspect the cited source and the prepared interpretation.
2. Verify applicability and all stated exceptions.
3. Verify that the machine interpretation preserves the regulation and fails closed on missing material input.
4. Select exactly one allowed decision for every rule.
5. Add comments only where needed and provide your name, professional role, license or registration identifier, and review date.

APPROVED_WITH_CHANGE requires the requested change, reason, affected logic or threshold or applicability or exception, and source basis. NEEDS_MORE_EVIDENCE requires the missing evidence, required source, materiality and risk of assumption.

Reviewer attribution

Reviewer name	
Professional role	
Professional license or registration	
Review date	

Summary decision sheet

Rule ID	Short title	Source	Risk	Decision	Comment
ARCH-RES-CIRCULATION-001	عرض راهروی داخلی واحد	مبحث چهارم، الزامات عمومی ساختمان	HIGH		
ARCH-RES-STAIRS-001	پله مسکونی گروه ۱ تا ۳	مبحث چهارم، الزامات عمومی ساختمان	CRITICAL		
ARCH-RES-STAIRS-002	پله مسکونی گروه ۴ تا ۷	مبحث چهارم، الزامات عمومی ساختمان	CRITICAL		
ARCH-RES-STAIRS-003	پله مسکونی گروه ۸	مبحث چهارم، الزامات عمومی ساختمان	CRITICAL		
ARCH-RES-EGRESS-001	بازشدن در خروج از داخل	مبحث چهارم، الزامات عمومی ساختمان	CRITICAL		
ARCH-RES-DOOR-001	در ورودی اتاق اقامت	مبحث چهارم، الزامات عمومی ساختمان	HIGH		
ARCH-RES-LIVING-001	اندازه حداقل یک فضای اقامت اصلی	مبحث چهارم، الزامات عمومی ساختمان	HIGH		
ARCH-RES-LIVING-002	فضای اقامت	مبحث چهارم،	HIGH		

Rule ID	Short title	Source	Risk	Decision	Comment
	واحد کوچک	الزامات عمومی ساختمان			
ARCH-RES-LIVING-003	مساحت عمومی اتاق اقامت	مبحث چهارم، الزامات عمومی ساختمان	HIGH		
ARCH-RES-BEDROOM-001	عرض سایر اتاق‌های اقامت مسکونی	مبحث چهارم، الزامات عمومی ساختمان	HIGH		
ARCH-RES-KITCHEN-001	آشپزخانه مستقل یا باز برای پخت‌وپز	مبحث چهارم، الزامات عمومی ساختمان	HIGH		
ARCH-RES-KITCHEN-002	آشپزخانه همراه محل صرف غذا	مبحث چهارم، الزامات عمومی ساختمان	HIGH		
ARCH-RES-KITCHEN-003	عرض آشپزخانه	مبحث چهارم، الزامات عمومی ساختمان	HIGH		
ARCH-RES-KITCHEN-004	فضای کار آشپزخانه دیواری	مبحث چهارم، الزامات عمومی ساختمان	HIGH		
ARCH-RES-KITCHEN-005	ممنوعیت عبور الزامی از آشپزخانه	مبحث چهارم، الزامات عمومی ساختمان	HIGH		
ARCH-RES-BATHROOM-001	ابعاد فضای بهداشتی مسکونی معمول	مبحث چهارم، الزامات عمومی ساختمان	HIGH		
ARCH-RES-BATHROOM-002	ارتفاع فضای بهداشتی مسکونی	مبحث چهارم، الزامات عمومی ساختمان	HIGH		
ARCH-RES-WC-001	پیش‌بینی توالت فرنگی برای واحد بزرگ	مبحث چهارم، الزامات عمومی ساختمان	HIGH		
ARCH-RES-DAYLIGHT-001	نور و هوای آشپزخانه مستقل	مبحث چهارم، الزامات عمومی ساختمان	HIGH		
ARCH-RES-DAYLIGHT-002	سطح شیشه اتاق اقامت	مبحث چهارم، الزامات عمومی ساختمان	HIGH		
ARCH-RES-DAYLIGHT-003	پنجره با لبه بالایی کوتاه	مبحث چهارم، الزامات عمومی ساختمان	HIGH		

Rule ID	Short title	Source	Risk	Decision	Comment
		ساختمان			
ARCH-RES-DAYLIGHT-004	عمق قابل قبول نورگیری	مبحث چهارم، الزامات عمومی ساختمان	HIGH		
ARCH-RES-DAYLIGHT-005	نورگیری زیر ایوان	مبحث چهارم، الزامات عمومی ساختمان	HIGH		
ARCH-RES-DAYLIGHT-006	حیاط بین دو تصرف مسکونی	مبحث چهارم، الزامات عمومی ساختمان	HIGH		
ARCH-RES-DAYLIGHT-007	حیاط مشترک آشپزخانه و اقامت	مبحث چهارم، الزامات عمومی ساختمان	HIGH		
ARCH-RES-VENTILATION-001	بازشوی تهویه آشپزخانه	مبحث چهارم، الزامات عمومی ساختمان	HIGH		
ARCH-RES-VENTILATION-002	هود به هوای آزاد	مبحث چهارم، الزامات عمومی ساختمان	HIGH		
ARCH-RES-BALCONY-001	فضای نیمه باز اختصاصی	مبحث چهارم، الزامات عمومی ساختمان	MEDIUM		
ARCH-RES-PRIVACY-001	دسترسی مستقل اتاقها	مبحث چهارم، الزامات عمومی ساختمان	MEDIUM		
ARCH-RES-PRIVACY-002	دید به سرویس بهداشتی	مبحث چهارم، الزامات عمومی ساختمان	MEDIUM		
ARCH-RES-PRIVACY-003	دید به محل کار آشپزخانه	مبحث چهارم، الزامات عمومی ساختمان	MEDIUM		
ARCH-RES-ACCESSIBILITY-001	فضای بهداشتی قابل استفاده معلول	مبحث چهارم، الزامات عمومی ساختمان	CRITICAL		

Critical and high risk review sheet

- HIGH ARCH-RES-CIRCULATION-001 عرض راهروی داخلی واحد
- CRITICAL ARCH-RES-STAIRS-001 پله ساختمان مسکونی گروه ۱ تا ۳
- CRITICAL ARCH-RES-STAIRS-002 پله ساختمان مسکونی گروه ۴ تا ۷
- CRITICAL ARCH-RES-STAIRS-003 پله ساختمان مسکونی گروه ۸

- CRITICAL ARCH-RES-EGRESS-001 بازشدن در خروج از داخل
- HIGH ARCH-RES-DOOR-001 در ورودی اتاق اقامت
- HIGH ARCH-RES-LIVING-001 اندازه حداقل یک فضای اقامت اصلی
- HIGH ARCH-RES-LIVING-002 فضای اقامت واحد کوچک
- HIGH ARCH-RES-LIVING-003 مساحت عمومی اتاق اقامت
- HIGH ARCH-RES-BEDROOM-001 عرض سایر اتاق‌های اقامت مسکونی
- HIGH ARCH-RES-KITCHEN-001 آشپزخانه مستقل یا باز برای پخت‌وپز
- HIGH ARCH-RES-KITCHEN-002 آشپزخانه همراه محل صرف غذا
- HIGH ARCH-RES-KITCHEN-003 عرض آشپزخانه
- HIGH ARCH-RES-KITCHEN-004 فضای کار آشپزخانه دیواری
- HIGH ARCH-RES-KITCHEN-005 ممنوعیت عبور الزامی از آشپزخانه
- HIGH ARCH-RES-BATHROOM-001 ابعاد فضای بهداشتی مسکونی معمول
- HIGH ARCH-RES-BATHROOM-002 ارتفاع فضای بهداشتی مسکونی
- HIGH ARCH-RES-WC-001 پیش‌بینی توالت فرنگی برای واحد بزرگ
- HIGH ARCH-RES-DAYLIGHT-001 نور و هوای آشپزخانه مستقل
- HIGH ARCH-RES-DAYLIGHT-002 سطح شیشه اتاق اقامت
- HIGH ARCH-RES-DAYLIGHT-003 پنجره با لبه بالایی کوتاه
- HIGH ARCH-RES-DAYLIGHT-004 عمق قابل قبول نورگیری
- HIGH ARCH-RES-DAYLIGHT-005 نورگیری زیر ایوان
- HIGH ARCH-RES-DAYLIGHT-006 حیاط بین دو تصرف مسکونی
- HIGH ARCH-RES-DAYLIGHT-007 حیاط مشترک آشپزخانه و اقامت
- HIGH ARCH-RES-VENTILATION-001 بازشوی تهویه آشپزخانه
- HIGH ARCH-RES-VENTILATION-002 هود به هوای آزاد
- CRITICAL ARCH-RES-ACCESSIBILITY-001 فضای بهداشتی قابل استفاده معلول

Dedicated Code 246 five percent decision

Source concept: حداقل 5 درصد واحدهای مسکونی. The prepared machine candidate stores raw_required_units = total_residential_units × 0.05. No integer conversion is active.

A	CEILING_TO_NEXT_INTEGER
B	ANOTHER_AUTHORITY_BASED_METHOD — explicit authority basis required
C	NEEDS_MORE_EVIDENCE
Reviewer selection	
Authority basis	
Comments	

Floor or truncation is not an available default. Any alternate interpretation requires an authoritative basis.

Dedicated M3 M4 Group 8 stair and egress review

M4 Group 8	Residential building height >23 m or floor count >7.
M4 stair geometry	Physical stair geometry remains distinct from fire egress logic.
M3 exit count	Two remote exits unless every condition of a specific exception is met.
M3 stair capacity	Occupant load and sprinkler-dependent width coefficients.
M3 enclosure and continuity	Explicit evidence required; missing status returns INPUT_REQUIRED.
One stair exception	The mapped residential exception is limited to <=6 storeys and <=23 m.
Code 246	Accessible route and stair requirements apply only in their qualified branch.
Required confirmation	Group 8 cannot inherit an inapplicable lower-group one-stair exception.
Reviewer decision	
Reviewer comments	

Individual rule cards

Rule 1 ARCH-RES-CIRCULATION-001

عرض راهروی داخلی واحد

Risk	HIGH
Plain language rule	پهنای الزامی حداقل ۰٫۹۰ متر؛ الزامات خروج و دسترس پذیری جداگانه کنترل شوند.
Classification	MANDATORY_NATIONAL
Enforcement consequence	BLOCK
Applicable conditions	Residential internal corridor or straight internal stair
Required inputs	corridor_width_m
Authoritative source	مبحث چهارم، الزامات عمومی ساختمان
Edition	1396
Clause	4-7-1-1-6
Page	printed 85 PDF 99
Source text or precise summary	پهنای الزامی حداقل ۰٫۹۰ متر؛ الزامات خروج و دسترس پذیری جداگانه کنترل شوند.
Exceptions	None recorded
Cross-code dependencies	IR-M3, IR-ACCESS
Machine interpretation	{"field":"corridor_width_m","op":">=","value":0.9,"unit":"m"}
PASS example	Applicable project with complete authoritative inputs satisfying ≥ 0.9 m
FAIL example	Applicable project with complete authoritative inputs violating ≥ 0.9 m
Boundary example	Evaluate exact threshold and immediately below/above values where numeric; otherwise exact predicate boundary.
NOT_APPLICABLE example	Project/object does not satisfy: Residential internal corridor or straight internal stair; result must be NOT_APPLICABLE, never PASS.
INPUT_REQUIRED behavior	If any material applicability or evaluation input is absent, return INPUT_REQUIRED. Required inputs: corridor_width_m.
Current unresolved interpretation	None beyond licensed professional confirmation of the prepared interpretation.
Proposed reviewer decision	No default. Reviewer must select one allowed decision.

Reviewer decision

☐ APPROVED ☐ APPROVED_WITH_CHANGE ☐ REJECTED ☐ NEEDS_MORE_EVIDENCE

Reviewer comments	
--------------------------	--

Requested change or missing evidence	
Source basis	
Reviewer name	
Professional role	
License or registration	
Review date	

Rule 2 ARCH-RES-STAIRS-001

پله ساختمان مسکونی گروه ۱ تا ۳

Risk	CRITICAL
Plain language rule	عرض مفید پله مستقیم حداقل ۰.۹۰ و پله دارای گردش یا پاگرد حداقل ۱.۱۰ متر.
Classification	MANDATORY_NATIONAL
Enforcement consequence	BLOCK
Applicable conditions	Residential building group 1,2,3 established by authority
Required inputs	building_group, stair_type, stair_clear_width_m
Authoritative source	مبحث چهارم، الزامات عمومی ساختمان
Edition	1396
Clause	4-7-1-1-3
Page	printed 85 PDF 99
Source text or precise summary	عرض مفید پله مستقیم حداقل ۰.۹۰ و پله دارای گردش یا پاگرد حداقل ۱.۱۰ متر.
Exceptions	None recorded
Cross-code dependencies	IR-M3, IR-ACCESS
Machine interpretation	<pre>{"review_predicate":{"inputs":["building_group","stair_type","stair_clear_width_m"],"expected":true,"missing_input":"INPUT_REQUIRED","false_result":"FAIL","not_applicable_result":"NOT_APPLICABLE"}}</pre>
PASS example	Applicable project with complete authoritative inputs satisfying qualitative predicate
FAIL example	Applicable project with complete authoritative inputs violating qualitative predicate
Boundary example	Evaluate exact threshold and immediately below/above values where numeric; otherwise exact predicate boundary.
NOT_APPLICABLE example	Project/object does not satisfy: Residential building group 1,2,3 established by authority; result must be NOT_APPLICABLE, never PASS.
INPUT_REQUIRED behavior	If any material applicability or evaluation input is absent, return INPUT_REQUIRED. Required inputs: building_group, stair_type, stair_clear_width_m.
Current unresolved interpretation	None beyond licensed professional confirmation of the prepared interpretation.
Proposed reviewer decision	No default. Reviewer must select one allowed decision.

Reviewer decision

☐ APPROVED ☐ APPROVED_WITH_CHANGE ☐ REJECTED ☐ NEEDS_MORE_EVIDENCE

Reviewer comments	
Requested change or missing evidence	
Source basis	
Reviewer name	
Professional role	
License or registration	
Review date	

Rule 3 ARCH-RES-STAIRS-002

پله ساختمان مسکونی گروه ۴ تا ۷

Risk	CRITICAL
Plain language rule	عرض مفید پله مستقیم حداقل ۱٫۱۰ و عرض قفسه پلکان دارای پاگرد حداقل ۲٫۴۰ متر.
Classification	MANDATORY_NATIONAL
Enforcement consequence	BLOCK
Applicable conditions	Residential building group 4,5,6,7 established by authority
Required inputs	building_group, stair_type, stair_clear_width_m, stair_enclosure_width_m
Authoritative source	مبحث چهارم، الزامات عمومی ساختمان
Edition	1396
Clause	4-7-1-1-4
Page	printed 85 PDF 99
Source text or precise summary	عرض مفید پله مستقیم حداقل ۱٫۱۰ و عرض قفسه پلکان دارای پاگرد حداقل ۲٫۴۰ متر.
Exceptions	None recorded
Cross-code dependencies	IR-M3, IR-ACCESS
Machine interpretation	<pre>{ "review_predicate": { "inputs": ["building_group", "stair_type", "stair_clear_width_m", "stair_enclosure_width_m"], "expected": true, "missing_input": "INPUT_REQUIRED", "false_result": "FAIL", "not_applicable_result": "NOT_APPLICABLE" } }</pre>
PASS example	Applicable project with complete authoritative inputs satisfying qualitative predicate
FAIL example	Applicable project with complete authoritative inputs violating qualitative predicate
Boundary example	Evaluate exact threshold and immediately below/above values where numeric; otherwise exact predicate boundary.
NOT_APPLICABLE example	Project/object does not satisfy: Residential building group 4,5,6,7 established by authority; result must be NOT_APPLICABLE, never PASS.
INPUT_REQUIRED behavior	If any material applicability or evaluation input is absent, return INPUT_REQUIRED. Required inputs: building_group, stair_type, stair_clear_width_m, stair_enclosure_width_m.
Current unresolved interpretation	None beyond licensed professional confirmation of the prepared interpretation.
Proposed reviewer decision	No default. Reviewer must select one allowed decision.

Reviewer decision

☐ APPROVED ☐ APPROVED_WITH_CHANGE ☐ REJECTED ☐ NEEDS_MORE_EVIDENCE

Reviewer comments	
Requested change or missing evidence	
Source basis	
Reviewer name	
Professional role	
License or registration	
Review date	

Rule 4 ARCH-RES-STAIRS-003

پله ساختمان مسکونی گروه ۸

Risk	CRITICAL
Plain language rule	برای ساختمان مسکونی گروه ۸، هندسه پله مبحث چهارم و ظرفیت، تعداد، دوربندی و پیوستگی خروج مبحث سوم باید مستقل و همزمان احراز شوند.
Classification	MANDATORY_NATIONAL
Enforcement consequence	BLOCK
Applicable conditions	building_use == RESIDENTIAL AND (building_height_m > 23 OR floor_count > 7)
Required inputs	building_use, building_height_m, floor_count, gross_residential_area_m2, sprinkler_status, exit_count, stair_count, stair_widths_cm, tread_depth_cm, riser_height_cm, headroom_cm, exit_enclosure_status, exit_continuity_status
Authoritative source	مبحث چهارم، الزامات عمومی ساختمان
Edition	1396
Clause	4-7-1-1-5
Page	printed 85 PDF 99
Source text or precise summary	M4 4-7-1-1-5 defers group-8 stair dimensions to occupant population and M3 means-of-egress requirements. M3 3-6-11-2-2 requires two remote exits for apartments unless narrow exceptions apply; M3 3-6-4-3 and 3-6-6 provide stair geometry and capacity.
Exceptions	M3 3-6-11-2-3 through 3-6-11-2-5 only when every stated condition is met; group-8 height/storey conditions do not qualify for the ≤6-storey, ≤23 m single-stair exceptions.
Cross-code dependencies	IR-M3, IR-ACCESS
Machine interpretation	<pre>{ "applicability": { "all": ["building_use == RESIDENTIAL"], "any": ["building_height_m > 23", "floor_count > 7"], "missing_input": "INPUT_REQUIRED", "false_result": "NOT_APPLICABLE", "m3_occupant_load": { "formula": "gross_residential_area_m2 / 18.6", "unit": "person", "source_clause": "3-6-5-1", "source_page": { "printed": 99, "pdf": 115 } }, "required_exit_count": { "operator": ">=", "value": 2, "source_clause": "3-6-11-2-2", "single_exit_exceptions": ["3-6-11-2-3", "3-6-11-2-4", "3-6-11-2-5"], "group8_exception_eligibility": false, "reason": "Single-stair apartment exceptions are capped at six storeys and 23 m; group 8 exceeds that scope." }, "stair_capacity": { "unsprinklered_mm_per_person": 8, "sprinklered_mm_per_person": 5, "source_clause": "3-6-6-1", "source_page": { "printed": 102, "pdf": 118 } }, "unknown_sprinkler": "INPUT_REQUIRED", "stair_geometry": { "minimum_clear_width_cm": 110, "conditional_minimum_width_cm": 90, "conditional_width_scope": "all floors using that stair have fewer than 50" } } }</pre>

	occupants","minimum_headroom_cm":205,"minimum_tread_cm":28,"riser_cm": {"minimum":10,"maximum":18},"tread_plus_two_risers_cm":{"minimum":63,"maximum":64},"source_clauses":["3-6-4-3-2","3-6-4-3-3","3-6-4-3-4"]},"egress_authority":{"requires":["exit_enclosure_status","exit_continuity_status"],"source_clauses":["3-6-3-3-3","3-6-2-16","3-6-11-2"],"missing_input":"INPUT_REQUIRED"},"combined_result":{"all_applicable_requirements_must_pass":true,"missing_input":"INPUT_REQUIRED","false_result":"FAIL","not_applicable_result":"NOT_APPLICABLE"}}}
PASS example	Group-8 apartment building with complete occupant/load/fire inputs, at least two independent exits, sufficient stair capacity, compliant stair geometry, enclosure and continuity.
FAIL example	Applicable group-8 building with one exit or insufficient stair width/geometry.
Boundary example	23.00 m / 7 storeys remains below group-8 trigger; >23.00 m or >7 storeys enters the group-8 branch.
NOT_APPLICABLE example	Project/object does not satisfy: Residential group 8: building height > 23 m, with the M4 floor-count branch (>7 storeys) retained as an independently tested trigger.; result must be NOT_APPLICABLE, never PASS.
INPUT_REQUIRED behavior	If any material applicability or evaluation input is absent, return INPUT_REQUIRED. Required inputs: building_use, building_height_m, floor_count, gross_residential_area_m2, sprinkler_status, exit_count, stair_count, stair_widths_cm, tread_depth_cm, riser_height_cm, headroom_cm, exit_enclosure_status, exit_continuity_status.
Current unresolved interpretation	Confirm the combined M4/M3/Code 246 interface and exclusion of lower-group one-stair exceptions.
Proposed reviewer decision	No default. Reviewer must select one allowed decision.

Reviewer decision

☐ APPROVED
 ☐ APPROVED_WITH_CHANGE
 ☐ REJECTED
 ☐ NEEDS_MORE_EVIDENCE

Reviewer comments	
Requested change or missing evidence	
Source basis	
Reviewer name	
Professional role	
License or registration	
Review date	

Rule 5 ARCH-RES-EGRESS-001

بازشدن در خروج از داخل

Risk	CRITICAL
Plain language rule	بازکردن در از داخل ساده و فوری باشد؛ قفل یا مانع نباید خروج به موقع را مختل کند.
Classification	MANDATORY_NATIONAL
Enforcement consequence	BLOCK
Applicable conditions	Doors on access/egress paths; explicit listed exceptions apply
Required inputs	door_hardware, egress_path, exception_authority
Authoritative source	مبحث چهارم، الزامات عمومی ساختمان
Edition	1396
Clause	4-5-1-5-4
Page	printed 47 PDF 61
Source text or precise summary	بازکردن در از داخل ساده و فوری باشد؛ قفل یا مانع نباید خروج به موقع را مختل کند.
Exceptions	None recorded
Cross-code dependencies	IR-M3
Machine interpretation	<pre>{"review_predicate":{"inputs":["door_hardware","egress_path","exception_authority"],"expected":true,"missing_input":"INPUT_REQUIRED","false_result":"FAIL","not_applicable_result":"NOT_APPLICABLE"}}</pre>
PASS example	Applicable project with complete authoritative inputs satisfying qualitative predicate
FAIL example	Applicable project with complete authoritative inputs violating qualitative predicate
Boundary example	Evaluate exact threshold and immediately below/above values where numeric; otherwise exact predicate boundary.
NOT_APPLICABLE example	Project/object does not satisfy: Doors on access/egress paths; explicit listed exceptions apply; result must be NOT_APPLICABLE, never PASS.
INPUT_REQUIRED behavior	If any material applicability or evaluation input is absent, return INPUT_REQUIRED. Required inputs: door_hardware, egress_path, exception_authority.
Current unresolved interpretation	None beyond licensed professional confirmation of the prepared interpretation.
Proposed reviewer decision	No default. Reviewer must select one allowed decision.

Reviewer decision

☐ APPROVED ☐ APPROVED_WITH_CHANGE ☐ REJECTED ☐ NEEDS_MORE_EVIDENCE

Reviewer comments	
Requested change or missing evidence	
Source basis	
Reviewer name	
Professional role	
License or registration	
Review date	

Rule 6 ARCH-RES-DOOR-001

در ورودی اتاق اقامت

Risk	HIGH
Plain language rule	پهنای مفید حداقل ۰٫۸۰ متر و ارتفاع مفید ۲٫۰۵ متر؛ لنگه فعال در دولنگه نیز حداقل ۰٫۸۰ متر.
Classification	MANDATORY_NATIONAL
Enforcement consequence	BLOCK
Applicable conditions	Habitable room entry; specific accessible/egress provisions also apply
Required inputs	door_clear_width_m, door_clear_height_m
Authoritative source	مبحث چهارم، الزامات عمومی ساختمان
Edition	1396
Clause	4-5-2-8-2
Page	printed 55 PDF 69
Source text or precise summary	پهنای مفید حداقل ۰٫۸۰ متر و ارتفاع مفید ۲٫۰۵ متر؛ لنگه فعال در دولنگه نیز حداقل ۰٫۸۰ متر.
Exceptions	None recorded
Cross-code dependencies	IR-M3, IR-ACCESS
Machine interpretation	<pre>{ "all": [{ "field": "door_clear_width_m", "op": ">=", "value": 0.8, "unit": "m" }, { "field": "door_clear_height_m", "op": ">=", "value": 2.05, "unit": "m" }] }</pre>
PASS example	Applicable project with complete authoritative inputs satisfying ≥ 0.8 m, ≥ 2.05 m
FAIL example	Applicable project with complete authoritative inputs violating ≥ 0.8 m, ≥ 2.05 m
Boundary example	Evaluate exact threshold and immediately below/above values where numeric; otherwise exact predicate boundary.
NOT_APPLICABLE example	Project/object does not satisfy: Habitable room entry; specific accessible/egress provisions also apply; result must be NOT_APPLICABLE, never PASS.
INPUT_REQUIRED behavior	If any material applicability or evaluation input is absent, return INPUT_REQUIRED. Required inputs: door_clear_width_m, door_clear_height_m.
Current unresolved interpretation	None beyond licensed professional confirmation of the prepared interpretation.
Proposed reviewer decision	No default. Reviewer must select one allowed decision.

Reviewer decision

☐ APPROVED ☐ APPROVED_WITH_CHANGE ☐ REJECTED ☐ NEEDS_MORE_EVIDENCE

Reviewer comments	
Requested change or missing evidence	
Source basis	
Reviewer name	
Professional role	
License or registration	
Review date	

Rule 7 ARCH-RES-LIVING-001

اندازه حداقل یک فضای اقامت اصلی

Risk	HIGH
Plain language rule	حداقل یک فضای اقامت با مساحت ۱۲ مترمربع و عرض ۲٫۷۰ متر لازم است.
Classification	MANDATORY_NATIONAL
Enforcement consequence	BLOCK
Applicable conditions	Residential unit area $\geq 75\text{m}^2$
Required inputs	unit_area_m2, largest_habitable_area_m2, largest_habitable_width_m
Authoritative source	مبحث چهارم، الزامات عمومی ساختمان
Edition	1396
Clause	4-7-1-1-8
Page	printed 85 PDF 99
Source text or precise summary	حداقل یک فضای اقامت با مساحت ۱۲ مترمربع و عرض ۲٫۷۰ متر لازم است.
Exceptions	None recorded
Cross-code dependencies	unit_area_m2, largest_habitable_area_m2, largest_habitable_width_m
Machine interpretation	<pre>{ "all": [{ "field": "largest_habitable_area_m2", "op": ">=", "value": 12, "unit": "m2" }, { "field": "largest_habitable_width_m", "op": ">=", "value": 2.7, "unit": "m" }] }</pre>
PASS example	Applicable project with complete authoritative inputs satisfying $\geq 12\text{ m}^2$, $\geq 2.7\text{ m}$
FAIL example	Applicable project with complete authoritative inputs violating $\geq 12\text{ m}^2$, $\geq 2.7\text{ m}$
Boundary example	Evaluate exact threshold and immediately below/above values where numeric; otherwise exact predicate boundary.
NOT_APPLICABLE example	Project/object does not satisfy: Residential unit area $\geq 75\text{m}^2$; result must be NOT_APPLICABLE, never PASS.
INPUT_REQUIRED behavior	If any material applicability or evaluation input is absent, return INPUT_REQUIRED. Required inputs: unit_area_m2, largest_habitable_area_m2, largest_habitable_width_m.
Current unresolved interpretation	None beyond licensed professional confirmation of the prepared interpretation.
Proposed reviewer decision	No default. Reviewer must select one allowed decision.

Reviewer decision

☐ APPROVED ☐ APPROVED_WITH_CHANGE ☐ REJECTED ☐ NEEDS_MORE_EVIDENCE

Reviewer comments	
Requested change or missing evidence	
Source basis	
Reviewer name	
Professional role	
License or registration	
Review date	

Rule 8 ARCH-RES-LIVING-002

فضای اقامت واحد کوچک

Risk	HIGH
Plain language rule	حداقل یک اتاق ۹ مترمربع و هیچ یک از ابعاد افقی آن کمتر از ۲٫۵ متر نباشد.
Classification	MANDATORY_NATIONAL
Enforcement consequence	BLOCK
Applicable conditions	Residential unit area <75m2
Required inputs	unit_area_m2, largest_habitable_area_m2, largest_habitable_width_m
Authoritative source	مبحث چهارم، الزامات عمومی ساختمان
Edition	1396
Clause	4-7-1-1-8
Page	printed 85 PDF 99
Source text or precise summary	حداقل یک اتاق ۹ مترمربع و هیچ یک از ابعاد افقی آن کمتر از ۲٫۵ متر نباشد.
Exceptions	None recorded
Cross-code dependencies	unit_area_m2, largest_habitable_area_m2, largest_habitable_width_m
Machine interpretation	<pre>{ "all": [{ "field": "largest_habitable_area_m2", "op": ">=", "value": 9, "unit": "m2" }, { "field": "largest_habitable_width_m", "op": ">=", "value": 2.5, "unit": "m" }] }</pre>
PASS example	Applicable project with complete authoritative inputs satisfying ≥ 9 m2, ≥ 2.5 m
FAIL example	Applicable project with complete authoritative inputs violating ≥ 9 m2, ≥ 2.5 m
Boundary example	Evaluate exact threshold and immediately below/above values where numeric; otherwise exact predicate boundary.
NOT_APPLICABLE example	Project/object does not satisfy: Residential unit area <75m2; result must be NOT_APPLICABLE, never PASS.
INPUT_REQUIRED behavior	If any material applicability or evaluation input is absent, return INPUT_REQUIRED. Required inputs: unit_area_m2, largest_habitable_area_m2, largest_habitable_width_m.
Current unresolved interpretation	None beyond licensed professional confirmation of the prepared interpretation.
Proposed reviewer decision	No default. Reviewer must select one allowed decision.

Reviewer decision

☐ APPROVED ☐ APPROVED_WITH_CHANGE ☐ REJECTED ☐ NEEDS_MORE_EVIDENCE

Reviewer comments	
Requested change or missing evidence	
Source basis	
Reviewer name	
Professional role	
License or registration	
Review date	

Rule 9 ARCH-RES-LIVING-003

مساحت عمومی اتاق اقامت

Risk	HIGH
Plain language rule	حداقل مساحت ۶٫۵ مترمربع؛ حکم اختصاصی تصرف مقدم است.
Classification	MANDATORY_NATIONAL
Enforcement consequence	BLOCK
Applicable conditions	Habitable room unless specific occupancy provisions supersede
Required inputs	room_area_m2
Authoritative source	مبحث چهارم، الزامات عمومی ساختمان
Edition	1396
Clause	4-5-2-2-1
Page	printed 52 PDF 66
Source text or precise summary	حداقل مساحت ۶٫۵ مترمربع؛ حکم اختصاصی تصرف مقدم است.
Exceptions	None recorded
Cross-code dependencies	room_area_m2
Machine interpretation	{ "field": "room_area_m2", "op": ">=", "value": 6.5, "unit": "m 2" }
PASS example	Applicable project with complete authoritative inputs satisfying $\geq 6.5 \text{ m}^2$
FAIL example	Applicable project with complete authoritative inputs violating $\geq 6.5 \text{ m}^2$
Boundary example	Evaluate exact threshold and immediately below/above values where numeric; otherwise exact predicate boundary.
NOT_APPLICABLE example	Project/object does not satisfy: Habitable room unless specific occupancy provisions supersede; result must be NOT_APPLICABLE, never PASS.
INPUT_REQUIRED behavior	If any material applicability or evaluation input is absent, return INPUT_REQUIRED. Required inputs: room_area_m2.
Current unresolved interpretation	None beyond licensed professional confirmation of the prepared interpretation.
Proposed reviewer decision	No default. Reviewer must select one allowed decision.

Reviewer decision

☐ APPROVED ☐ APPROVED_WITH_CHANGE ☐ REJECTED ☐ NEEDS_MORE_EVIDENCE

Reviewer comments	
--------------------------	--

Requested change or missing evidence	
Source basis	
Reviewer name	
Professional role	
License or registration	
Review date	

Rule 10 ARCH-RES-BEDROOM-001

عرض سایر اتاق‌های اقامت مسکونی

Risk	HIGH
Plain language rule	حداقل عرض سایر فضاهای اقامت ۲٫۴۰ متر است؛ مساحت طبق نوع استفاده کنترل شود.
Classification	MANDATORY_NATIONAL
Enforcement consequence	BLOCK
Applicable conditions	Other habitable rooms in residential units; use-specific dimensions also apply
Required inputs	room_width_m, room_use
Authoritative source	مبحث چهارم، الزامات عمومی ساختمان
Edition	1396
Clause	4-7-1-1-8
Page	printed 85 PDF 99
Source text or precise summary	حداقل عرض سایر فضاهای اقامت ۲٫۴۰ متر است؛ مساحت طبق نوع استفاده کنترل شود.
Exceptions	None recorded
Cross-code dependencies	room_width_m, room_use
Machine interpretation	<pre>{ "field": "room_width_m", "op": ">=", "value": 2.4, "unit": "m" }</pre>
PASS example	Applicable project with complete authoritative inputs satisfying ≥ 2.4 m
FAIL example	Applicable project with complete authoritative inputs violating ≥ 2.4 m
Boundary example	Evaluate exact threshold and immediately below/above values where numeric; otherwise exact predicate boundary.
NOT_APPLICABLE example	Project/object does not satisfy: Other habitable rooms in residential units; use-specific dimensions also apply; result must be NOT_APPLICABLE, never PASS.
INPUT_REQUIRED behavior	If any material applicability or evaluation input is absent, return INPUT_REQUIRED. Required inputs: room_width_m, room_use.
Current unresolved interpretation	None beyond licensed professional confirmation of the prepared interpretation.
Proposed reviewer decision	No default. Reviewer must select one allowed decision.

Reviewer decision

☐ APPROVED ☐ APPROVED_WITH_CHANGE ☐ REJECTED ☐ NEEDS_MORE_EVIDENCE

Reviewer comments	
--------------------------	--

Requested change or missing evidence	
Source basis	
Reviewer name	
Professional role	
License or registration	
Review date	

Rule 11 ARCH-RES-KITCHEN-001

آشپزخانه مستقل یا باز برای پخت‌وپز

Risk	HIGH
Plain language rule	مساحت حداقل ۵٫۵ مترمربع؛ سطح آزاد خارج از قفسه‌بندی حداقل ۲٫۷۵ مترمربع.
Classification	MANDATORY_NATIONAL
Enforcement consequence	BLOCK
Applicable conditions	Independent or open residential kitchen used only for cooking
Required inputs	kitchen_area_m2, kitchen_free_area_m2
Authoritative source	مبحث چهارم، الزامات عمومی ساختمان
Edition	1396
Clause	4-7-1-1-10
Page	printed 86 PDF 100
Source text or precise summary	مساحت حداقل ۵٫۵ مترمربع؛ سطح آزاد خارج از قفسه‌بندی حداقل ۲٫۷۵ مترمربع.
Exceptions	None recorded
Cross-code dependencies	kitchen_area_m2, kitchen_free_area_m2
Machine interpretation	<pre>{ "all": [{ "field": "kitchen_area_m2", "op": ">=", "value": 5.5, "unit": "m2" }, { "field": "kitchen_free_area_m2", "op": ">=", "value": 2.75, "unit": "m2" }] }</pre>
PASS example	Applicable project with complete authoritative inputs satisfying ≥ 5.5 m2, ≥ 2.75 m2
FAIL example	Applicable project with complete authoritative inputs violating ≥ 5.5 m2, ≥ 2.75 m2
Boundary example	Evaluate exact threshold and immediately below/above values where numeric; otherwise exact predicate boundary.
NOT_APPLICABLE example	Project/object does not satisfy: Independent or open residential kitchen used only for cooking; result must be NOT_APPLICABLE, never PASS.
INPUT_REQUIRED behavior	If any material applicability or evaluation input is absent, return INPUT_REQUIRED. Required inputs: kitchen_area_m2, kitchen_free_area_m2.
Current unresolved interpretation	None beyond licensed professional confirmation of the prepared interpretation.
Proposed reviewer decision	No default. Reviewer must select one allowed decision.

Reviewer decision

☐ APPROVED ☐ APPROVED_WITH_CHANGE ☐ REJECTED ☐ NEEDS_MORE_EVIDENCE

Reviewer comments	
Requested change or missing evidence	
Source basis	
Reviewer name	
Professional role	
License or registration	
Review date	

Rule 12 ARCH-RES-KITCHEN-002

آشپزخانه همراه محل صرف غذا

Risk	HIGH
Plain language rule	حداقل مساحت ۷٫۵۰ مترمربع.
Classification	MANDATORY_NATIONAL
Enforcement consequence	BLOCK
Applicable conditions	Residential independent/open kitchen for cooking and eating
Required inputs	kitchen_area_m2
Authoritative source	مبحث چهارم، الزامات عمومی ساختمان
Edition	1396
Clause	4-7-1-1-11
Page	printed 86 PDF 100
Source text or precise summary	حداقل مساحت ۷٫۵۰ مترمربع.
Exceptions	None recorded
Cross-code dependencies	kitchen_area_m2
Machine interpretation	{ "field": "kitchen_area_m2", "op": ">=", "value": 7.5, "unit": "m2" }
PASS example	Applicable project with complete authoritative inputs satisfying ≥ 7.5 m2
FAIL example	Applicable project with complete authoritative inputs violating ≥ 7.5 m2
Boundary example	Evaluate exact threshold and immediately below/above values where numeric; otherwise exact predicate boundary.
NOT_APPLICABLE example	Project/object does not satisfy: Residential independent/open kitchen for cooking and eating; result must be NOT_APPLICABLE, never PASS.
INPUT_REQUIRED behavior	If any material applicability or evaluation input is absent, return INPUT_REQUIRED. Required inputs: kitchen_area_m2.
Current unresolved interpretation	None beyond licensed professional confirmation of the prepared interpretation.
Proposed reviewer decision	No default. Reviewer must select one allowed decision.

Reviewer decision

☐ APPROVED ☐ APPROVED_WITH_CHANGE ☐ REJECTED ☐ NEEDS_MORE_EVIDENCE

Reviewer comments	
Requested change or missing evidence	

Source basis	
Reviewer name	
Professional role	
License or registration	
Review date	

Rule 13 ARCH-RES-KITCHEN-003

عرض آشپزخانه

Risk	HIGH
Plain language rule	حداقل عرض ۱٫۸۰ متر؛ برای پخت‌وپز همراه صرف غذا ۲٫۱۵ متر.
Classification	MANDATORY_NATIONAL
Enforcement consequence	BLOCK
Applicable conditions	Independent/open residential kitchen
Required inputs	kitchen_use, kitchen_width_m
Authoritative source	مبحث چهارم، الزامات عمومی ساختمان
Edition	1396
Clause	4-7-1-1-12
Page	printed 86 PDF 100
Source text or precise summary	حداقل عرض ۱٫۸۰ متر؛ برای پخت‌وپز همراه صرف غذا ۲٫۱۵ متر.
Exceptions	None recorded
Cross-code dependencies	kitchen_use, kitchen_width_m
Machine interpretation	<pre>{"review_predicate":{"inputs":["kitchen_use","kitchen_width_m"],"expected":true,"missing_input":"INPUT_REQUIRED","false_result":"FAIL","not_applicable_result":"NOT_APPLICABLE"}}</pre>
PASS example	Applicable project with complete authoritative inputs satisfying qualitative predicate
FAIL example	Applicable project with complete authoritative inputs violating qualitative predicate
Boundary example	Evaluate exact threshold and immediately below/above values where numeric; otherwise exact predicate boundary.
NOT_APPLICABLE example	Project/object does not satisfy: Independent/open residential kitchen; result must be NOT_APPLICABLE, never PASS.
INPUT_REQUIRED behavior	If any material applicability or evaluation input is absent, return INPUT_REQUIRED. Required inputs: kitchen_use, kitchen_width_m.
Current unresolved interpretation	None beyond licensed professional confirmation of the prepared interpretation.
Proposed reviewer decision	No default. Reviewer must select one allowed decision.

Reviewer decision

☐ APPROVED ☐ APPROVED_WITH_CHANGE ☐ REJECTED ☐ NEEDS_MORE_EVIDENCE

Reviewer comments	
Requested change or missing evidence	
Source basis	
Reviewer name	
Professional role	
License or registration	
Review date	

Rule 14 ARCH-RES-KITCHEN-004

فضای کار آشپزخانه دیواری

Risk	HIGH
Plain language rule	فضای کار آزاد در تمام طول از لبه قفسه‌ها حداقل ۱٫۱ متر و طول آشپزخانه حداقل ۳ متر.
Classification	MANDATORY_NATIONAL
Enforcement consequence	BLOCK
Applicable conditions	Wall kitchen in residential unit
Required inputs	work_aisle_width_m, wall_kitchen_length_m
Authoritative source	مبحث چهارم، الزامات عمومی ساختمان
Edition	1396
Clause	4-7-1-1-13
Page	printed 86 PDF 100
Source text or precise summary	فضای کار آزاد در تمام طول از لبه قفسه‌ها حداقل ۱٫۱ متر و طول آشپزخانه حداقل ۳ متر.
Exceptions	None recorded
Cross-code dependencies	work_aisle_width_m, wall_kitchen_length_m
Machine interpretation	<pre>{ "all": [{ "field": "work_aisle_width_m", "op": ">=", "value": 1.1, "unit": "m" }, { "field": "wall_kitchen_length_m", "op": ">=", "value": 3, "unit": "m" }] }</pre>
PASS example	Applicable project with complete authoritative inputs satisfying ≥ 1.1 m, ≥ 3 m
FAIL example	Applicable project with complete authoritative inputs violating ≥ 1.1 m, ≥ 3 m
Boundary example	Evaluate exact threshold and immediately below/above values where numeric; otherwise exact predicate boundary.
NOT_APPLICABLE example	Project/object does not satisfy: Wall kitchen in residential unit; result must be NOT_APPLICABLE, never PASS.
INPUT_REQUIRED behavior	If any material applicability or evaluation input is absent, return INPUT_REQUIRED. Required inputs: work_aisle_width_m, wall_kitchen_length_m.
Current unresolved interpretation	None beyond licensed professional confirmation of the prepared interpretation.
Proposed reviewer decision	No default. Reviewer must select one allowed decision.

Reviewer decision

☐ APPROVED ☐ APPROVED_WITH_CHANGE ☐ REJECTED ☐ NEEDS_MORE_EVIDENCE

Reviewer comments	
Requested change or missing evidence	
Source basis	
Reviewer name	
Professional role	
License or registration	
Review date	

Rule 15 ARCH-RES-KITCHEN-005

ممنوعیت عبور الزامی از آشپزخانه

Risk	HIGH
Plain language rule	دسترسی فضای اقامت از آشپزخانه نباشد؛ استثنای واحد دو فضایی فقط با ورودی فعال و نور و تهویه مستقل بررسی شود.
Classification	MANDATORY_NATIONAL
Enforcement consequence	BLOCK
Applicable conditions	Access to workplace/habitable room
Required inputs	access_graph, habitable_count, independent_openings
Authoritative source	مبحث چهارم، الزامات عمومی ساختمان
Edition	1396
Clause	4-5-5-1-2
Page	printed 58 PDF 72
Source text or precise summary	دسترسی فضای اقامت از آشپزخانه نباشد؛ استثنای واحد دو فضایی فقط با ورودی فعال و نور و تهویه مستقل بررسی شود.
Exceptions	None recorded
Cross-code dependencies	access_graph, habitable_count, independent_openings
Machine interpretation	<pre>{"review_predicate":{"inputs":["access_graph","habitable_count","independent_openings"],"expected":true,"missing_input":"INPUT_REQUIRED","false_result":"FAIL","not_applicable_result":"NOT_APPLICABLE"}}</pre>
PASS example	Applicable project with complete authoritative inputs satisfying qualitative predicate
FAIL example	Applicable project with complete authoritative inputs violating qualitative predicate
Boundary example	Evaluate exact threshold and immediately below/above values where numeric; otherwise exact predicate boundary.
NOT_APPLICABLE example	Project/object does not satisfy: Access to workplace/habitable room; result must be NOT_APPLICABLE, never PASS.
INPUT_REQUIRED behavior	If any material applicability or evaluation input is absent, return INPUT_REQUIRED. Required inputs: access_graph, habitable_count, independent_openings.
Current unresolved interpretation	None beyond licensed professional confirmation of the prepared interpretation.
Proposed reviewer decision	No default. Reviewer must select one allowed decision.

Reviewer decision

☐ APPROVED ☐ APPROVED_WITH_CHANGE ☐ REJECTED ☐ NEEDS_MORE_EVIDENCE

Reviewer comments	
Requested change or missing evidence	
Source basis	
Reviewer name	
Professional role	
License or registration	
Review date	

Rule 16 ARCH-RES-BATHROOM-001

ابعاد فضای بهداشتی مسکونی معمول

Risk	HIGH
Plain language rule	حداقل عرض ۱ متر و طول ۱٫۲۰ متر؛ برای دوش مستقل با رختکن داخل فضا حداقل یکی از ابعاد ۱٫۵۰ متر. ادامه و استثنای سرویس ترکیبی در صفحه بعد بررسی شود.
Classification	MANDATORY_NATIONAL
Enforcement consequence	BLOCK
Applicable conditions	Separate residential sanitary space without mandatory accessible designation
Required inputs	accessible_required, sanitary_width_m, sanitary_length_m, shower_dressing_inside
Authoritative source	مبحث چهارم، الزامات عمومی ساختمان
Edition	1396
Clause	4-7-1-1-18
Page	printed 86 PDF 100
Source text or precise summary	حداقل عرض ۱ متر و طول ۱٫۲۰ متر؛ برای دوش مستقل با رختکن داخل فضا حداقل یکی از ابعاد ۱٫۵۰ متر. ادامه و استثنای سرویس ترکیبی در صفحه بعد بررسی شود.
Exceptions	None recorded
Cross-code dependencies	accessible_required, sanitary_width_m, sanitary_length_m, shower_dressing_inside
Machine interpretation	<pre>{"review_predicate":{"inputs":["accessible_required","sanitary_width_m","sanitary_length_m","shower_dressing_inside"],"expected":true,"missing_input":"INPUT_REQUIRED","false_result":"FAIL","not_applicable_result":"NOT_APPLICABLE"}}</pre>
PASS example	Applicable project with complete authoritative inputs satisfying qualitative predicate
FAIL example	Applicable project with complete authoritative inputs violating qualitative predicate
Boundary example	Evaluate exact threshold and immediately below/above values where numeric; otherwise exact predicate boundary.
NOT_APPLICABLE example	Project/object does not satisfy: Separate residential sanitary space without mandatory accessible designation; result must be NOT_APPLICABLE, never PASS.
INPUT_REQUIRED behavior	If any material applicability or evaluation input is absent, return INPUT_REQUIRED. Required inputs: accessible_required, sanitary_width_m, sanitary_length_m, shower_dressing_inside.

Current unresolved interpretation	None beyond licensed professional confirmation of the prepared interpretation.
Proposed reviewer decision	No default. Reviewer must select one allowed decision.

Reviewer decision

☐ APPROVED ☐ APPROVED_WITH_CHANGE ☐ REJECTED ☐ NEEDS_MORE_EVIDENCE

Reviewer comments	
Requested change or missing evidence	
Source basis	
Reviewer name	
Professional role	
License or registration	
Review date	

Rule 17 ARCH-RES-BATHROOM-002

ارتفاع فضای بهداشتی مسکونی

Risk	HIGH
Plain language rule	ارتفاع حداقل ۲٫۲۰ متر در ۸۰ درصد سطح الزامی؛ زیر سقف شیب‌دار کوتاه‌ترین قسمت حداقل ۲٫۰۵ متر.
Classification	MANDATORY_NATIONAL
Enforcement consequence	BLOCK
Applicable conditions	Residential sanitary space
Required inputs	clear_height_m, height_coverage_fraction, sloped_roof_min_height_m
Authoritative source	مبحث چهارم، الزامات عمومی ساختمان
Edition	1396
Clause	4-7-1-1-19
Page	printed 87 PDF 101
Source text or precise summary	ارتفاع حداقل ۲٫۲۰ متر در ۸۰ درصد سطح الزامی؛ زیر سقف شیب‌دار کوتاه‌ترین قسمت حداقل ۲٫۰۵ متر.
Exceptions	None recorded
Cross-code dependencies	clear_height_m, height_coverage_fraction, sloped_roof_min_height_m
Machine interpretation	<pre>{"review_predicate":{"inputs":["clear_height_m","height_coverage_fraction","sloped_roof_min_height_m"],"expected":true,"missing_input":"INPUT_REQUIRED","false_result":"FAIL","not_applicable_result":"NOT_APPLICABLE"}}</pre>
PASS example	Applicable project with complete authoritative inputs satisfying qualitative predicate
FAIL example	Applicable project with complete authoritative inputs violating qualitative predicate
Boundary example	Evaluate exact threshold and immediately below/above values where numeric; otherwise exact predicate boundary.
NOT_APPLICABLE example	Project/object does not satisfy: Residential sanitary space; result must be NOT_APPLICABLE, never PASS.
INPUT_REQUIRED behavior	If any material applicability or evaluation input is absent, return INPUT_REQUIRED. Required inputs: clear_height_m, height_coverage_fraction, sloped_roof_min_height_m.
Current unresolved interpretation	None beyond licensed professional confirmation of the prepared interpretation.
Proposed reviewer decision	No default. Reviewer must select one allowed decision.

Reviewer decision

☐ APPROVED ☐ APPROVED_WITH_CHANGE ☐ REJECTED ☐ NEEDS_MORE_EVIDENCE

Reviewer comments	
Requested change or missing evidence	
Source basis	
Reviewer name	
Professional role	
License or registration	
Review date	

Rule 18 ARCH-RES-WC-001

پیش‌بینی توالی فرنگی برای واحد بزرگ

Risk	HIGH
Plain language rule	فضا و تأسیسات آب و فاضلاب لازم برای نصب حداقل یک توالی فرنگی فراهم شود.
Classification	MANDATORY_NATIONAL
Enforcement consequence	BLOCK
Applicable conditions	Residential unit area $\geq 75m^2$
Required inputs	unit_area_m2, wc_reservation, water_port, waste_port
Authoritative source	مبحث چهارم، الزامات عمومی ساختمان
Edition	1396
Clause	4-7-1-1-17
Page	printed 86 PDF 100
Source text or precise summary	فضا و تأسیسات آب و فاضلاب لازم برای نصب حداقل یک توالی فرنگی فراهم شود.
Exceptions	None recorded
Cross-code dependencies	unit_area_m2, wc_reservation, water_port, waste_port
Machine interpretation	<pre>{"review_predicate":{"inputs":["unit_area_m2","wc_reservation","water_port","waste_port"],"expected":true,"missing_input":"INPUT_REQUIRED","false_result":"FAIL","not_applicable_result":"NOT_APPLICABLE"}}</pre>
PASS example	Applicable project with complete authoritative inputs satisfying qualitative predicate
FAIL example	Applicable project with complete authoritative inputs violating qualitative predicate
Boundary example	Evaluate exact threshold and immediately below/above values where numeric; otherwise exact predicate boundary.
NOT_APPLICABLE example	Project/object does not satisfy: Residential unit area $\geq 75m^2$; result must be NOT_APPLICABLE, never PASS.
INPUT_REQUIRED behavior	If any material applicability or evaluation input is absent, return INPUT_REQUIRED. Required inputs: unit_area_m2, wc_reservation, water_port, waste_port.
Current unresolved interpretation	None beyond licensed professional confirmation of the prepared interpretation.
Proposed reviewer decision	No default. Reviewer must select one allowed decision.

Reviewer decision

☐ APPROVED ☐ APPROVED_WITH_CHANGE ☐ REJECTED ☐ NEEDS_MORE_EVIDENCE

Reviewer comments	
Requested change or missing evidence	
Source basis	
Reviewer name	
Professional role	
License or registration	
Review date	

Rule 19 ARCH-RES-DAYLIGHT-001

نور و هوای آشپزخانه مستقل

Risk	HIGH
Plain language rule	نور و تهویه طبیعی مستقل؛ در واحد زیر ۷۵ مترمربع اگر دورترین نقطه آشپزخانه از پنجره فضای مجاور کمتر از ۷ متر باشد استثنا بررسی شود.
Classification	MANDATORY_NATIONAL
Enforcement consequence	BLOCK
Applicable conditions	Independent residential kitchen
Required inputs	unit_area_m2, kitchen_type, distance_to_adjacent_window_m, natural_light, natural_ventilation
Authoritative source	مبحث چهارم، الزامات عمومی ساختمان
Edition	1396
Clause	4-7-1-1-14
Page	printed 86 PDF 100
Source text or precise summary	نور و تهویه طبیعی مستقل؛ در واحد زیر ۷۵ مترمربع اگر دورترین نقطه آشپزخانه از پنجره فضای مجاور کمتر از ۷ متر باشد استثنا بررسی شود.
Exceptions	None recorded
Cross-code dependencies	unit_area_m2, kitchen_type, distance_to_adjacent_window_m, natural_light, natural_ventilation
Machine interpretation	<pre>{"review_predicate":{"inputs":["unit_area_m2","kitchen_type","distance_to_adjacent_window_m","natural_light","natural_ventilation"],"expected":true,"missing_input":"INPUT_REQUIRED","false_result":"FAIL","not_applicable_result":"NOT_APPLICABLE"}}</pre>
PASS example	Applicable project with complete authoritative inputs satisfying qualitative predicate
FAIL example	Applicable project with complete authoritative inputs violating qualitative predicate
Boundary example	Evaluate exact threshold and immediately below/above values where numeric; otherwise exact predicate boundary.
NOT_APPLICABLE example	Project/object does not satisfy: Independent residential kitchen; result must be NOT_APPLICABLE, never PASS.
INPUT_REQUIRED behavior	If any material applicability or evaluation input is absent, return INPUT_REQUIRED. Required inputs: unit_area_m2, kitchen_type, distance_to_adjacent_window_m, natural_light, natural_ventilation.
Current unresolved interpretation	None beyond licensed professional confirmation of the prepared interpretation.

Proposed reviewer decision	No default. Reviewer must select one allowed decision.
-----------------------------------	--

Reviewer decision

☐ APPROVED
 ☐ APPROVED_WITH_CHANGE
 ☐ REJECTED
 ☐ NEEDS_MORE_EVIDENCE

Reviewer comments	
Requested change or missing evidence	
Source basis	
Reviewer name	
Professional role	
License or registration	
Review date	

Rule 20 ARCH-RES-DAYLIGHT-002

سطح شیشه اتاق اقامت

Risk	HIGH
Plain language rule	حداقل نسبت شیشه به کف ۱/۸؛ اگر پنجره‌ها تنها در یک دیوار و عمق بیش از ۴٫۵۰ متر باشد ۱/۷.
Classification	MANDATORY_NATIONAL
Enforcement consequence	BLOCK
Applicable conditions	Habitable room; chapter4-6 and window-head exception3 apply
Required inputs	floor_area_m2, glazing_area_m2, single_window_wall, room_depth_m, window_head_m
Authoritative source	مبحث چهارم، الزامات عمومی ساختمان
Edition	1396
Clause	4-5-2-3-2
Page	printed 53 PDF 67
Source text or precise summary	حداقل نسبت شیشه به کف ۱/۸؛ اگر پنجره‌ها تنها در یک دیوار و عمق بیش از ۴٫۵۰ متر باشد ۱/۷.
Exceptions	None recorded
Cross-code dependencies	floor_area_m2, glazing_area_m2, single_window_wall, room_depth_m, window_head_m
Machine interpretation	<pre>{"review_predicate":{"inputs":["floor_area_m2","glazing_area_m2","single_window_wall","room_depth_m","window_head_m"],"expected":true,"missing_input":"INPUT_REQUIRED","false_result":"FAIL","not_applicable_result":"NOT_APPLICABLE"}}</pre>
PASS example	Applicable project with complete authoritative inputs satisfying qualitative predicate
FAIL example	Applicable project with complete authoritative inputs violating qualitative predicate
Boundary example	Evaluate exact threshold and immediately below/above values where numeric; otherwise exact predicate boundary.
NOT_APPLICABLE example	Project/object does not satisfy: Habitable room; chapter4-6 and window-head exception3 apply; result must be NOT_APPLICABLE, never PASS.
INPUT_REQUIRED behavior	If any material applicability or evaluation input is absent, return INPUT_REQUIRED. Required inputs: floor_area_m2, glazing_area_m2, single_window_wall, room_depth_m, window_head_m.
Current unresolved interpretation	None beyond licensed professional confirmation of the prepared interpretation.
Proposed reviewer decision	No default. Reviewer must select one allowed decision.

Reviewer decision

☐ APPROVED ☐ APPROVED_WITH_CHANGE ☐ REJECTED ☐ NEEDS_MORE_EVIDENCE

Reviewer comments	
Requested change or missing evidence	
Source basis	
Reviewer name	
Professional role	
License or registration	
Review date	

Rule 21 ARCH-RES-DAYLIGHT-003

پنجره با لبه بالایی کوتاه

Risk	HIGH
Plain language rule	نسبت شیشه شفاف به کف حداقل ۱/۶؛ برای پنجره‌های یک‌طرفه و عمق بیش از ۴۵۰ متر حداقل ۱/۵.
Classification	MANDATORY_NATIONAL
Enforcement consequence	BLOCK
Applicable conditions	Window head below 2.10m excluding sloped-roof light
Required inputs	floor_area_m2, glazing_area_m2, window_head_m, single_window_wall, room_depth_m
Authoritative source	مبحث چهارم، الزامات عمومی ساختمان
Edition	1396
Clause	4-5-2-3-3
Page	printed 53 PDF 67
Source text or precise summary	نسبت شیشه شفاف به کف حداقل ۱/۶؛ برای پنجره‌های یک‌طرفه و عمق بیش از ۴۵۰ متر حداقل ۱/۵.
Exceptions	None recorded
Cross-code dependencies	floor_area_m2, glazing_area_m2, window_head_m, single_window_wall, room_depth_m
Machine interpretation	<pre>{"review_predicate":{"inputs":["floor_area_m2","glazing_area_m2","window_head_m","single_window_wall","room_depth_m"],"expected":true,"missing_input":"INPUT_REQUIRED","false_result":"FAIL","not_applicable_result":"NOT_APPLICABLE"}}</pre>
PASS example	Applicable project with complete authoritative inputs satisfying qualitative predicate
FAIL example	Applicable project with complete authoritative inputs violating qualitative predicate
Boundary example	Evaluate exact threshold and immediately below/above values where numeric; otherwise exact predicate boundary.
NOT_APPLICABLE example	Project/object does not satisfy: Window head below 2.10m excluding sloped-roof light; result must be NOT_APPLICABLE, never PASS.
INPUT_REQUIRED behavior	If any material applicability or evaluation input is absent, return INPUT_REQUIRED. Required inputs: floor_area_m2, glazing_area_m2, window_head_m, single_window_wall, room_depth_m.
Current unresolved interpretation	None beyond licensed professional confirmation of the prepared interpretation.
Proposed reviewer decision	No default. Reviewer must select one allowed decision.

Reviewer decision

☐ APPROVED ☐ APPROVED_WITH_CHANGE ☐ REJECTED ☐ NEEDS_MORE_EVIDENCE

Reviewer comments	
Requested change or missing evidence	
Source basis	
Reviewer name	
Professional role	
License or registration	
Review date	

Rule 22 ARCH-RES-DAYLIGHT-004

عمق قابل قبول نورگیری

Risk	HIGH
Plain language rule	حداکثر عمق قابل قبول نورگیری از یک پنجره ۷ متر.
Classification	MANDATORY_NATIONAL
Enforcement consequence	BLOCK
Applicable conditions	Habitable room served by a window
Required inputs	daylight_depth_m
Authoritative source	مبحث چهارم، الزامات عمومی ساختمان
Edition	1396
Clause	4-5-2-8-3
Page	printed 55 PDF 69
Source text or precise summary	حداکثر عمق قابل قبول نورگیری از یک پنجره ۷ متر.
Exceptions	None recorded
Cross-code dependencies	daylight_depth_m
Machine interpretation	{ "field": "daylight_depth_m", "op": "<=", "value": 7, "unit": "m" }
PASS example	Applicable project with complete authoritative inputs satisfying ≤ 7 m
FAIL example	Applicable project with complete authoritative inputs violating ≤ 7 m
Boundary example	Evaluate exact threshold and immediately below/above values where numeric; otherwise exact predicate boundary.
NOT_APPLICABLE example	Project/object does not satisfy: Habitable room served by a window; result must be NOT_APPLICABLE, never PASS.
INPUT_REQUIRED behavior	If any material applicability or evaluation input is absent, return INPUT_REQUIRED. Required inputs: daylight_depth_m.
Current unresolved interpretation	None beyond licensed professional confirmation of the prepared interpretation.
Proposed reviewer decision	No default. Reviewer must select one allowed decision.

Reviewer decision

☐ APPROVED ☐ APPROVED_WITH_CHANGE ☐ REJECTED ☐ NEEDS_MORE_EVIDENCE

Reviewer comments	
Requested change or missing evidence	
Source basis	

Reviewer name	
Professional role	
License or registration	
Review date	

Rule 23 ARCH-RES-DAYLIGHT-005

نورگیری زیر ایوان

Risk	HIGH
Plain language rule	عمق نورگیری از لبه خارجی ایوان محسوب شود.
Classification	MANDATORY_NATIONAL
Enforcement consequence	BLOCK
Applicable conditions	Window below balcony/terrace projection
Required inputs	balcony_outer_edge, room_daylight_geometry
Authoritative source	مبحث چهارم، الزامات عمومی ساختمان
Edition	1396
Clause	4-5-2-8-4
Page	printed 55 PDF 69
Source text or precise summary	عمق نورگیری از لبه خارجی ایوان محسوب شود.
Exceptions	None recorded
Cross-code dependencies	balcony_outer_edge, room_daylight_geometry
Machine interpretation	<pre>{"review_predicate":{"inputs":["balcony_outer_edge","room_daylight_geometry"],"expected":true,"missing_input":"INPUT_REQUIRED","false_result":"FAIL","not_applicable_result":"NOT_APPLICABLE"}}</pre>
PASS example	Applicable project with complete authoritative inputs satisfying qualitative predicate
FAIL example	Applicable project with complete authoritative inputs violating qualitative predicate
Boundary example	Evaluate exact threshold and immediately below/above values where numeric; otherwise exact predicate boundary.
NOT_APPLICABLE example	Project/object does not satisfy: Window below balcony/terrace projection; result must be NOT_APPLICABLE, never PASS.
INPUT_REQUIRED behavior	If any material applicability or evaluation input is absent, return INPUT_REQUIRED. Required inputs: balcony_outer_edge, room_daylight_geometry.
Current unresolved interpretation	None beyond licensed professional confirmation of the prepared interpretation.
Proposed reviewer decision	No default. Reviewer must select one allowed decision.

Reviewer decision

☐ APPROVED ☐ APPROVED_WITH_CHANGE ☐ REJECTED ☐ NEEDS_MORE_EVIDENCE

Reviewer comments	
Requested change or missing evidence	

Source basis	
Reviewer name	
Professional role	
License or registration	
Review date	

Rule 24 ARCH-RES-DAYLIGHT-006

حیاط بین دو تصرف مسکونی

Risk	HIGH
Plain language rule	فاصله دیوارهای پنجره‌های مقابل حداقل ۶ متر.
Classification	MANDATORY_NATIONAL
Enforcement consequence	BLOCK
Applicable conditions	Land area >200m2; main habitable rooms of two independent units use same internal court
Required inputs	land_area_m2, shared_court, opposing_room_uses, window_wall_distance_m
Authoritative source	مبحث چهارم، الزامات عمومی ساختمان
Edition	1396
Clause	4-7-1-1-24
Page	printed 87 PDF 101
Source text or precise summary	فاصله دیوارهای پنجره‌های مقابل حداقل ۶ متر.
Exceptions	None recorded
Cross-code dependencies	land_area_m2, shared_court, opposing_room_uses, window_wall_distance_m
Machine interpretation	<pre>{"review_predicate":{"inputs":["land_area_m2","shared_court","opposing_room_uses","window_wall_distance_m"],"expected":true,"missing_input":"INPUT_REQUIRED","false_result":"FAIL","not_applicable_result":"NOT_APPLICABLE"}}</pre>
PASS example	Applicable project with complete authoritative inputs satisfying qualitative predicate
FAIL example	Applicable project with complete authoritative inputs violating qualitative predicate
Boundary example	Evaluate exact threshold and immediately below/above values where numeric; otherwise exact predicate boundary.
NOT_APPLICABLE example	Project/object does not satisfy: Land area >200m2; main habitable rooms of two independent units use same internal court; result must be NOT_APPLICABLE, never PASS.
INPUT_REQUIRED behavior	If any material applicability or evaluation input is absent, return INPUT_REQUIRED. Required inputs: land_area_m2, shared_court, opposing_room_uses, window_wall_distance_m.
Current unresolved interpretation	None beyond licensed professional confirmation of the prepared interpretation.
Proposed reviewer decision	No default. Reviewer must select one allowed decision.

Reviewer decision

☐ APPROVED ☐ APPROVED_WITH_CHANGE ☐ REJECTED ☐ NEEDS_MORE_EVIDENCE

Reviewer comments	
Requested change or missing evidence	
Source basis	
Reviewer name	
Professional role	
License or registration	
Review date	

Rule 25 ARCH-RES-DAYLIGHT-007

حیات مشترک آشپزخانه و اقامت

Risk	HIGH
Plain language rule	فاصله دیوارهای پنجره‌های مقابل حداقل ۴ متر.
Classification	MANDATORY_NATIONAL
Enforcement consequence	BLOCK
Applicable conditions	Independent units: kitchen/habitable or two kitchens use same internal court
Required inputs	shared_court, opposing_room_uses, window_wall_distance_m
Authoritative source	مبحث چهارم، الزامات عمومی ساختمان
Edition	1396
Clause	4-7-1-1-25
Page	printed 87 PDF 101
Source text or precise summary	فاصله دیوارهای پنجره‌های مقابل حداقل ۴ متر.
Exceptions	None recorded
Cross-code dependencies	shared_court, opposing_room_uses, window_wall_distance_m
Machine interpretation	<pre>{"review_predicate":{"inputs":["shared_court","opposing_room_uses","window_wall_distance_m"],"expected":true,"missing_input":"INPUT_REQUIRED","false_result":"FAIL","not_applicable_result":"NOT_APPLICABLE"}}</pre>
PASS example	Applicable project with complete authoritative inputs satisfying qualitative predicate
FAIL example	Applicable project with complete authoritative inputs violating qualitative predicate
Boundary example	Evaluate exact threshold and immediately below/above values where numeric; otherwise exact predicate boundary.
NOT_APPLICABLE example	Project/object does not satisfy: Independent units: kitchen/habitable or two kitchens use same internal court; result must be NOT_APPLICABLE, never PASS.
INPUT_REQUIRED behavior	If any material applicability or evaluation input is absent, return INPUT_REQUIRED. Required inputs: shared_court, opposing_room_uses, window_wall_distance_m.
Current unresolved interpretation	None beyond licensed professional confirmation of the prepared interpretation.
Proposed reviewer decision	No default. Reviewer must select one allowed decision.

Reviewer decision

☐ APPROVED ☐ APPROVED_WITH_CHANGE ☐ REJECTED ☐ NEEDS_MORE_EVIDENCE

Reviewer comments	
Requested change or missing evidence	
Source basis	
Reviewer name	
Professional role	
License or registration	
Review date	

Rule 26 ARCH-RES-VENTILATION-001

بازشوی تهویه آشپزخانه

Risk	HIGH
Plain language rule	حداقل سطح بازشوی تهویه یک شانزدهم مساحت کف آشپزخانه.
Classification	MANDATORY_NATIONAL
Enforcement consequence	BLOCK
Applicable conditions	Kitchen serving habitable rooms
Required inputs	kitchen_area_m2, vent_opening_area_m2
Authoritative source	مبحث چهارم، الزامات عمومی ساختمان
Edition	1396
Clause	4-7-1-1-15
Page	printed 86 PDF 100
Source text or precise summary	حداقل سطح بازشوی تهویه یک شانزدهم مساحت کف آشپزخانه.
Exceptions	None recorded
Cross-code dependencies	kitchen_area_m2, vent_opening_area_m2
Machine interpretation	<code>{"field": "vent_opening_area_m2", "op": ">=", "rhs_field": "kitchen_area_m2", "factor": 0.0625, "unit": "m2"}</code>
PASS example	Applicable project with complete authoritative inputs satisfying factor 0.0625
FAIL example	Applicable project with complete authoritative inputs violating factor 0.0625
Boundary example	Evaluate exact threshold and immediately below/above values where numeric; otherwise exact predicate boundary.
NOT_APPLICABLE example	Project/object does not satisfy: Kitchen serving habitable rooms; result must be NOT_APPLICABLE, never PASS.
INPUT_REQUIRED behavior	If any material applicability or evaluation input is absent, return INPUT_REQUIRED. Required inputs: kitchen_area_m2, vent_opening_area_m2.
Current unresolved interpretation	None beyond licensed professional confirmation of the prepared interpretation.
Proposed reviewer decision	No default. Reviewer must select one allowed decision.

Reviewer decision

☐ APPROVED ☐ APPROVED_WITH_CHANGE ☐ REJECTED ☐ NEEDS_MORE_EVIDENCE

Reviewer comments	
Requested change or missing evidence	

Source basis	
Reviewer name	
Professional role	
License or registration	
Review date	

Rule 27 ARCH-RES-VENTILATION-002

هود به هوای آزاد

Risk	HIGH
Plain language rule	هود با کانال مستقل مکش به خارج ساختمان مرتبط شود.
Classification	MANDATORY_NATIONAL
Enforcement consequence	BLOCK
Applicable conditions	Kitchen ventilation requires over-cooktop extraction
Required inputs	extract_required, hood_port, independent_exhaust_route
Authoritative source	مبحث چهارم، الزامات عمومی ساختمان
Edition	1396
Clause	4-5-5-3-3
Page	printed 59 PDF 73
Source text or precise summary	هود با کانال مستقل مکش به خارج ساختمان مرتبط شود.
Exceptions	None recorded
Cross-code dependencies	extract_required, hood_port, independent_exhaust_route
Machine interpretation	<pre>{"review_predicate":{"inputs":["extract_required","hood_port","independent_exhaust_route"],"expected":true,"missing_input":"INPUT_REQUIRED","false_result":"FAIL","not_applicable_result":"NOT_APPLICABLE"}}</pre>
PASS example	Applicable project with complete authoritative inputs satisfying qualitative predicate
FAIL example	Applicable project with complete authoritative inputs violating qualitative predicate
Boundary example	Evaluate exact threshold and immediately below/above values where numeric; otherwise exact predicate boundary.
NOT_APPLICABLE example	Project/object does not satisfy: Kitchen ventilation requires over-cooktop extraction; result must be NOT_APPLICABLE, never PASS.
INPUT_REQUIRED behavior	If any material applicability or evaluation input is absent, return INPUT_REQUIRED. Required inputs: extract_required, hood_port, independent_exhaust_route.
Current unresolved interpretation	None beyond licensed professional confirmation of the prepared interpretation.
Proposed reviewer decision	No default. Reviewer must select one allowed decision.

Reviewer decision

☐ APPROVED ☐ APPROVED_WITH_CHANGE ☐ REJECTED ☐ NEEDS_MORE_EVIDENCE

Reviewer comments	
Requested change or missing evidence	
Source basis	
Reviewer name	
Professional role	
License or registration	
Review date	

Rule 28 ARCH-RES-BALCONY-001

فضای نیمه‌باز اختصاصی

Risk	MEDIUM
Plain language rule	حداقل یک فضای نیمه‌باز اختصاصی مطابق ۷-۵-۴ لازم است؛ اندازه بدون منبع فرض نشود.
Classification	MANDATORY_NATIONAL
Enforcement consequence	BLOCK
Applicable conditions	Apartment/unit without direct adjacency and access to open space
Required inputs	direct_open_space_access, private_semiopen_space, m4_5_7_result
Authoritative source	مبحث چهارم، الزامات عمومی ساختمان
Edition	1396
Clause	4-7-1-1-22
Page	printed 87 PDF 101
Source text or precise summary	حداقل یک فضای نیمه‌باز اختصاصی مطابق ۷-۵-۴ لازم است؛ اندازه بدون منبع فرض نشود.
Exceptions	None recorded
Cross-code dependencies	direct_open_space_access, private_semiopen_space, m4_5_7_result
Machine interpretation	<pre>{"review_predicate":{"inputs":["direct_open_space_access","private_semiopen_space","m4_5_7_result"],"expected":true,"missing_input":"INPUT_REQUIRED","false_result":"FAIL","not_applicable_result":"NOT_APPLICABLE"}}</pre>
PASS example	Applicable project with complete authoritative inputs satisfying qualitative predicate
FAIL example	Applicable project with complete authoritative inputs violating qualitative predicate
Boundary example	Evaluate exact threshold and immediately below/above values where numeric; otherwise exact predicate boundary.
NOT_APPLICABLE example	Project/object does not satisfy: Apartment/unit without direct adjacency and access to open space; result must be NOT_APPLICABLE, never PASS.
INPUT_REQUIRED behavior	If any material applicability or evaluation input is absent, return INPUT_REQUIRED. Required inputs: direct_open_space_access, private_semiopen_space, m4_5_7_result.
Current unresolved interpretation	None beyond licensed professional confirmation of the prepared interpretation.
Proposed reviewer decision	No default. Reviewer must select one allowed decision.

Reviewer decision

☐ APPROVED ☐ APPROVED_WITH_CHANGE ☐ REJECTED ☐ NEEDS_MORE_EVIDENCE

Reviewer comments	
Requested change or missing evidence	
Source basis	
Reviewer name	
Professional role	
License or registration	
Review date	

Rule 29 ARCH-RES-PRIVACY-001

دسترسی مستقل اتاق‌ها

Risk	MEDIUM
Plain language rule	دسترسی اتاق اقامت مستقیماً از اتاق دیگر یا نشیمن عمومی نباشد مگر استثنای صریح همین بند؛ دید مستقیم از نشیمن عمومی به خواب در هر حال مجاز نیست.
Classification	MANDATORY_NATIONAL
Enforcement consequence	BLOCK
Applicable conditions	Residential habitable rooms; apply listed exceptions a-1,a-2,a-3
Required inputs	access_graph, unit_area_m2, habitable_count, entry_buffer, sightlines
Authoritative source	مبحث چهارم، الزامات عمومی ساختمان
Edition	1396
Clause	4-7-1-1-2.a
Page	printed 84 PDF 98
Source text or precise summary	دسترسی اتاق اقامت مستقیماً از اتاق دیگر یا نشیمن عمومی نباشد مگر استثنای صریح همین بند؛ دید مستقیم از نشیمن عمومی به خواب در هر حال مجاز نیست.
Exceptions	None recorded
Cross-code dependencies	access_graph, unit_area_m2, habitable_count, entry_buffer, sightlines
Machine interpretation	<pre>{"review_predicate":{"inputs":["access_graph","unit_area_m2","habitable_count","entry_buffer","sightlines"],"expected":true,"missing_input":"INPUT_REQUIRED","false_result":"FAIL","not_applicable_result":"NOT_APPLICABLE"}}</pre>
PASS example	Applicable project with complete authoritative inputs satisfying qualitative predicate
FAIL example	Applicable project with complete authoritative inputs violating qualitative predicate
Boundary example	Evaluate exact threshold and immediately below/above values where numeric; otherwise exact predicate boundary.
NOT_APPLICABLE example	Project/object does not satisfy: Residential habitable rooms; apply listed exceptions a-1,a-2,a-3; result must be NOT_APPLICABLE, never PASS.
INPUT_REQUIRED behavior	If any material applicability or evaluation input is absent, return INPUT_REQUIRED. Required inputs: access_graph, unit_area_m2, habitable_count, entry_buffer, sightlines.
Current unresolved interpretation	None beyond licensed professional confirmation of the

	prepared interpretation.
Proposed reviewer decision	No default. Reviewer must select one allowed decision.

Reviewer decision

☐ APPROVED ☐ APPROVED_WITH_CHANGE ☐ REJECTED ☐ NEEDS_MORE_EVIDENCE

Reviewer comments	
Requested change or missing evidence	
Source basis	
Reviewer name	
Professional role	
License or registration	
Review date	

Rule 30 ARCH-RES-PRIVACY-002

دید به سرویس بهداشتی

Risk	MEDIUM
Plain language rule	دید به داخل سرویس ممنوع؛ پیش‌ورودی دارای روشویی فقط با حفظ حرکت و دسترسی به سایر تجهیزات مجاز است.
Classification	MANDATORY_NATIONAL
Enforcement consequence	BLOCK
Applicable conditions	Combined sanitary facility visible from living/hall
Required inputs	sanitary_sightlines, ante_room, fixture_access
Authoritative source	مبحث چهارم، الزامات عمومی ساختمان
Edition	1396
Clause	4-7-1-1-2.p
Page	printed 84 PDF 98
Source text or precise summary	دید به داخل سرویس ممنوع؛ پیش‌ورودی دارای روشویی فقط با حفظ حرکت و دسترسی به سایر تجهیزات مجاز است.
Exceptions	None recorded
Cross-code dependencies	sanitary_sightlines, ante_room, fixture_access
Machine interpretation	<pre>{"review_predicate":{"inputs":["sanitary_sightlines","ante_room","fixture_access"],"expected":true,"missing_input":"INPUT_REQUIRED","false_result":"FAIL","not_applicable_result":"NOT_APPLICABLE"}}</pre>
PASS example	Applicable project with complete authoritative inputs satisfying qualitative predicate
FAIL example	Applicable project with complete authoritative inputs violating qualitative predicate
Boundary example	Evaluate exact threshold and immediately below/above values where numeric; otherwise exact predicate boundary.
NOT_APPLICABLE example	Project/object does not satisfy: Combined sanitary facility visible from living/hall; result must be NOT_APPLICABLE, never PASS.
INPUT_REQUIRED behavior	If any material applicability or evaluation input is absent, return INPUT_REQUIRED. Required inputs: sanitary_sightlines, ante_room, fixture_access.
Current unresolved interpretation	None beyond licensed professional confirmation of the prepared interpretation.
Proposed reviewer decision	No default. Reviewer must select one allowed decision.

Reviewer decision

☐ APPROVED ☐ APPROVED_WITH_CHANGE ☐ REJECTED ☐ NEEDS_MORE_EVIDENCE

Planha Architecture Rulebook Review | Decisions blank until licensed review

Reviewer comments	
Requested change or missing evidence	
Source basis	
Reviewer name	
Professional role	
License or registration	
Review date	

Rule 31 ARCH-RES-PRIVACY-003

دید به محل کار آشپزخانه

Risk	MEDIUM
Plain language rule	از نشیمن عمومی یا سالن دید مستقیم به قسمت‌های اصلی پخت‌وپز و کار آشپزخانه نباشد.
Classification	MANDATORY_NATIONAL
Enforcement consequence	BLOCK
Applicable conditions	Residential unit area $\geq 75m^2$, wall/open kitchen
Required inputs	unit_area_m2, kitchen_type, living_kitchen_sightlines
Authoritative source	مبحث چهارم، الزامات عمومی ساختمان
Edition	1396
Clause	4-7-1-1-2.th
Page	printed 84 PDF 98
Source text or precise summary	از نشیمن عمومی یا سالن دید مستقیم به قسمت‌های اصلی پخت‌وپز و کار آشپزخانه نباشد.
Exceptions	None recorded
Cross-code dependencies	unit_area_m2, kitchen_type, living_kitchen_sightlines
Machine interpretation	<pre>{"review_predicate":{"inputs":["unit_area_m2","kitchen_type","living_kitchen_sightlines"],"expected":true,"missing_input":"INPUT_REQUIRED","false_result":"FAIL","not_applicable_result":"NOT_APPLICABLE"}}</pre>
PASS example	Applicable project with complete authoritative inputs satisfying qualitative predicate
FAIL example	Applicable project with complete authoritative inputs violating qualitative predicate
Boundary example	Evaluate exact threshold and immediately below/above values where numeric; otherwise exact predicate boundary.
NOT_APPLICABLE example	Project/object does not satisfy: Residential unit area $\geq 75m^2$, wall/open kitchen; result must be NOT_APPLICABLE, never PASS.
INPUT_REQUIRED behavior	If any material applicability or evaluation input is absent, return INPUT_REQUIRED. Required inputs: unit_area_m2, kitchen_type, living_kitchen_sightlines.
Current unresolved interpretation	None beyond licensed professional confirmation of the prepared interpretation.
Proposed reviewer decision	No default. Reviewer must select one allowed decision.

Reviewer decision

☐ APPROVED ☐ APPROVED_WITH_CHANGE ☐ REJECTED ☐ NEEDS_MORE_EVIDENCE

Reviewer comments	
Requested change or missing evidence	
Source basis	
Reviewer name	
Professional role	
License or registration	
Review date	

Rule 32 ARCH-RES-ACCESSIBILITY-001

فضای بهداشتی قابل استفاده معلول

Risk	CRITICAL
Plain language rule	در هر واحد مسکونی قابل دسترس، حداقل یک فضای بهداشتی باید هم‌زمان با بند ۳-۲-۳-۸ ضابطه ۲۴۶، ارجاع آن به ۳-۱-۱-۱۲ و حداقل ۱۷۰ × ۱۵۰ متر مبحث چهارم منطبق باشد.
Classification	MANDATORY_NATIONAL
Enforcement consequence	BLOCK
Applicable conditions	building_use == RESIDENTIAL AND accessible_residential_unit == true
Required inputs	building_use, units_per_floor, floor_count, total_residential_units, fully_government_funded, local_elevator_requirement, accessible_residential_unit, accessible_sanitary_space_count, sanitary_dimensions_m, accessible_route_result
Authoritative source	مبحث چهارم، الزامات عمومی ساختمان
Edition	1396
Clause	4-5-6-2-2
Page	printed 61 PDF 75
Source text or precise summary	Code 246 defines a residential complex as more than four units on one floor or more than eight units across multiple floors; 3-2-2-1 requires at least five percent accessible units and at least one in fully government-funded complexes under 20 units; 3-2-3-8 requires one sanitary space conforming to 3-1-1-12.
Exceptions	Five-percent integer conversion is not stated in the inspected Code 246 text and remains HUMAN_INTERPRETATION_REQUIRED.; The under-20 minimum-one-unit branch applies only to fully government-funded residential complexes.; Local elevator triggers are never inferred from floor count.
Cross-code dependencies	IR-ACCESS, IR-M4, IR-M3_ACCESSIBLE_EGRESS_WHEN_APPLICABLE
Machine interpretation	<pre> {"applicability": {"building_use":"RESIDENTIAL","accessible_residential_u nit":true,"missing_input":"INPUT_REQUIRED","false_result ":"NOT_APPLICABLE"},"residential_complex":{"any": ["units_per_floor > 4","floor_count > 1 AND total_residential_units > 8"],"source":"Code 246 Chapter 1 definition","source_page": {"printed":7,"pdf":25},"missing_input":"INPUT_REQUIRED "},"accessible_unit_requirement": {"private_or_general_complex": {"calculation_raw":"total_residential_units * 0.05","integer_conversion":"HUMAN_INTERPRETATION_R EQUIRED"},"fully_government_funded_under_20": {"when":"fully_government_funded == true AND total_residential_units < 20","minimum_accessible_units":1},"source_clause":"3- 2-2-1","source_page": </pre>

	<pre> {"printed":91,"pdf":109}}, "common_area_scope": {"local_elevator_required": {"when": "local_elevator_requirement == true", "result": "elevator_and_common_areas_accessible"} , "below_local_elevator_trigger": {"when": "local_elevator_requirement == false", "result": "ground_floor_and_common_areas_accessible"}, "unknown_local_elevator_requirement": "LOCAL_RULE_REQUIRED", "source_clauses": ["3-2-2-2", "3-2-2-3"], "source_page": {"printed":92,"pdf":110}}, "accessible_unit_dependencies": { "clauses": ["3-2-3-1", "3-2-3-2", "3-2-3-3", "3-2-3-4", "3-2-3-5", "3-2-3-6", "3-2-3-7", "3-2-3-8", "3-2-3-9"], "shared_rules": ["code246_entry", "code246_corridor", "code246_stair", "code246_ramp", "code246_elevator", "code246_openings", "code246_handrails", "code246_sanitary", "code246_controls"]}, "sanitary_check": {"minimum_count":1, "m4_minimum_dimensions_m": [1.5, 1.7], "requires_code246_clause": "3-2-3-8 -> 3-1-1-12", "missing_input": "INPUT_REQUIRED", "false_result": "FAIL"}, "parking_scope": {"accessible_unit_minimum_spaces":1, "source_clause": "3-2-3-1", "source_page": {"printed":93,"pdf":111}}, "public_parking_rule": "2-1-5-2", "local_general_parking_count": "LOCAL_RULE_REQUIRED", "result_logic": {"all_applicable_requirements_must_pass":true, "missing_input": "INPUT_REQUIRED", "false_result": "FAIL", "not_applicable_result": "NOT_APPLICABLE"}} </pre>
PASS example	An independently classified accessible residential unit contains at least one sanitary space meeting M4 dimensions and Code 246 clause 3-1-1-12.
FAIL example	An applicable accessible unit lacks a compliant sanitary space or route.
Boundary example	4 units on one floor is not a residential complex; 5 is. Eight units across multiple floors is not; 9 is. Five-percent integer conversion remains a bounded interpretation question.
NOT_APPLICABLE example	Project/object does not satisfy: Accessible residential unit sanitary space: applies only after Code 246 residential-complex/accessibility classification or an authoritative project requirement establishes an accessible unit.; result must be NOT_APPLICABLE, never PASS.
INPUT_REQUIRED behavior	If any material applicability or evaluation input is absent, return INPUT_REQUIRED. Required inputs: building_use, units_per_floor, floor_count, total_residential_units, fully_government_funded, local_elevator_requirement, accessible_residential_unit, accessible_sanitary_space_count, sanitary_dimensions_m, accessible_route_result.
Current unresolved interpretation	Code 246 five-percent integer conversion requires licensed interpretation.
Proposed reviewer decision	No default. Reviewer must select one allowed decision.

Reviewer decision

☐ APPROVED
 ☐ APPROVED_WITH_CHANGE
 ☐ REJECTED
 ☐ NEEDS_MORE_EVIDENCE

Reviewer comments	
--------------------------	--

Requested change or missing evidence	
Source basis	
Reviewer name	
Professional role	
License or registration	
Review date	