## **Java MCQ Questions - 8**

| 1. Using which keyword we can access value of the instance variables and <u>class variables</u> of that class inside the method of that class itself. |
|---|
| A) super  |
| B) final  |
| C) this   |
| D) either super or this   |
| 2. If a variable is declared final, it must include value.  |
| A) integer  |
| B) no   |
| C) initial  |
| D) float  |
| 3. State true or false.   |
| i) Jpanel is a class included in awt package.   |
| ii) Anonymous classes are mostly used for event handling.   |
| iii) Names of anonymous classes must be unique  |
| iv) JOptionPane is an inner class   |
| A) i-false, ii-false, iii-true, iv-true   |
| B) i-true, ii-false, iii-true, iv-false   |
| C) i-false, ii-true, iii-false, iv-false  |
| D) i-true, ii-false, iii-false, iv-true   |

| 4. In java, string is a   |
|---|
| A) primitive data type  |
| B) abstract data type   |
| C) combination of boolean   |
| D) None of the above  |
| 5. Methods can be overloaded with a difference only in the type of the return value                                 |
| A) Not supported  |
| B) False  |
| C) True   |
| D) None of the above  |
| <ul><li>6. Each method in a java class must have a unique name .</li><li>A) Not necessary</li><li>B) True</li></ul> |
| C) False  |
| D) None of the above  |
| 7. State true or false.   |
| i) comparisons precede logical operations in java   |
| ii) assignment operations succeed increment operations  |
| iii) arithmetic operations succeed comparisons  |
| iv) x precede +   |
| A) i-true, ii-true, iii-false, iv-true  |

## www.cullenboyytech.wordpress.com

| B) i-true, ii-false, iii-true, iv-false  |
|--|
| C) i-false, ii-true, iii-false, iv-false   |
| D) i-true, ii-false, iii-false, iv-true  |
| 8. It is important feature of java that it always provides a default constructor to a class. |
| A) Not supported   |
| B) False   |
| C) True  |
| D) None of the above   |
| 9 is the key to  |
| A) Serialization, persistence  |
| B) Persistence, inheritance  |
| C) Inheritance, object   |
| D) Persistence, serialization  |
| 10. State true of false.   |
| i) Public can only be assigned to class  |
| ii) Protected protects a statement   |
| iii) Protected method is never accessible outside the package                                |
| iv) Friendly variable may be accessible outside class  |
| A) i-true, ii-true, iii-false, iv-true   |
| B) i-true, ii-false, iii-true, iv-false  |
| C) i-false, ii-true, iii-false, iv-false   |

D) i-true, ii-false, iii-false, iv-true

## **Answers:**

- 1. C) this
- 2. C) initial
- 3. C) i-false, ii-true, iii-false, iv-false
- 4. B) abstract data type
- 5. B) False
- 6. A) Not necessary
- 7. A) i-true, ii-true, iii-false, iv-true
- 8. C) True
- 9. A) Serialization, persistence
- 10.C) i-false, ii-true, iii-false, iv-false

