

Outdoor Shading Design

Building Performance Simulation

Guide :
Mostapha Sadeghipour Roudsari

Submitted by :
Mansi Dhanuka



Meyerson Hall
University of Pennsylvania
Philadelphia
39°57'N 75°10'W
Weather Station : Philadelphia International Airport
Data Source : TMY3




Design of Shading for Outdoor Seating

2


1

3


Plan




Thermal Stress Period



Condition :
Fully Shaded
Percent of Time Comfortable :
41.28%




Condition :
Exposed to Solar Radiation
Percent of Time Comfortable :
37.34%




Bench 1
Condition :
With Context

Percent of Time Comfortable :
40.39%



Bench 2
Condition :
With Context


Percent of Time Comfortable :
40.57%




Bench 3
Condition :
With Context


Percent of Time Comfortable :
38.03%

Optimized Shading Zone






Bench 1
Condition :
With Context & Optimized Shading
Percent of Time Comfortable :
42.23%





Bench 2
Condition :
With Context & Optimized Shading
Percent of Time Comfortable :
41.89%




Bench 3
Condition :
With Context & Optimized Shading
Percent of Time Comfortable :
40.42%

Shading Device Design






Bench 1
Condition :
With Context & Shading Device
Percent of Time Comfortable :
42.05%



Bench 2
Condition :
With Context & Shading Device
Percent of Time Comfortable :
41.93%



Bench 3
Condition :
With Context & Shading Device
Percent of Time Comfortable :
41.37%