Assignment 1

Keaton Kane

1 September 2017


ARCH 633

DRY BULB X DEW POINT
ASHRAE Standard 55-2004 using PMV

LOCATION: Philadelphia International Ap, PA, USA

Latitude/Longitude: 39.87° North, 75.23° West, Time Zone from Greenwich -5

Data Source: TMY3 724080 WMO Station Number, Elevation 6 ft



DRY BULB X RELATIVE HUMIDITY ASHRAE Standard 55-2004 using PMV


LOCATION: Philadelphia International Ap, PA, USA

Latitude/Longitude: 39.87° North, 75.23° West, Time Zone from Greenwich -5

724080 WMO Station Number, Elevation 6 ft



Dry Bulb Humidity Comfort Zone Summer Winter At 50% Relative Humidity



GROUND TEMPERATURE (MONTHLY AVERAGE)


LOCATION:

Data Source:

Philadelphia International Ap, PA, USA

Latitude/Longitude: 39.87° North, 75.23° West, Time Zone from Greenwich -5 TMY3 724080 WMO Station Number, Elevation 6 ft


LEGEND



TEMPERATURE RANGE:

● 10 to 110 °F

Fit to Data



ILLUMINATION RANGE


LOCATION:


Philadelphia International Ap, PA, USA

Latitude/Longitude: 39.87° North, 75.23° West, Time Zone from Greenwich -5 TMY3 724080 WMO Station Number, Elevation 6 ft

Data Source:







MONTHLY DIURNAL AVERAGES ASHRAE Standard 55-2004 using PMV

LOCATION: Philadelphia International Ap, PA, USA

Latitude/Longitude: 39.87° North, 75.23° West, Time Zone from Greenwich -5

TMY3 724080 WMO Station Number, Elevation 6 ft



HOURLY AVERAGES

TEMPERATURE: (degrees F)

DRY BULB MEAN

WET BULB MEAN

DRY BULB (all hours)

COMFORT ZONE

SUMMER WINTER

(At 50% Relative Humidity)

RADIATION: (Btu/sq.ft)
GLOBAL HORIZ
DIRECT NORMAL


DIFFUSE

Display Dry Bulb Temp
(all hours)

TEMPERATURE RANGE:

● 10 to 110 °F

Fit to Data




Data Source:


PSYCHROMETRIC CHART ASHRAE Standard 55-2004 using PMV

LOCATION: Philadelphia International Ap, PA, USA

Latitude/Longitude: 39.87° North, 75.23° West, Time Zone from Greenwich -5

Data Source: TMY3 724080 WMO Station Number, Elevation 6 ft





RADIATION RANGE

LOCATION:


Philadelphia International Ap, PA, USA

Latitude/Longitude: 39.87° North, 75.23° West, Time Zone from Greenwich -5 724080 WMO Station Number, Elevation 6 ft

Data Source:




HOURLY AVERAGES DAYLIT HOURS ONLY












Tilted Surface Radiation Input:

- 0.0 Tilt degrees from ... (Vertical = 90°)
- 0.0 Bearing degrees fr...
 - (South = 0°, West ...
- 20.0 % Ground Reflecta... (20% = grass)

PLOT:

Hourly Avg Daily Total




SKY COVER RANGE


LOCATION:

Philadelphia International Ap, PA, USA

Latitude/Longitude: 39.87° North, 75.23° West, Time Zone from Greenwich -5 TMY3 724080 WMO Station Number, Elevation 6 ft

Data Source:





SUN CHART

LOCATION:

Philadelphia International Ap, PA, USA

Latitude/Longitude: 39.87° North, 75.23° West, Time Zone from Greenwich -5

Data Source: TMY3 724080 WMO Station Number, Elevation 6 ft

LEGEND

• WARM/HOT > 80°F (SHADE NEEDED)

COMFORT > 68°F(SHADE HELPS)


COOL/COLD < 68°F
 (SUN NEEDED)

■ GNOMON POSITION

PLOT MONTHS:
WINTER SPRING

December 21 to June 21
SUMMER FALL

O June 21 to December 21



SUN SHADING CHART

LOCATION:

Philadelphia International Ap, PA, USA

Latitude/Longitude: 39.87° North, 75.23° West, Time Zone from Greenwich -5

Data Source: TMY3 724080 WMO Station Number, Elevation 6 ft

LEGEND

WARM/HOT > 80°F

(SHADE NEEDED) 163 Hours Exposed 0 Hours Shaded

COMFORT > 68°F

(SHADE HELPS) 433 Hours Exposed 0 Hours Shaded

COOL/COLD < 68°F

(SUN NEEDED) 1914 Hours Exposed 0 Hours Shaded

PLOT MONTHS:

WINTER SPRING

December 21 to June 21

SUMMER FALL


O June 21 to December 21

Display Grid

Display Shading Calculator

Display Obstruction Elevation

Input Obstructions




TEMPERATURE RANGE ASHRAE Standard 55-2004 using PMV

LOCATION:

Data Source:

Philadelphia International Ap, PA, USA Latitude/Longitude: 39.87° North, 75.23° West, Time Zone from Greenwich -5


724080 WMO Station Number, Elevation 6 ft



COMFORT ZONE SUMMER WINTER (At 50% Relative Humidity)

DESIGN HIGH: Residential 1% of Hours Above .5% of Hours Above 0% of Hours Above DESIGN LOW: Residential 1% of Hours Below .5% of Hours Below 0% of Hours Below TEMPERATURE RANGE: ● 10 to 110 °F

Fit to Data



TIMETABLE PLOT

LOCATION:


Philadelphia International Ap, PA, USA

Latitude/Longitude: 39.87° North, 75.23° West, Time Zone from Greenwich -5 TMY3 724080 WMO Station Number, Elevation 6 ft

Data Source:

LEGEND

DRY BULB TEMP




- 81

- 100

> 100





WIND VELOCITY RANGE

LOCATION:

Philadelphia International Ap, PA, USA

Latitude/Longitude: 39.87° North, 75.23° West, Time Zone from Greenwich -5 TMY3 724080 WMO Station Number, Elevation 6 ft

Data Source:

LEGEND

RECORDED HIGH -**AVERAGE HIGH -**MEAN -**AVERAGE LOW-**RECORDED LOW -(mph)

PLOT:


mph

WIND VELOCITY:

O fpm

① 0 to 60 mph

Fit to Data



WIND WHEEL


LOCATION:


Data Source:

Philadelphia International Ap, PA, USA

Latitude/Longitude: 39.87° North, 75.23° West, Time Zone from Greenwich -5

TMY3 724080 WMO Station Number, Elevation 6 ft





Conclusions:

- 1) According to the Sun Chart, buildings should face South in order to gain the necessary levels of heat gain from the sun, especially during the winter months when heat gain is at a minimum. During the summer months when heat gain is much higher, moveable shades should be employed to reduce direct sun exposure.
- 2) As per the Wind Velocity chart, average wind speeds in Philadelphia are too high (avg. 8-12 mph) to allow for a comfortable natural ventilation. As such, incoming wind must be tempered to comfortably ventilate the interior of the building.
- 3) The humidity in Philadelphia is relatively high year-round (50-90%) according to the Relative Humidity Chart and as such buildings must be designed to deter water from accumulating and causing your structure to become a "sick building." A design priority must be ensuring that the façade is designed to expel water from its surface. Additionally, adequate air flow must be allowed inside in order to prevent excessive humidity and condensation.