

## **Problem-02: UVA 558 - Wormholes (Online Judge)**

[https://onlinejudge.org/index.php?option=com\\_onlinejudge&Itemid=8&page=show\\_problem&problem=1390](https://onlinejudge.org/index.php?option=com_onlinejudge&Itemid=8&page=show_problem&problem=1390)

### **Problem Description**

This problem focuses on detecting negative weight cycles in a graph.

In the story context, wormholes allow time travel by reducing time (negative time cost).

We must determine whether time travel is possible or not.

You are given:

N cities

M two-way roads

W wormholes (one-way time tunnels)

### **Goal**

Check whether the graph contains a negative weight cycle, which would indicate that using wormholes, it is possible to travel back in time indefinitely.

### **Graph Details**

1. Nodes = cities 1 to N
2. Normal roads:
  - Undirected (two-way)
  - Have positive weight
3. Wormholes:
  - Directed (one-way)
  - Have negative weight (they reduce time)
4. The graph is a combination of:
  - Positive edges (roads)
  - Negative edges (wormholes)

### **Objective**

Determine if any negative weight cycle exists in the graph.

If yes → Time travel is possible

If not → Time travel is impossible

### **Why Use Bellman–Ford?**

Bellman-Ford is ideal because:

### **Handles Negative Weights**

Dijkstra fails whenever there is a negative-weight edge.

Bellman-Ford works properly with both positive and negative edge weights.

### **Detects Negative Cycles**

By relaxing edges N times, if any edge can still be relaxed on the Nth iteration:

- A negative cycle exists
- Time travel is possible (the traveler can loop indefinitely and reduce time endlessly)

### Well-suited for UVA Constraints

With  $\leq 500$  nodes and limited edges, Bellman-Ford runs efficiently and reliably for this problem.

### Features of the Solution

1. Correctly handles negative weights from wormholes
2. Detects whether a negative cycle exists anywhere in the graph
3. Works efficiently for the typical UVA input sizes
4. Supports mixed graphs:
  - Positive weighted roads
  - Negative weighted wormholes
  - Directed + undirected edges combined
5. Simple and robust approach to determine time travel feasibility

### Pseudocode:

```
FUNCTION bellman_ford(edges, N, start):  
  
    DEFINE dist[1..N] = INFINITY  
    dist[start] = 0  
  
    FOR i = 1 TO N - 1:  
        FOR each edge (u, v, w) in edges:  
            IF dist[u] + w < dist[v]:  
                dist[v] = dist[u] + w  
  
    FOR each edge (u, v, w) in edges:  
        IF dist[u] + w < dist[v]:  
            RETURN True  
  
    RETURN False
```