ALPHA & OMEGA SEMICONDUCTOR

AO4407A

30V P-Channel MOSFET

General Description

The AO4407A uses advanced trench technology to provide excellent $R_{DS(ON)}$, and ultra-low low gate charge with a 25V gate rating. This device is suitable for use as a load switch or in PWM applications.

* RoHS and Halogen-Free Complaint

Product Summary

V_{DS} = -30V
I_D = -12A (V_{GS} = -20V)
$R_{DS(ON)}$ < 11mΩ (V_{GS} = -20V)
$R_{DS(ON)}$ < 13mΩ (V_{GS} = -10V)
$R_{DS(ON)}$ < 17mΩ (V_{GS} = -6V)

100% UIS Tested
100% Rg Tested

Green Product

SOIC-8

Top View **Bottom View**





Absolute Maximum Ratings T_A=25°C unless otherwise noted

Parameter		Symbol	Maximum	Units
Drain-Source Voltage		V_{DS}	-30	V
Gate-Source Voltage		V_{GS}	±25	V
Continuous Drain Current [A]	T_A=25°C	I_D	-12	A
	T_A=70°C		-10	
Pulsed Drain Current [B]		I_{DM}	-60	
Avalanche Current [G]		I_{AR}	-26	
Repetitive avalanche energy L=0.3mH [G]		E_{AR}	101	mJ
Power Dissipation [A]	T_A=25°C	P_D	3.1	W
	T_A=70°C		2.0	
Junction and Storage Temperature Range		T_J, T_{STG}	-55 to 150	°C

Thermal Characteristics

Parameter		Symbol	Typ	Max	Units
Maximum Junction-to-Ambient [A]	t ≤ 10s	$R_{\theta JA}$	32	40	°C/W
Maximum Junction-to-Ambient [A]	Steady State		60	75	°C/W
Maximum Junction-to-Lead [C]	Steady State	$R_{\theta JL}$	17	24	°C/W

Electrical Characteristics (T_J=25°C unless otherwise noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Units
STATIC PARAMETERS						
BV_{DSS}	Drain-Source Breakdown Voltage	I_D = -250µA, V_{GS} = 0V	-30			V
I_{DSS}	Zero Gate Voltage Drain Current	V_{DS} = -30V, V_{GS} = 0V			-1	µA
		T_J = 55°C			-5	
I_{GSS}	Gate-Body leakage current	V_{DS} = 0V, V_{GS} = ±25V			±100	nA
$V_{GS(th)}$	Gate Threshold Voltage	V_{DS} = V_{GS} I_D = -250µA	-1.7	-2.3	-3	V
$I_{D(ON)}$	On state drain current	V_{GS} = -10V, V_{DS} = -5V	-60			A
$R_{DS(ON)}$	Static Drain-Source On-Resistance	V_{GS} = -20V, I_D = -12A		8.5	11	mΩ
		T_J=125°C		11.5	15	
		V_{GS} = -10V, I_D = -12A		10	13	
		V_{GS} = -6V, I_D = -10A		12.7	17	
g_{FS}	Forward Transconductance	V_{DS} = -5V, I_D = -10A		21		S
V_{SD}	Diode Forward Voltage	I_S = -1A,V_{GS} = 0V		-0.7	-1	V
I_S	Maximum Body-Diode Continuous Current				-3	A
DYNAMIC PARAMETERS						
C_{iss}	Input Capacitance	V_{GS}=0V, V_{DS}=-15V, f=1MHz		2060	2600	pF
C_{oss}	Output Capacitance			370		pF
C_{rss}	Reverse Transfer Capacitance			295		pF
R_g	Gate resistance	V_{GS}=0V, V_{DS}=0V, f=1MHz		2.4	3.6	Ω
SWITCHING PARAMETERS						
Q_g	Total Gate Charge	V_{GS}=-10V, V_{DS}=-15V, I_D=-12A		30	39	nC
Q_{gs}	Gate Source Charge			4.6		nC
Q_{gd}	Gate Drain Charge			10		nC
$t_{D(on)}$	Turn-On DelayTime	V_{GS}=-10V, V_{DS}=-15V, R_L=1.25Ω, R_{GEN}=3Ω		11		ns
t_r	Turn-On Rise Time			9.4		ns
$t_{D(off)}$	Turn-Off DelayTime			24		ns
t_f	Turn-Off Fall Time			12		ns
t_{rr}	Body Diode Reverse Recovery Time	I_F=-12A, dI/dt=100A/µs		30	40	ns
Q_{rr}	Body Diode Reverse Recovery Charge	I_F=-12A, dI/dt=100A/µs		22		nC

A: The value of $R_{\theta JA}$ is measured with the device mounted on 1 in ^{2} FR-4 board with 2oz. Copper, in a still air environment with T_A = 25° C. The value in any given application depends on the user's specific board design. The current rating is based on the t ≤ 10s thermal resistance rating.
B: Repetitive rating, pulse width limited by junction temperature.
C. The $R_{\theta JA}$ is the sum of the thermal impedence from junction to lead $R_{\theta JL}$ and lead to ambient.
D. The static characteristics in Figures 1 to 6 are obtained using < 300µs pulses, duty cycle 0.5% max.
E. These tests are performed with the device mounted on 1 in ^{2} FR-4 board with 2oz. Copper, in a still air environment with T_A=25° C. The SOA curve provides a single pulse rating.
F. The current rating is based on the t ≤ 10s thermal resistance rating.
G. E_{AR} and I_{AR} ratings are based on low frequency and duty cycles to keep T_j=25C.

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS



Figure 1: On-Region Characteristics



Figure 2: Transfer Characteristics



Figure 3: On-Resistance vs. Drain Current and Gate Voltage



Figure 4: On-Resistance vs. Junction Temperature



Figure 5: On-Resistance vs. Gate-Source Voltage



Figure 6: Body-Diode Characteristics

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS



Figure 7: Gate-Charge Characteristics



Figure 8: Capacitance Characteristics



Figure 9: Maximum Forward Biased Safe Operating Area (Note E)



Figure 10: Single Pulse Power Rating Junction-to-Ambient (Note E)



Figure 11: Normalized Maximum Transient Thermal Impedance(Note E)

Gate Charge Test Circuit & Waveform





Resistive Switching Test Circuit & Waveforms





Unclamped Inductive Switching (UIS) Test Circuit & Waveforms





Diode Recovery Test Circuit & Waveforms