EXAMPLES



Documentation

Get Started

D Download

- D Build
- Releases
- Release Names
- D REPL

Learn

- Quick Start
- Headless Testing
- Screen Capture
- Network Monitoring
- D Page Automation
- D Inter Process Communicati
- D Command Line Interface

Get Help

- Troubleshooting
- D FAQ

Explore

- <u>Examples</u>
- Best Practices
- Tips and Tricks Supported Web Standards
- D Buzz Who's using PhantomJS?
- Related Projects

Contribute

- Contributing
- D Source Code
- D Test Suite
- Release Preparation
- Crash Reporting

Download

Note There is no need to ask when a binary package for a given platform will be ready. The packagers are fully aware of every release and they give their best effort to make the binaries available.

Windows

Download <u>phantomjs-2.1.1-windows.zip</u> (17.4 MB) and extract (unzip) the content.

The executable phantomis.exe is ready to use.

Note: For this static build, the binary is self-contained with no external dependency. It will run on a fresh install of Windows Vista or later versions. There is no requirement to install Qt, WebKit, or any other libraries.

Mac OS X

Download phantomjs-2.1.1-macosx.zip (16.4 MB) and extract (unzip) the content.

Note: For this static build, the binary is self-contained with no external dependency. It will run on a fresh install of OS X 10.7 (Lion) or later versions. There is no requirement to install Qt or any other libraries.

Linux 64-bit

Download phantomjs-2.1.1-linux-x86_64.tar.bz2 (22.3 MB) and extract the content.

Note: For this static build, the binary is self-contained. There is no requirement to install Qt, WebKit, or any other libraries. It however still relies on Fontconfig (the package fontconfig or libfontconfig, depending on the distribution). The system must have GLIBCXX_3.4.9 and GLIBC_2.7.

Linux 32-bit

Download phantomjs-2.1.1-linux-i686.tar.bz2 (23.0 MB) and extract the content.

Note: For this static build, the binary is self-contained. There is no requirement to install Qt, WebKit, or any other libraries. It however still relies on Fontconfig (the package fontconfig or libfontconfig, depending on the distribution). The system must have GLIBCXX_3.4.9 and GLIBC_2.7.

FreeBSD

Binary packages are available via pkg:

\$ sudo pkg install phantomjs

Source Code

Check the official git repository github.com/ariya/phantomjs.

Checksums

To verify the integrity of the downloaded files, use the following checksums.

MD5 Checksums

```
0396e8249e082f72c1e39d33fc9d8de6 phantomjs-2.1.1-linux-i686.tar.bz2
1c947d57fce2f21ce0b43fe2ed7cd361 phantomjs-2.1.1-linux-x86 64.tar.bz
b0c038bd139b9ecaad8fd321070c1651 phantomjs-2.1.1-macosx.zip
4104470d43ddf2a195e8869deef0aa69 phantomjs-2.1.1-windows.zip
```

SHA-256 Checksums

```
80e03cfeb22cc4dfe4e73b68ab81c9fdd7c78968cfd5358e6af33960464f15e3
86dd9a4bf4aee45f1a84c9f61cf1947c1d6dce9b9e8d2a907105da7852460d2f
538cf488219ab27e309eafc629e2bcee9976990fe90b1ec334f541779150f8c1
d9fb05623d6b26d3654d008eab3adafd1f6350433dfd16138c46161f42c7dcc8
                                                                 ph
```

Acknowledgement

Download service is kindly provided by <u>Bitbucket</u>. Previous releases download was provided by Google Code Project Hosting.

Community:



Read the release notes



