MotionBench: Agent-Independent Robot Evaluation through Goal-Referenced Outcome Scoring

An Open Framework and Preliminary Evaluation in Simulation

Abhay Yadav

Independent researcher, San Francisco Bay Area, California, USA [contact email]

https://motionbench.org https://github.com/motionbenchmark/mb-core

Draft v0.3, October 2026

Abstract

Comparing human-operated and autonomous robots is difficult when their control methods differ. In student robotics competitions, for example, match scores do not show whether a programmed routine performs better than a human driver under the same conditions. This paper introduces MotionBench, an open framework for evaluating robot task performance from externally observed trajectories and task-state measurements, without access to the agent's controller. MotionBench defines task-specific goals, reports the share of the goal an attempt achieved beside the level reached by chance, and specifies a protocol for comparing agents over repeated trials and previously unseen layouts. The framework is implemented as a deterministic scorer, trajectory-capture tools and a simulator that runs VEX AIM Python routines unchanged. In a preliminary simulated study of an object-sorting task, a routine that encodes the public layout scores 4.00 of 6 points there but 2.80 on unseen layouts, while a camera-based routine scores 2.45 and 2.35. These results illustrate the method; they do not establish real-world measurement accuracy or any comparison with real people, which remain to be tested. The implementation and protocol are released so that the method can be examined and validated on physical robots.

1 Introduction

In VEX robotics competitions, my team spends a lot of time improving autonomous routines. But I kept coming back to a basic question: was our code actually better than driving the robot ourselves? We could compare match scores, but those depended on the field, the opposing alliance and everything else that happened in the match. They did not tell us how much of a task each approach could complete under the same conditions.

I ran into the same problem working with friends on RoboBench, a project in which large language models write VEX robot code, the code runs on a robot, and the results are fed back to improve the next attempt. We needed a consistent way to say whether one attempt was better than another, without depending on how the code had been written.

MotionBench grew out of that problem. Instead of evaluating the controller, it measures the observable outcome of a task: where the robot went and what state it left the task in. The same scoring procedure can then be applied to a human driver, a programmed routine, AI-generated code or a commercial robot, provided the task and operating conditions are comparable. The




Figure 1: The MotionBench framework. Agents are never integrated with the benchmark: the scorer sees only what was observed during the attempt, and every agent is scored by the same rules.

research question is whether such *agent-independent* evaluation can be made fair, repeatable and cheap enough to run with a phone camera.

This is a framework and methodology paper. Its experiments use simulation, synthetic video, one real capture and one open dataset; they show how the method works and what it is designed to catch, and no empirical claim about real robots, real code or real people is made from them. The contributions are:

1. a **goal-referenced scoring model** that reports the share of a task's goal achieved, beside chance, with comparisons to people only where people use the same means (Section 3);
2. an **open implementation** whose only interface to an agent is a recorded trace of poses and task state (Section 4);
3. an **evaluation protocol** with public and unseen layouts, paired comparisons and explicit outcomes that separate "no difference found" from "equivalent" (Section 5);
4. a **preliminary simulated study** that runs the protocol end to end (Section 6).

Figure 1 shows the framework, and Table 1 separates what is built, what has been demonstrated (in simulation or on synthetic data) and what is not yet shown.

2 Related work

Benchmarks for robot policies. Meta-World [17], CALVIN [11] and LIBERO [10] evaluate learned manipulation policies in simulation; Habitat [15] does so for embodied navigation; SimplerEnv [9] studies how well simulated evaluation predicts real-robot results. RoboDojo [5] combines simulated and real tasks on standardized bimanual hardware, scores real trials by blinded human evaluators with partial credit, and verifies submissions on hidden layouts. RoboArena [3] distributes real-world evaluation across institutions through pairwise comparisons. Evaluating task completion, standardizing tasks and using held-out layouts are not new; MotionBench adopts explicit protocols, hidden layouts, repeatability reporting and a separation between verified and unverified results from this literature. What it changes is the unit being evaluated: the whole

Built and released	Demonstrated (simulated or synthetic)	Not yet shown
Scorer, trace format and task specifications (Apache-2.0 / CC BY 4.0)	The scorer is deterministic; published boards rebuild byte-identically from their traces	That task specifications capture what practitioners mean by "done"
Phone-video capture, with and without printed tags	Synthetic video: about 1 cm median error with tags, about 3 cm without	Accuracy on real footage (reflections, blur, occlusion, camera motion)
VEX AIM simulator running unmodified routines; parameterized simulated drivers	Simulation: a public-layout advantage can vanish on unseen layouts	That the simulator matches a real AIM robot; that simulated drivers resemble real students
Protocol: tiers, run counts, unseen layouts, paired comparisons	— (the verified tier is proposed and has not been exercised)	Repeatability of real sessions; a controlled comparison of real drivers and their code
Physical measurements in this paper: one hand-held video of a robot vacuum (no ground truth) and 120 motion-capture walks from an open dataset [16]. Everything else is simulated or synthetic.		

Table 1: Status of the work.

Dimension	Typical policy benchmark	MotionBench
Requires integration with the agent's software	Often	No
Can evaluate a human driver	Not usually its focus	Yes, where comparable
Can evaluate closed-source robots	Platform-dependent	Intended to
Accepts ordinary phone video	Generally not standard	Yes, with limitations
Tests unseen task layouts	Many do	Yes
Evaluates physical task completion	Yes	Yes

Table 2: How MotionBench differs from a typical policy benchmark.

agent (robot, software and any human operator), observed from outside. Table 2 summarizes the difference without claiming that other benchmarks could not be extended in the same direction.

Human reference points. Human-normalized scores were popularized by the Arcade Learning Environment [4, 12]. Section 3 explains why MotionBench moved from normalizing to people to a goal-referenced score.

Reporting under uncertainty. Agarwal et al. [2] show that point estimates over few runs mislead and recommend interval estimates. MotionBench uses bootstrap intervals [6], paired designs and an equivalence margin in the spirit of two one-sided tests [8].

Product test methods. IEC 62929 [1] specifies laboratory methods for household cleaning robots. MotionBench is complementary: it aims to measure robots where they are used, from ordinary video.

3 The MotionBench framework

What is measured. MotionBench scores task outcomes from externally observable trajectories and task-state measurements, without access to the agent's controller. A trace holds times-

Task	Platform	Goal	Arena	Budget	People comparable	Used here
MB-VEX-NAV@1.0	VEX V5	6 waypoints, 5 cm / 5°	3.66 m square	20 s	yes	index (App. B)
MB-VEX-PICK@1.0	VEX V5	deliver 6 objects	3.66 m square	60 s	yes	index (App. B)
MB-AIM-NAV@0.1	VEX AIM	5 waypoints, 3 cm / 10°	1.83 × 1.22 m	20 s	yes	—
MB-AIM-SORT@0.1	VEX AIM	sort 6 barrels by colour	1.83 × 1.22 m	45 s	yes	main study
MB-COVER@0.1	floor robots	cover free floor, 30 cm tool	4 × 3 m	180 s	no	index (App. B)
MB-FIELD-HALLWAY@0.1	robot vacuum	cover visible floor	1.3 × 3.0 m	137 s	no	demonstration

Table 3: Current task specifications. Only MB-AIM-SORT has a controlled (simulated) experiment; the others are implemented and used only for the demonstrations indicated. "People comparable": a person can do the same job with the same means, for example by driving the same robot.

tamped poses (t, x, y, θ) of the robot, optional events (for example "target knocked down") and, for tasks that move objects, the final positions of those objects. The scorer combines these with the task specification (arena geometry, robot footprint, goal, budget). For waypoint and coverage tasks the goal depends on the robot's path alone; for delivery tasks it depends on where the objects ended up, which the robot's path cannot determine and must be measured separately.

Tasks. A task specifies an arena (size, obstacles, zones), the robot footprint, a time budget, public layouts, rules for generating unseen layouts, and a goal of one of three kinds: *waypoints* (reach each in order within position and heading tolerances), *delivery* (each object rests in its target zone at the end) or *coverage* (share of free floor swept by a tool of given width). Table 3 lists the current task specifications and which of them are used in this paper; they use competition hardware but never copy a season's game. A task carries its own version (after the @); the trace format and scoring rules are versioned by the specification (0.2), and the software by the scorer version (0.1.0). Every report records all three.

Primary outcome: goal score. For a run with success S in task units and maximum $S_{\max}$, the goal score is $g = S/S_{\max} \in [0, 1]$. For each agent the board reports the mean over its runs with a 95% bootstrap interval, the worst run, and the *completion rate* (share of runs that achieved the whole goal). Time to goal is reported over runs that achieved it. The goal score is the headline and the only quantity used in this paper's comparisons.

Chance. Each task reports the goal score of a randomly moving robot beside the agents' scores, without subtracting it. On coverage, a random walk already covers about half a room; readers should see that rather than have it absorbed into a transformation.

Comparison with people (optional). The first specification normalized every agent to the median person on the task, following [12]. That turned differences in equipment into apparent differences in skill when means differed (a robot vacuum against a person with a stick vacuum), left tasks without a human baseline unscored, and saturated where most people finish. Specification 0.2 reports vs_people $= (S - S_{\text{chance}})/(S_{\text{people}} - S_{\text{chance}})$ only on tasks declared people-comparable, only when people's median beats chance by at least 10% of $S_{\max}$ (otherwise the ratio is unstable), and never as the headline.

Secondary measures. Boards also report path efficiency, consistency and safety, defined precisely in Appendix B. Path efficiency compares the path driven with a simple reference length computed by the scorer (straight lines through the waypoints reached; a greedy nearest-first single-carry tour for deliveries; covered area divided by tool width for coverage). The reference ignores

obstacles and robot kinematics, so it is a yardstick, not a shortest path. An optional index combines these measures with the goal score for ranking within one task. Combining them is a value judgement with known problems: consistency rewards an agent that always scores 1 of 6 over a better agent with varied results, and one safety violation means different things on different tasks. The index is therefore secondary, never averaged across tasks, not used in this paper's conclusions, and can be ignored; its definition and weight sensitivity are in Appendix B.

Ranks. For display, agents share a rank while their intervals overlap the leader's. This is a presentation convention, not a test of equivalence.

4 Implementation

Traces and the scorer. A run is a directory with a manifest (task, layout, agent and its class, capture method, tier, file hashes), timestamped poses, optional events and final object positions. This is the only interface between an agent and the benchmark. The scorer is implemented once in Rust and called from Python and the command line; it validates traces (hashes, monotonic time, sampling gaps), computes run reports and builds boards. A separate recount, written in JavaScript in the toolkit's report page, recomputes waypoints, deliveries and coverage from raw poses and flags disagreements with the scorer. Both were written with the same AI assistant, so they are not fully independent checks. Returning the same report for the same trace says nothing about whether the trace or the task specification is right; capture accuracy and task design are examined separately.

Capture. With printed AprilTags [13] in the arena corners and on the robot, a per-frame homography maps the image to the floor. Without tags, frames of a fixed or hand-held camera are aligned to the first frame; the per-pixel median gives an empty-floor image and the robot is the region that differs from it. The floor plane comes from four image points outlining a floor rectangle [7]; focal length and scale come from a measured width and length, or from the robot's known size. The robot's position is taken half a robot behind the lowest point of its silhouette, and its heading from its direction of travel, so tag-free capture cannot measure heading while the robot turns in place. Floor the camera cannot see is excluded from coverage and safety.

Simulation. A *game* is defined once (field, zones, wall-mounted fiducials, objects, layouts, layout rules, match length, scoring) and then simulated many times; a game may link to a task with the same layouts, in which case simulated runs are also scored by the standard scorer. The first platform is VEX AIM, a small holonomic classroom robot with a magnetic pick-up, a kicker and a camera. The simulator runs VEXcode AIM Python files unmodified: the robot API is replaced by stand-ins, every call advances simulated time, speeds are capped at the published API limits (200 mm/s, 150°/s), and each run draws its own wheel slip, drift, turn overshoot, kick scatter and camera noise. These are modelling assumptions; speed limits alone do not validate the simulator's dynamics, pick-up, kicking, perception or collisions against a real AIM robot. The *parameterized simulated-driver baseline* is a set of controller policies with explicit traits (reaction time with partial anticipation, share of full speed used, steering shake, placement precision, choice of next object, mistake and hesitation rates). Six named characters span a range of skill, and the *typical simulated driver* is the median member of a simulated class of twenty. The traits were chosen by hand to be plausible and are listed in Appendix C; they are not fitted to real students.

5 Evaluation protocol

Tiers. Results are *simulated* (S), *field* (F: a real robot captured and submitted by its owner, reviewed before publication) or *verified* (V). They are never mixed without labels. The verified tier is a proposed procedure that has not yet been carried out: it requires a layout sent at the start, one uncut fixed-camera video with a code word, every attempt reported, and a second reviewer re-scoring at least one run from raw video; reviewers declare conflicts of interest (details in the protocol document in the repository).

Runs and layouts. An agent needs at least five runs on a task to be ranked (ten recommended); runs are consecutive attempts and every attempt is reported. Public layouts are published; unseen layouts are generated from each task's layout rules with an unpublished seed.

Paired comparisons. In simulation, run i of every agent uses the same seed, so the same layout and the same draw of robot imperfections, and a comparison is the mean of paired differences. Intervals are 95% percentile bootstrap intervals from 4,000 resamples. On one layout the resampling unit is the paired run; across unseen layouts the bootstrap is hierarchical (layouts, then runs within each chosen layout). Paired simulated runs share the simulator and its assumptions, so they are not independent experimental replicates in the sense of separate physical sessions.

Outcomes. *Better* or *worse* when the interval excludes zero; *equivalent* when the interval lies strictly inside a margin of $\pm\delta$; *no difference found* otherwise. Requiring a 95% interval inside the margin is a conservative version of the two one-sided tests procedure [8], which uses a 90% interval. For the sorting task $\delta = 0.5$ points, half of the smallest scoring unit (one barrel), fixed before the study; it is a convention, not derived from what matters to users, and other tasks will need their own. "No difference found" does not mean equivalent.

6 Preliminary evaluation

All numbers in this section describe the simulation or synthetic video. Every agent, the robot model and every driver trait are assumptions, so they illustrate what the protocol reports and what it catches; they are not measurements of VEX AIM robots or of students.

6.1 Does a public-layout advantage generalize?

Setup. One VEX AIM robot must sort three orange and three blue barrels into the zone of their colour on a $1.83\,\mathrm{m} \times 1.22\,\mathrm{m}$ table within 45 s (one point per barrel; six maximum). Four routines, written for the public layout, span common approaches: *dead reckoning* (a fixed plan, no sensors); *vision* (the camera finds the nearest barrel, wheel odometry returns it to the zone); *vision + tags* (as vision, then homing on the AprilTag behind each zone); and *planner* (the barrel positions of the public layout, an efficient order, full speed, the camera only for the last few centimetres, and spread drop positions). Each routine, each driver character and the typical simulated driver play 20 paired runs on the public layout, and 20 paired runs over ten unseen layouts (two per layout; same start, barrels placed at random away from the zones, the start and each other).

Results. Table 4 summarizes the outcome. On the public layout the planner scores 4.00 points, ahead of the typical simulated driver (2.90) by a paired difference of +1.10 (+1.00 to +1.25).




Figure 2: Left: the simulated AIM sorting game (labelled as simulation in all outputs). Right: mean points on the public layout and on ten unseen layouts (20 paired runs per agent). The drivers are a parameterized, uncalibrated baseline.

	Public layout		Unseen layouts		Change
Routine	Mean	vs typical driver	Mean	vs typical driver	unseen − public
Dead reckoning	1.70	−1.20 [−1.50, −0.90] worse	0.65	−2.20 [−2.75, −1.55] worse	−1.05 [−1.50, −0.60]
Vision	2.45	−0.45 [−0.80, −0.10] worse	2.35	−0.50 [−1.15, +0.20] n.d.f.	−0.10 [−0.55, +0.40]
Vision + tags	2.25	−0.65 [−1.05, −0.30] worse	1.80	−1.05 [−1.55, −0.55] worse	−0.45 [−1.10, +0.15]
Planner	4.00	+1.10 [+1.00, +1.25] better	2.80	−0.05 [−0.65, +0.60] n.d.f.	−1.20 [−1.60, −0.85]
Typical simulated driver	2.90		2.85		

Table 4: Simulated AIM sorting: points (of 6) with 95% bootstrap intervals; n.d.f. = no difference found. The change column compares different layouts and is an unpaired bootstrap. The typical driver's paired runs average 2.90; the class median of per-driver means, used only to select that driver, is 2.83. Full results, including each driver character, are in `results/aim-sort-verdict-v0.1.json`.

On unseen layouts it scores 2.80: a change of −1.20 (−1.60 to −0.85) and no difference found against the typical simulated driver (−0.05; −0.65 to +0.60). The vision routine scores 2.45 on the public layout and 2.35 on unseen layouts; its change (−0.10; −0.55 to +0.40) is small, but the interval is wider than the margin, so the outcome is no difference found, not equivalence. The dead-reckoning routine, which also encodes the public layout, changes by −1.05 (−1.50 to −0.60). Interval endpoints are exact at the resolution of the data: with 20 runs and integer points, bootstrap means fall on multiples of 0.05.

What the study shows, and what it does not. The planner's public-layout advantage comes largely from knowing where the barrels are. That a routine which memorizes positions does worse when they move is expected; the point of the study is that the protocol catches it, and that a verdict based on the public layout alone would have recommended the planner. The within-routine change does not depend on the simulated drivers. Several limits apply. First, the planner was chosen as the strongest routine *on the public layout*, so its public-layout margin is inflated by that selection; the unseen layouts were not used for selection or development and give the less biased estimate. Second, ten unseen layouts with two runs each is a small sample of layouts, so the intervals may understate layout-to-layout variability. Layout by layout (Appendix D) the planner scores above the typical simulated driver on four layouts, the same on three and below on three; more layouts are needed before such a comparison could be relied on. Third, at the simulated top speed no

Capture	Scale from	Median error	90th percentile	Frames without position
Printed tags	tag geometry	1.2 cm	1.5 cm	0%
No tags	measured floor	3.2 cm	5.2 cm	8.2%
No tags	robot size only	3.2 cm	5.4 cm	8.2%

Table 5: Capture accuracy on rendered video (medians over three render seeds; `paper/analysis/capture_accuracy.py`).




Figure 3: Tag-free capture of a household robot vacuum from one hand-held phone video. Scale came from the robot's size; floor the camera could not see is excluded. There is no ground truth for this video.

agent sorts all six barrels in 45 s (best runs score 4 or 5). The goal score therefore measures partial progress under a tight budget rather than completion; this is a property of the task as specified, and whether the budget should be lengthened is an open question for the task's next version.

6.2 Capture accuracy on synthetic video

Table 5 reports per-frame position errors on rendered video with known ground truth, over three render seeds. With tags the robot is found in every frame with a median error of about 1 cm; without tags the median is about 3 cm whether scale comes from a measured floor or from the robot's size, and about 8% of frames have no position. Synthetic video lacks reflections, blur, occlusion and lighting changes, and whether these errors or the missing frames change goal scores (for example on a 5 cm waypoint tolerance) has not yet been measured. These figures are therefore a best case: errors on real footage are likely to be larger. They are not a validation.

6.3 Demonstrations on real data

A robot vacuum. A household robot vacuum was filmed for 137 s with a hand-held phone, without tags (Figure 3). The pipeline estimated that it covered 85% of 3.24 m^2 of visible floor with a 30 cm cleaning width, driving 18.6 m. This shows the pipeline running end to end on real footage;

without ground truth it says nothing about accuracy.

People in an open dataset. I scored 120 motion-capture walks along one route (about 7 m) from THÖR-MAGNI [16]. All 120 reached the goal (median 6.8 s), so the goal score could not separate walkers; with a 60 s budget a random walk reached the goal in 40% of runs. The example shows that budgets need to follow typical completion times, or the goal score saturates.

7 Discussion and limitations

The evidence supports three modest statements: the framework can be specified precisely and implemented reproducibly; its protocol, applied to simulated agents, distinguishes a public-layout advantage from one that generalizes; and tag-based and tag-free capture are accurate to a few centimetres on synthetic video. It does not yet support claims about real robots or people.

The main limitations follow. The simulator is custom and uncalibrated: its robot model, noise and every driver trait are assumptions, and simulated agents are less variable than real ones (some score the same in every run), so intervals are likely narrower than they will be on real robots. Tag-free capture needs a visible floor rectangle, cannot measure heading during turns in place, and has been tested only on synthetic video; the effect of capture error on scores is untested. Delivery tasks need object positions, which the current capture tools do not measure. Goal scores depend on how goals and budgets are set, and the sorting task's budget may be too tight. The synthetic VEX AIM boards published on the project site under specification 0.2 contain simulated agents faster than the AIM robot's top speed; they are marked invalid and are not used here. Coverage scores model cleaning rather than measure it. Tasks and protocol change only through public RFCs so that such issues are fixed openly.

8 Future work

The next step is a small real-world accuracy experiment that does not need a motion-capture lab: a robot driven between measured floor markers, 20–30 trials filmed with a fixed camera, comparing the position and waypoint completion estimated by MotionBench (with and without tags) against the measured marks, and checking whether capture error or missing frames change goal scores. Further work, in order: scoring the same simulated runs from ground truth and from rendered-video capture to test how capture error propagates to scores and rankings; more unseen layouts, at several difficulty levels, with layout-level reporting and a comparison of public-layout and unseen-layout rankings; running the routines of Section 6 on a real AIM robot to measure the simulator's prediction error; and a paired comparison of real student drivers with their own teams' code, which would require parental consent, a host institution's youth-protection rules and an ethics review.

9 Conclusion

MotionBench proposes evaluating any robot agent, whether a person, code or a product, by how much of a task's goal it achieves, from what can be observed from outside, with an open scorer and an explicit protocol. The framework and tools are built and released, and a preliminary simulated study shows why unseen layouts belong in any verdict. The next step is to test the measurement on real robots. Comments are welcome at `https://motionbench.org/paper`.

Author contributions

A.Y. conceived the project, developed the research questions, designed the evaluation framework and the experiments, specified the intended behaviour of the software, ran the experiments and reviewed the resulting analyses.

Use of AI tools

AI-assisted tools, primarily Claude (Anthropic), used through claude.ai, supported software implementation (scorer, capture tools, simulators and analysis scripts), synthetic data generation, analysis scripting and manuscript drafting. AI-generated implementations and outputs were examined and tested by the author, who takes responsibility for the methods, reported results and conclusions. The checks made so far are the automated test suites in the repository (unit tests of the scorer and of the Python toolkit), the separate recount described in Section 4, and reproduction of every reported number with `paper/reproduce.sh`; a set of hand-worked scoring examples is planned. AI tools are not listed as authors.

Acknowledgements

The author thanks his friends and teammates on RoboBench and in VEX competition for the questions that started this work, his family for their support, and the THÖR-MAGNI authors for releasing their data.

Ethics, data and code availability

No new data from human participants were collected for this paper; the human trajectories come from a published dataset [16]. The robot-vacuum video was recorded by the author in a private home. Footage from a public event broadcast was used only to measure camera geometry for the match simulator (Appendix E) and is not redistributed. Code (Apache-2.0), task specifications and data (CC BY 4.0) are at `https://github.com/motionbenchmark/mb-core`; the version described here is the release tagged `paper-v0.3`, and `paper/reproduce.sh` regenerates every number and figure (Appendix A).

References

[1] IEC 62929: Cleaning robots for household use – dry cleaning: Methods of measuring performance. Technical report, International Electrotechnical Commission, 2014.

[2] Rishabh Agarwal, Max Schwarzer, Pablo Samuel Castro, Aaron Courville, and Marc G. Bellemare. Deep reinforcement learning at the edge of the statistical precipice. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2021. arXiv:2108.13264.

[3] Pranav Atreya et al. RoboArena: Distributed real-world evaluation of generalist robot policies. In *Proceedings of the Conference on Robot Learning (CoRL)*, volume 305 of *PMLR*, 2025. arXiv:2506.18123.

[4] Marc G. Bellemare, Yavar Naddaf, Joel Veness, and Michael Bowling. The arcade learning environment: An evaluation platform for general agents. *Journal of Artificial Intelligence Research*, 47:253–279, 2013.

[5] Tianxing Chen, Yue Chen, Zixuan Li, et al. RoboDojo: A unified sim-and-real benchmark for comprehensive evaluation of generalist robot manipulation policies. *arXiv preprint arXiv:2607.04434*, 2026.

[6] Bradley Efron. Bootstrap methods: Another look at the jackknife. *The Annals of Statistics*, 7(1):1–26, 1979.

[7] Richard Hartley and Andrew Zisserman. *Multiple View Geometry in Computer Vision*. Cambridge University Press, 2 edition, 2004.

[8] Daniël Lakens. Equivalence tests: A practical primer for t tests, correlations, and meta-analyses. *Social Psychological and Personality Science*, 8(4):355–362, 2017.

[9] Xuanlin Li et al. Evaluating real-world robot manipulation policies in simulation. In *Proceedings of the Conference on Robot Learning (CoRL)*, volume 270 of *PMLR*, 2024. arXiv:2405.05941.

[10] Bo Liu, Yifeng Zhu, Chongkai Gao, Yihao Feng, Qiang Liu, Yuke Zhu, and Peter Stone. LIBERO: Benchmarking knowledge transfer for lifelong robot learning. In *Advances in Neural Information Processing Systems (NeurIPS), Datasets and Benchmarks Track*, 2023. arXiv:2306.03310.

[11] Oier Mees, Lukas Hermann, Erick Rosete-Beas, and Wolfram Burgard. CALVIN: A benchmark for language-conditioned policy learning for long-horizon robot manipulation tasks. *IEEE Robotics and Automation Letters*, 2022. arXiv:2112.03227.

[12] Volodymyr Mnih, Koray Kavukcuoglu, David Silver, et al. Human-level control through deep reinforcement learning. *Nature*, 518:529–533, 2015.

[13] Edwin Olson. AprilTag: A robust and flexible visual fiducial system. In *Proceedings of the IEEE International Conference on Robotics and Automation (ICRA)*, 2011.

[14] Ergys Ristani, Francesco Solera, Roger Zou, Rita Cucchiara, and Carlo Tomasi. Performance measures and a data set for multi-target, multi-camera tracking. In *European Conference on Computer Vision (ECCV) Workshops*, 2016.

[15] Manolis Savva, Abhishek Kadian, Oleksandr Maksymets, Yili Zhao, Erik Wijmans, Bhavana Jain, Julian Straub, Jia Liu, Vladlen Koltun, Jitendra Malik, Devi Parikh, and Dhruv Batra. Habitat: A platform for embodied AI research. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, 2019. arXiv:1904.01201.

[16] Tim Schreiter et al. THÖR-MAGNI: A large-scale indoor motion capture recording of human movement and robot interaction, 2024. arXiv:2403.09285.

[17] Tianhe Yu, Deirdre Quillen, Zhanpeng He, Ryan Julian, Karol Hausman, Chelsea Finn, and Sergey Levine. Meta-World: A benchmark and evaluation for multi-task and meta reinforcement learning. In *Proceedings of the Conference on Robot Learning (CoRL)*, 2019. arXiv:1910.10897.

A Reproducing the results

Release: `paper-v0.3` of https://github.com/motionbenchmark/mb-core. Environment used: Python 3.13, NumPy 2.5, SciPy 1.18, OpenCV 5.0, FFmpeg 6.1, Rust 1.97, motionbench 0.1.0 (specification 0.2); the exact versions and commit are written to `paper/results/environment.txt` on each run.

```
git clone https://github.com/motionbenchmark/mb-core && cd mb-core
git checkout paper-v0.3
pip install maturin
(cd python && maturin build --release)
pip install "target/wheels/motionbench-*.whl[tracker]"
bash paper/reproduce.sh     # ~5 min
```

Expected outputs: the synthetic board is byte-identical to `results/leaderboard-synthetic-v0.1.json`; `paper/results/aim-sort-verdict.json` reproduces Table 4; `aim-sort-per-layout.json` reproduces Table 8; `index-sensitivity.json` reproduces Table 6; `capture-accuracy.json` reproduces Table 5 (small differences are possible across OpenCV/FFmpeg versions). SHA-256 checksums of the deterministic outputs are in `paper/results/SHA256SUMS` and are checked by the script.

B Secondary measures and the experimental index

Definitions. Path efficiency $e = \min(1, L_{\text{ref}}/L)$, with L the path driven and L_{ref} the reference length: for waypoints, the straight-line length from the start through the waypoints reached; for deliveries, the greedy tour that repeatedly goes to the nearest remaining object and carries it to its zone centre, truncated at the number delivered; for coverage, the area covered divided by the tool width. $e = 0$ when nothing was achieved. Consistency $c = \text{clamp}(1 - \sigma_S/\mu_S, 0, 1)$ with σ_S the sample standard deviation of success over runs, $c = 0$ when $\mu_S = 0$, and $\sigma_S = 0$ for a single run (which is why agents with fewer than five runs are unranked). Safety $s = 1/(1 + \bar{v}) \in (0, 1]$ with $\bar{v}$ the mean number of contact or rule violations per run. The index is

$$\text{MBI} = 0.50\, g + 0.20\, e + 0.15\, c + 0.15\, s \ \in [0, 1].$$

The weights are a design choice, not an estimate of what performance means.

When not to use it. The index should not be used across tasks, to compare agents whose goal scores differ clearly (the goal score already answers the question), or where consistency is high only because the score is uniformly low, since c does not distinguish the two.

Weight sensitivity. On the synthetic boards whose simulated agents respect their robots' limits, the index was recomputed for 5,000 weight vectors drawn near the defaults (Dirichlet with concentration $50\,w$) and uniformly from the simplex (Table 6). Under local changes the rankings are stable (median Kendall's $\tau \geq 0.94$); under arbitrary weights the coverage ranking is the least stable. Ranking by goal score alone agrees with the index at $\tau = 0.81$ to 0.91. This shows the ranking is insensitive to small changes in the weights, not that the weights are right.

C Simulated driver parameters

Table 7 lists the six characters. The class of twenty is drawn from a single skill level per student (Beta(2.2, 2.0)), from which each trait follows linearly with small noise (`class_roster` in

Task	Agents	Local weights		Uniform weights	Goal only
		median τ	top agent same	median τ (5th pct.)	τ
MB-VEX-NAV@1.0	19	0.99	100%	0.95 (0.88)	0.91
MB-VEX-PICK@1.0	19	0.99	100%	0.90 (0.74)	0.81
MB-COVER@0.1	9	0.94	99.6%	0.83 (0.33)	0.83

Table 6: Kendall's τ between the default index ranking and rankings under perturbed weights (synthetic agents; `paper/analysis/index_sensitivity.py`).

`python/motionbench/game/driver.py`); the typical driver selected by the median of class means has reaction 0.35 s, speed use 0.71, steering shake 4.6°, precision 0.66, decisions 0.81, mistakes 0.08 and hesitation 0.22. All values were set by hand to span a plausible range and have not been fitted to any person.

Character	Reaction (s)	Speed use	Shake (°)	Precision	Decisions	Mistakes	Hesitation	Strafe
Rookie Riley	0.55	0.55	9.0	0.30	0.55	0.16	0.25	0.0
Nervous Noah	0.45	0.60	5.0	0.60	0.70	0.07	0.40	0.1
Average Alex	0.40	0.70	5.0	0.55	0.75	0.08	0.15	0.2
Speedy Sloane	0.30	1.00	7.0	0.40	0.70	0.13	0.05	0.3
Steady Sam	0.35	0.55	3.0	0.85	0.85	0.03	0.10	0.3
Pro Priya	0.22	0.95	2.0	0.85	0.95	0.02	0.03	0.6

Table 7: Simulated driver characters. Decisions: probability of choosing the sensible next object; mistakes: probability per delivery of a fumble; hesitation: probability per decision of pausing.

D Unseen layouts, layout by layout

Table 8 groups the unseen-layout runs of Table 4 by layout (two runs per layout; the script `per_layout.py` in `paper/analysis` replays the same runs and adds none). The planner scores above the typical simulated driver on four layouts, the same on three and below on three; its per-layout means range from 1.5 to 4.0, against 1.0 to 3.0 for the vision routine.

Agent	1	2	3	4	5	6	7	8	9	10	All
Dead reckoning	0.5	0.0	1.5	1.5	0.0	1.0	0.0	2.0	0.0	0.0	0.65
Vision	3.0	3.0	3.0	3.0	2.5	3.0	1.5	1.0	2.0	1.5	2.35
Vision + tags	1.5	0.0	2.0	0.0	3.0	3.0	3.0	1.0	2.5	2.0	1.80
Planner	1.5	3.0	3.5	3.0	2.5	3.0	4.0	3.0	3.0	1.5	2.80
Typical sim. driver	3.0	2.0	3.0	2.0	3.0	3.0	3.5	3.0	3.0	3.0	2.85

Table 8: Mean points (of 6) per unseen layout, simulated.

E Extension: multi-robot matches

The toolkit also includes a seeded 2-versus-2 match simulator, a renderer of broadcast-style video from a camera position measured on a real event broadcast, a per-robot report and a tracking benchmark. A baseline tracker finds 90–97% of robot positions with a median error of 7–9 cm on three simulated matches but switches identities 25–44 times per match (IDF1 [14] 48–66%). It is infrastructure for future work and is not used in the paper's conclusions.