

INDiC: Improved Non intrusive load monitoring using load Division and Calibration

Nipun Batra

Indraprastha Institute of Information Technology
India

Author2

Twentieth Century Fox
Springfield, USA

Email: homer@thesimpsons.com

James Kirk

and Montgomery Scott
Starfleet Academy

San Francisco, California 96678-2391

Telephone: (800) 555-1212

Fax: (888) 555-1212

Abstract—Non-Intrusive appliance load monitoring (NIALM) is the process of disaggregating the overall electricity usage into constituent appliances. In this paper we extend the Combinatorial Optimization (CO) approach for disaggregation, which was originally proposed in the seminal work on NIALM, in following two ways: 1) Breaking the problem into subproblems and reducing the state space; 2) Applying additional constraints backed by sound domain expertise. We evaluate our approach using REDD dataset and show practical problems which need to be solved while dealing with the dataset. We also propose a metric for evaluating NILM, which we believe overcomes many shortcomings of commonly used metrics.

I. INTRODUCTION

- Motivate the importance of energy consumption in building
- Motivate that appliance level information is crucial - detailed feedback and optimized decision making [1]
- Challenges with getting appliance level information - introduce NIALM [2]
- introduce your proposed approach
- Enumerate the contributions

Primary contributions of our work are:

- Fill it up with 2-3 crisp points

Open source implementation of the proposed work is released for comparative analysis with other NIALM approaches as an IPython notebook¹. We believe this is the first extensive release of a generic NIALM

II. RELATED WORK

Non-intrusive appliance load monitoring was first studied by Hart [2] in the early 1990s by examining signatures in aggregated load to indicate activities of appliances. The problem has been well studied in recent years and survey papers [3], [4], [5] present its classification across various dimensions including:

- **Frequency of data collection:**[REWRITE] Approaches such as harmonic analysis require data to be sampled at more than a thousand samples a second. Whereas approaches

- **Supervised/Unsupervised:** Supervised learning techniques include optimization-based methods such as integer programming [6] and genetic algorithms [7]. These approaches are compute intensive and appliances with similar or overlapping load signatures are difficult to discern. Machine Learning techniques (such as Artificial Neural Network (ANNs) [8] and Hidden Markov Models (HMM)[9]), on the other hand, have been shown to work well for load disaggregation. Variants such as factorial hidden Markov models (FHMMs) [10], additive FHMMs [11], conditional factorial hidden semi-Markov models [12] and difference HMMs [13] have also been applied to the task. In factorial HMMs several models evolve independently and in parallel and the observed output is some joint function of all the hidden states; additive HMMs allow emission of a single real-valued (unobserved) output from each HMM and the output is the sum of these HMMs. The applicability of these sophisticated techniques are generally hindered by the difficulty of inference from models with a large number of HMMs. In this paper, we put forward a simple idea – the aggregated load can be further split up by knowledge of mains and which appliance is assigned to which main. This would make the task of disaggregation inherently easier and any of the above sophisticated modeling approaches can still be applied to the task².

Finally, several datasets have been made available publicly including REDD[14], Blued[15] and Smart*[16]. Our empirical analysis is on the REDD data primarily because this dataset has been used extensively in evaluation of NIALM techniques and the performance of our approach is directly comparable to state-of-the-art techniques.

III. NIALM

NIALM is the process of disaggregating the total electrical load into constituent appliances [2]. A typical NIALM setup involves instrumenting the power mains with smart meters and individual appliances with appliance meters for ground truth. Figure 1 shows the house mains disaggregated into 3 appliances.

¹<http://www.ipython.org>

²The use of combinatorial optimization is only for the purpose of illustration and there is clearly no requirement to adhere to this modeling technique alone.




Fig. 1: The process of disaggregation

TABLE I: Terminologies and Functions

Symbol	Meaning
$t \in 1, \dots, T$	Time slice
$n \in 1, \dots, N$	Appliance number
$\theta^n = \{\theta_1^n, \dots, \theta_T^n\}$	Measured power sequence for each appliance
$\theta^{M1} = \{\theta_1^{M1}, \dots, \theta_T^{M1}\}$	Measured power sequence for Mains 1
$\theta^{M2} = \{\theta_1^{M2}, \dots, \theta_T^{M2}\}$	Measured power sequence for Mains 2
$x = \{x_1, \dots, x_T\}$	Measured aggregate power sequence
$\theta^{M1} + \theta^{M2}$	
$e = \{e_1, \dots, e_T\}$	Aggregate noise power sequence
$y^n = \{y_1^n, \dots, y_T^n\}$	Predicted power sequence for n^{th} appliance
$k \in 1, \dots, K$	Appliance power state
$z^n = \{z_1^n, \dots, z_T^n\}$	Appliance state sequence, $z_t^n \in [1, \dots, K]$
$z_{t,k}^n \in 0, 1$	Whether n^{th} appliance is in k^{th} state at time t
$\mu^n = \{\mu_1^n, \dots, \mu_K^n\}$	Power draw by n^{th} appliance in k^{th} state
$Mapping[n] \in M^1, M^2$	Mapping of n^{th} appliance to Mains
$Downsample(s, filter, interval)$	Function to downsample a timeseries s to an <i>interval</i> according to specified <i>filter</i>
$Preprocess([s^1, \dots, s^n], method)$	Function to ensure that n timeseries start and end at same times and handling missing data using specified <i>method</i>
$Sort([s^1, \dots, s^n], parameter, order)$	Function to sort n timeseries according to <i>parameter</i> in specified <i>order</i>
$Event_Detection(s, threshold, interval)$	Function returning magnitude and times of step events in time series s during an <i>interval</i> , whose absolute value is greater than <i>threshold</i>

We use some terminologies from previous work [14], [13], [2] and extend them for our analysis in Table I. Based on these terminologies, the NIALM problem in supervised setting can be formulated as predicting the power sequence for n^{th} appliance, y^n , given the labeled power sequence for each appliance θ^n and the total aggregate power sequence x .

Combinatorial optimization: At a given time an appliance can only be in a single state. Thus, we follow 1-of-K coding scheme for appliance states we have:

$$\sum_{k=1}^K z_{t,k}^n = 1$$

The power consumption by n^{th} appliance in k^{th} state at time t is given by:

$$\hat{\theta}_{t,k}^n = \sum_{k=1}^K z_{t,k}^n \mu_k^n$$

The overall power consumption of all appliances at a given time t is given by:

$$\hat{x}_t = \sum_{n=1}^N \sum_{k=1}^K z_{t,k}^n \mu_k^n \quad (1)$$

The error in power signal after the load assignment explained above is given by:

$$e_t = |x_t - \sum_{n=1}^N \sum_{k=1}^K z_{t,k}^n \mu_k^n| \quad (2)$$

Combinatorial optimization aims to minimize this error term, by the following state assignment scheme:

$$z_t = \underset{z_t}{\operatorname{argmin}} |x_t - \sum_{n=1}^N \sum_{k=1}^K z_{t,k}^n \mu_k^n| \quad (3)$$

The corresponding predicted power draw by n^{th} appliance is given by:

$$y^n = \{\mu_{z_1^n}^n, \dots, \mu_{z_T^n}^n\} \quad (4)$$

This optimization problem resembles subset sum problem [17] and is NP-complete. The state space of this optimization function is K^N , which means it is exponential in the number of appliances. Owing to the exponential nature of the state space and the fact that the algorithm requires all appliances be known, this approach has not been thoroughly studied in the past [13]. We chose to use this approach as a proof of concept of our contributions.

Load subdivision: In the US homes have 2 electrical mains corresponding to different phases. Many Asian countries have multiple meters per home. Different loads are electrically connected to different mains/meters. Since an NIALM deployment requires monitoring different electrical mains, we leverage the load division to perform disaggregation on these mains separately to improve load disaggregation. We assign N_i different loads to p different mains given by where $\sum_{i=1}^p N_i = N$

After load assignment to different mains, the state spaces for different mains are given by $K^{N_1} \dots K^{N_p}$. As a practical example, if a home has two mains and 20 appliances equally distributed across the two mains, state space before load division is given by 2^{20} and after load division is 2^{10} . Thus, there is an exponential reduction in state space. Moreover, this approach owing to the reduction in state space is expected to improve disaggregation results. **Unsure where to put why Load Division is expected to improve results**

IV. INDiC NIALM

In this section we explain our algorithm- Improved Non intrusive load monitoring using load Division and Calibration (INDiC). While INDiC can be used with any modeling technique such as Hidden Markov Models[18], combinatorial optimization, etc., we present INDiC-CO (INDiC using Combinatorial optimization as modeling approach). The various steps of INDiC-CO NIALM shown in Algorithm 1 are described below.

Preprocessing: Since multiple data streams (appliances and mains power time series) from varied hardware are used to produce data for NIALM applications, it is highly likely that some hardware malfunctions during the data collection process. In the preprocessing step we ensure that all the time series start and end at the same time. Moreover, small gaps in data collection can be filled using techniques such as forward filling(padding).




Fig. 2: Effect of downsampling appliance data

Downsampling: While performing CO it is desired that transients and fluctuations in the power signal are filtered[2]. The transients occur due to the high starting current of the appliance, whereas the fluctuations are a consequence of minor voltage fluctuations and oscillatory nature of loads. Figure 2a and Figure 2b show how starting current and voltage fluctuations can be filtered by down sampling. Filters such mean/median can be used to down sample a time series, whereby, where the value assigned to a time window is the mean/median of values occurring during that time window.


Assigning Loads to Mains³: This step aims to identify the mapping between appliances and mains. Patterns corresponding to appliances having higher peak power are generally easier to extract from main signal, thus we sort the appliance in decreasing order of peak power. usage are easier to Based on domain expertise we label the appliances in a home into background (loads which run independently throughout the day without user interference) such as refrigerator, and foreground (loads which are highly correlated with human usage) such as stove. Background loads are easier to detect since they are On even during periods of low human activity. Also loads with higher mean power consumption are easier to identify and thus we sort background loads based on power in descending order. For all such background loads we see if the mean power of the appliance is greater than mean power of any mains for all time instances. If so, we can safely assign the appliance to the other mains. If this step is unable to provide conclusive evidence we look at the periodicity associated with such background loads during periods of low or no human activity (such as night time). Figure 3a shows how based on refrigerator duty cycle it is mapped to Mains 2. On similar lines assignment of foreground loads can be done.

Appliance Power Calibration: Power measured by appliance level meters may need calibration due to the following reasons:

- Difference in measurement of different measurement instrument (diagram showing CC, ZWave, etc) [19]
- Fluctuation in voltage cause power to fluctuate as well
- Missing meta data, whether real or apparent power is being measured at appliance level

Since different hardware is used for measuring appliance and mains data there may be a need to calibrate the two. Since mains data is usually collected using better precision hardware,

³While we provide methods for 2 Mains, it can be easily extended



(a) Assigning refrigerator to Mains 2 since refrigerator power > Mains 1 power and on basis of duty cycle (b) Calibrating Refrigerator Power consumption

Fig. 3: Calibrating and assigning refrigerator to Mains 2

we keep mains data as a reference and calibrate appliance data against it. In practice we found appliance level monitors to usually provide only real power whereas the mains monitors can provide much more like reactive and active power. Like the previous step, time instances when an appliance in a particular mains is single used are identified. The ratio of mains and appliance power step changes occurring this window serve as the calibration factor for that appliance. Further each appliance power is corrected with the corresponding calibration factor.

Clustering to identify appliance states:

- 1) Step changes occurring in Mains vs Appliances
- 2) Isolating single appliance usage We use [20] to run our clustering

Appliance states identification using clustering (Possibly talk about unbalanced data, but leave it for future work) State space creation Applying CO for different mains Find energy distribution by appliance and assign weights (To be used in results)

V. EVALUATION

We use Reference Energy Disaggregation Data Set (REDD) [14] for validating our algorithms. This dataset contains power and voltage data for mains (2 phases) as well as appliances from 6 homes in Boston area collected in the summer of 2011. The data is made available as raw, high frequency (sampled at 15 KHz) and low frequency (Mains at 1 Hz, appliances at 0.3 Hz). Considering the practical implications of residential smart meter installation, we believe that low frequency data represents the most realistic scenario and thus we use this data for analysis.

A. Evaluation Metric

Commonly used metrics such as accuracy, sensitivity and specificity can be misleading when applied to NIALM. It can be seen from Figure 4 that since stove is mostly in state 0 (Off), accuracy will be largely decided by accuracy for this state. This does not tell how badly the prediction is misclassifying state 1 (On). Thus, we use the following metrics which have been used in the past work [13], [14]:

- **Mean Normalized Error (MNE %):** Normalized error in the energy assigned to an appliance n over

Algorithm 1: INDiC-CO

Input: $x, \theta^n, \theta^{M_1}, \theta^{M_2}, B, F, v$ **Output:** $y^n, \mu_k^n, \text{Calibrated } \theta^n$ **Preprocessing**

1 $\theta^1, \dots, \theta^n, \theta^{M_1}, \theta^{M_2} \leftarrow$
Preprocess($[\theta^1, \dots, \theta^n, \theta^{M_1}, \theta^{M_2}]$, forward fill)

Downsampling

2 **for** $n \in 1, N$ **do**
 $\theta^n \leftarrow \text{Downsample}(\theta^n, \text{mean}, 1 \text{ minute})$
3 $\theta^{M_1} \leftarrow \text{Downsample}(\theta^{M_1}, \text{mean}, 1 \text{ minute})$
4 $\theta^{M_2} \leftarrow \text{Downsample}(\theta^{M_2}, \text{mean}, 1 \text{ minute})$
5 $s \leftarrow \text{Sort}([\theta^1, \dots, \theta^n], \text{peak power})$

Appliance to Mains mapping

6 **for** Appliance $n \in s$ **do**
7 **if** $\theta_t^n > \theta_t^{M_1}$ for any $t \in 1, T$ **then**
 $\text{Mapping}[n] = 2$
8 **else if** $\theta_t^n > \theta_t^{M_2}$ for any $t \in 1, T$ **then**
 $\text{Mapping}[n] = 1$
9 **else**
10 **if** $\text{Event_Detection}(\theta^n, 15).Times \subset$
 $\text{Event_Detection}(\theta^{M_1}, 15, w).Times$ **then**
 $\text{Mapping}[n] = 1$
11 **else**
 $\text{Mapping}[n] = 2$
12 $\theta^{M_{\text{Mapping}[n]}} \leftarrow \theta^{M_{\text{Mapping}[n]}} - \theta^n$

Calibration

for $n \in 1, N$ **do**
13 $\theta^n \leftarrow \theta^n * \text{Step_Changes}(\theta^n, 15, w).Magnitude$
 $\div \text{Step_Changes}(\theta^{M_{\text{Mapping}[n]}}, 15, w).Magnitude$
14 $\theta^n \leftarrow \text{Normalize}(\theta^n, v)$

Clustering

for $n \in 1, N$ **do**
15 $\mu_k^n \leftarrow \text{Cluster}(\theta^n, K, kmeans++)$ for $k \in 1, K$
16 Solve combinatorial optimization using equations 1-6
17 **return** y^n

time period T , given by:

$$MNE(n) = \frac{\sum_{t=1}^T |\theta_t^n - y_t^n|}{\sum_{t=1}^T \theta_t^n} \quad (5)$$

- **RMS Error (RE Watts):** RMS error in power assignment to an appliance n per time slice t given by:

$$RE(n) = \sqrt{\frac{1}{T} \sum_{t=1}^T (\theta_t^n - y_t^n)^2} \quad (6)$$

Since both these quantities represent error, the lesser they are the better is the prediction.




Fig. 4: Confusion Matrix showing predicted state accuracy for Stove

B. Empirical Analysis

We performed empirical analysis on REDD dataset Home 2, which consists of 11 channels (including 2 mains and 9 appliances). We believe that the same analysis can be easily repeated across multiple homes. We aligned the data and downsampled it to one minute using mean filter. Since we had two weeks of clean data, we used the first week as the train set and the second week as the test set. We used INDiC algorithm described earlier to assign loads to different mains and calibrate appliance data. Table II shows the assignment of loads to different mains. Further this table also shows the learnt power states of these appliance via k-means++ clustering (which for several reasons is considered better than k-means) [20]. Refrigerator and lighting showed significant difference in power states post calibration. Based on prior experience and appliance circuitry, we believe that since only these two appliances needed calibration, it may be a case that the appliance level monitor measured real power instead of apparent power. These loads constitute a major chunk of Mains 2 power. Figure 5 shows the reduction in unassigned power due to calibrating these two appliances. Two loads - washer dryer and disposal did not have significant usage and we chose not to consider them in the analysis.

To show the significance of load division and calibration, we applied Combinatorial optimization on the test set, considering 4 possible cases: i) no calibration, no load division; ii) no calibration, load division; iii) calibration, no load division; iv) calibration, load division. These results are presented in Table III. For the overall dataset, it can be seen that MNE reduces from 187% to 39%, RE reduces from 478 W to 168 W, after applying INDiC. All appliances show reduction in MNE and RE after applying INDiC. However, there is significant improvement in correctly predicting refrigerator and lighting. Figure 6 shows the confusion matrix for refrigerator prediction pre and post applying INDiC. It can be seen that after applying INDiC there is a vast improvement in predicting refrigerator's state 0 and 1.

We had used Combinatorial Optimization which is the simplest NIALM technique to show the improvements which can be made by load division and appliance calibration. We believe that using state of the art NIALM algorithms will improve the results by leaps and bounds.




Fig. 5: Mains 2 Break down by load




Fig. 6: Confusion Matrix for refrigerator disaggregation

VI. CONCLUSION AND FUTURE WORK

The conclusion goes here. We also provide mains load assignment of all 6 homes from REDD to further the research in this direction.

- Applying model on noisy datasets
- 2 D CO (when Real and Reactive Power are known)
- Factoring in Time of Day etc.

TABLE II: Mains assignment and appliance states power

Appliance	Mains	States Power (W)					
		Pre calibration			Post calibration		
Refrigerator	2	7	162	423	9	210	423 ⁴
Microwave	2	10	832	1730	10	832	1730
Lighting	2	9	96	156	10	110	178
Dishwasher	1	0	256	1195	0	256	1195
Stove	1	0	374	-	0	374	-
Kitchen	1	5	727	-	5	727	-
Kitchen 2	1	1	204	1032	1	204	1032

TABLE III: MNE and RE with and without INDiC-CO

Appliance	Without calibration				With calibration			
	Without load division		With load division		Without load division		With load division	
	R.E. Watts	M.N.E. %	R.E. Watts	M.N.E. %	R.E. Watts	M.N.E. %	R.E. Watts	M.N.E. %
Refrigerator	136	109	71	32	130	95	59	21
Microwave	102	98	97	110	104	97	96	109
Lighting	51	164	48	195	44	83	38	60
Dishwasher	406	2947	63	100	377	2517	63	100
Stove	77	1191	36	281	75	1118	36	281
Kitchen	64	182	58	168	69	196	58	168
Kitchen 2	95	267	91	117	92	230	91	117
Overall	478	187	161	58	450	157	168	39

- Factoring in Appliance Correlation
- Factor in switch continuity, essentially leads to Factorial HMM
- Distributed NILM
- Adaptive Learning

ACKNOWLEDGMENT

The authors would like to thank TCS Research and Development for supporting the first author through PhD. fellowship. We would also like to thank NSF- DEITY for funding the project.

REFERENCES

- [1] S. Darby, "The effectiveness of feedback on energy consumption," *A Review for DEFRA of the Literature on Metering, Billing and direct Displays*, vol. 486, 2006.
- [2] G. W. Hart, "Nonintrusive appliance load monitoring," *Proceedings of the IEEE*, vol. 80, no. 12, pp. 1870–1891, 1992.
- [3] K. Carrie Armel, A. Gupta, G. Shrimali, and A. Albert, "Is disaggregation the holy grail of energy efficiency? the case of electricity," *Energy Policy*, 2012.
- [4] A. Zoha, A. Gluhak, M. A. Imran, and S. Rajasegarar, "Non-intrusive load monitoring approaches for disaggregated energy sensing: A survey," *Sensors*, vol. 12, no. 12, pp. 16 838–16 866, 2012.
- [5] M. Zeifman and K. Roth, "Nonintrusive appliance load monitoring: Review and outlook," *Consumer Electronics, IEEE Transactions on*, vol. 57, no. 1, pp. 76–84, 2011.
- [6] K. Suzuki, S. Inagaki, T. Suzuki, H. Nakamura, and K. Ito, "Nonintrusive appliance load monitoring based on integer programming," in *SICE Annual Conference, 2008*, 2008, pp. 2742–2747.
- [7] M. Baranski and J. Voss, "Genetic algorithm for pattern detection in nialm systems," in *Systems, Man and Cybernetics, 2004 IEEE International Conference on*, vol. 4, 2004, pp. 3462–3468 vol.4.
- [8] A. Ruzzelli, C. Nicolas, A. Schoofs, and G. M. P. O'Hare, "Real-time recognition and profiling of appliances through a single electricity sensor," in *Sensor Mesh and Ad Hoc Communications and Networks (SECON), 2010 7th Annual IEEE Communications Society Conference on*, 2010, pp. 1–9.
- [9] T. Zia, D. Bruckner, and A. Zaidi, "A hidden markov model based procedure for identifying household electric loads," in *IECON 2011 - 37th Annual Conference on IEEE Industrial Electronics Society*, 2011, pp. 3218–3223.
- [10] Z. Ghahramani, M. I. Jordan, and P. Smyth, "Factorial hidden markov models," in *Machine Learning*. MIT Press, 1997.
- [11] J. Z. Kolter and T. Jaakkola, "Approximate inference in additive factorial hmms with application to energy disaggregation," *Journal of Machine Learning Research - Proceedings Track*, vol. 22, pp. 1472–1482, 2012.
- [12] H. Kim, M. Marwah, M. F. Arlitt, G. Lyon, and J. Han, "Unsupervised disaggregation of low frequency power measurements," in *SDM*, 2011, pp. 747–758.
- [13] O. Parson, S. Ghosh, M. Weal, and A. Rogers, "Non-intrusive load monitoring using prior models of general appliance types," in *26th AAAI Conference on Artificial Intelligence*, 2012.
- [14] J. Z. Kolter and M. J. Johnson, "Redd: A public data set for energy disaggregation research," in *proceedings of the SustKDD workshop on Data Mining Applications in Sustainability*, 2011, pp. 1–6.
- [15] A. Filip, "Blued: A fully labeled public dataset for event-based non-intrusive load monitoring research."
- [16] S. Barker, A. Mishra, D. Irwin, E. Cecchet, P. Shenoy, and J. Albrecht, "Smart*: An open data set and tools for enabling research in sustainable homes," in *The 1st KDD Workshop on Data Mining Applications in Sustainability (SustKDD)*, 2011.
- [17] S. Martello and P. Toth, *Knapsack problems: algorithms and computer implementations*. John Wiley & Sons, Inc., 1990.

- [18] L. R. Rabiner, "A tutorial on hidden markov models and selected applications in speech recognition," in *Proceedings of the IEEE*, 1989, pp. 257–286.
- [19] M. Berges, E. Goldman, H. S. Matthews, and L. Soibelman, "Training load monitoring algorithms on highly sub-metered home electricity consumption data," *Tsinghua Science & Technology*, vol. 13, pp. 406–411, 2008.
- [20] D. Arthur and S. Vassilvitskii, "k-means++: The advantages of careful seeding," in *Proceedings of the eighteenth annual ACM-SIAM symposium on Discrete algorithms*. Society for Industrial and Applied Mathematics, 2007, pp. 1027–1035.