Q1.
```
import re

passwords = input("Type in :")
passwords = passwords.split(",")

accepted_pass = []
for i in passwords:

    if len(i) < 6 or len(i) > 12 :
        continue

    elif not re.search("([a-z])+", i) :
        continue

    elif not re.search("([A-Z])+", i) :
        continue

    elif not re.search("([0-9])+",i) :
        continue

    elif not re.search("([#@$])+", i) :
        continue

    else :
        accepted_pass.append(i)

print(("").join(accepted_pass))
```

Q2.

```python
def print_rangoli (size):
    width = size * 4 - 3
    string = ''

    for i in range (1, size+1):
        for j in range (0,i):
            string += chr (96+ size -j)
            if string len(string) < width :
                string += "-"
        for k in range (i-1,0,-1):
            string += chr (97+size -k )
            if len(string) < width :
                string += "-"
        print (string.center(width, '-'))
        string = ''

    for i in range (size-1,0,-1):
        string = ''
        for j in range (0,i):
            string += chr (96+ size -j)
            if length(string) < width:
                string += '-'
        for k in range (i-1,0,-1):
            string += chr (97+ size -k)
            if len (string) < width :
                string += '-'
        print (string.center (width, '-'))

if __name__ == '__main__':
    n = int (input())
    print_rangoli(n)
```