


§ 6 Applications of Depth-First Search

/ a generalization of preorder traversal */*

```
void DFS ( Vertex V ) /* this is only a template */
{  visited[ V ] = true; /* mark this vertex to avoid cycles */
  for ( each W adjacent to V )
    if ( !visited[ W ] )
      DFS( W );
} /* T = O( |E| + |V| ) as long as adjacency lists are used */
```

1. Undirected Graphs

DFS (0)



```
void ListComponents ( Graph G )
{  for ( each V in G )
    if ( !visited[ V ] ) {
      DFS( V );
      printf( "\n" );
    }
}

0 1 4 6 5 2 3
7 8
```


2. Biconnectivity

✎ v is an **articulation point** if $G' = \text{DeleteVertex}(G, v)$ has **at least 2** connected components.

✎ G is a **biconnected graph** if G is connected and has no articulation points.

✎ A **biconnected component** is a maximal **biconnected subgraph**.



[[Example]]



Note: No edges can be shared by two or more biconnected components. Hence $E(G)$ is partitioned by the biconnected components of G .


Finding the **biconnected components** of a connected undirected G

➤ Use **depth first search** to obtain a spanning tree of G



➤ Find the **articulation points** in G

- ⊕ The **root** is an articulation point iff it has **at least 2 children**
- ⊕ Any **other vertex u** is an articulation point iff u has **at least 1 child**, **and** it is impossible to **move down at least 1 step and then jump up to u 's ancestor**.



$$Low(u) = \min \{ Num(u), \min \{ Low(w) \mid w \text{ is a child of } u \}, \min \{ Num(w) \mid (u, w) \text{ is a back edge} \} \}$$



vertex	0	1	2	3	4	5	6	7	8	9
Num	4	3	2	0	1	5	6	7	9	8
Low	4	0	0	0	0	5	5	5	9	8

Therefore, u is an **articulation point** iff


- (1) u is the **root** and has **at least 2 children**; or
- (2) u is not the root, and has **at least 1 child** such that $Low(\text{child}) \geq Num(u)$.

Please read the pseudocodes on p.327 and p.329 for more details.

3. Euler Circuits



Draw each line exactly once without lifting your pen from the paper – *Euler tour*




Draw each line exactly once without lifting your pen from the paper, AND finish at the starting point – *Euler circuit*


[[Proposition]] An Euler circuit is possible only if the graph is connected and each vertex has an **even** degree.

[[Proposition]] An Euler tour is possible if there are exactly **two** vertices having odd degree. One must start at one of the odd-degree vertices.

DFS

**Note:**

- The path should be maintained as a linked list.
- For each adjacency list, maintain a pointer to the last edge scanned.
- $T = O(|E| + |V|)$



Find a simple cycle in an undirected graph that visits every vertex – *Hamilton cycle*