# Persistent and Fault-Tolerant UAV-IoT Coverage: A Multi-Agent Reinforcement Learning Framework for Joint Coverage, Connectivity, and Energy Management

Himanshu Nagwanshi
CS24BT055@iitdh.ac.in

Surya Prakash S
CS23BT068@iitdh.ac.in

Harsh Varshney
cs23bt004@iitdh.ac.in

Gaddam Viswaijeth
CS23BT076@iitdh.ac.in

Department of Computer Science and Engineering
Indian Institute of Technology Dharwad, Dharwad, India

***Abstract*—UAV swarms can provide temporary wireless coverage for Internet-of-Things (IoT) deployments in areas where fixed infrastructure is unavailable, damaged, or insufficient. Persistent operation is considerably harder than one-shot deployment because coverage, inter-UAV connectivity, battery depletion, limited charging resources, and UAV failures are tightly coupled. This paper formulates the problem of maintaining at least $K$ UAVs over every ground sensor while preserving a connected swarm and respecting finite energy and safety constraints. The resulting decision process is modelled as a cooperative Decentralized Partially Observable Markov Decision Process (Dec-POMDP). We propose a Multi-Agent Proximal Policy Optimization (MAPPO) controller under centralized training and decentralized execution (CTDE). Each UAV executes a shared policy from local observations, while a centralized critic is used only during training. The learned controller is combined with an explicit feasibility mask, a reserve-UAV recovery mechanism, and a small infrastructure-side charging arbitration procedure. A focused survey of ten closely related studies shows that coverage, connectivity, energy-aware operation, recharge scheduling, and fault recovery have largely been studied separately or in different combinations. The proposed framework targets their intersection and defines an evaluation protocol covering persistent coverage, connectivity availability, recovery delay, energy consumption, charging contention, safety, and scalability. Numerical performance claims are intentionally deferred until the proposed experiments are completed.**

***Index Terms*—UAV-IoT networks, persistent coverage, fault tolerance, multi-agent reinforcement learning, MAPPO, Dec-POMDP, connectivity maintenance, energy-aware coordination.**

## I. Introduction

The Internet of Things (IoT) increasingly operates in environments such as agricultural fields, disaster-affected regions, industrial sites, and remote monitoring areas where fixed communication infrastructure may be sparse or temporarily unavailable. UAVs can provide rapidly deployable aerial communication or sensing support because their positions can be changed in response to the spatial distribution of demand. Energy-efficient UAV control has therefore been studied for communication coverage, fairness, and connectivity, while aerial-base-station placement has been formulated as a learning-based spatial optimization problem [1], [2].

The practical difficulty changes substantially when the network must remain operational for a long mission rather than only achieve good coverage at one instant. The supplied project model considers $N$ UAVs operating over $M$ ground sensors, finite batteries, communication links between neighboring UAVs, a limited number of charging pads, and the possibility that an active UAV fails during the mission. The central requirement is persistent redundancy: every sensor should remain within coverage range of at least $K$ active UAVs. At the same time, the UAV communication graph should remain connected so that information can be forwarded through the swarm to a ground station or data sink.

These requirements conflict. A UAV that moves toward an uncovered sensor may leave a coverage gap elsewhere. A UAV that returns to charge may be the only communication bridge between two groups of UAVs. A failure removes both its coverage contribution and its communication links, requiring the remaining swarm to reconfigure. Charging is also a shared resource: several UAVs can become energy-critical simultaneously while only a small number of pads are available. Persistent service therefore requires a joint decision process rather than a sequence of unrelated coverage and charging heuristics.

A centralized controller faces a rapidly growing joint action space. In the proposed discrete action model, each UAV selects one of six actions: hover, move in one of four cardinal directions, or charge. The joint action space consequently contains $6^N$ combinations. This growth does not by itself make centralized learning impossible for every small swarm, but it makes explicit joint-action enumeration and centralized policy design progressively less attractive as $N$ increases. A decentralized execution architecture is therefore desirable for scalability and fault containment.

Multi-agent reinforcement learning (MARL) provides a natural framework for this setting. CTDE allows a centralized critic to use information unavailable to the individual UAV during training while retaining decentralized policies during deployment. MAPPO is particularly suitable because it combines centralized value estimation during training with

a policy-gradient actor that can be executed independently by each agent.

The research question addressed in this work is: *Can a decentralized MAPPO policy maintain persistent $K$-coverage and swarm connectivity while coordinating finite battery usage, charging, and single-UAV failure recovery without requiring a centralized trajectory controller?*

The contributions are:

1) A unified system model coupling persistent $K$-coverage, inter-UAV connectivity, finite battery energy, charging contention, and UAV failure recovery.
2) A CTDE MAPPO framework with parameter-shared decentralized actors, a centralized training critic, hard action feasibility masks, and an explicit reserve-UAV recovery mechanism.
3) A focused literature synthesis showing the difference between existing coverage, connectivity, recharge-scheduling, and fault-tolerant approaches and the combined problem considered here.
4) A benchmark and metric protocol designed to separate coverage, connectivity, energy, recovery, safety, and scalability effects rather than relying only on a single aggregate reward.

The remainder of the paper is organized as follows. Section II presents the literature survey and research gap. Section III defines the system architecture and mathematical model. Section IV presents the proposed MAPPO algorithm. Section V specifies the comparison models. Section VI defines the performance metrics and evaluation protocol. Section VII concludes the paper.

## II. Literature Survey

The survey is restricted to work that is directly related to at least one of four components of the target problem: UAV coverage/control, inter-agent connectivity, persistent energy-aware operation, or fault-tolerant swarm recovery. The ten core papers in Table I are discussed comparatively rather than as isolated summaries. MAPPO is cited separately as the underlying learning method [3].

A further recent line of work integrates communication and control directly within MARL. MAPPO itself is adopted from Yu et al. [3]. Sun et al. formulate joint resource allocation and 3D trajectory control and use action masking for constrained hybrid actions [11]. Carvalho and Aguiar address decentralized multi-agent coverage path planning with parameter sharing, CTDE, safety filtering, and zero-shot generalization [13]. Zhuang Chen et al. formulate UAV trajectory design for emergency communication as a constrained MDP and explicitly account for energy and turning behavior [12]. These works reinforce the practicality of CTDE, action masking, and structured rewards, but their primary objectives differ from persistent redundant coverage with explicit failure recovery.

### A. Research Gap

The literature can be grouped into complementary but incomplete directions. Energy-efficient coverage works jointly address coverage and energy, and some include connectivity, but they generally do not treat UAV failure and limited charging infrastructure as first-class elements of the same control problem [1], [4]. Connectivity research provides decentralized graph conditions and topology-repair mechanisms, but does not integrate persistent sensor coverage and energy-aware learning [5], [6]. Persistent-service studies explicitly model recharge schedules and energy limitations, yet typically assume fixed service locations and a planned fleet or replacement process rather than autonomous failure-driven reconfiguration [7], [8]. Recent fault-tolerant MARL and persistent-coverage MARL move closer to the target setting, but address different combinations of health state, outage memory, target assignment, or coverage objectives [9], [14].





Fig. 1. Color-coded system architecture. Active UAVs provide sensor coverage and maintain a range-limited communication graph. The reserve UAV supports post-failure recovery. The shared MAPPO actor is deployed locally, while the centralized critic is used only during training.

Based on this surveyed set, we did not identify a single framework that simultaneously models: (i) persistent $K$-coverage of fixed IoT sensors, (ii) explicit swarm-connectivity preservation using communication-graph criticality, (iii) finite battery operation with contested charging pads, (iv) failure-triggered reserve-UAV recovery, and (v) decentralized execution of the motion policy. The proposed formulation is designed around this intersection. This is a survey-derived gap statement, not a claim that no related component has ever appeared in the broader literature.

## III. System Model

### A. System Architecture

The system contains $N$ active UAVs, one reserve UAV, $M$ fixed IoT sensors, a ground data sink/base station, and $S$ charging pads distributed within the operating region $\Omega$. UAVs provide sensor coverage through a range-limited air-to-ground link and form a multi-hop communication network among themselves. Sensor data reaches the sink through the UAV communication graph whenever the graph is connected.

For tractability, the UAVs fly at a common nominal altitude $z_0$, so the decision process operates in the horizontal plane while the altitude remains part of the physical state. Let

TABLE I
FOCUSED LITERATURE SURVEY OF CLOSELY RELATED STUDIES.

| Ref. | Problem addressed | Method | Key findings / contribution | Limitation relative to this work | Relevance |
|---|---|---|---|---|---|
| [1] | Energy-efficient and fair UAV communication coverage. | DRL-based UAV control. | Jointly considers coverage, fairness, connectivity, and energy efficiency. | Does not model explicit UAV-failure recovery, charging-pad contention, or a persistent $K$-coverage SLA. | Baseline for coverage–connectivity–energy trade-offs. |
| [2] | Multi-aerial-base-station placement with irregular 3D coverage. | Prioritized-replay DDQN and two-level placement. | Uses a spatial representation to improve multi-ABS placement under terrain/blockage effects. | Primarily a placement problem; no persistent battery lifecycle or swarm fault recovery. | Motivates learning-based spatial control and size-invariant state representations. |
| [4] | Energy-efficiency optimization for multiple UAVs serving static/mobile users. | Cooperative MAD-DDQN. | Jointly optimizes 3D trajectories and user service while accounting for interference. | Energy efficiency is central; persistent $K$-coverage, charging coordination, and failure recovery are not jointly modelled. | Strong value-based MARL benchmark. |
| [5] | Decentralized biconnectivity in multi-robot systems. | Graph/Laplacian-based decentralized conditions. | Establishes sufficient conditions for avoiding articulation-point failures using neighbor-to-neighbor information. | No UAV coverage objective, finite battery, charging process, or learned policy. | Grounds the connectivity-risk feature and graph constraints. |
| [6] | Fault-tolerant ad hoc robot networks. | Movement-control and topology-repair algorithms. | Formalizes self-forming, self-healing, and self-organizing communication networks after node loss. | Focuses on network topology rather than persistent sensor coverage and battery-aware learning. | Provides the network-level motivation for failure recovery. |
| [7] | Recharging coordination for persistent multi-robot missions. | Combinatorial rendezvous planning with mobile charging robots. | Couples charging schedules with persistent task execution and routing constraints. | Charging is the main focus; UAV coverage/connectivity/failure are not unified in the same learned controller. | Supports explicit charging-resource modelling. |
| [8] | Persistent aerial service under limited flight and recharge times. | HORR and PHeRR scheduling schemes. | Provides fleet-size and recharge scheduling models for persistent service under energy constraints. | Service locations are scheduled rather than dynamically reconfigured after UAV failure. | Direct motivation for finite-energy persistent operation. |
| [9] | Fault-tolerant multi-UAV exploration with changing UAV health. | Fault-tolerant MARL with temporal information and health/topology inputs. | Allows UAV health degradation and faults during the mission and learns cooperative recovery behavior. | Exploration is the task; persistent sensor $K$-coverage and charging-pad contention are outside the main formulation. | Closest fault-aware MARL direction. |
| [10] | Robust UAV wireless coverage using multi-agent deep RL. | Centralized and decentralized deep Q-learning variants with a shared network. | Studies decentralized autonomous UAV coverage and compares centralized and decentralized control. | Focuses on coverage rather than explicit persistent redundancy, graph fault tolerance, and charging. | Recent decentralized coverage-learning benchmark. |
| [14] | Energy-aware persistent multi-UAV coverage with outage history. | POGS-QMIX with priority/outage guidance and return-energy masking. | Explicitly combines persistent coverage, outage memory, battery limits, and periodic recharging. | Uses a centralized online coordination layer and does not directly target articulation-point preservation plus reserve-UAV failure recovery in the same formulation. | Recent persistent-coverage benchmark and a key comparison model. |

$\mathbf{p}_i(t) = [x_i(t), y_i(t)]^\mathsf{T}$ denote the horizontal position of UAV $i$ and $\mathbf{q}_d = [x_d, y_d]^\mathsf{T}$ the position of sensor $d$.

### B. Dec-POMDP Formulation

The cooperative control problem is represented as

$$\mathcal{G} = \langle N, \mathcal{S}, \{\mathcal{A}_i\}, \{\mathcal{O}_i\}, \mathcal{T}, R, \gamma \rangle, \tag{1}$$

where $\mathcal{S}$ is the global state space, $\mathcal{A}_i$ is the action space of UAV $i$, $\mathcal{O}_i$ is its local observation space, $\mathcal{T}$ is the transition model, $R$ is the shared reward, and $\gamma \in (0, 1)$ is the discount factor. The training objective is

$$\max_{\pi} \ \mathbb{E}_\pi \left[ \sum_{t=0}^{T-1} \gamma^t R_t \right]. \tag{2}$$

### C. Global State

The state available to the centralized critic during training is

$$\mathbf{s}_t = \left\{ (\mathbf{p}_i, \mathbf{v}_i, b_i, m_i, F_i)_{i=1}^{N}, (\mathbf{q}_d)_{d=1}^{M}, \mathbf{Q}_t \right\}, \tag{3}$$

where $\mathcal{V}_t^{\text{act}} = \{ i \in \{1, \ldots, N\} : F_i(t) = 0 \}$ is the set of active UAVs, from which any UAV with $F_i(t) = 1$ is removed in all coverage, connectivity and energy sums. $\mathbf{v}_i$ is velocity, $b_i \in [0, 1]$ is normalized battery level, $m_i \in \{\text{serve}, \text{return}, \text{charge}\}$ is operating mode, $F_i \in \{0, 1\}$ is the failure indicator, and $\mathbf{Q}_t \in \{0, 1\}^S$ records charging-pad occupancy. A failed UAV is removed from the active set used in coverage and connectivity calculations.

### D. Local Observation

At deployment, UAV $i$ uses only locally available information:

$$\mathbf{o}_i(t) = \left[ \mathbf{p}_i, \mathbf{v}_i, b_i, \mathcal{N}_i, C_i^{\text{local}}, \rho_i, \tau_i^{\text{return}}, E_i^{\text{pad}} \right]. \tag{4}$$

Here $\mathcal{N}_i$ is the set of nearby UAVs, $C_i^{\text{local}}$ is the number of nearby sensors currently covered, $\rho_i$ is a locally computed bridge-risk estimate, $\tau_i^{\text{return}}$ is the estimated time until the return threshold is reached, and $E_i^{\text{pad}}$ is the estimated energy needed to reach a feasible charging pad.

Unlike the idealized global articulation-point indicator sometimes used in analysis, $\rho_i$ is intended to be computable during execution from neighborhood exchange. The simulator

TABLE II
LOCAL OBSERVATION VARIABLES AVAILABLE TO EACH DEPLOYED UAV.

| Feature | Symbol | Meaning at decision time |
|---|---|---|
| Position | $\mathbf{p}_i$ | Own horizontal location; altitude is fixed for the primary study. |
| Velocity | $\mathbf{v}_i$ | Current velocity for motion-limit awareness. |
| Battery | $b_i$ | Normalized remaining energy. |
| Neighbors | $\mathcal{N}_i$ | UAVs detected within $R_{\text{comm}}$. |
| Coverage | $C_i^{\text{local}}$ | Nearby sensors currently within coverage radius. |
| Bridge risk | $\rho_i$ | Local estimate of topology criticality. |
| Return urgency | $\tau_i^{\text{return}}$ | Estimated time until the return-energy threshold. |
| Pad energy | $E_i^{\text{pad}}$ | Estimated energy to the nearest feasible charging pad. |

TABLE III
DISCRETE ACTION SEMANTICS USED BY THE MAPPO ACTOR.

| Action | Effect |
|---|---|
| Hover | Remain at the current position and continue serving covered sensors. |
| $+x$ / $-x$ | Move by one control step along the horizontal $x$ direction. |
| $+y$ / $-y$ | Move by one control step along the horizontal $y$ direction. |
| Charge | Request charging when inside a pad service region; pad selection is handled by the scheduler. |

may additionally compute the exact articulation-point indicator for evaluation and for the centralized critic. This distinction avoids assuming that an individual UAV can magically obtain the complete global topology.

### *E. Discrete Action Space and Motion*

Each active UAV selects one of six actions:

$$\mathcal{A}_i = \{\text{Hover}, +x, -x, +y, -y, \text{Charge}\}, \qquad |\mathcal{A}_i| = 6. \quad (5)$$

For movement actions,

$$\mathbf{p}_i(t+1) = \Pi_\Omega\left(\mathbf{p}_i(t) + \mathbf{v}_i(t)\Delta t\right), \qquad \|\mathbf{v}_i(t)\| \le v_{\max}, \quad (6)$$

where $\Pi_\Omega$ projects into the permitted airspace. A charge request is feasible only when the UAV is inside a station neighborhood of a free pad. The RL layer does not select a pad as part of its action; pad choice is handled by the arbitration layer in Section III-I.

### *F. Persistent $K$-Coverage*

A UAV covers sensor $d$ in slot $t$ when

$$x_{id}(t) = \mathbb{1}[\|\mathbf{p}_i(t) - \mathbf{q}_d\|_2 \le R_{\text{cov}}]. \quad (7)$$

The number of active UAVs covering sensor $d$ is


$$n_d(t) = \sum_{i \in \mathcal{V}_t^{\text{act}}} x_{id}(t), \quad (8)$$

and the instantaneous normalized coverage score is

$$C_t = \frac{1}{M}\sum_{d=1}^{M} \min\left(\frac{n_d(t)}{K}, 1\right). \quad (9)$$

The instantaneous under-coverage rate is

$$U_t = \frac{1}{M}\sum_{d=1}^{M} \mathbb{1}[n_d(t) < K]. \quad (10)$$




Green dashed: sensor coverage.
Cyan solid: inter-UAV communication.

Fig. 2. Illustrative coupling between coverage and connectivity. Green dashed edges indicate coverage relationships, whereas cyan edges form the communication graph. Removing a topologically critical UAV can reduce both service redundancy and network connectivity.

The primary service condition is $n_d(t) \ge K$ for all $d$ whenever the geometry and available fleet make it feasible.

**Feasibility.** Persistent $K$-coverage is achievable only when the sensing radius is large enough for the available fleet. Comparing the area available for coverage with the area required gives a necessary condition: $N$ disks of radius $R_{\text{cov}}$ supply $N\pi R_{\text{cov}}^2$, while $K$-coverage of a region of area $A$ requires $KA$. Hence $R_{\text{cov}} \ge \sqrt{KA/(\pi N)}$. Accounting for the $\delta = \pi/(2\sqrt{3}) \approx 0.907$ packing density of congruent disks gives the stricter form $R_{\text{cov}} \ge \sqrt{KA/(\delta\pi N)}$. Substituting the parameters of Table VI ($A = 6400$ m$^2$, $M = 20$, $N = 5$, $K = 2$) yields $R_{\text{cov}} \ge 28.5$ m by area counting and 30.0 m after the packing correction, both satisfied by the chosen $R_{\text{cov}} = 35$ m. The resulting surplus ratio $\sigma = N\pi R_{\text{cov}}^2/(KA) = 1.50$ leaves margin for movement error and for a single-UAV failure, after which $\sigma = 1.20$ still exceeds one. The bound is necessary rather than sufficient, since it ignores coverage-disk overlap and the discreteness of the sensor layout; scenario S8 of Table X therefore sweeps $R_{\text{cov}}$ directly to characterize the transition.

### *G. Connectivity Model*

The inter-UAV communication graph is

$$G_t = (V_t, E_t), \qquad E_t = \{(i,j) : \|\mathbf{p}_i - \mathbf{p}_j\|_2 \le R_{\text{comm}}\}. \quad (11)$$

The swarm is connected when $G_t$ has one connected component. For analysis, the exact articulation-point indicator, where $G_t^{-i}$ denotes $G_t$ with vertex $i$ and its incident edges removed, is

$$kappa_i(t) = \mathbb{1}\left[G_t^{-i} \text{ is disconnected}\right]. \quad (12)$$





Fig. 3. Battery and failure state machine. Energy urgency triggers a return-to-charge transition; a detected failure transfers the mission to a recovery phase in which the reserve UAV can be activated when feasible.

The average criticality is

$$\text{Crit}_t = \frac{1}{|V_t^{\text{act}}|} \sum_{i \in V_t^{\text{act}}} \kappa_i(t). \tag{13}$$

The exact graph quantity is used by the simulator for evaluation. The actor receives the local proxy $\rho_i$ rather than the full graph.

### H. Battery Model

Let $B_i^{\max}$ be the battery capacity in joules and $E_i(t) = b_i(t) B_i^{\max}$ the remaining energy. The slot energy update is

$$E_i(t+1) = \text{clip}(E_i(t) - P_i(t)\Delta t + P_{\text{ch},i}(t)\Delta t,\ 0,\ B_i^{\max}), \tag{14}$$

where the action-dependent consumption is

$$P_i(t) = P_{\text{hover}} \mathbb{1}[a_i = \text{Hover}] + P_{\text{move}} \mathbb{1}[a_i \in \{+x, -x, +y, -y\}] + P_{\text{comm}}. \tag{15}$$

The charge power is zero unless the UAV is physically docked and granted service at a pad. A return threshold is defined by

$$E_i^{\text{req}}(t) = E_i^{\text{pad}}(t) + E_i^{\text{rejoin}}(t) + E^{\text{reserve}}, \tag{16}$$

and a return is mandatory when $E_i(t) \le E_i^{\text{req}}(t)$.

### I. Charging Coordination

Charging is a scarce resource. Let $y_{is} \in \{0, 1\}$ denote whether UAV $i$ is assigned to pad $s$. For a charge request, define a local assignment cost

$$c_{is} = \alpha \tilde{d}_{is} + \beta \tilde{q}_s + \mu \tilde{u}_i, \tag{17}$$

where $\tilde{d}_{is}$ is normalized distance, $\tilde{q}_s$ is normalized queue length, and $\tilde{u}_i$ is normalized battery urgency. The arbitration layer solves

$$\begin{aligned} \min_{\mathbf{y}} \quad & \sum_i \sum_s c_{is} y_{is} \\ \text{s.t.} \quad & \sum_s y_{is} \le 1,\ \forall i, \\ & \sum_i y_{is} \le 1,\ \forall s, \\ & y_{is} \in \{0, 1\}. \end{aligned} \tag{18}$$

Because only charge requests are handled, this is a small scheduling problem rather than a centralized trajectory controller. A Hungarian-style assignment implementation is sufficient for the expected fleet size.

### J. Safety Constraints

The environment enforces

$$\begin{aligned} &\|\mathbf{v}_i(t)\| \le v_{\max}, \qquad \mathbf{p}_i(t) \in \Omega, \\ &\|\mathbf{p}_i(t) - \mathbf{p}_j(t)\| \ge d_{\text{safe}},\ \forall i \ne j. \end{aligned} \tag{19}$$

An action is masked if it violates a locally predictable hard constraint such as workspace bounds, speed, minimum separation, or invalid charging. Connectivity is not assumed to be perfectly predictable from one-hop observations; instead, the actor receives the local bridge-risk feature $\rho_i$ and the team reward explicitly penalizes connectivity fragility. This avoids claiming a global connectivity guarantee from purely local information.

### K. Failure and Recovery

A failure event changes $F_i$ from 0 to 1 at the detection instant $t_f$. One reserve UAV is maintained with sufficient energy for deployment when feasible. After a detected failure, the reserve is activated and the active UAVs continue using their decentralized policies. The recovery time is defined as

$$\tau_f = \inf \{\tau \ge 0 :\ n_d(t_f + \tau) \ge K,\ \forall d\}, \tag{20}$$

when recovery is achieved before the evaluation horizon. If recovery is impossible under the available fleet, the event is reported as an unrecovered failure rather than assigning an artificial recovery time.

A recovery-time guarantee is therefore conditional: the reserve mechanism can reduce the time required for reconfiguration, but it cannot mathematically guarantee restoration for arbitrary sensor layouts, fleet sizes, or multiple simultaneous failures. This distinction is important for a realistic system model.

### L. Primary Objective and Reward Function

The project formulation adopts a "service first, efficiency second" objective. The primary quantity is persistent service loss, represented by the fraction of IoT sensors that are below the required redundancy level. Let

$$J_{\text{out}}(\pi) = \mathbb{E}_\pi \left[ \sum_{t=0}^{T-1} \gamma^t U_t \right], \tag{21}$$

where $U_t$ is the under-coverage rate in (10). The control policy therefore prioritizes minimizing long-horizon service loss rather than minimizing energy alone.

The corresponding multi-objective optimization is

$$\begin{aligned} \min_{\pi} \quad & J_{\text{out}}(\pi) + \lambda_E J_E(\pi) + \lambda_D J_D(\pi) \\ & + \lambda_W J_W(\pi) + \lambda_R J_R(\pi) + \lambda_C J_C(\pi), \end{aligned} \tag{22}$$

subject to the physical constraints in Section III-J. The secondary terms represent energy expenditure, degraded-service

TABLE IV
TEAM REWARD TERMS AND THEIR INITIAL WEIGHTS.

| Term | Definition | Weight |
|---|---|---|
| $U_t$ | Under-coverage rate, (10) | $\lambda_O = 1.00$ |
| $E_t^{\text{cons}}$ | $\sum_i \Delta E_i(t) \,/\, (NB^{\max})$ | $\lambda_E = 0.10$ |
| $D_t^{\text{deg}}$ | 1 if any service requirement is violated | $\lambda_D = 0.50$ |
| $W_t^{\text{mov}}$ | distance flown / distance that changed coverage | $\lambda_W = 0.05$ |
| $R_t^{\text{rec}}$ | normalized recovery delay during recovery | $\lambda_R = 0.30$ |
| $\text{Crit}_t$ | Articulation-point average, (13) | $\lambda_C = 0.20$ |

TABLE V
HARD CONSTRAINTS VERSUS LEARNED TRADE-OFFS.

| Constraint | Mathematical form | Enforcement / evaluation |
|---|---|---|
| Speed | $\|\mathbf{v}_i\| \le v_{\max}$ | Built into the action model and feasibility mask. |
| Workspace | $\mathbf{p}_i \in \Omega$ | Action mask prevents leaving the allowed region. |
| Separation | $\|\mathbf{p}_i - \mathbf{p}_j\| \ge d_{\text{safe}}$ | Action mask prevents predicted collisions. |
| Battery reachability | $E_i \ge E_i^{\text{req}}$ before departure | Prevents continuation when reaching a feasible charger is unsafe. |
| Charging capacity | At most one UAV per pad | Explicit pad assignment / scheduler. |
| $K$-coverage | $n_d(t) \ge K$ | Collective service objective and evaluation metric; not guaranteed by a single-agent mask. |
| Connectivity | $G_t$ connected | Topology-aware reward and connectivity metric. |
| Recovery | $\tau_f \le \tau_{\max}$ when feasible | Measured scenario requirement, not an unconditional guarantee. |

time, unnecessary movement, recovery delay, and topology criticality, respectively.

For reinforcement learning, the constrained objective is converted into a shared team reward:

$$r_t = -\big(\lambda_O U_t + \lambda_E E_t^{\text{cons}} + \lambda_D D_t^{\text{deg}} + \lambda_W W_t^{\text{mov}} + \lambda_R R_t^{\text{rec}} + \lambda_C \text{Crit}_t\big). \tag{23}$$

Since the learner maximises expected return while the control objective of (22) is a minimisation, the team reward of (23) is the negated weighted cost, and the two are equivalent up to sign. Table IV defines each term and gives the initial weights used in this work. The weight $\lambda_O$ is chosen to dominate the secondary efficiency terms, so that the learned controller does not sacrifice persistent service merely to reduce energy consumption or flight distance. The individual objective components remain separate evaluation metrics rather than being hidden inside a single final score.

All six quantities are dimensionless and lie in $[0, 1]$, so the weights are directly comparable; $U_t$ and $\text{Crit}_t$ are already normalized in (10) and (13). The values are initial settings to be tuned on a validation set; the ordering $\lambda_O \gg \lambda_D \ge \lambda_R > \lambda_C \ge \lambda_E \ge \lambda_W$ is the part on which the formulation depends.

### M. Parameter Settings and Scope

Table VI gives the initial simulation configuration derived from the project layout. These are implementation parameters for the proposed simulator rather than experimentally calibrated real-flight values.

TABLE VI
INITIAL SIMULATION PARAMETERS.

| Parameter | Symbol | Value |
|---|---|---|
| Active UAVs | $N$ | 5 |
| Reserve UAVs | $N_R$ | 1 |
| IoT sensors | $M$ | 20 |
| Operating region | $\Omega$ | $80 \times 80$ m$^2$ |
| Coverage radius | $R_{\text{cov}}$ | 35 m |
| Communication radius | $R_{\text{comm}}$ | 40 m |
| Nominal altitude | $z_0$ | 50 m |
| Coverage target | $K$ | 2 |
| Control interval | $\Delta t$ | 0.2 s |
| Maximum speed | $v_{\max}$ | 5 m/s |
| Safety distance | $d_{\text{safe}}$ | 5 m |
| Battery capacity | $B^{\max}$ | 30,000 J |
| Hover power | $P_{\text{hover}}$ | 50 W |
| Move power | $P_{\text{move}}$ | 75 W |
| Avionics and comms power | $P_{\text{elec}}$ | 5 W |
| RF transmit power | $P_{\text{tx}}$ | 0.5 W |
| Charge increment | – | 0.0002 battery fraction/step |
| Episode length | $T$ | 10 000 steps (2000 s) |

The control interval is chosen so that the relative displacement between two consecutive steps, $2v_{\max}\Delta t = 2$ m, is smaller than the safety distance $d_{\text{safe}} = 5$ m; a coarser step would allow a closing pair to cross the separation constraint between two samples. The charge increment is quoted per step and is therefore scaled with $\Delta t$. The resulting charge time is shorter than a real constant-current pack of this capacity would require, because a real pack would not complete a full charge within a tractable episode; this is stated as a modelling assumption rather than a physical prediction, and it means the cost of charging contention in (IX) is a lower bound. The nominal altitude is consistent with the coverage radius: a $74^\circ$ downward sensor at 50 m yields a footprint half-width of 37 m. The two power entries are distinct: $P_{\text{elec}}$ is the total avionics and communications budget, whereas $P_{\text{tx}}$ is the radiated transmit power, which is bounded by the 1 W ceiling of IEEE 802.11 and is two orders of magnitude below the avionics budget.

Within scope are spatial $K$-coverage, range-limited UAV connectivity, battery depletion, charging contention, single-UAV failure recovery, collision avoidance, and decentralized motion-policy execution. The primary model intentionally abstracts stochastic PHY-layer fading, detailed aerodynamic dynamics, obstacles, wind, battery aging, GPS denial, sensor failures, and multiple simultaneous UAV failures. These can be introduced as subsequent stress-test layers after the base control problem is validated.

## IV. PROPOSED ML ALGORITHM

### A. CTDE MAPPO

The proposed algorithm uses parameter-shared MAPPO. During training, the centralized critic observes $\mathbf{s}_t$ while every actor uses $\mathbf{o}_i(t)$. During deployment, the critic is removed and each UAV evaluates the same shared policy:

$$a_i(t) \sim \pi_\theta\left(a_i \mid \mathbf{o}_i(t)\right). \tag{24}$$





Fig. 4. MAPPO training and deployment pipeline. Solid arrows represent the environment/control loop. Dashed arrows denote training-only critic feedback and transfer of the learned actor to decentralized execution.

Parameter sharing is appropriate because the active UAVs have the same action semantics and physical model. It also avoids maintaining a separate actor network for each UAV.

For a collected rollout, the temporal-difference residual is

$$\delta_t = R_t + \gamma V_\phi(\mathbf{s}_{t+1}) - V_\phi(\mathbf{s}_t), \tag{25}$$

and the generalized advantage estimate (GAE) is

$$\widehat{A}_t = \sum_{l=0}^{T-t-1} (\gamma\lambda)^l \delta_{t+l}. \tag{26}$$

The probability ratio is

$$r_t(\theta) = \frac{\pi_\theta(a_t \mid o_t)}{\pi_{\theta_{\text{old}}}(a_t \mid o_t)}. \tag{27}$$

The clipped PPO objective is

$$L^{\text{actor}}(\theta) = -\mathbb{E}_t\big[\min(r_t\widehat{A}_t, \operatorname{clip}(r_t, 1-\epsilon, 1+\epsilon)\widehat{A}_t)\big]. \tag{28}$$

The critic is trained with

$$L^{\text{critic}}(\phi) = \mathbb{E}_t\left[\left(\widehat{R}_t - V_\phi(\mathbf{s}_t)\right)^2\right], \tag{29}$$

where $\widehat{R}_t = \widehat{A}_t + V_\phi(\mathbf{s}_t)$.

### B. Action Feasibility Mask

Before the sampled action is executed, the simulator evaluates the predicted next position and applies the following checks: workspace bounds, maximum speed, minimum UAV separation, charge validity, and connectivity-preservation constraints. If a candidate movement would disconnect the communication graph, it is masked in normal operation. During an active recovery event, the connectivity rule remains a hard constraint unless the simulator enters a predefined recovery mode in which temporary reconnection is required by the recovery objective.

This separation between policy learning and hard feasibility is important. The neural network learns how to trade off several feasible actions, while the safety layer prevents the network from selecting actions that violate non-negotiable physical constraints.

### C. Failure-Aware Execution

When a failure event is detected, the environment removes the failed UAV from the active graph, activates the reserve UAV if the reserve is available, and updates the local observations. The reserve UAV uses the same shared actor after insertion into the mission. The other UAVs also re-evaluate their local bridge-risk and coverage information. No prediction of the failure event is required; the controller reacts to the observed state change.

### D. Mapping from Model to Algorithm

The algorithm is deliberately aligned with the system model. Sensor positions produce the coverage quantities in (7)–(10); neighboring UAV positions produce the communication graph in (11); battery and action information produce the energy state in (14); charging requests enter the assignment problem in (18); and failure indicators activate the recovery process in (20). Thus, every actor input corresponds to an explicitly defined state quantity and every learned action has a defined environmental effect.

### E. Training and Generalization Protocol

Training episodes should randomize sensor layouts, initial UAV positions, initial battery levels, charging-pad locations within the allowed region, and failure times. A simple curriculum can be used: first train under no failures, then introduce single failures, and finally introduce simultaneous charging contention and near-disconnection scenarios. The final model should be evaluated on held-out random seeds and scenario configurations not used for parameter tuning.

A practical implementation can use a multilayer perceptron for the shared actor and centralized critic with normalized numerical features and masked action logits. If fixed-length neighbor features are insufficient, a permutation-invariant pooling operation or a small attention encoder can be added without changing the underlying Dec-POMDP formulation. A recurrent policy should be introduced only if experiments show that instantaneous observations do not provide sufficient temporal information.

**Algorithm 1** MAPPO training algorithm

Initialize shared actor $\pi_\theta$ and centralized critic $V_\phi$.
**for** each training episode **do**
  Reset UAV positions, batteries, sensors, charging pads, and failure schedule.
  **for** $t = 0, \ldots, T-1$ **do**
    Construct global state $\mathbf{s}_t$ and each local observation $\mathbf{o}_i(t)$.
    **for** each active UAV $i$ **do**
      Construct the feasible-action mask from Section III.
      Sample $a_i(t) \sim \pi_\theta(\cdot \mid \mathbf{o}_i(t))$ over feasible actions.
    **end for**
    Apply UAV actions and update positions.
    Recompute coverage and communication graph.
    Update battery states using (14).
    **if** one or more UAVs request charging **then**
      Solve the charging assignment in (18).
    **end if**
    **if** a UAV failure is detected **then**
      Activate the reserve UAV if feasible and update active-agent states.
    **end if**
    Compute $R_t$ from (23); store rollout transition data.
  **end for**
  Compute GAE advantages from (26).
  Update $\theta$ with the clipped PPO objective.
  Update $\phi$ with the critic loss.
**end for**
**return** Shared decentralized actor $\pi_\theta$.

TABLE VII
INITIAL MAPPO TRAINING CONFIGURATION.

| Parameter | Symbol | Initial value |
|---|---|---|
| Active UAVs | $N$ | 5 |
| IoT sensors | $M$ | 20 |
| Discount factor | $\gamma$ | 0.99 |
| PPO clipping | $\epsilon$ | 0.20 |
| GAE parameter | $\lambda$ | 0.95 |
| Control interval | $\Delta t$ | 0.2 s |

### F. Training Hyperparameters

The initial training configuration follows the values in the project presentation. These values are starting points for the implementation and can be tuned on a validation set without changing the system formulation.

### G. Implementation Plan

The implementation follows the three-stage validation strategy presented in the project plan. The objective is to validate the swarm-control logic before introducing detailed wireless-channel complexity.

Phase 1 contains geometric UAV motion, persistent $K$-coverage, connectivity, battery dynamics, charging coordination, failure/recovery, a heuristic controller, and MAPPO.





Fig. 5. Staged implementation plan. Phase 1 validates the control loop; Phase 2 adds wireless-network behaviour through OMNeT++/INET; Phase 3 introduces PHY-aware communication through Simu5G.

TABLE VIII
COMPARISON MODELS AND RATIONALE.

| Model | Type | Rationale |
|---|---|---|
| Fixed formation + threshold recharge | Rule-based | UAVs retain their initial formation and return to charge using a fixed battery threshold. Establishes a simple reference. |
| Greedy lowest-battery recharge | Rule-based | The most energy-critical UAV receives priority for charging. Tests energy-first scheduling without learned coordination. |
| Reactive reconfiguration | Heuristic | After a failure, remaining UAVs move toward uncovered sensor regions using deterministic coverage/connectivity rules. Tests fault recovery without MARL. |
| MAD-DDQN [4] | MARL | Representative value-based multi-UAV deep reinforcement learning benchmark for trajectory and energy control. |
| POGS-QMIX [14] | MARL | Recent persistent-coverage approach incorporating outage history, finite energy, and return-to-charge decisions. |
| MAHPPO-AM [11] | MARL | Recent PPO-family approach using action masking for joint UAV communication/control. Tests the added value of the proposed state, reward, charging, and recovery design. |
| Vanilla MAPPO [3] | MARL | Ablation reference: the same CTDE MAPPO learner with the proposed observation terms, reward shaping, charging arbitration, reserve-UAV mechanism and action mask removed. Isolates the contribution of the system design from that of the learning method. |

Once these components are stable, Phase 2 introduces wireless communication and network-level measurements. Phase 3 then adds PHY-aware communication. The same actor observation/action interface is retained across phases so that increasing simulator fidelity does not require redesigning the learning problem.

## V. COMPARISON MODELS

The comparison design preserves the practical baselines from the project presentation and adds recent learning-based methods required for a meaningful research comparison. The practical baselines test whether any adaptive coordination is useful; the MARL baselines test whether the proposed CTDE MAPPO design provides advantages over other learning formulations.

The fixed, greedy, and reactive controllers correspond directly to the practical alternatives already identified in the project plan. MAD-DDQN provides a value-based MARL comparison, while POGS-QMIX is particularly relevant to persistent coverage and energy-aware return behaviour. MAHPPO-AM provides a PPO-family comparison that also uses explicit action masking. Vanilla MAPPO is an internal ablation rather than a literature method: it applies the same

TABLE IX
PERFORMANCE METRICS AND OBJECTIVES.

| Metric | Definition and purpose |
|---|---|
| Persistent $K$-coverage | $C_K = \frac{1}{TM}\sum_t \sum_d \mathbb{1}[n_d(t) \geq K]$. Measures the fraction of sensor-slot pairs meeting the required redundancy. Higher is better. |
| Under-coverage | $\bar{U} = \frac{1}{T}\sum_t U_t$. Measures the fraction of sensors below $K$ coverage. Lower is better. |
| Connectivity availability | $A_G = \frac{1}{T}\sum_t \mathbb{1}[G_t \text{ connected}]$. Measures time for which the swarm is connected. Higher is better. |
| Connectivity fragility | Average $\mathrm{Crit}_t$ and number of partition events. Measures exposure to articulation-point failures and topology breaks. Lower is better. |
| Service continuity | Fraction of mission time for which both the $K$-coverage and connectivity requirements are satisfied. Measures end-to-end persistent service. |
| Outage severity | Time-integrated under-coverage during degraded and recovery intervals. Measures how much service is lost, not only whether a recovery eventually occurs. |
| Reserve utilization | Number of reserve activations, activation delay, and reserve mission time. Measures whether replacement capacity is used effectively. |
| Recovery | Mean/95th-percentile $\tau_f$, recovery success rate, and unrecovered-failure count. Measures fault tolerance directly. |
| Energy | Total energy consumption, energy per successfully covered sensor-slot, minimum battery level, and threshold violations. Measures efficiency and safety margin. |
| Charging | Mean wait time, denied requests, number of concurrent requests, and pad utilization. Captures contention and scheduling quality. |
| Movement | Total distance flown and unnecessary-movement ratio $W_t$. Quantifies motion overhead. |
| Safety | Collision events, out-of-bounds events, and hard-constraint violations. These should ideally be zero. |
| Scalability | Policy inference time and metric degradation as $N$ and $M$ increase. Tests the reason for adopting decentralized execution. |
| Stability | Mean and standard deviation across independent random seeds; training convergence time/episodes. Measures reproducibility. |

learner to the unmodified task so that the effect of the proposed system design can be separated from the effect of the learning algorithm. Because these literature methods solve related but not identical tasks, any adaptation to the common simulator must be documented rather than presented as an exact reproduction.

All models use the same sensor layouts, initial UAV positions, battery conditions, charging pads, failure traces, episode durations, and physical safety constraints. Where a literature method requires a different input representation or native action space, the adaptation should preserve its decision structure as far as possible. Results should be reported on common metrics when an exact one-to-one mapping is not available.

Ablation experiments should additionally remove one proposed mechanism at a time: connectivity-criticality input/reward, reserve-UAV recovery, charging arbitration, and action masking. This distinguishes improvements caused by the MAPPO learning method from improvements caused by the proposed system design.

## VI. PERFORMANCE METRICS

The evaluation should report separate metrics for service quality, connectivity, energy, charging, recovery, movement, safety, and scalability.

### A. Evaluation Scenarios

The first experiment varies sensor density while keeping the fleet fixed. The second varies fleet size to examine scalability. The third varies battery capacity and charge rate. The fourth varies the number of charging pads. The fifth varies $R_{\mathrm{comm}}$ and $R_{\mathrm{cov}}$ to create well-connected, marginally connected, and difficult coverage geometries. The sixth injects single-UAV failures at early, middle, and late mission times and at both central and peripheral locations.

TABLE X
PLANNED EXPERIMENTAL SCENARIOS AND RESEARCH QUESTIONS.

| ID | Variable | Research question |
|---|---|---|
| S1 | Sensor density | How does persistent coverage change as sensing demand becomes sparse or clustered? |
| S2 | Fleet size $N$ | Does decentralized execution retain performance as the number of UAVs grows? |
| S3 | Battery capacity | How sensitive are coverage and recovery to energy scarcity? |
| S4 | Charging pads $S$ | How does pad contention affect waiting time and mission continuity? |
| S5 | $R_{\mathrm{comm}}$ | How robust is the policy when connectivity becomes marginal? |
| S6 | $R_{\mathrm{cov}}$ | How does the controller respond to tighter coverage geometry? |
| S7 | Failure time/location | How quickly can the swarm recover from early/late and central/peripheral failures? |
| S8 | Combined stress | Can the policy jointly handle energy scarcity, weak connectivity, pad contention, and a failure? |

For each scenario, the same random seeds and initial conditions must be used for all comparison models. At least five independent seeds are recommended for each configuration, with the mean and sample standard deviation reported. When space permits, confidence intervals should also be shown. Raw reward curves may be included as supplementary evidence, but the principal conclusions should be based on the task-specific metrics in Table IX.

Ablation experiments should separately remove: (i) the connectivity-criticality feature/reward term, (ii) the reserve-UAV mechanism, (iii) charging arbitration, and (iv) action masking. This identifies whether each proposed component contributes a measurable effect. In particular, the comparison between the full proposed framework and vanilla MAPPO is necessary to distinguish improvements caused by MAPPO itself from improvements caused by the domain-specific system design.

## VII. EXPERIMENTAL DESIGN MATRIX

The final evaluation should vary the dominant environmental factors independently before combining them. Table X maps each experiment to a specific research question.

## VIII. CONCLUSION

This paper defines a persistent and fault-tolerant UAV-IoT coverage problem in which the swarm must jointly manage redundant sensor coverage, inter-UAV connectivity, finite battery energy, charging contention, and UAV failures. The proposed solution uses MAPPO under centralized training and decentralized execution, complemented by explicit feasibility masking, infrastructure-side charging arbitration, and a reserve-UAV recovery mechanism.

The formulation is intentionally implementable. The learned actors operate on quantities that a physical UAV can measure

or estimate locally, while the simulator computes the corresponding global quantities for training and evaluation. The literature survey indicates that the required components exist individually across coverage, connectivity, recharge scheduling, and fault-tolerant MARL studies, but the combined problem formulation remains a meaningful integration target. The experimental phase should therefore focus on whether the proposed combination produces measurable improvements in persistent coverage and recovery while keeping energy, charging, movement, and safety costs under control.

No performance advantage is claimed in this report before the experiments are executed. Once the implementation is complete, the same metric and comparison structure can be used to report both absolute results and trade-offs, including the possible cost of more conservative movement in exchange for improved connectivity robustness or faster recovery.

## REFERENCES


[1] C. H. Liu, Z. Chen, J. Tang, J. Xu, and C. Piao, "Energy-efficient UAV control for effective and fair communication coverage: A deep reinforcement learning approach," *IEEE Journal on Selected Areas in Communications*, vol. 36, no. 9, pp. 2059–2070, Sep. 2018, doi: 10.1109/JSAC.2018.2864373.

[2] J. Qiu, J. Lyu, and L. Fu, "Placement optimization of aerial base stations with deep reinforcement learning," arXiv:1911.08111, 2019.

[3] C. Yu, A. Velu, E. Vinitsky, J. Gao, Y. Wang, A. Bayen, and Y. Wu, "The surprising effectiveness of PPO in cooperative multi-agent games," in *Advances in Neural Information Processing Systems*, 2022.

[4] B. Omoniwa, B. Galkin, and I. Dusparic, "Optimizing energy efficiency in UAV-assisted networks using deep reinforcement learning," *IEEE Wireless Communications Letters*, vol. 11, no. 8, pp. 1590–1594, Aug. 2022, doi: 10.1109/LWC.2022.3167568.

[5] M. Zareh, L. Sabattini, and C. Secchi, "Decentralized biconnectivity conditions in multi-robot systems," in *Proc. IEEE Conf. Decision and Control (CDC)*, 2016, pp. 99–104, doi: 10.1109/CDC.2016.7798253.

[6] P. Basu and J. Redi, "Movement control algorithms for realization of fault-tolerant ad hoc robot networks," *IEEE Network*, vol. 18, no. 4, pp. 36–44, Jul.–Aug. 2004, doi: 10.1109/MNET.2004.1316760.

[7] N. Mathew, S. L. Smith, and S. L. Waslander, "Multi-robot rendezvous planning for recharging in persistent tasks," *IEEE Transactions on Robotics*, vol. 31, no. 1, pp. 128–142, Feb. 2015, doi: 10.1109/TRO.2014.2380593.

[8] E. Arribas, V. Cholvi, and V. Mancuso, "Optimizing UAV resupply scheduling for heterogeneous and persistent aerial service," *IEEE Transactions on Robotics*, vol. 39, no. 4, pp. 2639–2653, Aug. 2023, doi: 10.1109/TRO.2023.3263077.

[9] Z. Jiang, T. Song, B. Yang, and G. Song, "Fault-tolerant control for multi-UAV exploration system via reinforcement learning algorithm," *Aerospace*, vol. 11, no. 5, p. 372, May 2024, doi: 10.3390/aerospace11050372.

[10] M. R. Khan, G. R. V. Premkumar, and B. Van Scoy, "Robust UAV-oriented wireless communications via multi-agent deep reinforcement learning to optimize user coverage," *Drones*, vol. 9, no. 5, p. 321, Apr. 2025, doi: 10.3390/drones9050321.

[11] T. Sun, N. Guo, H. Gu, Y. Peng, and Z. Feng, "Integrated communication and control for energy-efficient UAV swarms: A multi-agent reinforcement learning approach," arXiv:2509.23905, 2025.

[12] Z. Zhuang, Y. Huang, C. Zhu, and W. Zhou, "Multi-agent reinforcement learning based trajectory design for UAV-assisted emergency wireless communication," in *Proc. 10th Int. Conf. Computer and Communication Systems (ICCCS)*, Chengdu, China, 2025, pp. 856–861, doi: 10.1109/ICCCS65393.2025.11069505.

[13] J. P. Carvalho and A. P. Aguiar, "Multi-agent reinforcement learning for zero-shot coverage path planning with dynamic UAV networks," *Robotics and Autonomous Systems*, vol. 195, p. 105163, Jan. 2026, doi: 10.1016/j.robot.2025.105163.

[14] H. Mei, C. Xu, R. Li, and X. Luo, "Energy-aware persistent multi-UAV coverage via reinforcement learning guided by user priority and outage," *Drones*, vol. 10, no. 9, p. 688, Sep. 2026, doi: 10.3390/drones10090688.