DAYFIT: Visual Clothing Search from Phone Photos

Progress report (internal, updated) — EECE 490 course project

Mouhammed Soumaille

November 11, 2026

Abstract

DAYFIT takes a phone photo of a garment and returns the most similar items from a shop catalogue. This report records everything done so far: the data and evaluation setup, every method tried, all results with 95% bootstrap confidence intervals and paired significance tests, and what we concluded from them. The main findings are: (i) fashion-specific pretrained models beat general CLIP by 40–54 points of Recall@1 and a colour histogram by far more; (ii) cheap tricks (multi-view catalogue embeddings, a two-model ensemble) add 2–5 significant points, while garment cropping with rembg significantly hurts; (iii) contrastive fine-tuning raises Recall@1 on our synthetic phone photos from 79.3% to 96.9% (medium) and from 51.0% to 84.7% (strong), but costs about 9 points of same-type Precision@5; and (iv) on real street photos (LookBench) the fine-tuning gain shrinks to +2.7 points (significant, $p = 0.014$), showing that most of the synthetic gain came from learning our own augmentation.

Contents

1 Problem and goal **2**

2 Data **2**

3 Methods **3**

4 Evaluation protocol **3**

5 Results on synthetic phone photos **4**

6 Fine-tuning **8**

7 Real photos: LookBench **9**

8 Conformal retrieval **9**

9 Summary of findings so far **10**

10 Limitations **10**

11 Remaining work **10**

A Reproducing the results **11**

1 Problem and goal

User and problem (approved proposal). Online shoppers and people browsing clothing catalogues often see a garment in a picture and want something similar, but find it hard to describe its colour, cut or style in a search bar. DAYFIT lets them search with the image instead: upload a photo, get the five most similar catalogue items.

How it is done today. Typing words into a search bar, or filtering by category and colour. A category + colour filter baseline that mimics this is planned (it uses the catalogue labels). [**Pending:** implement and evaluate.]

Question (approved). Can image features from a pretrained model find more relevant matches than a simple colour-based search, especially when the uploaded image is not a clean product photo?

Metrics. The proposal's main metric is **Precision@5**: are the five results the same kind of garment? We added a harder, second question: does the system find the *exact* item (Recall@1/@5)? The two can disagree (Section 6), so both are always reported.

Real-world constraint (approved). Robustness to imperfect user photos, while monitoring response time. Our evidence: the mild/medium/strong severity curve, real street photos (LookBench), the conformal shift experiment, and per-method latency (CPU latency in Docker pending).

Why ML and not a simpler method. The colour histogram finds the exact item for only 1% of medium phone photos and its Precision@5 is at chance level (0.08); a learned image embedding reaches 79–97% and 0.80–0.89 (Section 5.2).

2 Data

2.1 Catalogue

- Source: Kaggle *Fashion Product Images*. 6,197 items in 14 article types (Casual Shoes, Dresses, Heels, Jackets, Jeans, Kurtas, Shirts, Shorts, Sports Shoes, Sweatshirts, Tops, Track Pants, Trousers, Tshirts), 255–500 items per type.
- Near-duplicates removed with a difference hash (dHash) plus a coarse mean-colour check, so that a "duplicate" of the query cannot sit in the catalogue and inflate scores.
- Images: we first used the 60×80 px version, then swapped in high-resolution versions of the *same* items (longest side 512 px) from the full dataset. Same items, only image quality changed (see Section 5.1).

2.2 Queries: synthetic phone photos

294 catalogue items (21 per article type) are used as queries. Each appears as the clean catalogue image and as a synthetic "phone photo" at three severities. Since Kaggle images are a garment on a white background, a phone photo is simulated by: pasting the garment on a random background, rotating, cropping off-centre, changing brightness/contrast, blurring and JPEG compression.

severity	rotation (deg)	crop kept	brightness range	blur	JPEG quality
mild	±5	0.95	0.85–1.15	0.5	85
medium	±15	0.85	0.65–1.35	1.5	70
strong	±30	0.75	0.45–1.55	3.0	50

Table 1: Synthetic phone-photo severities (`data_prep/phone_aug.py`).

All three severities of one item use the *same* random draws (same background, same rotation direction, same crop position), only scaled. So when accuracy falls from mild to strong, it is because of severity and not because a different random background was picked. This makes the robustness curve a fair comparison.

2.3 Leakage controls

- Near-duplicate removal in the catalogue (above).
- Fine-tuning never sees the 294 test items: they are removed before training and appear only as gallery distractors.
- Fine-tuning uses its own validation set (300 held-out non-test items), so model selection (choosing the best epoch) never touches the test set.
- External test set: LookBench real street photos, which none of our models were trained or tuned on.

3 Methods

All methods implement the same interface (`build_index(catalog)`, `search(image, k)`), so the evaluation code treats them identically.

Random Returns random items. A floor for every metric (chance same-type Precision@5 is 0.07).

Colour histogram (non-ML baseline) HSV histogram with $8 \times 4 \times 4 = 128$ bins, normalised; similarity = cosine. Knows nothing about shape (a red T-shirt and red shoes look the same).

CLIP ViT-B/32 General-purpose pretrained image–text model (OpenAI weights), image encoder only.

FashionSigLIP, FashionCLIP Marqo's fashion-specific versions of SigLIP and CLIP, trained on fashion product data. Embeddings are normalised, so similarity = dot product; catalogue embeddings are computed once and cached.

Multi-view catalogue Each catalogue image is embedded three ways (original, padded to a white square, centre crop) and the three embeddings are averaged. Costs nothing at search time.

Garment cropping `rembg` (a pretrained segmentation network) cuts out the garment, we crop to its bounding box and paste it on white, so the query looks like a catalogue photo. Variants: crop the query only, or crop both query and catalogue.

Ensemble Concatenate the normalised embeddings of FashionSigLIP and FashionCLIP and divide by $\sqrt{2}$; the dot product is then the average of the two models' cosine similarities.

Fine-tuned FashionSigLIP Contrastive fine-tuning (Section 6).

Conformal retrieval Returns a variable-size set with a coverage guarantee (Section 8).

4 Evaluation protocol

Metrics.

- **Recall@1 / Recall@5** (exact item): is the source item the top result / in the top 5? Reported for phone queries only: for a clean query the query *is* the catalogue image, so Recall is 1.0 by construction.

- **Precision@5** (same article type): the source item is removed from the results, then we count how many of the top 5 have the same article type. This measures "are the alternatives sensible?", which matters if the exact item is out of stock.
- **Latency**: mean search time per query (embedding + search), on the laptop GPU (MPS).

Uncertainty. With only 294 queries every score is noisy. Each metric gets a 95% *bootstrap* confidence interval: resample the 294 queries with replacement, recompute the score, repeat 2,000 times, and take the 2.5th and 97.5th percentiles.

Comparing two methods. A *paired* bootstrap: both methods answered the same queries, so we resample queries and look at the *difference* between the two methods on each resample. Query difficulty cancels out, so this detects smaller real differences than checking whether two separate intervals overlap. With 2,000 resamples the smallest p-value we can resolve is about 1/2000, so a printed $p = 0$ is reported as $p < 0.0005$.

Multiple comparisons. Many tests are run. Results with p close to 0.05 are therefore described as borderline rather than as firm findings.

5 Results on synthetic phone photos

5.1 Resolution matters a lot

method	low-res (60×80)	high-res (max side 512)
CLIP	2.4	24.8
FashionSigLIP	6.1	79.3
FashionCLIP	15.3	79.3

Table 2: Recall@1 (%) on medium phone photos, same items and queries, only image resolution changed.

At 60×80 px, every model fails. The pretrained models expect inputs of about 224 px; upscaling a tiny image gives them almost no detail to work with. Moving to high-res images was the single most important data decision of the project.




Figure 1: Effect of image resolution.

5.2 The results ladder

		Recall@1 (%)			R@5 (%)	P@5		latency
row	method	mild	medium	strong	medium	clean	medium	(ms)
–	random	0.0	0.0	0.0	0.0	0.07	0.08	0.01
0	colour histogram	2.4	1.0	0.3	2.7	0.32	0.08	4
0c	colour histogram + crop	5.8	2.4	1.0	7.1	0.16	0.13	232
1	CLIP ViT-B/32	53.1	24.8	10.2	44.2	0.85	0.58	11
2	FashionSigLIP	94.9	79.3	51.0	91.2	0.90	0.89	18
2b	FashionCLIP	91.8	79.3	49.7	89.8	0.90	0.85	18
3	SigLIP + crop (query)	93.2	73.8	44.2	86.1	0.89	0.86	252
3b	SigLIP + crop (both)	93.9	74.5	39.1	86.1	0.90	0.86	253
3c	FashionCLIP + crop (query)	89.5	71.1	42.2	84.7	0.90	0.85	266
4	SigLIP + multi-view	96.9	82.3	54.4	92.2	0.90	0.89	19
4b	FashionCLIP + multi-view	94.9	81.6	54.1	94.2	0.89	0.86	18
5	ensemble	95.6	84.0	55.8	92.9	0.90	0.88	37
5b	ensemble, multi-view	96.3	85.4	58.2	94.9	0.90	0.88	37
7	fine-tuned SigLIP	**99.0**	**96.9**	**84.7**	**99.3**	0.81	0.80	14

Table 3: All methods on the 294 test queries. P@5 = same-article-type Precision@5 (chance 0.07). Selected 95% CIs (Recall@1): FashionSigLIP medium [74, 84], strong [45, 56]; ensemble multi-view medium [81, 89], strong [52, 64]; fine-tuned medium [95, 99], strong [80, 89]. Latency was measured on the laptop GPU while other jobs sometimes ran, so small differences (e.g. 14 vs 18 ms for two models of identical size) are noise.




Figure 2: Results ladder (Recall@1 on phone photos).

5.3 Which differences are real

change (Recall@1)	mild	medium	strong
colour histogram → CLIP	+50.7*	+23.8*	+9.9*
CLIP → FashionCLIP	+38.8*	+54.4*	+39.5*
FashionCLIP → FashionSigLIP	+3.1 (p=0.06)	+0.0 (p=1.0)	+1.4 (p=0.61)
SigLIP → + crop (query)	−1.7 (p=0.25)	−5.4*	−6.8*
SigLIP → + crop (both)	−1.0 (p=0.54)	−4.8* (p=0.04)	−11.9*
SigLIP → + multi-view	+2.0*	+3.1*	+3.4*
SigLIP → ensemble	+0.7 (p=0.64)	+4.8*	+4.8*
ensemble → ensemble multi-view	+0.7 (p=0.48)	+1.4 (p=0.11)	+2.4* (p=0.035)
SigLIP → fine-tuned	+4.1*	+17.7*	+33.7*
change (Precision@5)			
SigLIP → fine-tuned	−10.3*	−8.8*	−2.9* (p=0.047)

Table 4: Paired bootstrap differences in percentage points. * = significant at 0.05. Where no p is shown, $p < 0.03$; for the fine-tuning rows and the large early steps, $p < 0.0005$. Full table with CIs: `results/comparisons.csv`.

Interpretation.

- **Fashion-specific pretraining is the biggest single gain** (+39 to +54 points over CLIP). CLIP was trained on general internet images; the fashion models were trained on product photos, which is exactly our catalogue.
- **The two fashion models are tied.** No significant difference at any severity. We use FashionSigLIP as the base for fine-tuning because it is marginally ahead on strong photos and Precision@5, not because it is proven better.
- **Multi-view catalogue embeddings: small, consistent, free.** +2–3 points, significant at all severities, with no extra cost at search time (the extra work is done once, offline).
- **The ensemble helps on harder photos** (+4.8 points on medium and strong, no difference on mild), which suggests the two models make different mistakes. It doubles search time (37 vs 18 ms).
- **Garment cropping significantly hurts**, and cropping the catalogue too does not fix it, so the cause is not a framing mismatch between query and catalogue. The likely cause is that rembg's segmentation fails on our synthetic backgrounds (not yet inspected). Our synthetic photos contain no person or room, which is what cropping is meant to remove, so this test cannot show cropping's intended benefit. It also costs about 230 ms per query, about 12× the embedding time. For the colour histogram, cropping helps slightly (R@1 1.0 → 2.4% on medium, P@5 0.08 → 0.13), as expected: without cropping, the histogram is dominated by the background.
- **Mild photos are nearly solved** (95–97% before fine-tuning); medium and strong are where methods separate.

5.4 Robustness and cost




Figure 3: Recall@1 against photo severity. All methods degrade; the fashion models degrade far more gracefully than CLIP.




Figure 4: Accuracy vs search latency. Cropping is both slower and worse; the ensemble buys about 5 points for 2× latency.

6 Fine-tuning

6.1 Setup

- **Training pairs**: for each of the 5,603 training items (catalogue minus test items minus validation items), a fresh synthetic phone photo (random severity, new random draws every epoch) paired with its clean shop photo.
- **Loss**: contrastive with in-batch negatives. A batch of $B = 64$ pairs gives a 64×64 matrix of cosine similarities (divided by a temperature of 0.05). For phone photo i, the right answer is shop photo i and the other 63 are wrong; cross-entropy in both directions (phone→shop and shop→phone), averaged.
- **Hard batches**: every batch contains items of the *same* article type, so the negatives are similar garments (other T-shirts, not shoes).
- **Size**: only the last 4 of 12 transformer blocks (plus the final pooling/projection layers) are trained: 35.4M of the encoder's 92.9M parameters. Learning rate 10^{-5}, 5 epochs, about 26 minutes on the laptop GPU.
- **Validation**: 300 held-out non-test items, one fixed medium phone photo each, searched against the 5,903-image gallery (catalogue minus test items). The best epoch is kept.

6.2 Training curve

epoch	train loss	val Recall@1	val Recall@5
0 (pretrained)	–	0.807	–
1	0.501	0.957	0.997
2	0.162	0.973	0.997
3	0.114	**0.977** (saved)	0.997
4	0.091	0.977	1.000
5	0.091	0.977	1.000

Table 5: Fine-tuning log (`models/finetune_log.csv`).

Almost all of the gain comes in the first epoch (+15 points); the curve plateaus after epoch 3. The validation set is close to its ceiling (Recall@5 $\approx$ 100%), so it can no longer separate epochs. Sanity check: the pretrained model scores 80.7% on validation and 79.3% on the medium test queries, so the validation setup behaves like the test setup.

6.3 Test results and the trade-off

On the 294 test queries, fine-tuning raises Recall@1 significantly at every severity, and the gain grows with difficulty: +4.1 (mild), +17.7 (medium), +33.7 points (strong; 51.0% → 84.7%). Recall@5 on strong photos goes from 65.6% to 95.6%.

However, **same-type Precision@5 drops significantly**: −10.3 (mild), −8.8 (medium) and a small, borderline −2.9 points (strong, $p = 0.047$; it would not survive a Bonferroni correction over the six tests). The clean-query P@5 drops from 0.90 to 0.81.

Likely explanation (hypothesis). With same-type hard batches, every negative is the same article type as the positive. The loss therefore explicitly pushes *this* T-shirt away from all the *other* T-shirts. The model becomes very good at separating the exact item from lookalikes, but loses the property that T-shirts sit near T-shirts, so ranks 2–5 fill with items of other types. This is testable: retrain with random batches (`--hard_batches 0`) and see whether P@5 recovers. [**Pending:** ablation.]

Why this matters for the stakeholder. If the exact item is out of stock, the shop wants to offer similar items. Fine-tuning trades that ability for exact-match accuracy.

7 Real photos: LookBench

The fine-tuning caveat is that training and validation use the same synthetic augmentation as the test set, so part of the gain may be "learning the augmentation". Only real photos can check this. LookBench (Gao et al., 2026) is an open fashion-retrieval benchmark; we use its `real_streetlook` subset: 981 real street-style photos as queries against a 3,278-image product gallery. As in LookBench's own evaluation code, a result is correct if it has the same item ID as the query. Queries are LookBench's own garment crops (`--query_image image`).

method	Recall@1 (%)	Recall@5 (%)	Category P@5
FashionSigLIP	42.8 [39.8, 45.8]	64.1 [61.3, 67.0]	0.714 [0.692, 0.736]
fine-tuned	45.5 [42.6, 48.4]	67.3 [64.4, 70.2]	0.691 [0.670, 0.712]
paired difference	+2.7 [+0.5, +4.8]*	+3.2	−0.023 [−0.034, −0.012]*

Table 6: LookBench `real_streetlook`, 981 queries, 95% bootstrap CIs. * = significant in a paired bootstrap ($p = 0.014$ for Recall@1, $p < 0.0005$ for category P@5).

Interpretation.

- **The fine-tuning gain shrinks from +17.7 points (synthetic medium) to about +2.7 points (real).** Most of the synthetic gain was the model learning our augmentation, not getting better at real phone photos. This confirms the caveat with evidence.
- The small gain is real: the paired bootstrap gives +2.7 points [+0.5, +4.8], $p = 0.014$. Note that the two separate CIs overlap, yet the paired test is significant: because both models answer the same 981 queries, query difficulty cancels out in the differences.
- The category trade-off appears on real data too (−2.3 points category P@5, $p < 0.0005$), so it is not only a property of the synthetic photos.
- Absolute numbers are much lower on real photos (43% vs 79% Recall@1 for FashionSigLIP), so our synthetic phone photos are *easier* than reality. This is a limitation of the synthetic test set and must be stated.

Comparison with the LookBench paper. Our numbers are *not* directly comparable with the paper's. The paper's headline metric is *fine Recall@1*: the top result must have the query's category and all of its annotated attributes, searched against a 61,553-image corpus (positives plus Fashion200K distractors). We use the public release (3,278 gallery images, no distractors) and count a result as correct only if it has the same `item_ID`. The paper reports, for FashionSigLIP on RealStreetLook, fine Recall@1 55.2%, coarse (category-only) Recall@1 73.4% and nDCG@5 42.4. The closest comparable quantity we have is category Precision@5 = 71.4%, which is consistent with their 73.4% (not the same metric: ours averages over the top 5). The gap between our 42.8% and their 55.2% is therefore a difference in definition (smaller gallery vs. a different notion of "correct"), not evidence of a scoring bug. **[Pending:** optional: also record category Recall@1, which is exactly the paper's coarse Recall@1, for a direct check.]

8 Conformal retrieval

Idea. Instead of always returning 5 items, return a *set* that contains the true item with probability at least $1 - \alpha$ (e.g. 90%). A staff member then only checks this shortlist: small sets when the model is sure, larger sets when it is not.

Method (split conformal). Split the labelled phone queries at random into a calibration half and a test half.

- *Threshold variant*: on the calibration half let s_i = similarity between query i and its true item. Choose τ = the k-th smallest s_i with $k = \lfloor (n+1)\alpha \rfloor$. For a new query, return every item with similarity $\geq \tau$.
- *Relative variant*: let r_i = (best similarity of query i) − (similarity to its true item) ≥ 0. Choose q = the k-th smallest r_i with $k = \lceil (n+1)(1-\alpha) \rceil$. Return every item within q of the query's best similarity. Easy queries (clear winner) get small sets.

Guarantee. If calibration and test queries are exchangeable (drawn the same way), then for a new query $P(\text{true item} \in \text{set}) \geq 1 - \alpha$. Sketch: the new query's score is equally likely to land in any of the $n+1$ positions when sorted with the n calibration scores, so it falls beyond the k-th one with probability at most α. No assumption about the model or the data distribution is needed, only exchangeability.

Status. The code (`evaluation/conformal.py`) has unit tests and was validated on simulated scores: coverage hit the target; the relative variant gave sets about 30% smaller; and deliberately breaking exchangeability (calibrating on mild photos, testing on strong ones) dropped 90% target coverage to about 63%. That last result is the point of the shift experiment: the guarantee holds only when calibration data looks like deployment data. [**Pending:** run on real models: `ensemble_mv`, `fashion_siglip`, and now the fine-tuned model; add a coverage / set-size figure.]

9 Summary of findings so far

1. High-resolution images were essential (6% → 79% Recall@1 for FashionSigLIP).
2. Learned embeddings vastly beat the colour histogram (1% → 79% on medium photos).
3. Domain-specific pretraining is the largest gain; the two fashion models are tied.
4. Multi-view (+2–3, free) and the ensemble (+5, 2× latency) give significant extra gains.
5. rembg garment cropping significantly hurts on synthetic photos and is 12× slower.
6. Fine-tuning gives a large synthetic gain (+18 to +34 points) but only +2.7 on real photos (still significant, $p = 0.014$), and costs same-type Precision@5 (about −9 points synthetic, −2.3 real).
7. Synthetic phone photos are easier than real street photos (79% vs 43%).

10 Limitations

- The main test set is synthetic; real-photo results so far are LookBench only. Own photos of real garments are pending.
- 294 test queries is small; every number carries a CI, but small differences (<3 points) are hard to establish.
- Fine-tuning trains on the same augmentation family it is tested on (shown by LookBench).
- Latency so far is measured on a laptop GPU, not on the CPU a deployed service would use.
- Our LookBench metric (same `item_ID`, small gallery) differs from the paper's fine Recall@1, so our real-photo numbers cannot be placed on the paper's leaderboard.

11 Remaining work

1. Fix the fine-tuning trade-off: evaluate `ensemble_ft_mv`; random-batch ablation (`--hard_batches 0`); decide which model to recommend for "similar" vs "exact".
2. "How it's done today" baseline: filter by category + colour using catalogue labels.
3. Evaluate `finetuned_mv` and `ensemble_ft_mv` (synthetic and LookBench).
4. Conformal retrieval on real models, with figure; fine-tuning curve figure.

5. About 30 own photos (Precision@5).
6. Production: FastAPI `/search` (uploads kept in memory only), Streamlit UI, Docker, CPU latency in Docker.
7. Analysis: failure gallery, per-category breakdown, rembg failure inspection, manual check of about 30 queries.
8. Responsible ML with evidence: human oversight, robustness/shift, privacy, fairness.
9. README, final report, poster, talk, mock Q&A.

A Reproducing the results

Run from the repository root with the virtual environment active.

```
export PYTORCH_ENABLE_MPS_FALLBACK=1
python -m data_prep.build_catalog
python -m data_prep.hires_catalog \
    --zip data/raw_full/fashion-product-images-dataset.zip
python -m data_prep.make_queries
python -m evaluation.run_eval --method fashion_siglip
python -m evaluation.compare fashion_siglip finetuned
python -m evaluation.compare fashion_siglip finetuned --metric p5
python -m training.finetune
python -m evaluation.run_lookbench --subset real_streetlook \
    --method finetuned
python -m report.make_figures
```

Raw results: `results/summary.csv` (all metrics + CIs), `results/comparisons.csv` (paired tests), `results/lookbench_summary.csv`, `models/finetune_log.csv`.