

Source code: Handling User Authentication

Create package com.project.Authentication

Create AuthenticationApplication.java

```
package com.project.Authentication;

import org.springframework.boot.SpringApplication;
import org.springframework.boot.autoconfigure.SpringBootApplication; import
org.springframework.context.annotation.Import;
import
com.project.Authentication.controllers.AuthenticationController;
import com.project.Authentication.entities.User; import
com.project.Authentication.exceptions.UserNotFoundException; import
com.project.Authentication.services.AuthenticationService;

@SpringBootApplication
@Import({
    AuthenticationController.class,
    UserNotFoundException.class,
    AuthenticationService.class,
    User.class
})
public class AuthenticationApplication {

    public static void main(String[] args) {
        SpringApplication.run(AuthenticationApplication.class, args);
    }

}
```

Create package com.project.Authentication.controller

Create AuthenticationController.java

```
package com.project.Authentication.controllers; import
org.slf4j.Logger; import org.slf4j.LoggerFactory; import
org.springframework.beans.factory.annotation.Autowired;
import org.springframework.stereotype.Controller; import
org.springframework.web.bind.annotation.GetMapping; import
org.springframework.web.bind.annotation.PostMapping; import
org.springframework.web.bind.annotation.RequestParam; import
com.project.Authentication.entities.User;
```

```

import com.project.Authentication.services.AuthenticationService;

@Controller public class
AuthenticationController {

    Logger logger = LoggerFactory.getLogger(AuthenticationController.class);

    @Autowired

    AuthenticationService authService;

    @GetMapping("/")

    public String showGreeting() {

        return "greeting";

    }

    @GetMapping("/Auth")

    public String showLogin() {

        return "authenticate";

    }

    @PostMapping("/Auth")

    public String authenticateUser(@RequestParam("username") String username,
    @RequestParam("password") String pswd) {

        User user = authService.getUserByName(username);

        logger.info(user.getName() + " attempted to login with " + user.getPassword());        String path =
(authService.isValidPassword(pswd, user.getPassword())) ? "success" : "failure";

        logger.info("The path return: " + path);

        return path;

    }

}

```

Create package com.project.Authentication.entities

Crate User.java

```

package com.project.Authentication.entities;

import javax.persistence.Column; import
javax.persistence.Entity;

```

```
import javax.persistence.GeneratedValue;
import javax.persistence.GenerationType;
import javax.persistence.Id; import
javax.persistence.Table; import
javax.validation.constraints.NotNull;
```

```
@Entity
```

```
@Table(name = "user") public
```

```
class User {
```

```
    @Id
```

```
    @GeneratedValue(strategy = GenerationType.AUTO)
```

```
    @NotNull
```

```
    private Integer id;
```

```
    @Column(name = "name")
```

```
    @NotNull
```

```
    private String name;
```

```
    @Column(name = "email")
```

```
    @NotNull
```

```
    private String email;
```

```
    @Column(name = "password")
```

```
    @NotNull
```

```
    private String password;
```

```
    public User() {
```

```
        super();
```

```
    }
```

```
        public User(@NotNull String name, @NotNull String password) {  
            this.name = name;  
this.password = password;  
        }  
    }
```

```
        public User(@NotNull String name, @NotNull String email, @NotNull String password) {  
            super();  
            this.name = name;  
this.email = email;  
this.password = password;  
        }  
    }
```

```
        public Integer getId() {  
            return id;  
        }  
    }
```

```
        public void setId(Integer id) {  
            this.id = id;  
        }  
    }
```

```
        public String getName() {  
            return name;  
        }  
    }
```

```
        public void setName(String name) {  
            this.name = name;  
        }  
    }
```

```
        public String getEmail() {  
            return email;  
        }  
    }
```

```

public void setEmail(String email) {

    this.email = email;

}

public String getPassword() {

    return password;

}

public void setPassword(String password) {

    this.password = password;

}

@Override

public String toString() {

    return "User [id=" + id + ", name=" + name + ", email=" + email + ", password=" + password + "];"

}

}

```

Create package com.project.Authentication.exceptions

Create UserNotFoundException.java

```

package com.project.Authentication.exceptions;

public class UserNotFoundException extends RuntimeException {
    private static final long serialVersionUID = 1L;
}

```

Create package com.project.Authentication.repositories

Create AuthenticationRepository.java

```

package com.project.Authentication.repositories; import

java.util.Optional; import

org.springframework.data.repository.CrudRepository;

import org.springframework.stereotype.Repository; import

com.project.Authentication.entities.User;

@Repository

```

```

public interface AuthenticationRepository extends CrudRepository<User, Integer> { public
Optional<User> findUserByName(String name);
}

```

Create package com.project.Authentication.services

Create AuthenticationService.java

```

package com.project.Authentication.services; import java.util.Optional;

import org.springframework.beans.factory.annotation.Autowired; import

org.springframework.stereotype.Service; import

com.project.Authentication.entities.User; import

com.project.Authentication.exceptions.UserNotFoundException; import

com.project.Authentication.repositories.AuthenticationRepository;

@Service public class

AuthenticationService {

    @Autowired

    AuthenticationRepository authRepo;

    public User GetUserByName(String name) {

        Optional<User> found =

authRepo.findUserByName(name);                if(found.isPresent())

return found.get();                else throw new

UserNotFoundException();

    }

    public Boolean isValidPassword(String cmp, String actual) { return

((cmp.equals(actual)) ? true : false);

    }

}

```

Src/main/resources application.properties

```

spring.jpa.hibernate.ddl-auto=update
spring.datasource.url=jdbc:mysql://localhost:3306/Moulaali_db
spring.datasource.username=root spring.datasource.password=Aashiyana@11

```

logging.level.org.springframework.web: **DEBUG** spring.mvc.view.prefix=/WEB-INF/jsp/
spring.mvc.view.suffix=.jsp server.port=8080

Open src/main/webapp/jsp

Create authenticate.jsp

```
<%@ page language="java" contentType="text/html; charset=ISO-8859-1"    pageEncoding="ISO-8859-1"%>
<%@ taglib prefix="form" uri="http://www.springframework.org/tags/form"%>

<!DOCTYPE html>
<html>
<head>
<meta charset="ISO-8859-1">
<title>Authentication Page</title>
</head>
<h2>Login Page</h2>
<body>
welcome to the authentication page

<form:form action="Auth" method="post" commandName="login">
    <label for="username"> Username:</label>
    <input name="username" id="username" type="text" placeholder="Username" required/>
    <label for="password">Password:</label>
    <input name="password" id="password" type="password" placeholder="Password"
required/>
    <input type="submit" name="Submit"/>
</form:form>
</body>
</html>
```

Create failure.jsp

```
<%@ page language="java" contentType="text/html; charset=ISO-8859-1"    pageEncoding="ISO-8859-1"%>
<!DOCTYPE html>
<html>
<head>
<meta charset="ISO-8859-1">
<title>Failed Login</title>
</head>
<body>
<h1>You failed your login pal!
</h1><br/>
<a href="/Auth">Attempt Login again</a>
</body>
</html>
```

Create greeting.jsp

```
<%@ page language="java" contentType="text/html; charset=ISO-8859-1" pageEncoding="ISO-8859-1"%>
<!DOCTYPE html>
<html>
<head>
<meta charset="ISO-8859-1">
<title>Landing Page</title>
</head>
<h2>Welcome Page</h2>
<body> you reached the
landing page
<a href="Auth">Login</a>
</body>
</html>
```

Create success.jsp

```
<%@ page language="java" contentType="text/html; charset=ISO-8859-1" pageEncoding="ISO-8859-1"%>
<!DOCTYPE html>
<html>
<head>
<meta charset="ISO-8859-1">
<title>Successful Login Page</title>
</head>
<body>
<h1>Successful Login</h1>
</body>
</html>
```