

[Dashboard](#) / [My courses](#) / [CS23331-DAA-2023-CSE](#) / [Greedy Algorithms](#) / [4-G-Array Sum max problem](#)

<b>Started on</b>	Friday, 23 August 2024, 2:52 PM
<b>State</b>	Finished
<b>Completed on</b>	Friday, 23 August 2024, 2:52 PM
<b>Time taken</b>	46 secs
<b>Marks</b>	1.00/1.00
<b>Grade</b>	<b>10.00</b> out of 10.00 ( <b>100%</b> )

## Question 1

Correct

Mark 1.00 out of 1.00

Given an array of N integer, we have to maximize the sum of  $\text{arr}[i] * i$ , where  $i$  is the index of the element ( $i = 0, 1, 2, \dots, N$ ). Write an algorithm based on Greedy technique with a Complexity  $O(n \log n)$ .

Input Format:

First line specifies the number of elements- $n$

The next  $n$  lines contain the array elements.

Output Format:

Maximum Array Sum to be printed.

Sample Input:

```
5
2 5 3 4 0
```

Sample output:

```
40
```

**Answer:** (penalty regime: 0 %)

```
1 #include<stdio.h>
2 #include<stdlib.h>
3
4 int compare(const void *a, const void *b) {
5     return (*(int*)b - *(int*)a);
6 }
7
8 int main() {
9     int n;
10    scanf("%d", &n);
11    int arr[n];
12    for(int i = 0; i < n; i++) {
13        scanf("%d", &arr[i]);
14    }
15    qsort(arr, n, sizeof(int), compare);
16    int sum = 0;
17    for(int i = n-1; i >= 0; i--) {
18        sum += arr[n-i-1] * i;
19    }
20    printf("%d\n", sum);
21    return 0;
22 }
23
24
```

	Input	Expected	Got	
✓	5 2 5 3 4 0	40	40	✓

	Input	Expected	Got	
✓	10 2 2 2 4 4 3 3 5 5 5	191	191	✓
✓	2 45 3	45	45	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

◀ 3-G-Burger Problem

Jump to...

5-G-Product of Array elements-Minimum ▶