

SOLVENT-BASED AIR DUCT SEALANT WDS 1700

WDS – 1700 Duct Sealant is a solvent-based sealant suitable for use to seal up joints or gaps up to 1.5mm wide or 1.5mm in diameter.

Recommended for adhesion of metals such as zinc sheet and galvanised sheets. It has good initial grab and does not slump or sag when applied not more than 2mm thick. It will remain soft, flexible and not crack.

Technical Specification

Colour / Appearance	Grey
Principal Composition	Synthetic Rubber Water Resistant Good
Viscosity Cp	Flash Point Highly inflammable solvent but fire retardant when dried
Specific Gravity	1.3 ± 0.1
Total Solids	65 ± 3
Heat Resistance	Good up to 70°C for 8 hours
Packaging	19 KGs / Pail
Drying Time	24 hours depending on ambient temperature; maximum strength after 72 hours depending on ambient temperature
Shelf Life	Up to 6 months in cool place Viscosity increases with storage time
Electrical Conduction	Insulative
Application Method	1. Ensure surfaces to be bonded are clean, sound, dry and free from dust and oil 2. Apply onto seam

MANAGED &
MARKETED BY:

TSYL
MARKETING
SDN. BHD.

*Built to Supply,
Committed to Safety.*

202501017635 (1619049-W)
TIN NO. C60038149080

KL BRANCH

📍 22, Jalan Tago 11, Taman Perindustrian Tago,
52200 Kepong, Kuala Lumpur, Malaysia.

🏠 +60 3-6272 9166 📞 +60 12-448 9166, +60 12-329 9166
✉️ tsylmarketing@hotmail.com 🌐 www.insulationsolutions.com.my

KUCHING BRANCH

📍 Room 13, 2nd Floor, Lot 13011 (Sublot 29), Block 16, Kuching Central
Land District, 29 Galacity, Jalan Tun Jugah, 93350 Kuching, Sarawak.

📞 +60 12-258 9166, +60 12-287 9166
✉️ tsylmarketingkch@hotmail.com 🌐 www.insulationsolutions.com.my

