

		<h1 style="text-align: center;">INDUCTION MOTOR</h1> <h2 style="text-align: center;">DATA SHEET</h2>		PROJECT No.		P42-4160-201904-1162	
				HS No.		201904-6424_2000_003	
				L-SPEC No.		DSML10966F003H	
SHEET 1 OF 1				CUSTOMER :			
FOR PROPOSAL				JOB No. : N/A		ITEM No. :	
SERVICE : N/A				SITE :		QUANTITY 1 SET	
GENERAL DATA				PERFORMANCE DATA			
FRAME No.		80M		OUTPUT		1.1 kW	
TYPE		TEFC		POLES		2 P	
ENCLOSURE		TE		ROTOR TYPE		SQUIRREL CAGE	
COOLING METHOD		FC(IC411)		STARTING METHOD		DIRECT ON LINE	
INSULATION CLASS		F CLASS		PHASE		3 PHASE	
TEMP. RISE AT FULL LOAD				FREQUENCY		50 Hz	
RES. METHOD		80 K (at S.F:1.0)		SPEED (AT FULL LOAD)		2825 r/min	
RATING		S1		PRIMARY			
LOCATION		INDOOR		VOLTAGE		220 / 380 V	
ALTITUDE		LESS THAN 1000 m		NO LOAD CURRENT		2.9 / 1.7 A	
HUMIDITY		LESS THAN 80 %		FULL LOAD CURRENT		4.6 / 2.7 A	
AMBIENT TEMP.		40 °C		LOCKED-ROTOR CURRENT		770 %	
EXPLOSION PROOF TYPE		N/A		EFFICIENCY			
MOUNTING		B5		AT 1/2 LOAD		76.6 %	
BEARING TYPE		ANTI-FRICTION		AT 3/4 LOAD		78.6 %	
NDE/DE BRG. No.		6203ZZ / 6204ZZ		AT FULL LOAD		79.6 %	
BRG. LUBRICATION		N/A		POWER FACTOR			
PROTECTION GRADE		IP55		AT 1/2 LOAD		63.0 %	
SERVICE FACTOR		1.0		AT 3/4 LOAD		73.0 %	
DRIVE		DIRECT COUPLED		AT FULL LOAD		78.0 %	
SHAFT				TORQUE			
EXTENSION		SINGLE		FULL LOAD		0.37 kg-m	
EXTERNAL THRUST		N/A				3.6 N-m	
NOISE LEVEL(MEAN VALUE AT 1m FROM MOTOR)				LOCKED ROTOR		250 %	
NO-LOAD		STANDARD		BREAKDOWN		290 %	
VIBRATION		1.6 mm/s (r.m.s)		MOTOR GD ²		0.007 kg-m ²	
NUMBER OF CONSECUTIVE STARTS		COLD : 2 / HOT : 1 (2P)		MAX LOAD GD ² AT MOTOR SHAFT		0.5 kg-m ²	
ROTATION(VIEWED FROM DE)		C.C.W		MOTOR APPROX. WEIGHT		19 kg	
				PAINTING		0.5PB 3.2/4.4 (ENAMEL)	
ACCESSORIES (OPTIONAL)				SUBMITTAL DRAWINGS			
TEMPERATURE DETECTOR				OUTLINE DIMENSION		ES1AS33101	
WINDING		NO		CONDUIT BOX & COVER		ES1B100101	
TYPE		N/A		SPEED-TORQUE & CURRENT CURVE		1STP42-4160-201904-1162	
BEARING		NO		THERMAL LIMIT & TIME-CURRENT		1TLP42-4160-201904-1162	
TYPE		N/A		LOAD vs POWER & EFFICIENCY		1PEP42-4160-201904-1162	
SPACE HEATER		NO		<div><REMARKS></div> <div>1. ABOVE ALL DATA ARE CALCULATED AT 100% VOLTAGE.</div> <div>2. HIGH EFFICIENCY TYPE MOTOR</div>			
RATING		N/A					
APPLICATION STANDARDS							
IEC60034-1							
<div>< NOTE > 1. THESE DATA ARE ONLY DESIGN VALUES AND SHALL BE GUARANTEED WITH TOLERANCE OF APPLICATION STANDARD.</div> <div>2. EXCEPT FOR STATEMENTS SPECIFIED ON THIS SHEET, ANYTHING ELSE SHALL BE IN ACCORDANCE WITH MAKER'S STANDARD.</div> <div>3. THE TEMPERATURE MEASURED AT BEARING HOUSING DOES NOT EXCEED 105</div>							
				0		2019-05-09	
				REV. NO		DATE	
				PREPARED		CHECKED	
		APPROVED					