## 创建字典

● 创建目录(comm\_sex ,数据聚合或前端显示要用到)



• 创建字典值



# 前端页面怎么引用数据字典

• 导入依赖


```
import { getTypeValue } from '@/api/dict/dictValue/index';
```

• 获取字典

```
// comm_sex为字典目录值
getTypeValue('comm_sex').then(response => {
   this.sexOptions = response.data.rows;
});
```

### 用户模块性别示例(前端代码路

劲: /src/views/admin/user/index.vue)



● 表单下拉参考

```
<el-form-item label="性别">
        <el-select class="filter-item" v-model="form.sex"
placeholder="请选择">
        <el-option v-for="item in sexOptions" :key="item.id"
:label="item.labelDefault" :value="item.value"> </el-option>
        </el-select>
</el-form-item>
```

• 属性配置

```
sexOptions: [],
    dialogFormVisible: false,
    dialogStatus: '',
   userManager_btn_edit: false,
   userManager_btn_del: false,
   userManager_btn_add: false,
    textMap: {
     update: '编辑',
     create: '创建'
   tableKey: 0
},
created() {
 this.getList();
 this.userManager_btn_edit = this.elements['userManager:btn_edit'];
 this.userManager_btn_del = this.elements['userManager:btn_del'];
 this.userManager_btn_add = this.elements['userManager:btn_add'];
  getTypeValue('comm_sex').then(response =>
    this.sexOptions = response.data.rows;
  });
```

### 后端数据聚合

前提说明:该框架主要聚合的数据类型必须为List,可以解决大多数分页数据属性展示问题

• 引入数据聚合框架

```
@EnableAceMerge
```

• 加入聚合配置

```
# 跨服务数据合并
merge:
    enabled: true
    guavaCacheNumMaxSize: 1000 # 缓存总个数
    guavaCacheRefreshWriteTime: 10 # 缓存自动刷新时间,单位分钟
    guavaCacheRefreshThreadPoolSize: 10 # 缓存异步刷新线程数大小
    aop:
    enabled: true # 是否开启自动切面数据聚合
```

#### • 配置feign调用

特别说明: 聚合调用的返回结果一定为 Map<String,String>, 且参数只有一个 String。

```
@FeignClient(value = "ace-dict", configuration =
FeignApplyConfiguration.class)
public interface DictFeign {
    /**
    * 获取字典对对应值
    * @param code
    * @return
    */
    @RequestMapping(value = "/dictValue/feign/{code}", method =
RequestMethod.GET)
    public Map<String, String> getDictValues(@PathVariable("code")
String code);
}
```

#### • 配置实体关联

```
@Table(name = "base_user")
@AceAudit
public class User {
    @Id
    @GeneratedValue(generator = "UUID")
    private String id;

    private String username;
    // ...... 省略其他属性
    // 加入聚合属性,配置上边的feign调用
    @MergeField(key="comm_sex", feign = DictFeign.class,method = "getDictValues")
    private String sex;
}
```

- 聚合两种方式
- 1. 手动聚合(参考: UserBiz)

```
@Autowired
private MergeCore mergeCore;
```

```
@Override
public List<User> selectByExample(Object example) {
    List<User> users = super.selectByExample(example);
    try {
        mergeCore.mergeResult(User.class,users);
    } catch (Exception e) {
        e.printStackTrace();
    }finally {
        return users;
    }
}
```

### 2. aop自动聚合

```
// 加入MergeResult即可
@MergeResult
@Override
public List<Element> selectByExample(Object example) {
    return super.selectByExample(example);
}
```