

---

# **confduino Documentation**

***Release 0.0.2***

**ponty**

July 12, 2011

# CONTENTS

<b>1</b>	<b>Basic usage</b>	<b>2</b>
<b>2</b>	<b>Installation</b>	<b>3</b>
2.1	General . . . . .	3
2.2	Ubuntu . . . . .	3
2.3	Uninstall . . . . .	3
<b>3</b>	<b>Usage with libraries</b>	<b>4</b>
3.1	Arduino path . . . . .	4
3.2	List installed libraries . . . . .	4
3.3	Install new library . . . . .	5
3.4	Upgrade existing library . . . . .	5
3.5	Remove existing library . . . . .	5
<b>4</b>	<b>Usage with boards</b>	<b>7</b>
4.1	List installed boards . . . . .	7
4.2	Install new board . . . . .	11
4.3	Remove existing board . . . . .	12
<b>5</b>	<b>Usage with programmers</b>	<b>13</b>
5.1	List installed programmers . . . . .	13
5.2	Install new programmer . . . . .	13
5.3	Remove existing programmer . . . . .	14
<b>6</b>	<b>Examples</b>	<b>15</b>
<b>7</b>	<b>command line help</b>	<b>18</b>
7.1	lib . . . . .	18
7.2	board . . . . .	19
7.3	programmer . . . . .	19
<b>8</b>	<b>API</b>	<b>21</b>
8.1	lib . . . . .	21
8.2	board . . . . .	21
8.3	programmer . . . . .	22
<b>9</b>	<b>Indices and tables</b>	<b>23</b>
	<b>Python Module Index</b>	<b>24</b>



## confduino

**Date** July 12, 2011

**PDF** [confduino.pdf](#)

Contents:

confduino is an [arduino](#) library configurator

### Links:

- home: <https://github.com/ponty/confduino>
- documentation: <http://ponty.github.com/confduino>
- arduino libraries: <http://www.arduino.cc/en/Reference/Libraries>

### Features:

- list, install, remove [arduino](#) libraries
- install libraries from internet or local drive
- fix `examples` directory name
- clean library (`.*_*.py`)
- move examples to right location
- list, install, remove [arduino](#) programmers
- list, install, remove [arduino](#) boards
- written in python
- crossplatform
- can be used as a python library or as a console program
- unpacker backend: [patool](#)
- downloader backend: [urllib](#)

### Known problems:

- Python 3 is not supported
- tested only on linux
- some libraries with unusual structure can not be installed
- not all commands have console interface

# BASIC USAGE

install library:

```
>>> from confduino.libinstall import install_lib
>>> install_lib('http://arduino.cc/playground/uploads/Main/PS2Keyboard002.zip')
```

or on console:

```
python -m confduino.libinstall http://arduino.cc/playground/uploads/Main/PS2Keyboard002.zip
```

# INSTALLATION

## 2.1 General

- install `arduino`
- install `python`
- install `setuptools`
- install unpackers for `patool`
- install `patool` (`easy_install` does not work)
- install the program:

```
# as root
easy_install confduino
```

## 2.2 Ubuntu

```
sudo apt-get install arduino
sudo apt-get install python-setuptools
sudo apt-get install unzip
sudo easy_install http://sourceforge.net/projects/patool/files/0.13/patool-0.13.tar.gz/download
sudo easy_install confduino
```

## 2.3 Uninstall

first install `pip`:

```
# as root
pip uninstall confduino
```

# USAGE WITH LIBRARIES

## 3.1 Arduino path

If Arduino can not be found at default path, then ARDUINO\_HOME environment variable should be set.

on Ubuntu: in ~/.profile:

```
ARDUINO_HOME=~/.opt/arduino
export ARDUINO_HOME
```

**Default path:**

- Mac: /Applications/Arduino.app/Contents/Resources/Java
- Linux: /usr/share/arduino/

## 3.2 List installed libraries

From python:

```
>>> from confduino.liblist import libraries
>>> libraries()
['AdvButton', 'Bounce', 'CapSense', 'Charlieplex', 'DallasTemperature', 'DateTime', 'DateTimeStrings', 'DigitalToggle', 'EEPROM', 'Enerlib', 'EventFuse', 'Flash', 'FreqCounter', 'LiquidCrystal', 'Metro', 'MsTimer2']
```

From console:

```
$ python -m confduino.liblist
AdvButton
Bounce
CapSense
Charlieplex
DallasTemperature
DateTime
DateTimeStrings
DigitalToggle
EEPROM
Enerlib
EventFuse
Flash
FreqCounter
LiquidCrystal
Metro
MsTimer2
```

```
NewSoftSerial
OneWire
PID_v1
PS2Keyboard
PString
PinChangeInt
QtouchIWire
SSerial2Mobile
SerialIP
SevenSegment
Streaming
TimedAction
TimerOne
Tone
UComms
bassdll
```

### 3.3 Install new library

Existing library will not be changed.

From python:

```
>>> from confduino.libinstall import install_lib
>>> install_lib('http://arduino.cc/playground/uploads/Main/PS2Keyboard002.zip')
```

From console:

```
python -m confduino.libinstall http://arduino.cc/playground/uploads/Main/PS2Keyboard002.zip
```

### 3.4 Upgrade existing library

Same as install with *replace\_existing* option.

From python:

```
>>> from confduino.libinstall import install_lib
>>> install_lib('http://arduino.cc/playground/uploads/Main/PS2Keyboard002.zip', replace_existing=1)
```

From console:

```
python -m confduino.libinstall http://arduino.cc/playground/uploads/Main/PS2Keyboard002.zip --replace
```

### 3.5 Remove existing library

From python:

```
>>> from confduino.libremove import remove_lib
>>> remove_lib('PS2Keyboard')
```

From console:



```
python -m confduino.libremove PS2Keyboard
```

# USAGE WITH BOARDS

## 4.1 List installed boards

From python:

```
>>> from confduino.boardlist import boards
>>> boards()
AutoBunch(atmega168=AutoBunch(bootloader=AutoBunch(extended_fuses='0x00', file='ATmegaBOOT_168_ng.hex',
```

From console:

```
$ python -m confduino.boardlist
{'atmega168': {'bootloader': {'extended_fuses': '0x00',
                             'file': 'ATmegaBOOT_168_ng.hex',
                             'high_fuses': '0xdd',
                             'lock_bits': '0x0F',
                             'low_fuses': '0xff',
                             'path': 'atmega',
                             'unlock_bits': '0x3F'},
              'build': {'core': 'arduino',
                        'f_cpu': '16000000L',
                        'mcu': 'atmega168'},
              'name': 'Arduino NG or older w/ ATmega168',
              'upload': {'maximum_size': '14336',
                        'protocol': 'stk500',
                        'speed': '19200'}}},
{'atmega328': {'bootloader': {'extended_fuses': '0x05',
                             'file': 'ATmegaBOOT_168_atmega328.hex',
                             'high_fuses': '0xDA',
                             'lock_bits': '0x0F',
                             'low_fuses': '0xFF',
                             'path': 'atmega',
                             'unlock_bits': '0x3F'},
              'build': {'core': 'arduino',
                        'f_cpu': '16000000L',
                        'mcu': 'atmega328p'},
              'name': 'Arduino Duemilanove or Nano w/ ATmega328',
              'upload': {'maximum_size': '30720',
                        'protocol': 'stk500',
                        'speed': '57600'}}},
{'atmega8': {'bootloader': {'file': 'ATmegaBOOT.hex',
                           'high_fuses': '0xca',
                           'lock_bits': '0x0F',
                           'low_fuses': '0xdf',
```

```

        'path': 'atmega8',
        'unlock_bits': '0x3F'},
    'build': {'core': 'arduino',
              'f_cpu': '16000000L',
              'mcu': 'atmega8'},
    'name': 'Arduino NG or older w/ ATmega8',
    'upload': {'maximum_size': '7168',
               'protocol': 'stk500',
               'speed': '19200'}},
    'atmega88p': {'build': {'core': 'arduino',
                           'f_cpu': '16000000L',
                           'mcu': 'atmega88'},
                  'name': 'Atmega88 parallel 16MHz',
                  'upload': {'using': 'parallel'}},
    'atmega88u': {'build': {'core': 'arduino',
                           'f_cpu': '16000000L',
                           'mcu': 'atmega88'},
                  'name': 'Atmega88 usbaspp 16MHz',
                  'upload': {'using': 'usbaspp'}},
    'attiny2313at8': {'build': {'core': 'arduino',
                              'f_cpu': '8000000L',
                              'mcu': 'attiny2313'},
                     'name': 'ATTiny2313 @ 8 MHz',
                     'upload': {'maximum_size': '2048', 'using': 'usbaspp'}},
    'bt': {'bootloader': {'extended_fuses': '0x00',
                          'file': 'ATmegaBOOT_168.hex',
                          'high_fuses': '0xdd',
                          'lock_bits': '0x0F',
                          'low_fuses': '0xff',
                          'path': 'bt',
                          'unlock_bits': '0x3F'},
           'build': {'core': 'arduino',
                     'f_cpu': '16000000L',
                     'mcu': 'atmega168'},
           'name': 'Arduino BT w/ ATmega168',
           'upload': {'disable_flushing': 'true',
                     'maximum_size': '14336',
                     'protocol': 'stk500',
                     'speed': '19200'}},
    'bt328': {'bootloader': {'extended_fuses': '0x05',
                            'file': 'ATmegaBOOT_168_atmega328_bt.hex',
                            'high_fuses': '0xd8',
                            'lock_bits': '0x0F',
                            'low_fuses': '0xff',
                            'path': 'bt',
                            'unlock_bits': '0x3F'},
              'build': {'core': 'arduino',
                        'f_cpu': '16000000L',
                        'mcu': 'atmega328p'},
              'name': 'Arduino BT w/ ATmega328',
              'upload': {'disable_flushing': 'true',
                        'maximum_size': '28672',
                        'protocol': 'stk500',
                        'speed': '19200'}},
    'diecimila': {'bootloader': {'extended_fuses': '0x00',
                                'file': 'ATmegaBOOT_168_diecimila.hex',
                                'high_fuses': '0xdd',
                                'lock_bits': '0x0F',

```

```

        'low_fuses': '0xff',
        'path': 'atmega',
        'unlock_bits': '0x3F'},
    'build': {'core': 'arduino',
              'f_cpu': '16000000L',
              'mcu': 'atmega168'},
    'name': 'Arduino Diecimila, Duemilanove, or Nano w/ ATmega168',
    'upload': {'maximum_size': '14336',
               'protocol': 'stk500',
               'speed': '19200'}},
'fio': {'bootloader': {'extended_fuses': '0x05',
                      'file': 'ATmegaBOOT_168_atmega328_pro_8MHz.hex',
                      'high_fuses': '0xDA',
                      'lock_bits': '0x0F',
                      'low_fuses': '0xFF',
                      'path': 'arduino:atmega',
                      'unlock_bits': '0x3F'},
        'build': {'core': 'arduino:arduino',
                  'f_cpu': '8000000L',
                  'mcu': 'atmega328p'},
        'name': 'Arduino Fio',
        'upload': {'maximum_size': '30720',
                   'protocol': 'stk500',
                   'speed': '57600'}}},
'lilypad': {'bootloader': {'extended_fuses': '0x00',
                          'file': 'LilyPadBOOT_168.hex',
                          'high_fuses': '0xdd',
                          'lock_bits': '0x0F',
                          'low_fuses': '0xe2',
                          'path': 'lilypad',
                          'unlock_bits': '0x3F'},
            'build': {'core': 'arduino',
                      'f_cpu': '8000000L',
                      'mcu': 'atmega168'},
            'name': 'LilyPad Arduino w/ ATmega168',
            'upload': {'maximum_size': '14336',
                       'protocol': 'stk500',
                       'speed': '19200'}}},
'lilypad328': {'bootloader': {'extended_fuses': '0x05',
                             'file': 'ATmegaBOOT_168_atmega328_pro_8MHz.hex',
                             'high_fuses': '0xDA',
                             'lock_bits': '0x0F',
                             'low_fuses': '0xFF',
                             'path': 'atmega',
                             'unlock_bits': '0x3F'},
               'build': {'core': 'arduino',
                         'f_cpu': '8000000L',
                         'mcu': 'atmega328p'},
               'name': 'LilyPad Arduino w/ ATmega328',
               'upload': {'maximum_size': '30720',
                          'protocol': 'stk500',
                          'speed': '57600'}}},
'mega': {'bootloader': {'extended_fuses': '0xF5',
                       'file': 'ATmegaBOOT_168_atmega1280.hex',
                       'high_fuses': '0xDA',
                       'lock_bits': '0x0F',
                       'low_fuses': '0xFF',
                       'path': 'atmega',

```

```

        'unlock_bits': '0x3F'},
'build': {'core': 'arduino',
          'f_cpu': '16000000L',
          'mcu': 'atmega1280'},
'name': 'Arduino Mega (ATmega1280)',
'upload': {'maximum_size': '126976',
            'protocol': 'stk500',
            'speed': '57600'}},
'mega2560': {'bootloader': {'extended_fuses': '0xFD',
                             'file': 'stk500boot_v2_mega2560.hex',
                             'high_fuses': '0xD8',
                             'lock_bits': '0x0F',
                             'low_fuses': '0xFF',
                             'path': 'stk500v2',
                             'unlock_bits': '0x3F'},
             'build': {'core': 'arduino',
                       'f_cpu': '16000000L',
                       'mcu': 'atmega2560'},
             'name': 'Arduino Mega 2560',
             'upload': {'maximum_size': '258048',
                        'protocol': 'stk500v2',
                        'speed': '115200'}},
'mini': {'bootloader': {'extended_fuses': '0x00',
                         'file': 'ATmegaBOOT_168_ng.hex',
                         'high_fuses': '0xdd',
                         'lock_bits': '0x0F',
                         'low_fuses': '0xff',
                         'path': 'atmega',
                         'unlock_bits': '0x3F'},
          'build': {'core': 'arduino',
                    'f_cpu': '16000000L',
                    'mcu': 'atmega168'},
          'name': 'Arduino Mini',
          'upload': {'maximum_size': '14336',
                     'protocol': 'stk500',
                     'speed': '19200'}},
'pro': {'bootloader': {'extended_fuses': '0x00',
                       'file': 'ATmegaBOOT_168_pro_8MHz.hex',
                       'high_fuses': '0xdd',
                       'lock_bits': '0x0F',
                       'low_fuses': '0xc6',
                       'path': 'atmega',
                       'unlock_bits': '0x3F'},
        'build': {'core': 'arduino',
                  'f_cpu': '8000000L',
                  'mcu': 'atmega168'},
        'name': 'Arduino Pro or Pro Mini (3.3V, 8 MHz) w/ ATmega168',
        'upload': {'maximum_size': '14336',
                   'protocol': 'stk500',
                   'speed': '19200'}},
'pro328': {'bootloader': {'extended_fuses': '0x05',
                          'file': 'ATmegaBOOT_168_atmega328_pro_8MHz.hex',
                          'high_fuses': '0xDA',
                          'lock_bits': '0x0F',
                          'low_fuses': '0xFF',
                          'path': 'atmega',
                          'unlock_bits': '0x3F'},
           'build': {'core': 'arduino',
                     'f_cpu': '8000000L',
                     'mcu': 'atmega328p'},
           'name': 'Arduino Pro Mini (3.3V, 8 MHz) w/ ATmega328P',
           'upload': {'maximum_size': '14336',
                      'protocol': 'stk500',
                      'speed': '19200'}}}

```

```

        'f_cpu': '8000000L',
        'mcu': 'atmega328p'},
    'name': 'Arduino Pro or Pro Mini (3.3V, 8 MHz) w/ ATmega328',
    'upload': {'maximum_size': '30720',
               'protocol': 'stk500',
               'speed': '57600'}},
    'pro5v': {'bootloader': {'extended_fuses': '0x00',
                             'file': 'ATmegaBOOT_168_diecimila.hex',
                             'high_fuses': '0xdd',
                             'lock_bits': '0x0F',
                             'low_fuses': '0xff',
                             'path': 'atmega',
                             'unlock_bits': '0x3F'},
              'build': {'core': 'arduino',
                        'f_cpu': '16000000L',
                        'mcu': 'atmega168'},
              'name': 'Arduino Pro or Pro Mini (5V, 16 MHz) w/ ATmega168',
              'upload': {'maximum_size': '14336',
                         'protocol': 'stk500',
                         'speed': '19200'}}},
    'pro5v328': {'bootloader': {'extended_fuses': '0x05',
                                 'file': 'ATmegaBOOT_168_atmega328.hex',
                                 'high_fuses': '0xDA',
                                 'lock_bits': '0x0F',
                                 'low_fuses': '0xFF',
                                 'path': 'atmega',
                                 'unlock_bits': '0x3F'},
                 'build': {'core': 'arduino',
                           'f_cpu': '16000000L',
                           'mcu': 'atmega328p'},
                 'name': 'Arduino Pro or Pro Mini (5V, 16 MHz) w/ ATmega328',
                 'upload': {'maximum_size': '30720',
                            'protocol': 'stk500',
                            'speed': '57600'}}},
    'uno': {'bootloader': {'extended_fuses': '0x05',
                           'file': 'optiboot_atmega328.hex',
                           'high_fuses': '0xde',
                           'lock_bits': '0x0F',
                           'low_fuses': '0xff',
                           'path': 'optiboot',
                           'unlock_bits': '0x3F'},
            'build': {'core': 'arduino',
                      'f_cpu': '16000000L',
                      'mcu': 'atmega328p'},
            'name': 'Arduino Uno',
            'upload': {'maximum_size': '32256',
                       'protocol': 'stk500',
                       'speed': '115200'}}}

```

## 4.2 Install new board

Existing board will not be changed.

From python:

```
from confduino.boardinstall import install_board
from confduino.util import AutoBunch
from entrypoint2 import entrypoint

@entrypoint
def install():
    'install atmega88 board'
    atmega88 = AutoBunch()
    atmega88.name='Atmega88 usbasp 16MHz'

    atmega88.upload.using='usbasp'

    atmega88.build.mcu='atmega88'
    atmega88.build.f_cpu='16000000L'
    atmega88.build.core='arduino'

    install_board('atmega88', atmega88, replace_existing=0)
```

console is not implemented

## 4.3 Remove existing board

From python:

```
>>> from confduino.boardremove import remove_board
>>> remove_board('diecimila')
```

From console:

```
python -m confduino.boardremove diecimila
```

# USAGE WITH PROGRAMMERS

## 5.1 List installed programmers

From python:

```
>>> from confduino.proglist import programmers
>>> programmers()
AutoBunch(arduinoisp=AutoBunch(communication='serial', name='Arduino as ISP', protocol='stk500v1', speed='19200'),
```

From console:

```
$ python -m confduino.proglist
{'arduinoisp': {'communication': 'serial',
                'name': 'Arduino as ISP',
                'protocol': 'stk500v1',
                'speed': '19200'},
 'avrisp': {'communication': 'serial',
            'name': 'AVR ISP',
            'protocol': 'stk500v1'},
 'avrispmkii': {'communication': 'usb',
                'name': 'AVRISP mkII',
                'protocol': 'stk500v2'},
 'parallel': {'force': 'true',
              'name': 'Parallel Programmer',
              'protocol': 'dapa'},
 'stk200': {'force': 'true', 'name': 'STK200', 'protocol': 'dapa'},
 'usbasp': {'communication': 'usb', 'name': 'USBasp', 'protocol': 'usbasp'},
 'usbtinyisp': {'name': 'USBtinyISP', 'protocol': 'usbtiny'}}
```

## 5.2 Install new programmer

Existing programmer will not be changed.

From python:

```
from confduino.proginstall import install_programmer
from confduino.util import AutoBunch
from entrypoint2 import entrypoint

@entrypoint
def install(replace_existing=False):
    'install usbasp programmer'
```



```
usbasp = AutoBunch()
usbasp.name = 'USBasp'
usbasp.communication = 'usb'
usbasp.protocol = 'usbasp'

install_programmer('usbasp', usbasp, replace_existing=replace_existing)
```

console is not implemented

## 5.3 Remove existing programmer

From python:

```
>>> from confduino.progremove import remove_programmer
>>> remove_programmer('parallel')
```

From console:

```
python -m confduino.progremove parallel
```

# EXAMPLES

Many libraries are upgraded in examples/upgrademany.py, this can be started:

```
python -m confduino.examples.upgrademany
```

Code:

```
from confduino.libinstall import install_lib
from entrypoint2 import entrypoint

UPGRADE = True

def upgrade(url):
    print 'upgrading ' + url
    install_lib(url, UPGRADE)

@entrypoint
def upgrade_many():
    'upgrade many libs'

    # you can set your arduino path if it is not default
    #os.environ['ARDUINO_HOME'] = '/home/...'

    #####
    # arduino.cc
    #####
    upgrade('http://arduino.cc/playground/uploads/Main/PS2Keyboard002.zip')
    upgrade('http://arduino.cc/playground/uploads/Code/Metro.zip')
    upgrade('http://www.arduino.cc/playground/uploads/Main/MsTimer2.zip')
    # upgrade('http://www.arduino.cc/playground/uploads/Code/Time.zip')
    # upgrade('http://arduino.cc/playground/uploads/Main/LedControl.zip')
    # upgrade('http://www.arduino.cc/playground/uploads/Code/ks0108GLCD.zip')
    upgrade('http://arduino.cc/playground/uploads/Code/Bounce.zip')
    upgrade('http://arduino.cc/playground/uploads/Main/CapacitiveSense003.zip')
    upgrade('http://arduino.cc/playground/uploads/Main/PinChangeInt.zip')
    # upgrade('http://arduino.cc/playground/uploads/Code/TimerThree.zip')
    upgrade('http://arduino.cc/playground/uploads/Code/TimedAction-1_6.zip')
    # upgrade('http://www.arduino.cc/playground/uploads/Code/Time.zip')
    upgrade('http://arduino.cc/playground/uploads/Code/EventFuse.zip')
    upgrade('http://arduino.cc/playground/uploads/Code/Charlieplex.zip')
    upgrade('http://arduino.cc/playground/uploads/Code/DigitalToggle.zip')
    upgrade('http://arduino.cc/playground/uploads/Code/Enerlib.zip')

    upgrade('http://arduino.cc/playground/uploads/Code/AdvButton_11.zip')
    #upgrade('http://arduino.cc/playground/uploads/Code/AdvButton.zip') # old version
```

```
#####
# arduiniana.org
#####
# TODO: how to get latest version??
upgrade('http://arduiniana.org/PString/PString2.zip')
upgrade('http://arduiniana.org/Flash/Flash3.zip')
upgrade('http://arduiniana.org/NewSoftSerial/NewSoftSerial10c.zip')
upgrade('http://arduiniana.org/Streaming/Streaming4.zip')
# upgrade('http://arduiniana.org/PWMServo/PWMServo.zip')
# upgrade('http://arduiniana.org/TinyGPS/TinyGPS10.zip')

#####
# google
#####
upgrade('http://rogue-code.googlecode.com/files/Arduino-Library-Tone.zip')
# upgrade('http://arduino-playground.googlecode.com/files/LedDisplay03.zip')
upgrade('http://sserial2mobile.googlecode.com/files/SSerial2Mobile-1.1.0.zip')
# upgrade('http://webduino.googlecode.com/files/webduino-1.4.1.zip')
upgrade('http://arduino-pid-library.googlecode.com/files/PID_v1.0.1.zip')
upgrade('http://ideoarduinolibraries.googlecode.com/files/Qtouch1Wire.zip')
upgrade('http://arduino-timerone.googlecode.com/files/TimerOne-v2.zip')

#####
# others
#####
upgrade('http://download.milesburton.com/Arduino/MaximTemperature/DallasTemperature_370Beta.zip')
upgrade('http://interface.khm.de/wp-content/uploads/2009/01/FreqCounter1.zip')
# upgrade('http://github.com/wimleers/flexitimer2/zipball/v1.0')
# upgrade('http://www.state-machine.com/arduino/qp_arduino.zip')
# upgrade('ftp://momjian.us/pub/arduino/TButton.zip') # AdvButton is better
upgrade('http://johnmchilton.com/media/UComms.zip')
upgrade('http://www.shikadi.net/files/arduino/SerialIP-1.0.zip')
```

Install USBasp programmer:

```
python -m confduino.examples.usbasp
```

Code:

```
from confduino.progininstall import install_programmer
from confduino.util import AutoBunch
from entrypoint2 import entrypoint

@entrypoint
def install(replace_existing=False):
    'install usbasp programmer'
    usbasp = AutoBunch()
    usbasp.name = 'USBasp'
    usbasp.communication = 'usb'
    usbasp.protocol = 'usbasp'

    install_programmer('usbasp', usbasp, replace_existing=replace_existing)
```

Install STK200 programmer:

```
python -m confduino.examples.stk200
```

Code:

```
from confduino.proginstall import install_programmer
from confduino.util import AutoBunch
from entrypoint2 import entrypoint

@entrypoint
def install(replace_existing=False):
    'install stk200 programmer'
    bunch = AutoBunch()
    bunch.name = 'STK200'
    bunch.protocol = 'dapa'
    bunch.force = 'true'
    # bunch.delay=200

    install_programmer('stk200', bunch, replace_existing=replace_existing)
```

# COMMAND LINE HELP

## 7.1 lib

### 7.1.1 list

```
$ python -m confduino.liblist --help
usage: liblist.py [-h] [--debug]

print installed arduino libraries

optional arguments:
  -h, --help  show this help message and exit
  --debug     set logging level to DEBUG
```

### 7.1.2 install

```
$ python -m confduino.libinstall --help
usage: libinstall.py [-h] [-r] [--debug] url

install library from web or local files system

positional arguments:
  url                  web address or file path

optional arguments:
  -h, --help          show this help message and exit
  -r, --replace-existing
                        bool
  --debug             set logging level to DEBUG
```

### 7.1.3 remove

```
$ python -m confduino.libremove --help
usage: libremove.py [-h] [--debug] lib_name

remove library

positional arguments:
  lib_name    library name (e.g. 'PS2Keyboard')
```

optional arguments:

- h, --help show this help message and exit
- debug set logging level to DEBUG

## 7.2 board

### 7.2.1 list

```
$ python -m confduino.boardlist --help
usage: boardlist.py [-h] [--debug]
```

```
print boards from boards.txt
```

optional arguments:

- h, --help show this help message and exit
- debug set logging level to DEBUG

### 7.2.2 install

not implemented

### 7.2.3 remove

```
$ python -m confduino.boardremove --help
usage: boardremove.py [-h] [--debug] board_id
```

```
remove board
```

positional arguments:

- board\_id board id (e.g. 'diecimila')

optional arguments:

- h, --help show this help message and exit
- debug set logging level to DEBUG

## 7.3 programmer

### 7.3.1 list

```
$ python -m confduino.proglist --help
usage: proglist.py [-h] [--debug]
```

```
print programmers from programmers.txt
```

optional arguments:

- h, --help show this help message and exit
- debug set logging level to DEBUG

### 7.3.2 install

not implemented

### 7.3.3 remove

```
$ python -m confduino.progremove --help
usage: progremove.py [-h] [--debug] programmer_id
```

```
remove programmer
```

positional arguments:

programmer\_id programmer id (e.g. 'avrisp')

optional arguments:

-h, --help show this help message and exit  
--debug set logging level to DEBUG

# API

## 8.1 lib

```
confduino.liblist.libraries()  
    return installed library names  
  
confduino.liblist.libraries_dir()  
    return library root path  
  
confduino.liblist.print_libraries()  
    print installed arduino libraries  
  
confduino.libinstall.clean_lib_dir(root)  
    remove .* and _* files and directories under root  
  
confduino.libinstall.find_lib_dir(root)  
    search for lib dir under root  
  
confduino.libinstall.fix_examples_dir(lib_dir)  
    rename examples dir to examples  
  
confduino.libinstall.install_lib(url, replace_existing=False)  
    install library from web or local files system
```

### Parameters

- **url** – web address or file path
- **replace\_existing** – bool

**Return type** None

```
confduino.libinstall.move_examples(root, lib_dir)  
    find examples not under lib dir, and move into examples  
  
confduino.libremove.remove_lib(lib_name)  
    remove library
```

**Parameters** **lib\_name** – library name (e.g. 'PS2Keyboard')

**Return type** None

## 8.2 board

```
confduino.boardlist.boards()  
    read boards from boards.txt
```



`confduino.boardlist.boards_txt()`  
path of boards.txt

`confduino.boardlist.print_boards()`  
print boards from boards.txt

`confduino.boardinstall.install_board(board_id, board_options, replace_existing=False)`  
install board in boards.txt

**Parameters**

- **board\_id** – string identifier
- **board\_options** – dict like
- **replace\_existing** – bool

**Return type** None

`confduino.boardremove.remove_board(board_id)`  
remove board

**Parameters** **board\_id** – board id (e.g. ‘diecimila’)

**Return type** None

## 8.3 programmer

`confduino.proglist.print_programmers()`  
print programmers from programmers.txt

`confduino.proglist.programmers()`  
read programmers from programmers.txt

`confduino.proglist.programmers_txt()`  
path of programmers.txt

`confduino.proginstall.install_programmer(programmer_id, programmer_options, replace_existing=False)`  
install programmer in programmers.txt

**Parameters**

- **programmer\_id** – string identifier
- **programmer\_options** – dict like
- **replace\_existing** – bool

**Return type** None

`confduino.progremove.remove_programmer(programmer_id)`  
remove programmer

**Parameters** **programmer\_id** – programmer id (e.g. ‘avrisp’)

**Return type** None

# INDICES AND TABLES

- *genindex*
- *modindex*
- *search*

# PYTHON MODULE INDEX

## C

- `confduino.boardinstall`, [22](#)
- `confduino.boardlist`, [21](#)
- `confduino.boardremove`, [22](#)
- `confduino.libinstall`, [21](#)
- `confduino.liblist`, [21](#)
- `confduino.libremove`, [21](#)
- `confduino.proginstall`, [22](#)
- `confduino.proglist`, [22](#)
- `confduino.progremove`, [22](#)

# INDEX

## B

`boards()` (in module `confduino.boardlist`), 21  
`boards_txt()` (in module `confduino.boardlist`), 22

## C

`clean_lib_dir()` (in module `confduino.libinstall`), 21  
`confduino.boardinstall` (module), 22  
`confduino.boardlist` (module), 21  
`confduino.boardremove` (module), 22  
`confduino.libinstall` (module), 21  
`confduino.liblist` (module), 21  
`confduino.libremove` (module), 21  
`confduino.proginstall` (module), 22  
`confduino.proglist` (module), 22  
`confduino.progremove` (module), 22

## F

`find_lib_dir()` (in module `confduino.libinstall`), 21  
`fix_examples_dir()` (in module `confduino.libinstall`), 21

## I

`install_board()` (in module `confduino.boardinstall`), 22  
`install_lib()` (in module `confduino.libinstall`), 21  
`install_programmer()` (in module `confduino.proginstall`),  
22

## L

`libraries()` (in module `confduino.liblist`), 21  
`libraries_dir()` (in module `confduino.liblist`), 21

## M

`move_examples()` (in module `confduino.libinstall`), 21

## P

`print_boards()` (in module `confduino.boardlist`), 22  
`print_libraries()` (in module `confduino.liblist`), 21  
`print_programmers()` (in module `confduino.proglist`), 22  
`programmers()` (in module `confduino.proglist`), 22  
`programmers_txt()` (in module `confduino.proglist`), 22

## R

`remove_board()` (in module `confduino.boardremove`), 22  
`remove_lib()` (in module `confduino.libremove`), 21  
`remove_programmer()` (in module `conf-  
duino.progremove`), 22