## grammar - moses0.1

```
// GRAMMAR OF A STATEMENT
statement -> compound-statement
         | if-statement
         | while-statement
         | break-statement
         | continue-statement
         | return-statement
         | expression-statement
         | declaration-statement
if-statement ->
    "if" expression compound-statement "else" compound-statement
while-statement -> "while" expression compound-statement
break-statement -> "break" ";"
compound-statement -> "{" statement * "}"
continue-statement -> "continue" ";"
return-statement -> "return" expression? ";"
expression-statement -> expression? ";"
class-body -> "{" variable-declaration* "}"
// GRAMMAR OF EXPRESSION
expression -> assignment-expression
assignment-expression -> condition-or-expression
              | unary-expression assignment-operator condition-or-expression
assignment-operator -> "=" | "*=" | "/=" | "+=" | "-=" | "&&=" | "||="
cond-or-expression -> condition-and-expression
         | condition-or-expression "||" cond-andition-expression
cond-and-expression -> equality-expression
         | condition-and-expression "&&" equality-expression
equality-expression -> rel-expression
         | equality-expression "==" rel-expression
         | equality-expression "!=" rel-expression
rel-expression -> additive-expression
         | rel-expression "<" additive-expression
```

```
| rel-expression "<=" additive-expression
          | rel-expression ">" additive-expression
          | rel-expression ">=" additive-expression
additive-expression -> m-d-expression
          | additive-expression "+" m-d-expression
          | additive-expression "-" m-d-expression
multiplicate-expression -> u-expression
          | multiplicate-expression "*" u-expression
          | multiplicate-expression "/" u-expression
unary-expression -> "-" unary-expression
          | "!" unary-expression
         | ++ post-expression
          | -- post-expression
          | post-expression
postfix-expression -> primary-expression
          | post-expression . identifier
          | post-expression ++
          | post-expression --
primary-expression -> identifier arg-list?
          | "(" expression ")"
          | INTLITERAL
          | BOOLLITERAL
// GRAMMAR OF PARAMETERS
para-list -> "(" proper-para-list? ")"
proper-para-list -> para-declaration ( "," para-decl ) *
para-decl -> type identifier
arg-list -> "(" proper-arg-list ? ")"
proper-arg-list -> arg ("," arg) *
arg -> expression
// GRAMMAR OF DECLARATION
declaration-statement -> function-declaration
          | constant-declaration
          | variable-declaration
          | class-declaration
function-declaration -> identifier para-list compound-statement
variable-declaration -> "var" identifier initializer ";"
          | "var" identifier type-annotation ";"
```

```
class-declaration -> "class" identifier class-body ";"

constant-declaration -> "const" identifier init-expression ";"

| "const" identifier type-annotation ";"

init-expression -> "=" expression

type-annotation -> ":" type

// GRAMMAR OF PRIMITIVE TYPES

type -> "int" | "bool"

// GRAMMAR OF IDENTIFIERS

identifier -> ID

// TOP-LEVEL
```

top\_level: statement\*

## moses 0.1 - LL(1)

```
statement -> compound-statement | if-statement | while-statement | break-statement |
continue-statement | return-statement | expression-statement | declaration-statement
if-statement -> if expression compound-statement else compound-statement
while-statement -> while expression compound-statement
break-statement -> break;
compound-statement -> { statement-list }
statement-list -> EPSILON | statement statement-list
continue-statement -> continue;
return-statement -> return expression;
return-statement -> return;
expression-statement -> expression-list;
expression-list -> expression | EPSILON
class-body -> { variable-declaration-list }
variable-declaration-list -> variable-declaration variable-declaration-list | EPSILON
expression -> assignment-expression
assignment-expression -> condition-or-expression
              | u-expression assignment-operator condition-expression
assignment-operator -> = | *= | /= | += | -= | &&= | XX=
condition-or-expression -> condition-and-expression condition-or-expression-tail
condition-or-expression-tail
                                       EPSILON
                                                            XX
                                                                     condition-and-expression
condition-or-expression-tail
condition-and-expression -> equality-expression condition-and-expression-tail
```

```
condition-and-expression-tail -> && equality-expression equality-expression-tail | EPSILON
equality-expression -> rel-expression equality-expression-tail
equality-expression-tail -> EPSILON | == rel-expression equality-expression-tail | !=
rel-expression equality-expression-tail
rel-expression -> additive-expression rel-expression-tail
rel-expression-tail -> EPSILON | < additive-expression rel-expression-tail | <= additive-expression
rel-expression-tail | > additive-expression rel-expression-tail | >= additive-expression
rel-expression-tail
additive-expression -> m-d-expression additive-expression-tail
additive-expression-tail -> EPSILON | + m-d-expression additive-expression-tail | -
m-d-expression additive-expression-tail
m-d-expression -> u-expression m-d-expression-tail
m-d-expression-tail -> EPSILON | * u-expression m-d-expression-tail | / u-expression
m-d-expression-tail
u-expression -> - u-expression | ! u-expression | ++ post-expression | -- post-expression
              | post-expression
post-expression -> primary-expression | primary-expression post-expression-tail
post-expression-tail -> . identifier post-expression-tail | ++ post-expression-tail
              | -- post-expression-tail | EPSILON
primary-expression -> identifier | identifier arg-list | ( expression ) | INT-LITERAL |
BOOL-LITERAL
para-list -> () | ( proper-para-list )
proper-para-list -> para-declaration proper-para-list-tail
proper-para-list-tail -> , para-declaration proper-para-list-tail | EPSILON
para-declaration -> type identifier
arg-list -> () | ( proper-arg-list )
proper-arg-list -> arg proper-arg-list-tail
```

```
proper-arg-list-tail -> , arg proper-arg-list-tail | EPSILON

arg -> expression

declaration-statement -> function-declaration | constant-declaration | variable-declaration |
class-declaration
function-declaration -> identifier para-list compound-statement

variable-declaration -> var identifier init-expression; | var identifier type-annotation;

class-declaration -> class identifier init-expression; | class identifier type-annotation;

constant-declaration -> const identifier init-expression; | const identifier type-annotation;

init-expression -> = expression

type-annotation -> : type

type -> int | bool

top-level -> statement top-level | EPSILON

(注: 由于 '||' 运算会被识别为分隔符,所以使用 XX 代替)
```