Editing Rotoplas

Antenna Configurations

Port 1 (Portal1)   🗑 Delete   📋 Clone   ▲

Antenna Name ❓
Portal1

Antenna Port
1

Transmit Power (cdBm) ❓
1000

Session ❓
1

Population Estimate ❓
8

Receive Sensitivity (dBm) ❓
-70

Tag Access Password Hex ❓

FastId ❓
Disabled ▼

Search Mode ❓
Single Target ▼

RF Mode
0 - Max Throughput ▼

☐ Power Sweeping

Enables inventory rounds to be performed at progressively higher power levels, repeating once the configured Transmit Power is reached.

☐ Tag Authentication

Enables a tag authentication challenge to be sent to each inventoried tag.

Filters

[Add Filter]

Tag Memory Reads ❓

[Add Tag Memory Read]

[Add Antenna Config]

Event Configuration

Common
Configuration that applies to all events.

☐ Include Reader Hostname

Tag Inventory - Included Fields
Controls which fields are included in Tag Inventory events.

☑ Antenna Port ❓	☑ EPC ❓	☑ EPC Hex ❓
☐ XPC Hex ❓	☐ Frequency ❓	☑ Last Seen Time ❓
☐ PC Word ❓	☐ Peak RSSI ❓	☐ Phase Angle ❓
☐ TID ❓	☐ TID Hex ❓	☐ Transmit Power ❓

Tag Inventory - Behavior
Controls how and when Tag Inventory events are reported.

Reporting Interval (s) ⊙

10

Tag Cache Size ⊙

2048

Antenna Identifier

Name ▾

Tag Identifier

EPC ▾

Antenna

Controls which antenna related events are reported.

☐ Enable Activation Event ⊙

Start Triggers ⊙

Create Start Trigger

Stop Triggers ⊙

Create Stop Trigger

You have unsaved changes.

Cancel   Save