

Using Git

Matthieu Moy

Matthieu.Moy@imag.fr

2012

Outline

- 1 Revision Control System
- 2 Git: Basic Principles
- 3 An Example Using Git
- 4 Advices Using Git

Backups: The Old Good Time

- **Basic problems:**

- ▶ “Oh, my disk crashed.” / “Someone has stolen my laptop!”
- ▶ “@#%!!, I’ve just deleted this important file!”
- ▶ “Oops, I introduced a bug a long time ago in my code, how can I see how it was before?”

Backups: The Old Good Time

- Basic problems:

- ▶ “Oh, my disk crashed.” / “Someone has stolen my laptop!”
- ▶ “@#%!!, I’ve just deleted this important file!”
- ▶ “Oops, I introduced a bug a long time ago in my code, how can I see how it was before?”

- Historical solutions:

- ▶ Replicate:

```
$ cp -r ~/project/ ~/backup/
```

(or better, copy to a remote machine like telesun)

- ▶ Keep history:

```
$ cp -r ~/project/ ~/backup/project-2012-02-02
```

- ▶ ...

Collaborative Development: The Old Good Time

- **Basic problems:** Several persons working on the same set of files
 - ① “Hey, you’ve modified the same file as me, how do we merge?”,
 - ② “Your modifications are broken, your code doesn’t even compile. Fix your changes before sending it to me!”,

Collaborative Development: The Old Good Time

- Basic problems: Several persons working on the same set of files
 - ① “Hey, you’ve modified the same file as me, how do we merge?”,
 - ② “Your modifications are broken, your code doesn’t even compile. Fix your changes before sending it to me!”,
- Historical solutions:
 - ▶ Never two person work at the same time. ⇒ Doesn’t scale up!
Unsafe.
 - ▶ People work on the same directory (same machine, NFS, ACLs . . .)
⇒ Painful because of (2) above.
 - ▶ People work trying to avoid conflicts, and merge later.

Merging: Problem and Solution

● My version

```
#include <stdio.h>

int main () {
    printf("Hello");

    return EXIT_SUCCESS;
}
```

● Your version

```
#include <stdio.h>

int main () {
    printf("Hello!\n");

    return 0;
}
```

Merging: Problem and Solution

● My version

```
#include <stdio.h>

int main () {
    printf("Hello");

    return EXIT_SUCCESS;
}
```

● Your version

```
#include <stdio.h>

int main () {
    printf("Hello!\n");

    return 0;
}
```

● Common ancestor

```
#include <stdio.h>

int main () {
    printf("Hello");

    return 0;
}
```


Merging: Problem and Solution

● My version

```
#include <stdio.h>

int main () {
    printf("Hello");

    return EXIT_SUCCESS;
}
```

● Your version

```
#include <stdio.h>

int main () {
    printf("Hello!\n");

    return 0;
}
```

● Common ancestor

```
#include <stdio.h>

int main () {
    printf("Hello");

    return 0;
}
```

This merge can be done for you by an automatic tool

Merging relies on history!

Merging: Problem and Solution

● My version

```
#include <stdio.h>

int main () {
    printf("Hello");

    return EXIT_SUCCESS;
}
```

● Your version

```
#include <stdio.h>

int main () {
    printf("Hello!\n");

    return 0;
}
```

● Common ancestor

```
#include <stdio.h>

int main () {
    printf("Hello");

    return 0;
}
```

This merge can be done for you by an automatic tool

Merging relies on history!

Collaborative development linked to backups

Merging

Space of possible revisions
(arbitrarily represented in 2D)

Merging

Space of possible revisions
(arbitrarily represented in 2D)


Mine



Yours


Merging

Space of possible revisions
(arbitrarily represented in 2D)



Merging

Space of possible revisions
(arbitrarily represented in 2D)



Revision Control System: Basic Idea

- Keep track of **history**:
 - ▶ `commit` = snapshot of the current state,
 - ▶ Meta-data (user's name, date, descriptive message,...) recorded in `commit`.
- Use it for **merging**/collaborative development.
 - ▶ Each user works on its own copy,
 - ▶ User explicitly “takes” modifications from others when (s)he wants.

Outline

1 Revision Control System

2 Git: Basic Principles

3 An Example Using Git

4 Advices Using Git

Git: Basic concepts

- Each working directory contains:
 - ▶ The files you work on (as usual)
 - ▶ The history, or “repository” (in the directory `.git/`)
- Basic operations:
 - ▶ **git clone**: get a copy of an existing repository (files + history)
 - ▶ **git commit**: create a new revision in a repository
 - ▶ **git pull**: get revisions from a repository
 - ▶ **git push**: send revisions to a repository
 - ▶ **git add**, **git rm** and **git mv**: tell Git which files should be tracked
 - ▶ **git status**: know what's going on
- For us:
 - ▶ Each team creates a shared repository, in addition to work trees

Outline


1 Revision Control System

2 Git: Basic Principles


3 An Example Using Git

4 Advices Using Git


Starting the project with Git




Starting the project with Git




Starting the project with Git




Starting the project with Git




Starting the project with Git




Starting the project with Git




Starting the project with Git



Starting the project with Git



Starting the project with Git



Starting the project with Git: in Practice

```
Alice$ git clone ssh://ldb42@telesun.imag.fr/~git ipsim
Initialized empty Git repository in /perms/Alice/ipsim/.git/
remote: Counting objects: 960, done.
remote: Compressing objects: 100% (555/555), done.
remote: Total 960 (delta 341), reused 949 (delta 330)
Receiving objects: 100% (960/960), 1.51 MiB, done.
Resolving deltas: 100% (341/341), done.
```

Starting the project with Git: in Practice

```
Alice$ git clone ssh://ldb42@telesun.imag.fr/~git ipsim  
Alice$ cd ipsim/sandbox  
Alice$ vi hello.c
```

Starting the project with Git: in Practice

```
Alice$ git clone ssh://ldb42@telesun.imag.fr/~git ipsim
Alice$ cd ipsim/sandbox
Alice$ vi hello.c
Alice$ git status
# On branch master
# Changed but not updated:
#   (use "git add <file>..." to update what will be committed)
#   (use "git checkout -- <file>..." to discard changes ...)
#
#       modified:   hello.c
#
```

Starting the project with Git: in Practice

```
Alice$ git clone ssh://ldb42@telesun.imag.fr/~git ipsim
Alice$ cd ipsim/sandbox
Alice$ vi hello.c
Alice$ git status
Alice$ git diff HEAD
--- a/projet/sandbox/hello.c
+++ b/projet/sandbox/hello.c
@@ -1,5 +1,5 @@
    /* Chacun ajoute son nom ici */
-/* Auteurs : ... et ... */
+/* Auteurs : Alice et ... */

#include <stdio.h>
```

Starting the project with Git: in Practice

```
Alice$ git clone ssh://ldb42@telesun.imag.fr/~git ipsim
Alice$ cd ipsim/sandbox
Alice$ vi hello.c
Alice$ git status
Alice$ git diff HEAD
Alice$ git commit -a
[master d943af5] Added my name.
 1 files changed, 1 insertions(+), 1 deletions(-)
```


Starting the project with Git: in Practice


```
Alice$ git clone ssh://ldb42@telesun.imag.fr/~git ipsim
Alice$ cd ipsim/sandbox
Alice$ vi hello.c
Alice$ git status
Alice$ git diff HEAD
Alice$ git commit -a
Alice$ git log
commit d943af53ec13b43eac31d4cca3b11f51746a90cc
Author: Alice <Alice@ensimag.imag.fr>
```

Added my name.

```
commit 96e1dead6dc0f8e23308726d22bbf42d0e99352f
Author: Equipe ldb42 <ldb42@telesun.imag.fr>
```

Personalisation du dépôt pour ldb42

Starting the project with Git



Starting the project with Git: in Practice

```
Bob$ git clone ssh://ldb42@telesun.imag.fr/~git ipsim
Initialized empty Git repository in /perms/Bob/ipsim/.git/
remote: Counting objects: 960, done.
remote: Compressing objects: 100% (555/555), done.
remote: Total 960 (delta 341), reused 949 (delta 330)
Receiving objects: 100% (960/960), 1.51 MiB, done.
Resolving deltas: 100% (341/341), done.
```

Starting the project with Git: in Practice

```
Bob$ git clone ssh://ldb42@telesun.imag.fr/~git ipsim  
Bob$ cd ipsim/sandbox  
Bob$ vi hello.c
```

Starting the project with Git: in Practice

```
Bob$ git clone ssh://ldb42@telesun.imag.fr/~git ipsim
Bob$ cd ipsim/sandbox
Bob$ vi hello.c
Bob$ git commit -a
[master ae00028] Removed a piece of code.
 1 files changed, 0 insertions(+), 10 deletions(-)
```

Starting the project with Git: in Practice


```
Bob$ git clone ssh://ldb42@telesun.imag.fr/~/.git ipsim
Bob$ cd ipsim/sandbox
Bob$ vi hello.c
Bob$ git commit -a
Bob$ git log
commit ae000285167885b286401ea3eb3379a7a3946260
Author: Bob <Bob@telesun.imag.fr>
Date: Thu Nov 19 16:52:53 2009 +0100
```

Removed a piece of code.

```
commit 96eldead6dc0f8e23308726d22bbf42d0e99352f
Author: Equipe ldb42 <ldb42@telesun.imag.fr>
Date: Thu Nov 19 16:30:54 2009 +0100
```

Personalisation du dépôt pour ldb42

Starting the project with Git



Starting the project with Git: in Practice

```
Bob$ git push
Counting objects: 9, done.
Delta compression using up to 16 threads.
Compressing objects: 100% (4/4), done.
Writing objects: 100% (5/5), 432 bytes, done.
Total 5 (delta 2), reused 0 (delta 0)
To ssh://ldb42@telesun.imag.fr/~git
    96eldea..ae00028  master -> master
```


Starting the project with Git: in Practice

```
Bob$ git push
```

```
# back to Alice
```

```
Alice$ git push
```

```
To ssh://ldb42@telesun.imag.fr/~git
```

```
! [rejected]        master -> master (non-fast forward)
```

```
error: failed to push some refs to 'ssh://ldb42@telesun.imag.fr/~git'
```

```
To prevent you from losing history, non-fast-forward updates were rejected
```

```
Merge the remote changes before pushing again.  See the 'non-fast forward'  
section of 'git push --help' for details.
```

Starting the project with Git: in Practice

```
Bob$ git push

# back to Alice
Alice$ git push
Alice$ git pull
Unpacking objects: 100% (5/5), done.
From ssh://telesun.imag.fr/~git
   96eldea..ae00028  master    -> origin/master
Auto-merging sandbox/hello.c
Merge made by recursive.
  sandbox/hello.c |   10 -----
  1 files changed, 0 insertions(+), 10 deletions(-)
```

Starting the project with Git: in Practice

```
Bob$ git push

# back to Alice
Alice$ git push
Alice$ git pull
Alice$ vi hello.c
Alice$ git commit -a
[master ee9f864] Test
 1 files changed, 1 insertions(+), 0 deletions(-)
```

Starting the project with Git: in Practice

```
Bob$ git push


# back to Alice
Alice$ git push
Alice$ git pull
Alice$ vi hello.c
Alice$ git commit -a
Alice$ git log --graph --oneline
* ee9f864 Test
* 830a084 Merge branch 'master' of ...
|\
| * ae00028 Removed a piece of code.
* | d943af5 Added my name.
|/
* 96eldea Personalisation du dépôt pour ldb42
```

Starting the project with Git: in Practice

```
Bob$ git push

# back to Alice
Alice$ git push
Alice$ git pull
Alice$ vi hello.c
Alice$ git commit -a
Alice$ git log --graph --oneline
Alice$ git push
Counting objects: 23, done.
Delta compression using up to 16 threads.
Compressing objects: 100% (12/12), done.
Writing objects: 100% (15/15), 1.20 KiB, done.
Total 15 (delta 6), reused 0 (delta 0)
To ssh://ldb42@telesun.imag.fr/~git
   ae00028..ee9f864  master -> master
```

Starting the project with Git



Outline

1 Revision Control System

2 Git: Basic Principles

3 An Example Using Git

4 Advices Using Git

Advices Using Git (for beginners)

- **Never** exchange files outside Git's control (email, scp, usb key), except if you *really* know what you're doing;

Advices Using Git (for beginners)

- **Never** exchange files outside Git's control (email, scp, usb key), except if you *really* know what you're doing;
- Always use `git commit -a`;
- Make a `git push` after each `git commit -a` (use `git pull` if needed);
- Do `git pull` regularly, to remain synchronized with your teammates. You need to make a `git commit -a` before you can make a `git pull` (this is to avoid mixing manual changes with merges).