Linked Lists

Saikrishna Arcot M. Hudachek-Buswell

July 19, 2020


Recall Linked Lists

- A linked list is a data structure consisting of a sequence of nodes.
- Each node in the linked list stores the data and a pointer to the next/previous node(s).
- Nodes are created/destroyed as necessary. When adding a new element, a new node is created, and linked into the linked list. When removing an element, the node containing the element is destroyed.
- Linked list have a head pointer, and may have a tail pointer.

Recall Singly Linked Lists

We refrain from creating "dummy" nodes that lead to null references at the end of a singly linked list. We just have the next reference of the last node point to null.


head



- A doubly linked list is a version of a linked list where each node has a pointer to the next node and a pointer to the previous node.
- Doubly linked lists can be traversed forward and backward.

- A doubly linked list is a version of a linked list where each node has a pointer to the next node and a pointer to the previous node.
- Doubly linked lists can be traversed forward and backward.
- Nodes store:
 - element
 - link to the previous node
 - link to the next node

- A doubly linked list is a version of a linked list where each node has a pointer to the next node and a pointer to the previous node.
- Doubly linked lists can be traversed forward and backward.
- Nodes store:
 - element
 - link to the previous node
 - link to the next node



Generic Code For Doubly Linked List Node

```
public class DoublyLinkedList<Type> {
   private class Node<Type> {
      private Type data;
      private Node<Type> next;
      private Node<Type> prev;
      private Node(Type data, Node<Type> next,
        Node<Type> prev) {
         this.data = data:
         this.next = next;
         this.prev = prev;
```

Generic Code For Doubly Linked List Node


```
// Node constructor chaining
private Node(Type data) {
    this(data, null, null)

// this.data = data

// this.next = null

// this.prev = null
}
```


Example of a doubly linked list:



Notice that prev reference of the first node points to null, as does the next reference of the last node


Insertion

Create new node X. Insert a new node, X, between node C and node D. Set new node's prev reference to C and next reference to D. head




Insertion

Create new node X. Insert a new node, X, between node C and node D. Set new node's prev reference to C and next reference to D.




Insertion



Once node X is connected, set Node C's next reference to node X, and Node D's prev reference to node X.


Deletion

Remove node D, between nodes C and E. The order in which you redirect references is important so you do not lose your linked list. head



Deletion


Remove node D, between nodes C and E. The order in which you redirect references is important so you do not lose your linked list.



Deletion

Set node C's next reference to node E, and node E's prev reference to C. Node D will be garbage collected.

head



 Linked Lists are most definitely dynamic, and can store primitives or objects.

- Linked Lists are most definitely dynamic, and can store primitives or objects.
- Accessing or searching any linked list is a cost of O(n), linear time

- Linked Lists are most definitely dynamic, and can store primitives or objects.
- Accessing or searching any linked list is a cost of O(n), linear time
- Adding or removing from the front of any linked list with a head pointer is a cost of O(1), constant time

- Linked Lists are most definitely dynamic, and can store primitives or objects.
- Accessing or searching any linked list is a cost of O(n), linear time
- Adding or removing from the front of any linked list with a head pointer is a cost of O(1), constant time
- Linked lists are useful when you have to manipulate data

- Linked Lists are most definitely dynamic, and can store primitives or objects.
- Accessing or searching any linked list is a cost of O(n), linear time
- Adding or removing from the front of any linked list with a head pointer is a cost of O(1), constant time
- Linked lists are useful when you have to manipulate data
- Singly linked lists are used in RFID scanning, app wizards or levels in a video game


- Linked Lists are most definitely dynamic, and can store primitives or objects.
- Accessing or searching any linked list is a cost of O(n), linear time
- Adding or removing from the front of any linked list with a head pointer is a cost of O(1), constant time
- Linked lists are useful when you have to manipulate data
- Singly linked lists are used in RFID scanning, app wizards or levels in a video game
- Doubly linked lists are used in browser history, scroll bars or forward/back buttons

 Circular Linked List is a more complicated Linked list where the last node points to the first node, (and the first node could point to the last node).


- Circular Linked List is a more complicated Linked list where the last node points to the first node, (and the first node could point to the last node).
- Circular linked lists can be either singly or doubly linked.

- Circular Linked List is a more complicated Linked list where the last node points to the first node, (and the first node could point to the last node).
- Circular linked lists can be either singly or doubly linked.
- Depending on single or double links, adding or removing is the same as for the type of link

- Circular Linked List is a more complicated Linked list where the last node points to the first node, (and the first node could point to the last node).
- Circular linked lists can be either singly or doubly linked.
- Depending on single or double links, adding or removing is the same as for the type of link
- Applications that use circular linked lists are gifs, music playlists; round-robin scheduling algorithms for operating systems



Example of Singly Circular Linked List



Example of Doubly Circular Linked List

