

Chipathon 2026 Tapeout – Export Control & GF180 Configuration Information

mahardhika.adipratama@gmail.com [Switch account](#)



Your email will be recorded when you submit this form

* Indicates required question

7. GF180 project configuration

Project-level inputs from the 180MCU configurator. Wafer/die-wide settings such as final die name/size, scribe line, mirror shot, and post-fab services will be completed centrally after the tapeout projects are selected.

[GF180 CFG] Is this an automotive device/application? *

☒ Yes

☐ No

[GF180 CFG] Core voltage(s) used by this project *

Select every core voltage used.

☒ 3.3 V

☐ 5 V

☐ 6 V



[GF180 CFG] I/O voltage(s) used by this project *

Select every I/O voltage used.

☒ 3.3 V

☐ 5 V

☐ 6 V

[GF180 CFG] Custom voltage(s), if any

Enter value(s) and purpose. Leave blank if none.

Your answer

[GF180 CFG] Other special process/configuration requirements

Your answer

[Back](#)

[Next](#)

Page 8 of 11

[Clear form](#)

Never submit passwords through Google Forms.

This content is neither created nor endorsed by Google. - [Contact form owner](#) - [Terms of Service](#) - [Privacy Policy](#)

Does this form look suspicious? [Report](#)

Google Forms



