

Chipathon 2026 Tapeout – Export Control & GF180 Configuration Information

mahardhika.adipratama@gmail.com [Switch account](#)



Your email will be recorded when you submit this form

8. Foundry IP used

Select every foundry/library IP used by this project. Leave a checkbox group blank if none.

[GF180 CFG IP – MEMORY] Select all IP used

- ☐ Globalfoundries 0.18um 3.3V Single Port 8192x16 bits SRAM Green Process
- ☐ GF 180nm Green 5V synchronous single port 128x8M8WM1 SRAM Memory Macro IP
- ☐ GF 180nm Green 5V synchronous single port 256x8M8WM1 SRAM Memory Macro IP
- ☐ GF 180nm Green 5V synchronous single port 512x8M8WM1 SRAM Memory Macro IP
- ☐ GF 180nm Green 5V synchronous single port 64x8M8WM1 SRAM Memory Macro IP

[GF180 CFG IP] Other foundry or third-party IP used that is not listed above

Give IP name, provider/owner, version if known, and whether separate approval/license is required.

Your answer



[Back](#)[Next](#)

Page 9 of 11

[Clear form](#)

Never submit passwords through Google Forms.

This content is neither created nor endorsed by Google. - [Contact form owner](#) - [Terms of Service](#) - [Privacy Policy](#).

Does this form look suspicious? [Report](#)

Google Forms



