IEEE Access
Multidisciplinary | Rapid Review | Open Access Journal

ComNetX: Local Hierarchical Adaptation for Batched Dynamic Community Detection

GRIGORIY BOKOV[1], ALEKSANDR KONOVALOV[1], ANNA UPOROVA[1], ALEXANDER DROBYSHEV[1], and IAROSLAV EGOROV[1]
[1]AI Research Center, Lomonosov Moscow State University, 1 Leninskie Gory, Moscow 119991, Russian Federation

Corresponding author: Grigoriy Bokov (e-mail: grigoriy.bokov@math.msu.ru).

This work was supported by the Ministry of Economic Development of the Russian Federation under subsidy agreement 000000C313925P4H0002, Grant 139-15-2025-012.

ABSTRACT Dynamic community detection requires updating a graph partition as edges change, but rerunning a detector after every update batch can be expensive. We present ComNetX, a hierarchical method that adapts existing community detectors to batched edge updates. For each batch, ComNetX expands the set of affected endpoints to include their r-hop neighbors and selects all communities intersecting this neighborhood. It then contracts vertex groups defined by a stored hierarchy into weighted supernodes, applies the detector to the reduced graph, and maps the partition back to the original vertices. The finest partition is reported, while subsequent passes update the coarser hierarchy levels for future batches. This procedure preserves nesting across hierarchy levels. Contraction preserves modularity on the selected induced subgraph for partitions that keep each contracted group intact. We analyze time and memory costs and evaluate update streams constructed from six real graphs. In five maintenance comparisons initialized from approximately 99.9% of each graph's stored update records, ComNetX reduces measured processing time relative to warm-started Leiden on the full graph by factors of 6.60–98.72, with absolute differences in final modularity of 0.0035–0.0213. In 500-update experiments on PubMed and ArxivMath covering the final 10% of each stored record sequence, the speedup factors are 24.46 and 72.67, respectively, while the absolute modularity difference remains below 0.008 at every update. Graph-growth and parameter studies identify conditions under which the method is effective, and feature-aware experiments demonstrate the use of aggregated node attributes through the same update procedure.

INDEX TERMS community detection, dynamic graphs, graph clustering, hierarchical graph contraction, incremental graph analytics

I. INTRODUCTION

MANY communication, social, information, and collaboration systems are represented by networks whose edges evolve over time [1]–[3]. Community detection seeks groups of vertices that are densely connected or otherwise form coherent modules [4]–[7]. The appropriate notion of a community depends on the objective and on whether the analysis uses topology, node attributes, temporal consistency, or a combination of these signals [8], [9]. Modularity is a common structural criterion [10], [11]; Louvain and Leiden are widely used methods for optimizing it [12], [13], and parallel implementations make them effective static baselines [14], [15]. In a dynamic setting, however, applying the same optimizer after every batch requires processing the full graph, even when the structural change is local.

One approach to dynamic community detection applies a static detector to each graph snapshot, optionally initializing it with the previous partition. The unseeded and seeded Grappolo schemes are examples of these two initialization choices [16]. Other methods reduce repeated work through incremental modularity optimization, screening of affected vertices, or dynamic frontier expansion [17]–[20]. Their update rules are formulated for a particular objective or optimization procedure. Adapting such rules to a detector with a different objective or feature representation requires further algorithmic work. This issue is relevant to attributed and representation-learning methods, whose detector calls may include feature construction or iterative training [21]–[23].

ComNetX reuses a detector by changing the graph supplied to it. For each batch, it expands the set of affected endpoints to include their neighbors and selects every current community intersecting that neighborhood. This makes every vertex in the selected communities part of the update region. A stored hierarchy then defines groups of vertices to contract into weighted supernodes, reducing the number of vertices presented to the detector. The returned partition is mapped back to the original graph. The first pass updates the reported finest partition; later passes update the coarser hierarchy levels for future batches. Because contracted groups cannot split and edges leaving the selected region are omitted, the resulting

optimization is a local approximation to full recomputation.

The contributions of this work are as follows.

1) We introduce ComNetX, which selects complete communities around each edge-update batch, contracts vertex groups defined by a stored hierarchy, and reuses a compatible detector on the resulting weighted graphs. The same construction accepts topology-only and feature-aware backends, with node attributes aggregated over atoms for the latter.
2) We establish that the fine-to-coarse update preserves a nested partition hierarchy. We apply the standard modularity-preserving contraction identity to the selected induced subgraphs and derive time and memory bounds for the update procedure, including its graph-wide worst case.
3) We evaluate the method on streams constructed from six real graphs, including 500-update maintenance sequences, graph growth, batch-granularity controls, and parameter and feature studies. The comparisons quantify the observed quality–time trade-off against full Leiden recomputation and a native dynamic implementation, and examine a feature-aware adapter.

II. RELATED WORK

A. STATIC OBJECTIVES AND SCALABLE OPTIMIZATION

Structural community definitions include dense-subgraph, cut-based, information-flow, and null-model views [4]–[6]. Modularity compares within-community edge weight with a degree-preserving null model [10], [11]. Louvain combines local moves with graph aggregation [12]; Leiden adds a refinement stage that addresses poorly connected communities [13]. Shared-memory heuristics and fast Leiden implementations extend this family to large static graphs [14], [15]. Other approaches include the map equation used by Infomap [24], fast label propagation [25], modularity-guided label updates [26], greedy modularity disassembly [27], and iterated local moves [28].

No single score fully determines whether a partition is useful. Modularity has resolution effects and a highly degenerate optimization landscape [8], [29]; comparative studies also show that algorithm rankings depend on the planted structure and evaluation design [30]. Class labels or other metadata may describe a different organizing principle from graph structure [31], [32]. We therefore report structural quality and agreement with reference labels separately, using normalized mutual information (NMI) as an external agreement measure [33].

B. DYNAMIC, TEMPORAL, AND LOCAL COMMUNITY DETECTION

Dynamic community detection includes incremental partition maintenance and methods that explicitly model temporal evolution [3]. Methods for successive graph snapshots include incremental batch processing [34], dynamic label propagation [35], [36], and incremental modularity optimization [17], [37]. C-Blondel constructs a compressed graph whose supernodes represent communities detected at the previous step and applies Louvain to that graph [38]. Delta-Screening uses modularity-based tests to select vertices for reconsideration [18]. Shared-memory and distributed implementations include dynamic-frontier methods and DyG-DPCD [19], [39], [40]. Sattar et al. compare dynamic community-detection strategies and develop the shared-memory DyComPar algorithm [41]; a broader survey covers fully dynamic graph algorithms [42].

Other formulations make temporal persistence part of the objective. NOME balances snapshot quality and temporal smoothness [43]; flow stability, Matthew-effect models, and modularity-based tracking likewise model temporal continuity [44]–[46]. Continuous-time L-modularity avoids choosing snapshot boundaries [47], while recent work addresses sparse temporal observations and random-walk snapshot clustering [48], [49]. ComNetX instead targets batched snapshot maintenance through a reusable partitioning interface and returns a complete partition after every batch.

Some local community-detection methods solve a different task. Seed-, query-, and anchor-based methods find one or several nearby communities rather than a partition of every vertex [50]–[52]. OLCPM maintains overlapping communities online [53]. ComNetX preserves a complete label vector and keeps community assignments outside the update region unchanged. It therefore uses locality to maintain a full partition.

C. ATTRIBUTED AND REPRESENTATION-LEARNING METHODS

Attributed community detection combines topology with node information [9]. Message-passing graph neural networks provide a general representation framework [54]; later methods designed for community detection include SEAL [55], DMoN [21], CommDGI [56], MAGI [22], and DGCluster [57]. Comparative and survey work documents the range of embeddings, clustering losses, and evaluation choices [58], [59]. DAG learns clusters without a prescribed cluster count [60]; structural-entropy objectives provide another unsupervised signal [61], while fairness-aware spectral and deep methods incorporate group-sensitive connectivity into community detection [62].

Efficiency-oriented designs include pre-train-and-refine community detection and inductive graph partitioning [63], [64], while Spectral Subspace Clustering for Attributed Graphs (S^2CAG) provides a feature-aware spectral approach [23]. Community structure can also be part of a downstream dynamic prediction model [65]. Kong et al. combine matrix factorization clustering (MFC) with a topological regularizer, TopoReg, to encourage consistent inter-community structure across successive snapshots [66]. For feature-aware backends that return a compatible partition, ComNetX supplies a contracted adjacency and aggregated group features. The fixed-budget S^2CAG experiments in Section VI-B evaluate this feature-aware interface alongside topology-only and native

dynamic calls. Because contraction and feature aggregation change the input representation, interface compatibility does not imply preservation of a feature-aware objective.

D. DIFFERENCE FROM EXISTING LOCAL AND DYNAMIC METHODS

Existing dynamic methods reduce work at different stages of community detection. C-Blondel reuses previously detected communities in a compressed graph on which Louvain is applied [38]. For Leiden, Sahu et al. combine affected-vertex processing with selective refinement and changes to community renumbering and aggregation [20]. Later work adds community-identifier tracking and a refinement rule based on accumulated changes in community edge weight [67]. LD-Leiden maintains an affected frontier and repairs its stored hierarchy locally [68]; HIT-Leiden maintains connected components and hierarchical community structures to restrict the affected range [69].

ComNetX specifies the update through the graph supplied to a compatible detector. It extends the affected neighborhood to include every vertex in each community it intersects, contracts groups determined by the stored hierarchy, and lifts the detector's partition to the original vertices. The construction therefore combines selection of the update region, hierarchical contraction, and a common partitioning interface. Seed- and anchor-based methods address a different output requirement by returning selected communities rather than a partition of all vertices [50]–[52].

The adapter reuses each detector's partitioning interface and does not retain the backend's internal state between calls.

A specialized dynamic solver can be used as a ComNetX backend only if it can independently partition each supplied quotient graph; DF-Leiden used in this way is reinitialized on every quotient and is not equivalent to its native streaming mode.

III. PROBLEM FORMULATION

A. BATCHED GRAPH MODEL

Let $G_t = (V, E_t, \boldsymbol{A}_t, \boldsymbol{X})$ be the graph after batch t, with a fixed vertex set V, $n = |V|$, sparse adjacency $\boldsymbol{A}_t$, and optional node-feature matrix $\boldsymbol{X} \in \mathbb{R}^{n\times d}$. A sparse signed batch $\boldsymbol{\Delta}_t$ updates the stored adjacency as

$$\boldsymbol{A}_t = \boldsymbol{A}_{t-1} + \boldsymbol{\Delta}_t. \tag{1}$$

The affected endpoints are

$$S_t = \{i : \exists j,\ \Delta_t(i,j) \neq 0 \text{ or } \Delta_t(j,i) \neq 0\}. \tag{2}$$

This fixed-vertex model accepts signed sparse batches. The experiments use nonnegative edge updates with fixed attributes, including edge insertions and increments to existing edge weights under the stream construction below.

We treat a community-detection backend as a partition-producing procedure

$$\mathcal{B}(\boldsymbol{A}, \boldsymbol{X}, \boldsymbol{y}_0; \boldsymbol{\theta}) \longmapsto \boldsymbol{y}, \tag{3}$$

where $\boldsymbol{X}$ and the initial partition $\boldsymbol{y}_0$ are optional, and $\boldsymbol{\theta}$ denotes backend-specific settings such as resolution or a fixed iteration budget. For an input of m vertices, the interface requires one integer label per input vertex; equality of labels defines the returned partition, while their numerical values and ordering are immaterial. This interface covers modularity heuristics and attributed clustering methods. It also covers a native dynamic implementation when that implementation can be called independently on each supplied graph and returns one label per input vertex. ComNetX does not reuse backend state between its quotient calls; each backend retains its own objective and optimization procedure.

Full-snapshot recomputation at update t invokes $\mathcal{B}$ on $\boldsymbol{A}_t$. When the backend accepts an initialization, its own previous partition is supplied:

$$\boldsymbol{y}_t^{\text{full}} = \mathcal{B}(\boldsymbol{A}_t, \boldsymbol{X}, \boldsymbol{y}_{t-1}^{\text{full}}; \boldsymbol{\theta}). \tag{4}$$

The full Leiden baseline follows this warm-started definition. The ComNetX state instead comprises the stored sparse adjacency matrix, optional full feature matrix, and L full-length label vectors used to construct the local problems described next.

B. QUALITY METRICS AND TIMING

All main comparisons use an undirected graph representation. Directed source graphs are symmetrized within each paired full/local experiment. For a weighted adjacency, let $W = \sum_{i,j} A_{ij} > 0$, $d_i^{\text{out}} = \sum_j A_{ij}$, and $d_j^{\text{in}} = \sum_i A_{ij}$. For a partition C, we compute directed modularity at resolution γ as

$$Q_\gamma(\boldsymbol{A}, C) = \frac{1}{W} \sum_{i,j} \left(A_{ij} - \gamma \frac{d_i^{\text{out}} d_j^{\text{in}}}{W} \right) \mathbf{1}\{C(i) = C(j)\}, \tag{5}$$

which reduces to the standard undirected expression when $\boldsymbol{A}$ is symmetric, $W = 2m$, and $d_i^{\text{out}} = d_i^{\text{in}} = d_i$. The main experiments use $\gamma = 1$. We also use normalized mutual information (NMI),

$$\text{NMI}(C, Z) = \frac{2I(C;Z)}{H(C) + H(Z)}, \tag{6}$$

between partition C and reference class labels Z [33]. These labels are metadata, not asserted structural ground truth [32].

The principal efficiency measure is cumulative processing time. The full and ComNetX paths use wall-clock elapsed time minus the adapter-reported conversion and preprocessing interval. Native DF-Leiden instead supplies the duration returned by its `apply()` call, after its exposed `update()` call. Table 1 specifies the boundaries in the preserved benchmarking code. These intervals are not end-to-end batch latency. The native and ComNetX intervals are instrumented differently, so their ratios compare the reported execution paths. Speedup is the full or native-dynamic time divided by ComNetX time for the paired dataset and protocol.

For S^2CAG, feature preparation and graph normalization are subtracted, but dense feature conversion, all five solver

calls, and internal accuracy, NMI, and adjusted Rand index (ARI) calculations remain timed. Only the external metrics computed by the benchmarking script are excluded. The archive does not establish identical timer implementations for the separate S^{2}CAG series discussed in Appendix C.

IV. COMNETX METHOD

A. UPDATE PROCEDURE AND STORED STATE

Each ComNetX update selects a region of the graph, divides its vertices into groups that will be kept together, and contracts those groups into a weighted graph for the detector. We denote the update region at level ℓ by U_t^ℓ, its partition into contraction groups by $\mathcal{G}_t^\ell$, and the contracted adjacency by $\bar{\boldsymbol{A}}_\ell$. We call these indivisible groups *atoms*. All update regions are selected from the previous hierarchy before any level is changed. The method then processes the levels from fine to coarse, calls the detector once per level, and lifts each returned partition to the original vertices. Fig. 1 summarizes the procedure.

The maintained state consists of the accumulated sparse adjacency $\boldsymbol{A}_t$, the optional feature matrix $\boldsymbol{X}$, and an $L \times n$ array of integer community labels $\boldsymbol{C}_t = (C_t^0, \ldots, C_t^{L-1})$, where $C_t^\ell(v)$ is the community label assigned to vertex v at level ℓ after batch t. Let $\mathcal{P}_t^\ell$ denote the partition induced by C_t^ℓ. For any two partitions $\mathcal{P}$ and $\mathcal{Q}$ of the same vertex set, we write $\mathcal{P} \preceq \mathcal{Q}$ if every block of $\mathcal{P}$ is contained in a block of $\mathcal{Q}$; then $\mathcal{P}$ refines $\mathcal{Q}$. We use the implementation order in Fig. 1: C_t^0 is the finest, reported partition and C_t^{L-1} is the coarsest level. Thus every block of $\mathcal{P}_t^\ell$ is contained in a block of $\mathcal{P}_t^{\ell+1}$.

Every stored block H is represented canonically by $\kappa(H) = \min H$. Canonical labels are deterministic original-vertex indices and, unlike raw backend labels, cannot collide for disjoint blocks. At initialization, a designated full-graph method produces $\mathcal{P}_0^0$; the experiments use Leiden for this initialization, including experiments with other local backends. Each successive coarser partition is obtained by partitioning the quotient graph of the preceding level and lifting its labels to V. The initial hierarchy is therefore nested, although adjacent levels need not be distinct. These are the partitions maintained by ComNetX, rather than the internal levels of a backend run. Only C_t^0 is reported; the coarser partitions determine contraction groups in later batches.

B. SELECTING THE COMMUNITIES TO RECOMPUTE

After applying a batch, ComNetX expands S_t by r hops on the support of $\boldsymbol{A}_t + \boldsymbol{A}_t^{\mathsf{T}}$. The resident adjacency is assumed nonnegative after the signed batch has been applied, as it is in the evaluated nonnegative update streams; under this condition the sparse matrix–vector traversal equals reachability on the symmetrized support. Let

$$B_t = N_r(S_t) = \{v : \operatorname{dist}(v, S_t) \le r\}. \tag{7}$$

Before any hierarchy row is modified, an update region is computed for each level from the immutable pre-update state:

$$U_t^\ell = \bigcup_{\substack{H \in \mathcal{P}_{t-1}^\ell \\ H \cap B_t \neq \varnothing}} H, \qquad 0 \le \ell < L. \tag{8}$$

Hence U_t^ℓ is the union of all pre-update communities at level ℓ that meet B_t.

This closure is the smallest union of complete $\mathcal{P}_{t-1}^\ell$-blocks containing B_t. Because the stored partitions are nested, the corresponding update regions are nested as well,

$$B_t \subseteq U_t^0 \subseteq U_t^1 \subseteq \cdots \subseteq U_t^{L-1}. \tag{9}$$

A fine block meeting B_t lies in a coarse block that also meets B_t. Closure therefore includes all members of each intersected community without performing another graph-distance expansion.

C. CONSTRUCTING THE CONTRACTED GRAPHS

1) Atoms and Quotient Construction

The first pass, at the reported level 0, uses the base atoms

$$\begin{aligned}\mathcal{G}_t^0 = \{\{v\} : v \in B_t\} \\ \cup \big\{(H \cap U_t^0) \setminus B_t : H \in \mathcal{P}_{t-1}^{L-1}, \\ (H \cap U_t^0) \setminus B_t \neq \varnothing\big\}.\end{aligned} \tag{10}$$

During the first pass, vertices in B_t can be reassigned individually. The remaining vertices in U_t^0 are kept together according to their coarsest pre-update community. Such a group may contain vertices from several communities at the finest level. Thus the update region retains the full membership of every selected community, while contraction restricts how those vertices can be separated. At each coarser pass, a complete block of the already updated finer partition becomes one atom:

$$\mathcal{G}_t^\ell = \{H \in \mathcal{P}_t^{\ell-1} : H \subseteq U_t^\ell\}. \tag{11}$$

Every pass starts from a fresh restriction of the resident adjacency,

$$\boldsymbol{A}_\ell^{\text{work}} = \boldsymbol{D}_\ell \boldsymbol{A}_t \boldsymbol{D}_\ell, \tag{12}$$

where $\boldsymbol{D}_\ell = \operatorname{diag}(\mathbf{1}_{U_t^\ell})$ masks rows and columns outside U_t^ℓ. This ambient $n \times n$ matrix is used with the membership matrix below; restricting the row and column indices to U_t^ℓ instead gives the locally indexed induced adjacency $\boldsymbol{A}_t[U_t^\ell]$. Each pass reconstructs its induced subgraph directly from $\boldsymbol{A}_t$. If $k_\ell = |\mathcal{G}_t^\ell|$, the membership matrix $\boldsymbol{P}_\ell \in \{0,1\}^{k_\ell \times n}$ contains one unit entry in each column indexed by U_t^ℓ and zero columns outside the update region. The backend adjacency is

$$\bar{\boldsymbol{A}}_\ell = \boldsymbol{P}_\ell \boldsymbol{A}_\ell^{\text{work}} \boldsymbol{P}_\ell^{\mathsf{T}}. \tag{13}$$

The backend therefore receives one vertex per atom and the total weight between every ordered pair of atoms.

For a feature-aware backend, ComNetX supports sum and mean aggregation. For $G_{\ell a} \in \mathcal{G}_t^\ell$,

$$\bar{\boldsymbol{x}}_{\ell a} = \begin{cases} \displaystyle\sum_{i \in G_{\ell a}} \boldsymbol{x}_i, & \text{sum}, \\ \dfrac{1}{|G_{\ell a}|} \displaystyle\sum_{i \in G_{\ell a}} \boldsymbol{x}_i, & \text{mean}. \end{cases} \tag{14}$$

TABLE 1. Measurement boundaries in the preserved benchmarking code. "Excluded" means outside the timer or explicitly subtracted. In the graph-growth experiments there is no separate bootstrap; processing the first snapshot is included.

Stage	Full	ComNetX	Native DF
Data loading and initial feature generation	Excluded	Excluded	Excluded
Initial partition/bootstrap	Excluded	Excluded	Excluded
Applying the batch / exposed update call	Excluded	Excluded	Excluded
Neighborhood expansion and community closure	–	Included	Internal[a]
Induced subgraph, quotient, aggregation, lifting	–	Included	Internal[a]
Adapter conversion/preprocessing interval	Subtracted	Subtracted	–
Detector optimization	Included	All passes	Reported time[a]
S^2CAG densification and five solver calls	Included	Included	–
S^2CAG internal accuracy/NMI/ARI	Included	Included	–
External modularity and reference-label metrics	Excluded	Excluded	Excluded

[a]Native DF-Leiden reports the duration of `apply()`; the binding does not expose its internal stages. The table does not assume that its internal work matches the ComNetX stages.

2) Modularity under Contraction

The construction uses the standard modularity-preserving graph contraction [70]. To apply it to one update region, let $\boldsymbol{A}_U \in \mathbb{R}^{|U|\times|U|}$ be the locally indexed adjacency induced by one update region, assume its total weight W_U is positive, and let $\mathcal{G} = \{G_1, \ldots, G_k\}$ be a partition of U. Define the local membership matrix $\boldsymbol{P}_U \in \{0,1\}^{k\times|U|}$ and let $\bar{\boldsymbol{A}} = \boldsymbol{P}_U \boldsymbol{A}_U \boldsymbol{P}_U^{\mathsf{T}}$, retaining the self-loops created by aggregation. Then

$$\bar{A}_{ab} = \sum_{i\in G_a} \sum_{j\in G_b} A_{ij}. \tag{15}$$

Consequently, the quotient preserves total weight and the sums of outgoing and incoming weighted degrees. Every quotient partition Z induces a unique partition C of U that keeps each atom intact, and, under the same directed or symmetric adjacency, self-loop, and resolution conventions,

$$Q_\gamma(\bar{\boldsymbol{A}}, Z) = Q_\gamma(\boldsymbol{A}_U, C). \tag{16}$$

The identity follows by expanding each quotient entry in the internal-weight and degree terms of (5). Hence contraction preserves modularity on the induced subgraph for partitions that keep each atom intact. This identity does not cover atom splits, omitted boundary edges, or arbitrary feature-aware objectives.

3) Lifting the Partition

The current implementation calls the backend without an initial quotient partition: the stored hierarchy determines the atoms but is not passed as $\boldsymbol{y}_0$. After the backend returns a quotient label vector, its induced blocks are lifted through $\boldsymbol{P}_\ell$. Each lifted block $H \subseteq U_t^\ell$ receives the canonical label $\kappa(H) = \min H$; labels outside U_t^ℓ remain unchanged. Algorithm 1 summarizes one batch update.

Algorithm 1 ComNetX update for one batch

Require: $\boldsymbol{A}_{t-1}, \boldsymbol{C}_{t-1}$, optional $\boldsymbol{X}$, update $\boldsymbol{\Delta}_t$, radius r, backend $\mathcal{B}$, settings $\boldsymbol{\theta}$

$\boldsymbol{A}_t \leftarrow \boldsymbol{A}_{t-1} + \boldsymbol{\Delta}_t$
$S_t \leftarrow$ endpoints of the updated edges; $B_t \leftarrow N_r(S_t)$
for $\ell = 0, \ldots, L-1$ **do**
  $U_t^\ell \leftarrow$ closure of B_t under $\mathcal{P}_{t-1}^\ell$ ▷ immutable
end for
$\boldsymbol{C}_t \leftarrow \boldsymbol{C}_{t-1}$
for $\ell = 0, \ldots, L-1$ **do** ▷ fine to coarse
  if $\ell = 0$ **then**
    $\mathcal{G}_t^\ell \leftarrow$ singleton atoms for B_t and the nonempty residual groups in (10)
  else
    $\mathcal{G}_t^\ell \leftarrow$ complete updated $\mathcal{P}_t^{\ell-1}$-blocks in U_t^ℓ
  end if
  $\boldsymbol{A}_\ell^{\text{work}} \leftarrow \boldsymbol{D}_\ell \boldsymbol{A}_t \boldsymbol{D}_\ell$
  build $\boldsymbol{P}_\ell$ from $\mathcal{G}_t^\ell$
  $\bar{\boldsymbol{A}}_\ell \leftarrow \boldsymbol{P}_\ell \boldsymbol{A}_\ell^{\text{work}} \boldsymbol{P}_\ell^{\mathsf{T}}$
  aggregate $\bar{\boldsymbol{X}}_\ell$ if $\mathcal{B}$ uses features
  $\bar{\boldsymbol{y}}_\ell \leftarrow \mathcal{B}(\bar{\boldsymbol{A}}_\ell, \bar{\boldsymbol{X}}_\ell, \varnothing; \boldsymbol{\theta})$
  lift $\bar{\boldsymbol{y}}_\ell$ to U_t^ℓ; set $C_t^\ell(v) \leftarrow \min H$ for every lifted block H and $v \in H$
end for
return $\boldsymbol{C}_t$ with reported partition C_t^0

D. HIERARCHY CONSISTENCY ACROSS LEVELS

Recomputing hierarchy levels independently can produce incompatible partitions. ComNetX instead makes every updated finer block an indivisible atom of the next coarser pass.

Under Algorithm 1, assume that the pre-update hierarchy is canonical and nested, all update regions are computed before any partition is modified, lifting uses canonical labels while retaining the partition outside each update region, and every coarser backend call treats the updated blocks of the preceding finer level as indivisible atoms. Then the updated partitions remain nested:

$$\mathcal{P}_t^0 \preceq \mathcal{P}_t^1 \preceq \cdots \preceq \mathcal{P}_t^{L-1}. \tag{17}$$

Equation (9) places each update region at a finer level inside the corresponding coarser update region. Moreover, U_t^ℓ is a union of pre-update blocks at level ℓ and therefore, by pre-update nesting, a union of complete blocks at level $\ell - 1$. The finer pass changes only $U_t^{\ell-1}$; its lifted blocks stay inside




FIGURE 1. **Illustrative ComNetX update with $r = 1$. (a) Colored outlines show two pre-update fine communities sharing a coarsest parent; red vertices form the expanded neighborhood B_t. (b) Every vertex in B_t remains a singleton atom. Only residual vertices 8 and 10 form a shared atom R; their internal undirected edge contributes quotient diagonal weight 2. (c) An illustrative backend partition lifted to the original vertices. Vertex 5 lies outside U_t^0 and retains its assignment. Coarser passes use complete blocks of the updated finer partition as atoms. All update regions are fixed before any partition is changed.**

that update region, while canonical labels prevent them from colliding with retained outside blocks. Since $U_t^{\ell-1} \subseteq U_t^{\ell}$, the coarser update region remains a union of complete updated blocks at level $\ell - 1$. Equation (11) makes each of these blocks one quotient vertex, so the coarser backend may merge but cannot split it. Ascending induction over ℓ gives (17). Adjacent hierarchy levels may coincide.

Canonical labels also make lifting invariant to backend label permutations: disjoint lifted blocks receive distinct original-vertex identifiers. Retaining labels outside U_t^{ℓ} yields a complete label vector after each pass.

E. RELATION TO THE FULL-GRAPH OBJECTIVE

The contraction identity (16) applies to the induced subgraph. A local backend does not see edges crossing from U_t^{ℓ} to the rest of the graph, so its modularity ranking need not equal the full-graph ranking. The exact decomposition in Appendix A attributes this discrepancy to boundary degrees and global-versus-local null-model normalization. We therefore evaluate every returned partition on the full graph.

F. TIME AND MEMORY COMPLEXITY

For $r = 1$, let $d_t(v)$ denote the degree of v in the symmetrized support graph. Then

$$|B_t| \le |S_t| + \sum_{v \in S_t} d_t(v). \tag{18}$$

Thus, a small edge batch can still have a large radius-one expansion when it touches hubs. If $\mathcal{P}_{t-1}^{\ell}$ is the pre-update partition at level ℓ, the update-region size $h_\ell = |U_t^{\ell}|$ is exactly

$$h_\ell = \sum_{H \in \mathcal{P}_{t-1}^{\ell} : H \cap B_t \neq \varnothing} |H|. \tag{19}$$

The batch size, endpoint degrees, and sizes of the intersected communities determine different parts of the workload. Let $r_t \le r$ be the number of neighborhood traversals, s_t the number of stored adjacency entries, e_ℓ the number of entries in $\boldsymbol{A}_t[U_t^{\ell}]$, and k_ℓ and q_ℓ the numbers of quotient

vertices and stored entries in the quotient adjacency matrix. Let $\overline{T}_{\mathcal{B}}(k,q,d)$ and $\overline{M}_{\mathcal{B}}(k,q,d)$ be nondecreasing worst-case envelopes for the core backend time and working memory, excluding format conversion. Assume that conversion of a quotient to the backend representation is linear in its stored adjacency and feature arrays; these terms are dominated below by the quotient-construction and feature terms. The following bound assumes direct endpoint relabeling and comparison-based sort-and-reduce; the current PyTorch realization is analyzed separately below and in Appendix B.

1) Worst-Case Resources

For a feature-aware call, let $F = nd$, a valid upper bound for dense or sparse feature storage; for a topology-only call, let $F = 0$. Suppose quotient edges are assembled by relabeling their endpoints followed by comparison-based sort-and-reduce and levels are processed sequentially. After the batch has been applied, one update can be implemented in

$$T_{\text{update}} = O\Big(r_t(n+s_t) + L\big[(n+s_t)\log(2+n+s_t) + F\big] + \sum_{\ell=0}^{L-1} \overline{T}_{\mathcal{B}}(k_\ell, q_\ell, d)\Big) \tag{20}$$

time and

$$M_{\text{peak}} = O\Big(s_t + Ln + F + \max_{\ell}\{e_\ell + h_\ell + q_\ell + \overline{M}_{\mathcal{B}}(k_\ell, q_\ell, d)\}\Big) \tag{21}$$

memory. The maintained state alone occupies $O(s_t + Ln + F)$ memory. The time bound follows from at most r_t sparse traversals, L scans of the label and edge arrays, sort-and-reduce construction of at most s_t quotient entries per level, at most one feature aggregation and linear format conversion per level, and the L backend calls. The space bound follows because only one level, converted quotient, and backend call need to be materialized at a time.

Since $h_\ell, k_\ell \le n$ and $e_\ell, q_\ell \le s_t$, a nondecreasing backend cost gives the explicit graph-wide worst case

$$T_{\text{worst}} = O\Big(r_t(n+s_t) + L\big[(n+s_t)\log(2+n+s_t) + F + \overline{T}_{\mathcal{B}}(n, s_t, d)\big]\Big). \tag{22}$$

Thus ComNetX has no unconditional asymptotic speedup: a hub-centered update or a large intersected community can make every local problem comparable to the full snapshot, and up to L backend calls are then required.

2) Costs of the Present Implementation

The present PyTorch implementation uses tensor sparse primitives rather than the sort-and-reduce realization assumed in (20). It filters the full resident edge array at every hierarchy level. Conditional on executing all r_t traversals and L passes, it therefore incurs

$$\Omega(r_t s_t + L(n+s_t)) \tag{23}$$

full-scan memory traffic even when the quotient graphs are small. The time and temporary-memory costs of these sparse operations are given in Appendix B.

This full-scan cost is not required by the update rule. Maintaining adjacency, community-member, and incident-edge indices can replace mandatory global scans by work proportional to the reached regions, although index maintenance has its own cost and the graph-wide worst case remains. Appendix B gives the corresponding output-sensitive bound.

Contraction is beneficial when the detector work saved exceeds the cost of neighborhood search, closure, restriction, aggregation, lifting, and format conversion. This balance depends on the backend and on $|B_t|$, h_ℓ, e_ℓ, k_ℓ, and q_ℓ. These quantities describe the update workload and can inform a future choice between local and full processing.

V. EXPERIMENTAL DESIGN

We organize the evaluation around five questions.

RQ1 What quality–time trade-off does ComNetX achieve relative to warm-started full-snapshot recomputation?

RQ2 How does this trade-off change with the wrapped backend, including feature-aware calls under backend-specific interface rules and a specialized dynamic implementation?

RQ3 How do radius expansion and community closure change the update region, and how does quotient contraction determine the final backend input?

RQ4 How sensitive is the measured quality–time behavior to hierarchy depth, radius, feature representation, aggregation, and random-feature initialization?

RQ5 How does the trade-off evolve over longer update sequences, and how does it depend on update granularity and the fraction of the graph already available at initialization?

A. DATASETS AND STREAM CONSTRUCTION

Table 2 lists the six input graphs. Cora, ACM, CiteSeer, and PubMed are static attributed topologies converted into reproducible update benchmarks with artificial edge orders. Patent and ArxivMath use timestamped sequences from temporal graph-clustering resources [71], [72]; their records are sorted by the provided timestamps. We distinguish source-graph objects from stream records: an undirected edge is an unordered vertex pair, a directed arc is an ordered pair, and a stored record is one entry in the input sequence. The source counts in Table 2 count each undirected edge once for Cora, ACM, and CiteSeer, and count directed arcs for PubMed, Patent, and ArxivMath. All protocol fractions and batch sizes below refer to stored records, not to distinct undirected edges in the symmetrized graph.

For reproducibility, Cora, ACM, and CiteSeer can be obtained from the open dataset collection associated with [59]. The Cora and CiteSeer topologies match the preprocessed Planetoid graphs [73]. PubMed uses the 44,338-arc variant distributed through PyTorch Geometric's

TABLE 2. Source graphs and actual updates under 999:10. Source counts are undirected edges for Cora, ACM, and CiteSeer, and directed arcs for the other graphs. The protocol operates on stored records.

Dataset	Vertices	Source count	Order	Updates
Cora	2,708	5,278	artificial	10
ACM	3,025	13,128	artificial	10
CiteSeer	3,327	4,552	artificial	8
Patent	12,214	41,916	timestamp	10
PubMed	19,717	44,338	artificial	10
ArxivMath	270,013	799,745	timestamp	10

`AttributedGraphDataset`.[1] The artifact documents exact input comparisons and the stored edge order.

Stream construction partitions stored edge records. Cora, ACM, and CiteSeer store both orientations of each undirected edge, and the loader symmetrizes each update. When a tail is subdivided, the two records of an edge can occur in different batches: the first inserts a symmetric unit-weight edge and the second raises its weight to two. For example, Cora's ten short-protocol updates process five distinct undirected edges. Full and ComNetX runs receive identical weighted snapshots. Thus the artificial streams test additive edge updates, including weight increments, rather than only previously absent edges.

A real-graph protocol p:q partitions the stored record sequence into $p+1$ coarse bins of approximately equal record counts, uses the first p bins as the initial graph, and splits the tail bin into at most q chunks whose record counts differ by at most one. Empty chunks are skipped. The primary 999:10 protocol therefore measures ten updates on five graphs and eight on CiteSeer. It tests maintenance of an almost complete graph. The short Leiden comparison contains Cora, ACM, CiteSeer, PubMed, and ArxivMath; the archive contains no Patent Leiden execution for this protocol. S^{2}CAG covers all six graphs. The growth comparison instead contains Cora, ACM, CiteSeer, Patent, and PubMed: an ArxivMath full run is present, but its ComNetX record is empty. These subsets reflect the availability of complete pairs; the archive does not record the reasons for the missing executions.

We distinguish three complementary controls. First, 999:q with $q \in \{5, 10, 20, 40, 80, 160, 320\}$ varies granularity while retaining the same initial graph and tail records. The PubMed tail contains 44 records and the ArxivMath tail 799, so the number of nonempty updates is bounded by these counts. Second, 99:50 and 9:500 reserve approximately 1% and 10% of the records for updates. The latter supplies 500 nonempty updates on both graphs and tests sustained maintenance over a larger evolving portion of the graph. Third, protocol 0:10 divides the entire record sequence into ten bins and processes all ten, including the first snapshot, without a separate Leiden bootstrap. It tests graph growth from singleton initialization rather than maintenance of an almost complete graph. The archived launcher records this protocol using the legacy key `10`; the notation 0:10 is used throughout the article.

Each method and parameter/feature configuration is measured once, unless explicitly stated otherwise. Five feature seeds examine random-input sensitivity on the same graph streams, rather than repeated executions with identical inputs. Protocols that subdivide the same record sequence are controlled comparisons, not independent temporal windows. Table 3 summarizes the design.

The timing experiments were run on a Dockerized Linux server with two AMD EPYC 7742 64-core central processing units (CPUs), 2.0 TiB of random-access memory (RAM), and eight NVIDIA A100-SXM4 graphics processing units (GPUs; 80 GB each). The NVIDIA driver was 535.216.03, `nvidia-smi` reported CUDA 12.2, and the container used Python 3.10.13, PyTorch 2.3.1 with CUDA 11.8, and TensorFlow 2.14.0.

For RQ3, separate instrumented CPU executions record the neighborhood, update-region, and contracted-graph sizes on Cora, PubMed, and ArxivMath. They use 999:10, $L = 3$, $r = 1$, the public `leidenalg` backend, and the same stream construction. Their initial hierarchies and software versions are included in the accompanying artifact. Only graph dimensions from these executions are reported; their timings are not combined with the server comparisons.

The topology-parameter and feature controls use separate experiments. Each control is interpreted within its stated protocol and is not pooled with the main comparison.

B. METHODS AND FIXED CONFIGURATION

Leiden is the primary backend and uses resolution 1. Full recomputation receives the previous partition as a warm start. ComNetX uses $L = 3$, $r = 1$, and the Leiden initialization described in Section IV for p:q protocols with $p > 0$. The 0:10 growth control instead starts every hierarchy row from singletons and includes processing the first snapshot in its measured time. ComNetX does not pass an initial partition to quotient calls: the stored hierarchy determines the contracted groups only. The DF-Leiden baseline retains one native streaming object across batches, whereas ComNetX creates a fresh instance for each contracted graph.

All reported pairs are matched by dataset, update protocol, and graph representation. LD-Leiden is discussed as the closest Leiden-specific alternative but is not included in the quantitative benchmark. Its available implementation cannot be distributed with the artifact, and its native initialization and timing interfaces do not match the paired protocol used here; we therefore avoid a cross-protocol performance ranking.

1) S^{2}CAG Solver Settings

The preserved adapter uses `sub`, with propagation order $T = 10$, $\alpha = 1$, $\tau = 7$ SVD iterations, ten oversampling columns, and 100 rounding iterations. The argument `gamma=1` is unused by `sub`; it does not select the separate `mod` branch. Modularity is evaluated externally at resolution one.

[1] https://pytorch-geometric.readthedocs.io/en/latest/generated/torch_geometric.datasets.AttributedGraphDataset.html

TABLE 3. Evaluation protocols: 999:q (including 999:10), 99:50, 9:500, and 0:10. Each method/setting is measured once; the last column lists execution counts or varied controls, not timing replications.

Purpose	Graphs	Protocol	Actual updates	Runs and controls
Main Leiden comparison	five real topologies	999:10	8–10	one paired execution
Feature-aware backend	six real topologies	999:10	8–10	dataset/random features
Topology parameters	Cora, PubMed, ArxivMath	999:10	10	12 settings per graph
Graph-size diagnostics	Cora, PubMed, ArxivMath	999:10	10	separate CPU executions
S^2CAG feature controls	Cora, PubMed	999:10	10	modes, aggregation, radius
Feature-input sensitivity	six real topologies	999:10	8–10	five feature seeds
Batch granularity	PubMed, ArxivMath	999:q	5–320	seven requested chunk counts
Larger update windows	PubMed, ArxivMath	99:50, 9:500	50, 500	one edge order per graph
Graph growth	five paired real topologies	0:10	10	singleton initialization

Each invocation makes five solver calls and returns the last result. Both SVD implementations default to seed zero, so these are not independent random restarts. The printed internal standard deviations use one observation collected after the loop and are not used to assess stability. The feature-seed study below instead varies five input-feature initializations.

2) Requested and Realized Cluster Counts

In a full S^2CAG call, the previous labels determine only the requested cluster count k; they do not initialize the spectral solver or its rounding procedure. Thus this call is not warm-started. A local call receives no prior labels and requests as many clusters as there are quotient vertices. For an input with n vertices and d feature columns, the implemented singular-vector slice `U[:, 1:k+1]` discards the first vector and retains s columns, where $s \leq \min\{k, \min(n,d)-1\}$. Rounding assigns rows to these columns and may leave some columns empty. The number of nonempty communities can therefore be smaller than both s and the requested k. The archived records do not store this realized count or the output label vectors, so it cannot be recovered from their quality scores. These details distinguish the implemented adapter from an experiment with a fixed, equal number of communities in the full and local paths.

3) Feature Inputs and Preprocessing

The main comparisons use paired undirected representations. In the feature ablation, Cora uses its stored undirected representation and PubMed is symmetrized; each full/local pair uses the same representation. Local feature-aware calls use mean aggregation unless the sum-aggregation control is specified. The retained presets for the main comparison and the feature, aggregation, and radius controls specify 64-dimensional random features; their omitted seed resolves to the loader default 42. The seed-study presets explicitly use 64 dimensions and seeds 1–5. The loader generates an $n \times 64$ float32 matrix with independent $N(0,1)$ entries using a CPU `torch.Generator`, once per loaded graph. These preset values are not per-run metadata: exact dimension and seed cannot be established for the later records in Appendix C.

Local S^2CAG calls first aggregate signed features over atoms, then apply elementwise absolute value, followed by TF–IDF and row L2 normalization. Positive and negative values can therefore cancel inside an atom before the absolute value is taken. Full calls apply the absolute value directly to the original features. The one-hot control supplies an identity feature matrix, whose rows are aggregated using the same atom membership.

VI. RESULTS AND DISCUSSION

A. QUALITY AND PROCESSING TIME ON SHORT MAINTENANCE STREAMS (RQ1)

ComNetX substantially reduces the measured cost of repeated Leiden optimization across the five short-stream comparisons in Table 4. The speedup ranges from 6.60× to 98.72×, while the absolute final-modularity difference remains between 0.0035 and 0.0213. The largest graph, ArxivMath, combines a reduction from 110.4 s to 1.118 s with final modularity of 0.8812 compared with 0.8858 for full recomputation. This result illustrates the central benefit of the method: repeated global detector calls can be replaced by local quotient calls while keeping modularity close to that of the full-graph baseline.

The quality differences are graph dependent. ACM has the largest modularity difference, whereas CiteSeer has the smallest. NMI decreases in all five pairs, with an almost unchanged value on CiteSeer and a larger difference on ArxivMath. The time gains should therefore be interpreted together with both quality measures: closeness in modularity does not imply identical partitions or identical agreement with reference labels.

B. RESULTS WITH DIFFERENT COMMUNITY-DETECTION BACKENDS (RQ2)

The same local-update interface supports topology-only, native dynamic, and feature-aware detectors. Table 5 reports S^2CAG on all six graphs with dataset and random features. With dataset features, ComNetX reduces measured processing time on five graphs, including a 51.72-fold reduction on ArxivMath from 4151.6 s to 80.270 s. Final NMI increases on five graphs as well. These results demonstrate that the update construction can accommodate aggregated attributes in addition to graph topology.

TABLE 4. Final quality and cumulative measured processing time for full-snapshot and ComNetX Leiden on 999:10 streams.

Dataset	Full Q	Local Q	Full NMI	Local NMI	Full T (s)	Local T (s)	Speedup
Cora	0.8240	0.8141	0.4667	0.4507	0.982	0.149	6.60
ACM	0.8255	0.8042	0.2700	0.2659	0.930	0.123	7.54
CiteSeer	0.8932	0.8897	0.3305	0.3304	0.647	0.077	8.43
PubMed	0.7872	0.7822	0.2067	0.1983	4.727	0.157	30.12
ArxivMath	0.8858	0.8812	0.4226	0.4070	110.4	1.118	98.72

TABLE 5. Main S^{2}CAG feature comparison under 999:10; quality and time values are full-snapshot/ComNetX. Local calls use $L = 3, r = 1$ and mean aggregation. These paired executions are distinct from the later unpaired records discussed in Appendix C.

Dataset	Features	Q	NMI	T (s)	Time ratio
Cora	dataset	0.6951/0.7859	0.4355/0.4504	29.949/5.553	5.39
ACM	dataset	0.0536/0.6219	0.0814/0.2538	224.2/10.713	20.93
CiteSeer	dataset	0.7770/0.7719	0.2542/0.3262	135.8/1.792	75.83
Patent	dataset	0.3970/0.5520	0.0604/0.3560	11.390/13.474	0.85
PubMed	dataset	0.6221/0.4987	0.1686/0.1524	78.869/13.609	5.80
ArxivMath	dataset	0.0003/0.0844	0.0002/0.1410	4151.6/80.270	51.72
Cora	random	-0.0020/0.7877	0.0233/0.4505	9.408/4.357	2.16
ACM	random	0.0004/0.6222	0.0089/0.2567	11.286/5.256	2.15
CiteSeer	random	-0.0031/0.7719	0.0170/0.3262	9.519/0.073	129.81
Patent	random	-0.0055/0.6579	0.0009/0.3560	10.165/8.802	1.15
PubMed	random	0.0027/0.5010	0.0003/0.1580	18.272/6.199	2.95
ArxivMath	random	0.0012/0.5875	0.0002/0.1769	3889.9/63.597	61.16

The full and local S^{2}CAG calls use the cluster-count rules specified in Section V. Their time ratios consequently describe the implemented interface rather than equal-cluster-count optimization. With random features, full-run modularity is near zero, whereas ComNetX retains substantially higher values. The local procedure combines the feature input with graph structure and the stored hierarchy; the comparison does not attribute the quality difference to features alone. Patent with dataset features is the exception to the time reduction: ComNetX takes 13.474 s versus 11.390 s, while increasing both modularity and NMI.

The comparison with native DF-Leiden gives different results on the two graphs. Over 500 ArxivMath updates (Table 11), ComNetX is 9.94 times faster than the native dynamic stream, with higher final modularity and NMI. On PubMed, ComNetX takes 4.796 s compared with 4.442 s for the native stream, while also improving both quality measures. The common interface therefore offers a different trade-off between partition quality and measured processing time; its value depends on how much work the native backend already avoids.

C. REDUCTION IN BACKEND PROBLEM SIZE (RQ3)

Community closure and contraction play complementary roles. Closure determines the vertices whose memberships can change; contraction determines the size of the instance presented to the detector. Their distinction is important because a complete intersected community can be much larger than the expanded neighborhood. During the first pass, (10) represents each vertex in the expanded neighborhood individually and groups the remaining vertices by their coarsest stored block. Thus the vertices outside B_t contribute one quotient vertex per nonempty coarsest-block remainder rather than one per original vertex. On each later pass, every updated finer block contributes one vertex. This structural reduction preserves modularity on the induced subgraph according to (16) and preserves the hierarchy in (17).

Table 6 measures these dimensions in the separate CPU executions. On PubMed and ArxivMath, the update region at level 0 contains, on average, 64.3% and 78.7% of all vertices, although the radius-one neighborhoods contain only 154.9 and 782.0 vertices. Community closure can therefore select a substantial part of a graph even for small batches. Contraction reduces these regions to an average of 167.9 and 825.3 vertices, respectively; the later passes use still smaller graphs. Thus a small contracted graph does not require a small update region.

The equality of k_1 and k_2 is present in every one of the 30 update records, before averaging. The corresponding update-region and quotient-edge counts also agree. These executions have coincident initial hierarchy levels, and the second pass does not further reduce the number of atoms supplied to the third pass. Equal adjacent levels are allowed; $k_1 = k_2$ is not a general property of ComNetX.

The cost analysis expresses detector work in terms of k_ℓ and q_ℓ, separately from the cost of selecting and lifting the update region. The implementation still scans full label and edge arrays, as described in Section IV. These size measurements

TABLE 6. Measured graph dimensions, averaged over ten updates in the separate CPU diagnostics (999:10, $L = 3$, $r = 1$). Parentheses give percentages of all n vertices. Here $h_0 = |U_t^0|$, k_ℓ is the number of contracted vertices at level ℓ, and q_0 counts stored adjacency entries, including self-loops and both orientations of symmetric edges. The final column combines k_1 and k_2, which coincide in all 30 update records of this series.

Dataset	$\lvert B_t\rvert$	h_0	k_0	q_0	$k_1 = k_2$
Cora	9.4	314.2 (11.6%)	11.6 (0.43%)	45.6	3.0
PubMed	154.9	12,686.8 (64.3%)	167.9 (0.85%)	1,393.9	13.0
ArxivMath	782.0	212,558.8 (78.7%)	825.3 (0.31%)	7,408.8	47.4

characterize the constructed inputs; they do not isolate the timing contribution of each stage. The depth and radius study below examines the resulting quality–time trade-off.

D. EFFECTS OF THE UPDATE REGION, CONTRACTION, AND PARAMETERS (RQ4)

Figure 2 shows all 36 tested depth–radius configurations. Every local point is faster than its full-snapshot baseline. The ranges are 8.52–23.42× on Cora, 7.63–125.54× on PubMed, and 15.27–636.84× on ArxivMath. The nondominated points reveal several useful operating choices instead of a single universally preferred setting.

On PubMed, $L = 2, r = 0$ yields modularity 0.7847 at 72.88× speedup, compared with full modularity of 0.7872. The highest local modularity on this graph, 0.7851, occurs at $L = 2, r = 2$. On ArxivMath, the fastest configuration, $L = 1, r = 0$, reaches 636.84× with modularity 0.8792; the higher-quality $L = 2, r = 2$ configuration reaches modularity 0.8819. Cora attains its highest local modularity at $L = 3, r = 2$. Neither a larger radius nor a deeper hierarchy consistently improves modularity. The common $L = 3, r = 1$ setting provides a consistent comparison across datasets rather than a separate per-dataset optimum.

1) Effect of Feature Representation

Table 7 reports a separate feature-ablation execution series with the same solver settings as Table 5. The overlapping dataset/random-feature settings on Cora and PubMed have identical final Q and NMI at stored precision, but independently recorded times. Each table uses the full and local runs from its own series; these timings are not pooled. Each cell here gives final Q, final NMI, and cumulative measured time. The 999:10 protocol produces ten updates on both graphs.

On Cora, ComNetX maintains similar modularity across all three feature modes, 0.7859–0.7877. Random features give near-zero modularity in the full calls, yet the corresponding ComNetX results remain close to the local dataset-feature results: 0.7877 versus 0.7859 on Cora and 0.5010 versus 0.4987 on PubMed. With the one-hot input mode, ComNetX reduces the PubMed processing time from 1973.0 s to 120.0 s. These results show that the computational benefit can persist across the tested input representations, while the effect on partition quality depends on the graph and the backend's feature and cluster-count rules.

2) Feature Aggregation and Radius

The matching quality scores in Table 8 are expected under the S^{2}CAG preprocessing used here. For each nonempty atom a, $\boldsymbol{x}_{\mathrm{mean}}(a) = \boldsymbol{x}_{\mathrm{sum}}(a)/|a|$. Taking absolute values preserves this positive scale factor and leaves the feature supports, hence the IDF weights, unchanged. Linear TF–IDF weighting preserves the factor, and row L2 normalization cancels it; zero rows remain zero. Thus mean and sum yield the same normalized features in exact arithmetic, although floating-point rounding can introduce small differences. The single-execution timings do not establish a systematic runtime difference.

The radius study in Table 9 shows the importance of controlling the update region. Radius zero yields the highest modularity on both graphs in this control, while expanding to radius two reduces modularity from 0.6601 to 0.1659 on PubMed. A larger backend input is therefore not a sufficient condition for improved feature-aware clustering; locality is part of the model's behavior as well as a means of reducing computation.

3) Variation across Random-Feature Seeds

Table 10 summarizes five random-feature seeds under the common local configuration. Cora, ACM, and CiteSeer exhibit small variation in final quality. Patent has a modularity standard deviation of 0.0522, exceeding PubMed's 0.0434, while its NMI remains nearly constant (standard deviation 0.0003). PubMed and ArxivMath vary in both quality measures. Thus feature-input sensitivity depends on both the dataset and the metric. The reported standard deviations characterize these runs on fixed graph streams, not variation across independent graph realizations.

E. QUALITY AND PROCESSING TIME OVER 500 UPDATES (RQ5)

ComNetX retains a substantial time advantage when a tenth of the stored record sequence is processed over 500 updates. Under 9:500, Leiden processing time falls from 248.6 s to 10.165 s on PubMed and from 5652.7 s to 77.788 s on ArxivMath, corresponding to 24.46-fold and 72.67-fold speedups. Table 11 reports final quality and time for both topology backends. For Leiden, the final modularity gaps are 0.0078 on PubMed and 0.0062 on ArxivMath. PubMed NMI increases from 0.2017 to 0.2045; ArxivMath NMI changes from 0.4205 to 0.4006. Thus PubMed's higher NMI accompanies a small




FIGURE 2. Leiden quality–time grid under 999:10 for hierarchy depth $L \in \{1, 2, 3, 4\}$ and radius $r \in \{0, 1, 2\}$. Marker numbers show L; color and shape show r; and the black line connects nondominated measured points. The outlined orange square is the fixed $L = 3, r = 1$ configuration. Each point is one execution; ratios use the full baseline from the same parameter study.

TABLE 7. S²CAG feature sensitivity under 999:10, with ten updates on each graph. Each cell reports Q / NMI / T (seconds). These executions are separate from the main feature comparison in Table 5.

Variant	Cora	PubMed
Full, dataset features	0.6951/0.4355/30.156	0.6221/0.1686/78.119
ComNetX, dataset features	0.7859/0.4504/5.407	0.4987/0.1524/14.394
Full, random features	-0.0020/0.0233/8.571	0.0027/0.0003/18.861
ComNetX, random features	0.7877/0.4505/4.240	0.5010/0.1580/6.017
Full, one-hot input	0.6974/0.3528/35.310	0.6540/0.1071/1973.0
ComNetX, one-hot input	0.7862/0.4500/5.632	0.5349/0.1884/120.0

TABLE 8. S²CAG feature aggregation under 999:10, at $L = 3, r = 1$, using random features.

Dataset	Aggregation	Q	NMI	T (s)
Cora	mean	0.7877	0.4505	5.929
Cora	sum	0.7877	0.4505	4.197
PubMed	mean	0.5010	0.1580	6.177
PubMed	sum	0.5010	0.1580	5.995

TABLE 9. S²CAG radius sensitivity under 999:10, at $L = 3$, with random features and mean aggregation.

Dataset	r	Q	NMI	T (s)
Cora	0	0.8156	0.4509	1.740
Cora	1	0.7877	0.4505	4.368
Cora	2	0.6541	0.4120	4.829
PubMed	0	0.6601	0.1350	4.386
PubMed	1	0.5010	0.1580	6.248
PubMed	2	0.1659	0.0329	30.304

modularity decrease, whereas both scores decrease on ArxivMath.

Fig. 3 shows that the absolute modularity difference remains below 0.008 at every measured update on both graphs. The mean local-minus-full difference is -0.00584 on PubMed and -0.00524 on ArxivMath; the minima are -0.00790 at update 477 and -0.00617 at update 500, respectively. The cumulative time ratio remains above one throughout both trajectories. The measurements therefore show sustained time savings with a modularity difference below 0.008 throughout both sequences.

The native dynamic comparison also remains favorable on the larger graph. ComNetX with DF-Leiden reduces ArxivMath time from 134.4 s to 13.517 s, while increasing final modularity from 0.8551 to 0.8792 and NMI from 0.3884 to 0.3967. On PubMed, a 0.354 s increase in processing time accompanies higher modularity (0.7786 versus 0.7619) and NMI (0.2051 versus 0.1946). The benefit of ComNetX therefore depends on the efficiency of the native dynamic implementation.

F. UPDATE GRANULARITY, WINDOW SIZE, AND INITIALIZATION (RQ5)

1) Subdivision of a Fixed Update Window

Table 12 varies the number of chunks in the final 0.1% of each stored record sequence. Finer subdivision increases the number of full-graph recomputations while reducing the number of records per update. The $q = 10$ row repeats the nominal short-maintenance setting in a separate execution

TABLE 10. ComNetX with S^{2}CAG and random features under 999:10: mean ± sample standard deviation across feature seeds 1–5, with $L = 3, r = 1$ and mean aggregation.

Dataset	Q	NMI	T (s)
Cora	0.7853±0.0014	0.4499±0.0012	5.128±1.890
ACM	0.6211±0.0018	0.2580±0.0017	4.200±2.300
CiteSeer	0.7719±0.0000	0.3262±0.0000	1.415±0.753
Patent	0.6343±0.0522	0.3562±0.0003	6.962±3.834
PubMed	0.4746±0.0434	0.1399±0.0327	4.945±2.709
ArxivMath	0.5432±0.1034	0.2162±0.1061	50.524±28.162

TABLE 11. Quality and measured processing time after 500 updates under 9:500. Values are baseline/ComNetX; the baseline is full Leiden or native dynamic DF-Leiden. The time ratio is baseline time divided by ComNetX time.

Dataset	Backend	Q	NMI	T (s)	Time ratio
PubMed	Leiden	0.7864/0.7786	0.2017/0.2045	248.6/10.165	24.46
PubMed	DF-Leiden	0.7619/0.7786	0.1946/0.2051	4.442/4.796	0.93
ArxivMath	Leiden	0.8860/0.8799	0.4205/0.4006	5652.7/77.788	72.67
ArxivMath	DF-Leiden	0.8551/0.8792	0.3884/0.3967	134.4/13.517	9.94




FIGURE 3. Leiden trajectories over 500 updates under 9:500. Left: per-batch modularity difference (ComNetX minus full Leiden), where negative values favor the full partition. Right: cumulative full/ComNetX processing-time ratio, where values above one favor ComNetX. Both curves cover the complete 500-update sequence.

series and uses its own full baseline. Thus PubMed's time ratio of 31.42 here differs from 30.12 in Table 4, although final Q and NMI coincide. This difference does not represent a change in parameters. On ArxivMath, the Leiden speedup grows from 64.12 to 695.84 as the requested count increases from 5 to 320; the final modularity gap increases from 0.0039 to 0.0134. The result identifies a favorable regime for local maintenance, but the larger ratio also reflects more baseline calls over the same set of stored records. It is not an increase in the amount of graph evolution tested.

PubMed reaches one record per update at 44 updates. Requests for 80, 160, and 320 chunks therefore produce the same 44-update stream. Its Leiden ratios of 45.43–45.57 and identical final quality describe repeated processing of that stream, not three longer trajectories. Across all granularity settings, ComNetX with DF-Leiden has higher final modularity and NMI than the native stream on both graphs; its time ratio is 8.45–10.73 on ArxivMath and below one on PubMed.

2) Increasing the Updated Fraction

The 99:50 control processes approximately 1% of the stored records, between the 0.1% maintenance window and the 10% window of 9:500. Table 13 shows Leiden speedups of 24.16 on PubMed and 60.26 on ArxivMath, with final modularity differences of 0.0074 and 0.0041. DF-Leiden exhibits the same qualitative pattern as at 500 updates: the native stream is slightly faster on PubMed, while ComNetX is faster on ArxivMath and improves both quality measures on both graphs. Since both the initial snapshot and the number of calls change between protocols, these comparisons do not isolate update-window size as a single causal factor.

TABLE 12. Fixed-window granularity control, 999:*q*. Here *u* is the actual number of nonempty updates, *b* the stored records per update, ΔQ final ComNetX-minus-baseline modularity, and *S* baseline/ComNetX time. DF-Leiden uses its native dynamic baseline. Each row is one execution per method. The unpaired S^{2}CAG records are reported separately in Appendix C.

Dataset	q	u	b	Leiden ΔQ	Leiden S	DF ΔQ	DF S
PubMed	5	5	8–9	-0.0043	5.24	+0.0206	0.32
PubMed	10	10	4–5	-0.0050	31.42	+0.0207	0.71
PubMed	20	20	2–3	-0.0060	39.21	+0.0277	0.61
PubMed	40	40	1–2	-0.0167	44.83	+0.0076	0.49
PubMed	80	44	1	-0.0179	45.57	+0.0077	0.51
PubMed	160	44	1	-0.0179	45.49	+0.0077	0.51
PubMed	320	44	1	-0.0179	45.43	+0.0077	0.51
ArxivMath	5	5	159–160	-0.0039	64.12	+0.0306	8.45
ArxivMath	10	10	79–80	-0.0046	99.58	+0.0309	10.05
ArxivMath	20	20	39–40	-0.0049	149.57	+0.0354	10.34
ArxivMath	40	40	19–20	-0.0065	232.46	+0.0215	10.71
ArxivMath	80	80	9–10	-0.0080	381.84	+0.0193	10.73
ArxivMath	160	160	4–5	-0.0084	556.49	+0.0207	10.42
ArxivMath	320	320	2–3	-0.0134	695.84	+0.0204	9.99

TABLE 13. Intermediate-window control, 99:50: 50 updates collectively covering approximately 1% of the stored record sequence. Values are baseline/ComNetX, with the same baseline and timing conventions as Table 11.

Dataset	Backend	Q	NMI	T (s)	Time ratio
PubMed	Leiden	0.7883/0.7809	0.2049/0.2052	24.831/1.028	24.16
PubMed	DF-Leiden	0.7401/0.7808	0.1875/0.2068	0.447/0.485	0.92
ArxivMath	Leiden	0.8855/0.8813	0.4181/0.4006	571.3/9.480	60.26
ArxivMath	DF-Leiden	0.8377/0.8810	0.3952/0.4002	13.637/1.506	9.05

3) Growth from Singleton Initialization

The ten-bin control tests a substantially larger change in input conditions: the entire graph is processed, and no precomputed Leiden partition is supplied. Table 14 reports the five complete paired graphs. ComNetX with Leiden is faster on all five, with ratios of 1.17–1.79 and final modularity differences of 0.0003–0.0080. NMI increases on Patent and PubMed. These smaller speedups show that the method can remain useful during graph growth, while the largest maintenance gains rely on small updates to an established graph and hierarchy.

The archived S^{2}CAG growth records require a separate provenance check and are not used to infer the effect of initialization; see Appendix C.

G. PRACTICAL IMPLICATIONS

The clearest benefit of ComNetX is the reduction in repeated Leiden processing on established graphs. The smaller gains during graph growth show that initialization and the fraction of the graph being updated matter. Against native DF-Leiden, ComNetX is faster on ArxivMath, whereas the native implementation is faster on PubMed; ComNetX has higher final modularity and NMI on both graphs in these maintenance comparisons.

The feature-aware experiments show that the same construction can supply aggregated attributes to a detector. Their sensitivity to initialization, radius, and requested cluster count makes backend configuration part of the quality–time tradeoff. For deployment, the relevant choice is therefore between full recomputation, a native dynamic solver, and ComNetX under a configuration suited to the graph and detector. The region and quotient sizes in the cost analysis could support an adaptive choice among these execution modes; developing and evaluating such a policy remains future work.

VII. REPRODUCIBILITY AND SCOPE OF THE RESULTS

All quantitative tables and figures are generated from archived measurement records. The accompanying program verifies the required experiment keys, update counts, graph representations, and feature-seed coverage before generating the LaTeX tables and vector figures. The accompanying reproducibility artifact contains the ComNetX core, the public Leiden adapter, tests, configurations, archived measurements, and the table and figure generators. A separate source package contains the manuscript and its assets. Data-file checksums, preparation instructions, and the dependencies required for optional backends are documented in the artifact. The versioned packages and their SHA-256 checksums are publicly available under the repository tag `ieee-access-r2-20261102`.[2] The structural diagnostics also include their initial hierarchies and runtime metadata. Archived native DF-Leiden graph-growth runs are excluded because the benchmarking script applied the first edge batch twice; the launcher is corrected and a regression test covers initialization. The original records are retained with explicit exclusion reasons.

[2]https://github.com/mpailab/comnetx/tree/ieee-access-r2-20261102/artifacts/ieee-access

TABLE 14. Graph growth under 0:10 from singleton initialization, including the first processed snapshot. Values are full Leiden/ComNetX; each row is one paired execution. The entire stored record sequence is divided into ten batches.

Dataset	Q	NMI	T (s)	Time ratio
Cora	0.8230/0.8150	0.4715/0.4642	0.985/0.640	1.54
ACM	0.8248/0.8232	0.2704/0.2687	0.934/0.801	1.17
CiteSeer	0.8932/0.8860	0.3302/0.3272	0.847/0.473	1.79
Patent	0.8567/0.8564	0.3617/0.3673	2.197/1.351	1.63
PubMed	0.7866/0.7797	0.2014/0.2094	5.652/3.972	1.42

The original DF-Leiden implementation is publicly available.[3] The experiments use an external Python binding whose exact binary revision was not retained. The public repository therefore identifies the original implementation but cannot establish the revision of the measured binding. Native DF-Leiden and the adapted S^2CAG integration require external components that are not included in the reproducibility package; their archived results can still be regenerated as tables and figures.

The evaluation targets fixed-vertex nonnegative edge-update streams with fixed attributes. Four real-graph benchmarks use artificial edge orders, while Patent and ArxivMath use timestamps. The 500-update experiments reserve the final tenth of each stored record sequence; the window and granularity controls use nested tails of the same record order. The ten-bin control processes the complete sequence from singleton initialization. These controls do not supply independent real-data windows. Parameter comparisons use single executions, and the feature-seed study varies feature inputs on the same graph streams. The main paired S^2CAG experiments and feature controls use the budgets and cluster-count rules documented in Section V. The separate graph-size diagnostics characterize closure and contraction; repeated runs with consistent timing of individual processing stages would be needed to attribute the observed speedups to individual components. Deletion streams, arriving vertices, changing node features, and independent real-data windows remain outside the empirical scope.

Further evaluation can use stochastic blockmodels and their dynamic extensions [74], [75] to separate controlled community evolution from edge-order effects. Complementary objectives such as normalized cut [76] can assess partition properties not determined by modularity or agreement with metadata.

VIII. CONCLUSION

ComNetX adapts existing community detectors to batched graph updates by selecting complete affected communities and contracting groups defined by a stored hierarchy. The first pass updates the reported partition, and later passes update the coarser levels while preserving nesting. The method reuses the detector implementation, and its analysis separates the cost of selecting the update region from that of partitioning the contracted graph.

The experiments support using ComNetX for maintenance of an established graph: it reduces repeated Leiden processing with small modularity differences over both short and sustained update streams. The advantage is smaller during graph growth. ComNetX also outperforms native DF-Leiden in measured time and final quality on ArxivMath; on PubMed, higher final quality comes with a longer processing time. The feature-aware results demonstrate the interface's broader applicability, subject to the adapter's feature processing and cluster-count rules.

Future work can use update-region and quotient statistics to choose between local and full processing and can extend the evaluation to deletion streams, arriving vertices, and changing node attributes.

APPENDIX A BOUNDARY TERM FOR MODULARITY

To relate modularity on the induced subgraph and on the full graph, assume $A_{ij} \geq 0$, $W = \sum_{i,j} A_{ij} > 0$, and $\gamma \geq 0$. Let $U = U_t^{\ell}$, $W_U = \sum_{i,j\in U} A_{ij} > 0$. Write $\boldsymbol{A}[U] = (A_{ij})_{i,j\in U}$ for the adjacency matrix of the induced subgraph on U, and let Z be a partition of U whose labels are disjoint from the fixed outside partition. Let C_Z combine Z with that retained outside partition. For each block a contained in U, let x_a and y_a be its outgoing and incoming degree within U, and define its boundary degrees by

$$p_a = \sum_{i\in a, j\notin U} A_{ij}, \qquad q_a = \sum_{i\notin U, j\in a} A_{ij}. \tag{24}$$

If $K_{V\setminus U}$ is the full-modularity contribution independent of Z, direct substitution in (5) gives

$$\begin{aligned} D(Z) &= Q_\gamma(\boldsymbol{A}, C_Z) - K_{V\setminus U} - \frac{W_U}{W} Q_\gamma(\boldsymbol{A}[U], Z) \\ &= \frac{\gamma}{W^2}\left[\frac{W - W_U}{W_U}\sum_a x_a y_a \right. \\ &\qquad \left. - \sum_a (x_a q_a + y_a p_a + p_a q_a)\right]. \end{aligned} \tag{25}$$

The internal-edge term is unchanged; the mismatch consists of the global-versus-local null-model normalization and the boundary degrees.

[3] https://github.com/puzzlef/leiden-communities-openmp-dynamic

Write $\beta_{\text{out}} = \sum_a p_a$ and $\beta_{\text{in}} = \sum_a q_a$. Nonnegativity gives

$$-B_- \le D(Z) \le B_+, \tag{26}$$

where

$$\begin{aligned} B_+ &= \frac{\gamma}{W^2} W_U (W - W_U), \\ B_- &= \frac{\gamma}{W^2} \left[W_U (\beta_{\text{out}} + \beta_{\text{in}}) + \beta_{\text{out}} \beta_{\text{in}} \right]. \end{aligned} \tag{27}$$

For example, $\sum_a x_a y_a \le W_U^2$, $\sum_a x_a q_a \le W_U \beta_{\text{in}}$, and the analogous bounds for the remaining terms give (26).

For one fixed family $\mathcal{S}$ of partitions respecting the declared atoms, define $F(Z) = Q_\gamma(\boldsymbol{A}, C_Z) - K_{V \setminus U}$ and $L(Z) = (W_U/W) Q_\gamma(\boldsymbol{A}[U], Z)$. If Z_U maximizes L and Z_G maximizes F over $\mathcal{S}$, then

$$0 \le F(Z_G) - F(Z_U) \le B_- + B_+. \tag{28}$$

This bound compares exact optima only within the same atom-respecting candidate family; it does not bound loss against an unrestricted full-graph optimum or certify the output of a heuristic backend.

APPENDIX B IMPLEMENTATION COST AND AN INDEXED ALTERNATIVE

The current PyTorch implementation symmetrizes and traverses the resident adjacency for neighborhood expansion. At every hierarchy level, it scans the global label and edge arrays, restricts the working graph, compacts group labels, contracts sparse edges, optionally aggregates features, and invokes the backend. Filtering the resident adjacency independently for every immutable update region produces the Ls_t term in (23): quotient graphs can be small while front-end memory traffic remains graph-wide.

The implementation stores Boolean masks for all immutable update regions and processes levels sequentially. Let $M_{\text{SpMM},\ell}$ and $M_{\mathcal{B},\ell}$ denote sparse-product and backend workspace at level ℓ. Let $M_{\text{feat},\ell}$ denote the additional storage for preparing and aggregating features at that level; it is zero when attributes are not used. The implementation's total additional space is conservatively bounded by

$$\begin{aligned} M_{\text{extra}} = O\Big(Ln + \max\big\{ s_t + n, \\ \max_\ell \big[e_\ell + h_\ell + q_\ell + M_{\text{feat},\ell} \\ + M_{\text{SpMM},\ell} + M_{\mathcal{B},\ell} \big] \big\} \Big). \end{aligned} \tag{29}$$

An indexed realization can store immutable update regions as vertex lists, replacing the Ln closure masks in additional workspace by $\sum_\ell h_\ell$; the resident adjacency, hierarchy, feature, and backend-workspace terms remain. With adjacency lists, an index mapping each community to its member vertices, and indexed incident edges, let μ_r be the support-edge volume visited by the radius search and ρ_ℓ the incident-edge volume inspected at level ℓ. Let f_ℓ be the selected feature entries ($f_\ell = h_\ell d$ for dense features in the update region). Including the cost $T_{\text{index}}(\boldsymbol{\Delta}_t)$ of maintaining these indices, expected hash-based aggregation gives the output-sensitive bound

$$\begin{aligned} T_{\text{indexed}} = T_{\text{index}}(\boldsymbol{\Delta}_t) + O\Bigg(\mu_r + \sum_{\ell=0}^{L-1} \big[h_\ell + \rho_\ell + q_\ell + f_\ell \\ + \overline{T}_{\mathcal{B}}(k_\ell, q_\ell, d) \big] \Bigg). \end{aligned} \tag{30}$$

This alternative removes mandatory full scans only in local cases; it retains the graph-wide worst case when the reached regions span the snapshot.

APPENDIX C PROVENANCE OF ADDITIONAL S²CAG RECORDS

The archive contains later S²CAG records that cannot be treated as matched extensions of the main feature comparison. The main random-feature results for PubMed and ArxivMath come from `main_gnn_feature_20261001_1236.json`; their local times under 999:10 are 6.199 and 63.597 s. The separate file `s2cag-smart_20261003_0244.json` contains local-only results of 0.100 and 0.216 s for the same dataset and protocol keys, with different final modularity and NMI. Its exact source revision, full configuration, feature dimension and seed, initial hierarchy, and stage timings were not retained. The available evidence cannot attribute these discrepancies to a particular implementation or parameter change.

Table 15 reports the later records as archive diagnostics, with absolute Q, NMI, and time. No matched full S²CAG runs accompany them, so neither a modularity difference from full recomputation nor a speedup can be computed. For each graph, final Q and NMI coincide at the precision stored in all seven records, not only after table rounding. For PubMed, $q = 80, 160, 320$ produces the same 44 nonempty single-record updates. Equal scores do not establish identical output partitions; without saved labels and execution metadata, subdivision invariance cannot be verified. On PubMed at $q = 5$, the first update takes 1.662569 s, or 97.49% of the 1.705393 s total; the remaining four average 0.010706 s. At $q = 10$, the mean is 0.009992 s. The apparent drop is thus concentrated in one first observation. Lazy initialization could contribute, but the archive cannot establish its cause; the observation is not discarded.

The same file includes 99:50 and 9:500 records with these provenance gaps. Separate 0:10 full S²CAG records match analytical singleton Q and NMI scores on all five paired graphs, but no label vectors confirm their partitions. The retained `sub` solver has fewer than n embedding columns, so requesting $k = n$ cannot itself explain these scores. These records remain in the artifact but cannot support conclusions about the effects of granularity, window size, or initialization. Such comparisons require matched executions with saved source revisions, configurations, initial hierarchies, output labels, and consistent stage timings.

TABLE 15. Additional local S²CAG records under 999:*q*, retained as archive diagnostics with incomplete configuration provenance. Here *u* is the number of nonempty updates; *Q* and NMI are final values and *T* is cumulative recorded time. No paired full baseline is available.

Dataset	*q*	*u*	*Q*	NMI	T (s)
PubMed	5	5	0.5345	0.1887	1.705
PubMed	10	10	0.5345	0.1887	0.100
PubMed	20	20	0.5345	0.1887	0.194
PubMed	40	40	0.5345	0.1887	0.379
PubMed	80	44	0.5345	0.1887	0.416
PubMed	160	44	0.5345	0.1887	0.421
PubMed	320	44	0.5345	0.1887	0.424
ArxivMath	5	5	0.6894	0.4055	0.115
ArxivMath	10	10	0.6894	0.4055	0.216
ArxivMath	20	20	0.6894	0.4055	0.379
ArxivMath	40	40	0.6894	0.4055	0.650
ArxivMath	80	80	0.6894	0.4055	1.154
ArxivMath	160	160	0.6894	0.4055	2.134
ArxivMath	320	320	0.6894	0.4055	4.170

ACKNOWLEDGMENT

The research was carried out using the MSU-270 supercomputer of Lomonosov Moscow State University.

OpenAI Codex (https://openai.com/codex/) was used to assist with language editing and structural revision of the Abstract, Introduction, Related Work, Method, Experimental Design, Results and Discussion, and Conclusion; with consistency checks against the archived measurements; and with preparation of vector-figure code. The authors reviewed and revised all resulting text, code, figures, citations, and numerical claims and take responsibility for the article's content and conclusions.

REFERENCES

[1] J.-P. Onnela, J. Saramäki, J. Hyvönen, G. Szabó, D. Lazer, K. Kaski, J. Kertész, and A.-L. Barabási, "Structure and tie strengths in mobile communication networks," *Proc. Natl. Acad. Sci. USA*, vol. 104, no. 18, pp. 7332–7336, 2007. [Online]. Available: https://doi.org/10.1073/pnas.0610245104

[2] G. Palla, A.-L. Barabási, and T. Vicsek, "Quantifying social group evolution," *Nature*, vol. 446, no. 7136, pp. 664–667, 2007. [Online]. Available: https://doi.org/10.1038/nature05670

[3] G. Rossetti and R. Cazabet, "Community discovery in dynamic networks: A survey," *ACM Comput. Surv.*, vol. 51, no. 2, pp. 1–37, 2018, art. no. 35. [Online]. Available: https://doi.org/10.1145/3172867

[4] M. A. Porter, J.-P. Onnela, and P. J. Mucha, "Communities in networks," *Notices Amer. Math. Soc.*, vol. 56, no. 9, pp. 1082–1097, 1164–1166, 2009. [Online]. Available: https://www.ams.org/notices/200909/rtx090901082p.pdf

[5] S. Fortunato, "Community detection in graphs," *Phys. Rep.*, vol. 486, no. 3–5, pp. 75–174, 2010. [Online]. Available: https://doi.org/10.1016/j.physrep.2009.11.002

[6] F. Radicchi, C. Castellano, F. Cecconi, V. Loreto, and D. Parisi, "Defining and identifying communities in networks," *Proc. Natl. Acad. Sci. USA*, vol. 101, no. 9, pp. 2658–2663, 2004. [Online]. Available: https://doi.org/10.1073/pnas.0400054101

[7] G. W. Flake, S. Lawrence, C. L. Giles, and F. M. Coetzee, "Self-organization and identification of Web communities," *Computer*, vol. 35, no. 3, pp. 66–71, 2002. [Online]. Available: https://doi.org/10.1109/2.989932

[8] S. Fortunato and D. Hric, "Community detection in networks: A user guide," *Phys. Rep.*, vol. 659, pp. 1–44, 2016. [Online]. Available: https://doi.org/10.1016/j.physrep.2016.09.002

[9] P. Chunaev, "Community detection in node-attributed social networks: A survey," *Comput. Sci. Rev.*, vol. 37, 2020, art. no. 100286. [Online]. Available: https://doi.org/10.1016/j.cosrev.2020.100286

[10] M. E. J. Newman and M. Girvan, "Finding and evaluating community structure in networks," *Phys. Rev. E*, vol. 69, no. 2, 2004, art. no. 026113. [Online]. Available: https://doi.org/10.1103/PhysRevE.69.026113

[11] U. Brandes, D. Delling, M. Gaertler, R. Görke, M. Hoefer, Z. Nikoloski, and D. Wagner, "On modularity clustering," *IEEE Trans. Knowl. Data Eng.*, vol. 20, no. 2, pp. 172–188, 2008. [Online]. Available: https://doi.org/10.1109/TKDE.2007.190689

[12] V. D. Blondel, J.-L. Guillaume, R. Lambiotte, and E. Lefebvre, "Fast unfolding of communities in large networks," *J. Stat. Mech.: Theory Exp.*, vol. 2008, no. 10, 2008, art. no. P10008. [Online]. Available: https://doi.org/10.1088/1742-5468/2008/10/P10008

[13] V. A. Traag, L. Waltman, and N. J. van Eck, "From Louvain to Leiden: Guaranteeing well-connected communities," *Sci. Rep.*, vol. 9, 2019, art. no. 5233. [Online]. Available: https://doi.org/10.1038/s41598-019-41695-z

[14] H. Lu, M. Halappanavar, and A. Kalyanaraman, "Parallel heuristics for scalable community detection," *Parallel Comput.*, vol. 47, pp. 19–37, 2015. [Online]. Available: https://doi.org/10.1016/j.parco.2015.03.003

[15] S. Sahu, K. Kothapalli, and D. S. Banerjee, "Fast Leiden algorithm for community detection in shared memory setting," in *Proc. 53rd Int. Conf. Parallel Process.*, 2024, pp. 11–20. [Online]. Available: https://doi.org/10.1145/3673038.3673146

[16] M. Halappanavar, H. Lu, A. Kalyanaraman, and A. Tumeo, "Scalable static and dynamic community detection using Grappolo," in *Proc. IEEE High Perform. Extreme Comput. Conf.*, 2017, pp. 1–6. [Online]. Available: https://doi.org/10.1109/HPEC.2017.8091047

[17] D. Zhuang, J. M. Chang, and M. Li, "DynaMo: Dynamic community detection by incrementally maximizing modularity," *IEEE Trans. Knowl. Data Eng.*, vol. 33, no. 5, pp. 1934–1945, 2021. [Online]. Available: https://doi.org/10.1109/TKDE.2019.2951419

[18] N. Zarayeneh and A. Kalyanaraman, "Delta-Screening: A fast and efficient technique to update communities in dynamic graphs," *IEEE Trans. Netw. Sci. Eng.*, vol. 8, no. 2, pp. 1614–1629, 2021. [Online]. Available: https://doi.org/10.1109/TNSE.2021.3067665

[19] S. Sahu, K. Kothapalli, and D. S. Banerjee, "Parallel multicore algorithms for community detection in dynamic graphs," *Int. J. Netw. Comput.*, vol. 15, no. 1, pp. 2–31, 2025. [Online]. Available: https://doi.org/10.15803/ijnc.15.1_2

[20] ——, "Towards dynamic community detection with Leiden algorithm," in *Proc. Supercomputing India (SCI)*. IEEE, 2025, pp. 1–8. [Online]. Available: https://doi.org/10.1109/SCI68648.2025.11333864

[21] A. Tsitsulin, J. Palowitch, B. Perozzi, and E. Müller, "Graph clustering with graph neural networks," *J. Mach. Learn. Res.*, vol. 24, no. 127, pp. 1–21, 2023. [Online]. Available: https://www.jmlr.org/papers/v24/20-998.html

[22] Y. Liu, J. Li, Y. Chen, R. Wu, E. Wang, J. Zhou, S. Tian, S. Shen, X. Fu, C. Meng, W. Wang, and L. Chen, "Revisiting modularity maximization for graph clustering: A contrastive learning perspective," in *Proc. 30th ACM SIGKDD Conf. Knowl. Discovery Data Mining*, 2024, pp. 1968–1979. [Online]. Available: https://doi.org/10.1145/3637528.3671967

[23] X. Lin, R. Yang, H. Zheng, and X. Ke, "Spectral subspace clustering for attributed graphs," in *Proc. 31st ACM SIGKDD Conf. Knowl. Discovery Data Mining*, 2025, pp. 789–799. [Online]. Available: https://doi.org/10.1145/3690624.3709207

[24] M. Rosvall and C. T. Bergstrom, "Maps of random walks on complex networks reveal community structure," *Proc. Natl. Acad. Sci. USA*, vol. 105, no. 4, pp. 1118–1123, 2008. [Online]. Available: https://doi.org/10.1073/pnas.0706851105

[25] V. A. Traag and L. Šubelj, "Large network community detection by fast label propagation," *Sci. Rep.*, vol. 13, 2023, art. no. 2701. [Online]. Available: https://doi.org/10.1038/s41598-023-29610-z

[26] Y. Ma, Y. Zhao, J. Wang, M. Liu, W. Shen, and Y. Ma, "Modularity-based incremental label propagation algorithm for community detection," *Appl. Sci.*, vol. 10, no. 12, 2020, art. no. 4060. [Online]. Available: https://doi.org/10.3390/app10124060

[27] H. C. Rustamaji, W. A. Kusuma, S. Nurdiati, and I. Batubara, "Community detection with greedy modularity disassembly strategy," *Sci. Rep.*, vol. 14, 2024, art. no. 4694. [Online]. Available: https://doi.org/10.1038/s41598-024-55190-7

[28] S. Taibi, L. Toumi, and S. Bouamama, "Complex network community discovery using fast local move iterated greedy algorithm," *J. Supercomput.*, vol. 81, no. 1, 2025, art. no. 182. [Online]. Available: https://doi.org/10.1007/s11227-024-06614-8

[29] B. H. Good, Y.-A. de Montjoye, and A. Clauset, "Performance of modularity maximization in practical contexts," *Phys. Rev. E*,

vol. 81, no. 4, 2010, art. no. 046106. [Online]. Available: https://doi.org/10.1103/PhysRevE.81.046106

[30] Z. Yang, R. Algesheimer, and C. J. Tessone, "A comparative analysis of community detection algorithms on artificial networks," *Sci. Rep.*, vol. 6, 2016, art. no. 30750. [Online]. Available: https://doi.org/10.1038/srep30750

[31] J. Yang and J. Leskovec, "Defining and evaluating network communities based on ground-truth," *Knowl. Inf. Syst.*, vol. 42, no. 1, pp. 181–213, 2015. [Online]. Available: https://doi.org/10.1007/s10115-013-0693-z

[32] L. Peel, D. B. Larremore, and A. Clauset, "The ground truth about metadata and community detection in networks," *Sci. Adv.*, vol. 3, no. 5, 2017, art. no. e1602548. [Online]. Available: https://doi.org/10.1126/sciadv.1602548

[33] L. Danon, A. Díaz-Guilera, J. Duch, and A. Arenas, "Comparing community structure identification," *J. Stat. Mech.: Theory Exp.*, vol. 2005, no. 9, 2005, art. no. P09008. [Online]. Available: https://doi.org/10.1088/1742-5468/2005/09/P09008

[34] W. H. Chong and L.-N. Teow, "An incremental batch technique for community detection," in *Proc. 16th Int. Conf. Inf. Fusion*. IEEE, 2013, pp. 750–757. [Online]. Available: https://ieeexplore.ieee.org/document/6641069/

[35] J. Xie, M. Chen, and B. K. Szymanski, "LabelRankT: Incremental community detection in dynamic networks via label propagation," in *Proc. 4th Workshop Dyn. Netw. Manage. Mining*, 2013, pp. 25–32. [Online]. Available: https://doi.org/10.1145/2489247.2489249

[36] J. Han, W. Li, L. Zhao, Z. Su, Y. Zou, and W. Deng, "Community detection in dynamic networks via adaptive label propagation," *PLOS ONE*, vol. 12, no. 11, 2017, art. no. e0188655. [Online]. Available: https://doi.org/10.1371/journal.pone.0188655

[37] J. Shang, L. Liu, F. Xie, Z. Chen, J. Miao, X. Fang, and C. Wu, "A real-time detecting algorithm for tracking community structure of dynamic networks," arXiv:1407.2683 [cs.SI], Jul. 2014. [Online]. Available: https://arxiv.org/abs/1407.2683

[38] M. Seifikar, S. Farzi, and M. Barati, "C-Blondel: An efficient Louvain-based dynamic community detection algorithm," *IEEE Trans. Comput. Social Syst.*, vol. 7, no. 2, pp. 308–318, 2020. [Online]. Available: https://doi.org/10.1109/TCSS.2020.2964197

[39] S. Sahu, "DF Louvain: Fast incrementally expanding approach for community detection on dynamic graphs," arXiv:2404.19634 [cs.DC], Apr. 2024. [Online]. Available: https://arxiv.org/abs/2404.19634

[40] N. S. Sattar, K. Z. Ibrahim, A. Buluç, and S. Arifuzzaman, "DyG-DPCD: A distributed parallel community detection algorithm for large-scale dynamic graphs," *Int. J. Parallel Program.*, vol. 53, no. 1, 2025, art. no. 4. [Online]. Available: https://doi.org/10.1007/s10766-024-00780-1

[41] N. S. Sattar, A. Buluç, K. Z. Ibrahim, and S. Arifuzzaman, "Exploring temporal community evolution: Algorithmic approaches and parallel optimization for dynamic community detection," *Appl. Netw. Sci.*, vol. 8, 2023, art. no. 64. [Online]. Available: https://doi.org/10.1007/s41109-023-00592-1

[42] K. Hanauer, M. Henzinger, and C. Schulz, "Recent advances in fully dynamic graph algorithms: A quick reference guide," *ACM J. Exp. Algorithmics*, vol. 27, no. 1, pp. 1.11:1–1.11:45, 2022, art. no. 1.11. [Online]. Available: https://doi.org/10.1145/3555806

[43] L. Cai, J. Zhou, and D. Wang, "Improving temporal smoothness and snapshot quality in dynamic network community discovery using NOME algorithm," *PeerJ Comput. Sci.*, vol. 9, 2023, art. no. e1477. [Online]. Available: https://doi.org/10.7717/peerj-cs.1477

[44] A. Bovet, J.-C. Delvenne, and R. Lambiotte, "Flow stability for dynamic community detection," *Sci. Adv.*, vol. 8, no. 19, 2022, art. no. eabj3063. [Online]. Available: https://doi.org/10.1126/sciadv.abj3063

[45] Z. Sun, Y. Sun, X. Chang, F. Wang, Z. Pan, G. Wang, and J. Liu, "Dynamic community detection based on the Matthew effect," *Physica A*, vol. 597, 2022, art. no. 127315. [Online]. Available: https://doi.org/10.1016/j.physa.2022.127315

[46] M. Mazza, G. Cola, and M. Tesconi, "Modularity-based approach for tracking communities in dynamic social networks," *Knowl.-Based Syst.*, vol. 281, 2023, art. no. 111067. [Online]. Available: https://doi.org/10.1016/j.knosys.2023.111067

[47] V. Brabant, A. Bonifati, and R. Cazabet, "Discovering communities in continuous-time temporal networks by optimizing L-modularity," in *Proc. IEEE Int. Conf. Data Mining*. IEEE, 2025, pp. 1065–1074. [Online]. Available: https://doi.org/10.1109/ICDM65498.2025.00115

[48] N. Djurdjevac Conrad, E. Tonello, J. Zonker, and H. Siebert, "Detection of dynamic communities in temporal networks with sparse data," *Appl. Netw. Sci.*, vol. 10, no. 1, 2025, art. no. 1. [Online]. Available: https://doi.org/10.1007/s41109-024-00687-3

[49] F. Blašković, T. O. F. Conrad, S. Klus, and N. Djurdjevac Conrad, "Random walk based snapshot clustering for detecting community dynamics in temporal networks," *Sci. Rep.*, vol. 15, no. 1, 2025, art. no. 24414. [Online]. Available: https://doi.org/10.1038/s41598-025-09340-0

[50] D. J. DiTursi, G. Ghosh, and P. Bogdanov, "Local community detection in dynamic networks," in *Proc. IEEE Int. Conf. Data Mining*, 2017, pp. 847–852. [Online]. Available: https://doi.org/10.1109/ICDM.2017.103

[51] K. Christopoulos, G. Baltsou, and K. Tsichlas, "Local community detection in graph streams with anchors," *Information*, vol. 14, no. 6, 2023, art. no. 332. [Online]. Available: https://doi.org/10.3390/info14060332

[52] J. Liu, Y. Shao, and S. Su, "Multiple local community detection via high-quality seed identification over both static and dynamic networks," *Data Sci. Eng.*, vol. 6, no. 3, pp. 249–264, 2021. [Online]. Available: https://doi.org/10.1007/s41019-021-00160-6

[53] S. Boudebza, R. Cazabet, F. Azouaou, and O. Nouali, "OLCPM: An online framework for detecting overlapping communities in dynamic social networks," *Comput. Commun.*, vol. 123, pp. 36–51, 2018. [Online]. Available: https://doi.org/10.1016/j.comcom.2018.04.003

[54] F. Scarselli, M. Gori, A. C. Tsoi, M. Hagenbuchner, and G. Monfardini, "The graph neural network model," *IEEE Trans. Neural Netw.*, vol. 20, no. 1, pp. 61–80, 2009. [Online]. Available: https://doi.org/10.1109/TNN.2008.2005605

[55] Y. Zhang, Y. Xiong, Y. Ye, T. Liu, W. Wang, Y. Zhu, and P. S. Yu, "SEAL: Learning heuristics for community detection with generative adversarial networks," in *Proc. 26th ACM SIGKDD Conf. Knowl. Discovery Data Mining*. ACM, 2020, pp. 1103–1113. [Online]. Available: https://doi.org/10.1145/3394486.3403154

[56] T. Zhang, Y. Xiong, J. Zhang, Y. Zhang, Y. Jiao, and Y. Zhu, "CommDGI: Community detection oriented deep graph infomax," in *Proc. 29th ACM Int. Conf. Inf. Knowl. Manage.* ACM, 2020, pp. 1843–1852. [Online]. Available: https://doi.org/10.1145/3340531.3412042

[57] A. Bhowmick, M. Kosan, Z. Huang, A. Singh, and S. Medya, "DGCLUSTER: A neural framework for attributed graph clustering via modularity maximization," in *Proc. AAAI Conf. Artif. Intell.*, vol. 38, no. 10, 2024, pp. 11 069–11 077. [Online]. Available: https://doi.org/10.1609/aaai.v38i10.28983

[58] Devesh Kumar V V, S Sreesankar, Krishnpriya Dinesan, Pranav B Nair, and L R Deepthi, "Analyzing GNN models for community detection using graph embeddings: A comparative study," in *Proc. 15th Int. Conf. Comput. Commun. Netw. Technol.* IEEE, 2024, pp. 1–8. [Online]. Available: https://doi.org/10.1109/ICCCNT61001.2024.10725530

[59] Y. Liu, J. Xia, B. Wu, S. Zhou, X. Yang, K. Liang, C. Fan, Y. Zhuang, G. Yu, S. Z. Li, X. Liu, and K. He, "A survey of deep graph clustering: Taxonomy, challenge, application, and open resource," *IEEE Trans. Knowl. Data Eng.*, vol. 38, no. 6, pp. 3365–3384, 2026. [Online]. Available: https://doi.org/10.1109/TKDE.2026.3669747

[60] C. Liu, Y. Yang, Y. Ding, H. Lu, W. Lin, Z. Wu, and W. Bi, "DAG: Deep adaptive and generative K-free community detection on attributed graphs," in *Proc. 30th ACM SIGKDD Conf. Knowl. Discovery Data Mining*. ACM, 2024, pp. 5454–5465. [Online]. Available: https://doi.org/10.1145/3637528.3671615

[61] J. Zhang, H. Peng, L. Sun, G. Wu, C. Liu, and Z. Yu, "Unsupervised graph clustering with deep structural entropy," in *Proc. 31st ACM SIGKDD Conf. Knowl. Discovery Data Mining V.2*, vol. 2. ACM, 2025, pp. 3752–3763. [Online]. Available: https://doi.org/10.1145/3711896.3737173

[62] C. Gkartzios, E. Pitoura, and P. Tsaparas, "Modularity-fair deep community detection," in *Proc. IEEE Int. Conf. Data Mining*. IEEE, 2025, pp. 287–296. [Online]. Available: https://doi.org/10.1109/ICDM65498.2025.00036

[63] M. Qin, C. Zhang, Y. Gao, W. Zhang, and D.-Y. Yeung, "Pre-train and refine: Towards higher efficiency in K-agnostic community detection without quality degradation," in *Proc. 30th ACM SIGKDD Conf. Knowl. Discovery Data Mining*. ACM, 2024, pp. 2467–2478. [Online]. Available: https://doi.org/10.1145/3637528.3671686

[64] M. Qin, C. Zhang, Y. Gao, Y. Ding, W. Jiang, W. Zhang, W. Han, and B. Bai, "Towards faster graph partitioning via pre-training and inductive inference," in *Proc. IEEE High Perform. Extreme Comput. Conf.*, 2024, pp. 1–7. [Online]. Available: https://doi.org/10.1109/HPEC62836.2024.10938459

[65] S. Ji, X. Lu, M. Liu, L. Sun, C. Liu, B. Du, and H. Xiong, "Community-based dynamic graph learning for popularity prediction," in *Proc. 29th*

ACM SIGKDD Conf. Knowl. Discovery Data Mining. ACM, 2023, pp. 930–940. [Online]. Available: https://doi.org/10.1145/3580305.3599281
[66] D. Kong, A. Zhang, and Y. Li, "Learning persistent community structures in dynamic networks via topological data analysis," in *Proc. AAAI Conf. Artif. Intell.*, vol. 38, no. 8, 2024, pp. 8617–8626. [Online]. Available: https://doi.org/10.1609/aaai.v38i8.28706
[67] S. Sahu, "Efficient tracking of communities on evolving graphs with Leiden algorithm," in *Proc. 35th Int. Symp. High-Perform. Parallel Distrib. Comput.* ACM, 2026, pp. 498–508. [Online]. Available: https://doi.org/10.1145/3806645.3807601
[68] G. Bokov, A. Konovalov, A. Uporova, S. Moiseev, I. Safonov, and A. Radionov, "LD-Leiden: Local parallel community detection in large dynamic networks," arXiv:2502.18497v2 [cs.SI], Jul. 2026. [Online]. Available: https://arxiv.org/abs/2502.18497v2
[69] C. Lin, Y. Xie, Y. Fang, Y. Hu, Y. Hu, and C. Chen, "Maintaining Leiden communities in large dynamic graphs," arXiv:2601.08554v5 [cs.SI], Jun. 2026. [Online]. Available: https://arxiv.org/abs/2601.08554v5
[70] A. Arenas, J. Duch, A. Fernández, and S. Gómez, "Size reduction of complex networks preserving modularity," *New J. Phys.*, vol. 9, no. 6, 2007, art. no. 176. [Online]. Available: https://doi.org/10.1088/1367-2630/9/6/176
[71] M. Liu, K. Liang, S. Wang, X. Hu, S. Zhou, and X. Liu, "Deep temporal graph clustering: A comprehensive benchmark and datasets," *IEEE Trans. Pattern Anal. Mach. Intell.*, vol. 47, no. 12, pp. 11 561–11 578, 2025. [Online]. Available: https://doi.org/10.1109/TPAMI.2025.3596609
[72] M. Liu, K. Liang, Y. Liu, S. Wang, S. Zhou, and X. Liu, "arXiv4TGC: Large-scale datasets for temporal graph clustering," arXiv:2306.04962 [cs.AI], Jun. 2023. [Online]. Available: https://arxiv.org/abs/2306.04962
[73] Z. Yang, W. W. Cohen, and R. Salakhutdinov, "Revisiting semi-supervised learning with graph embeddings," in *Proc. 33rd Int. Conf. Mach. Learn.*, ser. Proc. Mach. Learn. Res., vol. 48. PMLR, 2016, pp. 40–48. [Online]. Available: https://proceedings.mlr.press/v48/yanga16.html
[74] P. W. Holland, K. B. Laskey, and S. Leinhardt, "Stochastic blockmodels: First steps," *Social Networks*, vol. 5, no. 2, pp. 109–137, 1983. [Online]. Available: https://doi.org/10.1016/0378-8733(83)90021-7
[75] K. S. Xu and A. O. Hero, III, "Dynamic stochastic blockmodels for time-evolving social networks," *IEEE J. Sel. Topics Signal Process.*, vol. 8, no. 4, pp. 552–562, 2014. [Online]. Available: https://doi.org/10.1109/JSTSP.2014.2310294
[76] J. Shi and J. Malik, "Normalized cuts and image segmentation," *IEEE Trans. Pattern Anal. Mach. Intell.*, vol. 22, no. 8, pp. 888–905, 2000. [Online]. Available: https://doi.org/10.1109/34.868688

GRIGORIY BOKOV received the Candidate of Physical and Mathematical Sciences degree in 2014. He is currently the Director of the AI Research Center, Lomonosov Moscow State University, Moscow, Russia, and an Associate Professor and the Head of the Laboratory of Mathematical Problems of Artificial Intelligence at the Faculty of Mechanics and Mathematics. His research interests include logical calculi, functional systems, automata, machine-learning algorithms, optimization, and large dynamic graphs.

ALEKSANDR KONOVALOV received the Specialist degree from the Faculty of Mechanics and Mathematics, Lomonosov Moscow State University, Moscow, Russia, in 2013, and the Candidate of Physical and Mathematical Sciences degree in 2018. He is currently a Junior Researcher with Lomonosov Moscow State University. His research interests include constructive mathematical logic, graph neural networks, and dynamic community detection.

ANNA UPOROVA is currently pursuing a Specialist degree in the Faculty of Mechanics and Mathematics, Lomonosov Moscow State University, Moscow, Russia. Her research interests include dynamic graphs, community detection, and graph neural networks.

ALEXANDER DROBYSHEV is currently a postgraduate student with the Chair of Mathematical Theory of Intelligent Systems, Faculty of Mechanics and Mathematics, Lomonosov Moscow State University, Moscow, Russia. His research interests include Boolean-network dynamics, limit cycles, computational complexity, and dynamic graph algorithms.

IAROSLAV EGOROV is affiliated with the AI Research Center, Lomonosov Moscow State University, Moscow, Russia. His recent work includes scalable dynamic community detection.